

USB Peripherals

Expand your horizons with Kouwell

USB Cards


2 PORTS



KW2580E2- Kouwell PCI USB 2.0 Card 2 Ports

- Chipset: VIA
- Compliant with USB 2.0 (Data Rate 1.5/12/480 Mbps)
- Provides 2 external USB 2.0 Ports
- Compliant with Universal Host Controller Interface Specification Rev 1.1
- Compliant with Enhanced Host Controller Interface Specification Rev 1.0
- Hot-Swapping and Plug-n-Play
- Compatible with Windows 98SE, ME, 2000, XP


4+1
PORTS



KW2580E4- Kouwell PCI USB 2.0 Card 4 Ext. Ports & 1 Shared Int.

- Chipset: VIA
- Compliant with USB 2.0 (Data Rate 1.5/12/480 Mbps)
- Root hub with 4 external and 1 internal shared downstream facing ports which are shared by OHCI and EHCI Host Controller core
- Supports PCI-Bus Power Management Interface release 1.1
- Hot-Swapping and Plug-n-Play
- Compatible with Windows 98SE, ME, 2000, XP

**LOW
PROFILE**



KWL2580E- Kouwell PCI USB 2.0 Low Profile Card 3 Ports

- Chipset: VIA
- Compliant with USB 2.0 (Data Rate 1.5/12/480 Mbps)
- Low profile bracket for slimline PC
- Provides 3 external and 1 internal USB 2.0 Ports
- Supports PCI-Bus Power Management Interface release 1.1
- Hot-Swapping and Plug-n-Play
- Compatible with Windows 98SE, ME, 2000, XP

**USB 2.0
HOST**



KWF2580N- Kouwell PCI USB 2.0 Card 3.5" Front 4 Ports

- Chipset: NEC
- Compliant with USB 2.0 (Data Rate 1.5/12/480 Mbps)
- Provides 4 USB 2.0 ports
- Fits in any 3.5" front bay
- 32-bits 33MHz host interface compliant to PCI specification release 2.2
- Compatible with Windows 98SE, ME, 2000, XP

**LAPTOP
USERS**



KW20022- Kouwell CardBus USB 2.0 Card 2 Ports

- Compliant with USB 2.0 (Data Rate 1.5/12/480 Mbps)
- Compliant with 32-bit Cardbus specification
- Root hub with 2 external downstream facing ports which are shared by OHCI and EHCI Host Controller Core
- Plug'n'Play
- Compatible with Windows 98SE, ME, 2000, XP

USB Peripherals

Expand your horizons with Kouwell

USB Hubs

MULTI FUNCTION



KW586- Kouwell USB 1.1 Hub 3 Ports + Parallel + Serial

- 1 upstream B-type USB Port (to host PC)
- 3 downstream A-type USB ports
- 1 25-pin IEEE 1284 ECP/EPP/SPP high speed parallel port
- 1 9-pin 16C550 UART high-speed serial port
- Plug'n'Play
- Compatible with Windows 98, 2000

4 PORTS



KW2580H- Kouwell External USB 2.0 Hub 4 Ports

- Compliant with USB 2.0 (Data Rate 1.5/12/480 Mbps)
- Tiered star topology supporting up to 5 tiers and 127 devices
- Plug'n'Play
- Auto detect speeds and connections of device
- Supports Self-powered mode
- Compatible with Windows 98SE, ME, 2000, XP

FRONT BAY



KW2591- Kouwell Internal 3.5" USB 2.0 Hub 4 Ports

- Chipset: NEC
- Compliant with USB 2.0 (Data Rate 1.5/12/480 Mbps)
- 4 downstream ports and one upstream port
- Plug'n'Play
- Tiered star topology supporting up to 5 tiers and 127 devices
- Compatible with Windows 98SE, ME, 2000, XP

USB Cables

NETWORK




KW585A- Kouwell USB 1.1 Network Link Cable

- USB host to host communication to host to hub communication
- Full compliance with the Universal Serial Bus specification Ver. 1.1
- Dual data buffer supporting two-way data transfer
- Low power consumption
- Supports suspend and resume for power management
- Supports remote wake-up
- IBus powered from either USB port
- Compatible with Windows 98, 2000 & Windows 95 OSR 2.1

USB Adaptors

ETHERNET



KW588- Kouwell USB 1.1 to 10 Base Ethernet Adaptor

- Connects to any 10Base-T LAN, HAN or Mobile Network Applications
- Advanced 16-bit processor for USB transaction processing & control data processing
- Fully IEEE 802.3 compliant 10Mbit/sec Ethernet MAC Layer
- 1.5K x 16 internal RAM buffer and 32K x 8SRAM
- Serial interface for EEPROM
- Watchdog timer & Internal clock generation
- Plug'n'Play
- Compatible with Windows 98, 2000

ETHERNET



KW588A- Kouwell USB 1.1 to 10/100 Ethernet Adaptor

- 10/100Mbps auto-negotiation adaptor
- Full speed USB device
- USB interface Ver. 1.0/1.1 compliant
- Transaction speed 12Mbps maximum
- IEEE 802.3 MII compliant
- Support IEEE 802.3x flow control
- Supports configurable threshold for transmitting PAUSE frame
- Supports wakeup frame, link status change and magic packet wake-up
- Supports all USB standard commands
- Plug'n'Play
- 32KB external SRAM and 2KB internal memory
- Unused any external power adaptor
- Compatible with Windows 98SE, ME

BLUETOOTH



KW9006BU- Kouwell USB 1.1 to Bluetooth Adaptor (Class II)

- Standard: Bluetooth v1.1
- Frequency Band: 2.400~2.4835GHz Unlicensed ISM Band
- Power Class: Bluetooth Class II operation
- Transmission Distance: Up to 30 meters (open space)
- Interface: USB UHCI/OHCI Spec. 1.1 compliant
- Operating Power: 5V DC
- Compatible with Windows 98SE, ME, 2000, XP

Verbatim is the exclusive distributor of Kouwell products throughout Australia and New Zealand. For more information on these products, visit www.verbatim.com.au



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>