ViewSonic[®] VP201s/VP201b LCD Display 20.1" THINEDGETM ULTRA-SLIM BEZEL DISPLAY




VP201b shown. Also available in silver (VP201s)

Immerse yourself in the panorama of this big-picture LCD.

Turn your ideas into breathtaking reality with the 20" VP201s and VP201b LARGE-SCREEN THINEDGE ULTRA-SLIM BEZEL LCD displays. With astounding 176° ultrawide viewing angles, UXGA 1.92 megapixel resolution, ClearMotiv[™] broadcast-quality video technology and native HDTV high-scan 720p compatibility, these displays boost professional productivity and heighten user enjoyment for video editors, financial traders, CAD/CAM engineers and power gamers. Ideal for multiple-panel

configurations with height/pivot adjustments, digital/analog inputs and USB 2.0 high-speed connectivity, the VP201s and VP201b are the infinitely versatile professional desktop displays of choice.



ThinEdge design is ideal for multi-panel setups. Four unit panel-module-only (without base) multi-packs available.

Uncompromised features and versatility to have you seeing 20/20.

- **ThinEdge maximizes your productivity** The ultra-slim 0.67" bezel design enhances your visual experience with clean, minimalist borders around the active image area. Suitable for tiling and stacking.
- --->Ideal for multiple-monitor setups

ThinEdge minimizes bezel gaps between panels for a virtually continuous viewing area in multiple-panel setups.

---->Pivot, height and wall-mount versatility

VESA[®] wall-mount interface and detachable base for ergonomic flexibility with pivot, height, tilt and swivel adjustments.

Includes one DVI-I (analog or digital capable) and one analog input. Integrated USB 2.0 high-speed hub enables unlimited connectivity options.

----- ClearMotiv™ technology

Ultra-fast 16ms video response enables digital HD broadcast-quality full-motion video at 62.5 fps.

- ···
 1600x1200 native resolution
- •••• **High brightness and contrast** 250-nit brightness (typ) and 400:1 contrast ratio (typ) for rich images.
- ••• Image clarity from all directions XtremeView[®] performance features ultra-wide 176° viewing angles horizontally and vertically.
- Integrated power supply with hard power switch
- •••• TCO'03 and ENERGY STAR[®] TCO'03 for silver and TCO'99 for black models.



Download from Www.Somanuals.com. All Manuals Search And Download.

ViewSonic[®] VP201s/VP201b LCD Display 20.1" THINEDGETM ULTRA-SLIM BEZEL DISPLAY



Pivot feature saves time Spend less time scrolling long documents. Simply rotate your screen from landscape to portrait.

| tears another | |
|---|--|
| ** | |
| and the second second | |
| | Torona and the second s |
| | |
| NAME OF A DESCRIPTION OF A DESCRIPTION OF A | |

Wide-travel height adjustment With over 4¼ inches of travel, this LCD fits just right.

Hard power switch

N. S. C. C.

Integrated power supply

| LCD PANEL | Туре | 20.1" color TFT active matrix UXGA LCD |
|----------------------|--------------------------------------|--|
| | Display Area | 16.1" (horizontal) x 12.1" (vertical); 20.1" diagonal |
| | Optimum Resolution Contrast Ratio | |
| | Viewing Angles | 400:1 (typ) 176° horizontal, 176° vertical |
| | Response Time | 16ms (typ) |
| | Brightness | 250 cd/m2 (typ) |
| | Glass Surface | Anti-glare |
| I | Analog | RGB Analog (75 ohms, 0.7/1.0 Vp-p) |
| | Digital - | DVI-D (TMDS, 100 ohms, or analog capable) |
| | Frequency | Fh: 30~92kHz, Fv: 50~85Hz H/V separated, composite, sync-on-green (TTL) |
| | Sync | |
| | PC Mac®* | VGA up to 1600x1200 non-interlaced Power Mac™ G3/G4 up to 1600x1200 |
| | HDTV | 480p, 720p |
| CONNECTOR | Analog | 15-pin mini D-sub |
| CONTECTOR | Digital | Digital DVI-I |
| | USB | V 2.0 Up stream (B type) x1; Down stream (A type) x4 |
| | Power | 3-pin plug (CEE22) |
| POWER | Voltage | AC 100–240V (universal), 50–60Hz |
| | Consumption | 70W (typ) |
| CONTROLS | Basic | Power, 1, down, up, 2 |
| | OnView [®] | Auto image adjust, contrast, brightness, input select (D-sub, DVI-A, DVI-D), color adjust (9300K, 6500K, 5400K, 5000K, user color), information (H/V |
| | | frequency, resolution, model number, serial number, web site), manual |
| | | image adjust (H. size, H/V position, fine tune, sharpness, scaling), setup |
| | | menu (language, resolution notice, input priority, OSD position, OSD time- |
| | | out, OSD background, OSD pivot), memory recall |
| OPERATING | Temperature | 32–104° F (0–40° C) |
| CONDITION | Humidity | 10–90% (non-condensing) |
| DIMENSIONS | Physical: | 448mm x 480mm x 267mm (w/ stand) |
| (W x H X D) | | 17.6" x 18.9" x 10.5" (w/ stand) 448mm x 346mm x 71mm (w/out stand) |
| | | 17.6" x 13.6" x 2.8" (w/out stand) |
| WEIGHT | Net | 18.7 lbs. (8.5 kgs) w/ stand; 11.5 lbs. (5.2 kgs) w/out stand |
| | Gross | 24.7 lbs. (11.2 kgs) w/ stand; 15.9 lbs. (7.2 kgs) w/out stand |
| REGULATIONS | | UL, cUL, FCC-B, CB, CE, ENERGY STAR [®] , NOM, TUV/GS, TUV Ergo, (covers |
| | | ISO13406-2 and MPR II) TCO'03 (VP201s), TCO'99 (VP201b), NEMKO, |
| | | SEMKO, DEMKO, FIMKO, GOST-R, hygienic, SASO, PCBC, VCCI, BSMI, CCC, |
| | | PSB, C-TICK, TUV-S |
| POWER MANAG | EMENT | Meets TCO and ENERGY STAR standards |
| WARRANTY | | Three-year limited warranty on parts, labor and backlight. |
| nnector | | NEY ENER |
| | | |
| alog DVI-I connector | E. | 99 |
| | BSI | |
| | | |
| | | |
| | | |

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution. ViewSonic®

See the difference.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com *Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2003 ViewSonic Corporation. All rights reserved. [11116-038-11/03] VP2015-1

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com