N4060w

40" WIDESCREEN LCD HDTV WITH CLEARPICTURETH ELECTRONICS

Ultimate HDTV entertainment.

ViewSonic's 40" widescreen N4060w LCD HDTV is the perfect display to finish your high-performance home theater. Prepare to be amazed by PERFECTLY SHARP, CRYSTAL CLEAR OFF-THE-AIR HDTV broadcasts, DVDs, movies, games and more on the N4060w. Multiple connectivity options let you connect all your electronic components, making the N4060w the focal point of your home entertainment. It's packed with performance features such as ADVANCED CLEARPICTURE[™] ELECTRONICS, super-fast 8ms video response time and HDMI digital video with HDCP for long-term compatibility. View HD movies and television in their native format thanks to the widescreen aspect ratio. Experience SRS TRUSURROUND XT[®] DIGITAL AUDIO for a theater-like sensation.





INSPIRE ENVY

> Experience widescreen HDTV

Enjoy a widescreen theater experience and high-definition picture quality with this display's widescreen aspect ratio, true HDTV capability, and wide viewing angles.

> ClearPicture[™] electronics

Advanced ClearPicture electronics provide superior picture quality through precision deinterlacing, 10-bit color processing, and advanced scaling for smoother, sharper full-motion video with incredibly rich colors.

> Vivid graphics, clear text, stunning TV

Ultra-high brightness of 500 nits (typ), high contrast ratio of 1000:1 (typ), and 1360x768 optimum PC resolution provides vibrant video and crisp data images on the desktop or in the living room.

> Expand your options with plug-and-play connectivity and universal remote control

This true HDTV provides the ultimate viewing experience with plug-and-play, high-end connectivity for set-top boxes, DVDs, game consoles and camcorders.

> OptiSync[®] technology featuring HDMI

Add versatility to your LCD TV with support for HDMI with high-definition content protection (HDCP) and analog (VGA) signals, plus component, S-video, composite, and TV/cable input.

Powerful high-fidelity audio It's all accompanied by an ultra-high fidelity 20-watt SRS TruSurround XT[®] audio system that completes the entertainment experience.



the choice of professionals

ViewSonic 🎎

N4060w

40" WIDESCREEN LCD HDTV WITH ADVANCED CLEARPICTURE™ TECHNOLOGY





LCD	Туре	40" (39.9" viewable) color TFT active matrix, wide LCD
	Display Area	34.9" horizontal x 19.6" vertical; 40" diagonal
	Native Resolution	1366x768
	Contrast Ratio	1000:1 (typ)
	Viewing Angles	170° horizontal, 170° vertical
	Response Time	8ms
	Light Source	Long life, 60,000 hrs. (typ)
	Brightness	500 cd/m2 (typ)
	Aspect Ratio	16:9
	Glass Surface	Haze 44%, hard coating (3H)
INPUT	PC	RGB analog (75 ohms, 0.7 Vp-p)
	TV	TV/cable, composite (RCA), component YPbPr/YCbCr, S-video
	Audio	3.5mm mini stereo audio in/out and RCA (left/right) audio in
	RGB Frequency	F _h : 30~64kHz, F _v : 60~75Hz
	Sync	H/V separated (TTL)
	Digital	HDMI (with HDCP and audio support)
	Tuner	NTSC/ATSC
	Speakers	2x10-watt SRS TruSurround XT
COMPATIBILITY	PC	1360x768 (preferred), 1024x768, 1280x768
	FC Mac®*	Power Mac [™] G3/G4/G5 up to 1280x1024, 1280x720 (preferred)
INPUT SIGNAL		
CONNECTOR	TV/Video Comp.	480i, 480p, 720p, 1080i
CONNECTOR	Analog	15-pin mini D-sub (VGA)
	Digital	HDMI
	Power	3-pin plug
POWER	Voltage	AC 90–240V (universal), 60/50Hz
	Consumption	260W (typ)
CONTROLS	Basic	Power, enter, channel +/-, volume +/-, menu
	OnView [®] (PC Mode)	Auto adjust, contrast, brightness, H. position, V. position, H.
		size, fine tune, aspect ratio, information, text/graphic mode,
		color temperature
	(Video Mode)	Picture (contrast, brightness, color, tint, sharpness, aspect ratio,
		color temperature), sound (volume, balance, bass, treble), input
		menu (TV, AV, S-video, YCbCr, YPbPr, HDMI, VGA), parental contro
		(caption, change password, TV ratings, MPAA movie ratings,
		V-chip temporary disable), PIP (input, POP, mode disable,
		audio, SWAP, size/position), set up (OSD H/V position), time
		out, transparency, OSD color, language, memory recall
	(TV Mode)	MTS, TV/CATV, auto scan, set channel, channel delete, label,
		favorite, fine tune
OPERATING	Temperature	32–104°F (0–40°C)
CONDITIONS	Humidity	20–85% (non-condensing)
DIMENSIONS	Physical (mm)	1015mm x 755mm x 280mm (with stand)
(W x H x D)		1015mm x 700mm x 136mm (without stand)
	Physical (in.)	40.0" x 29.7" x 11.0" (with stand)
		40.0" x 27.6" x 5.4" (without stand)
VESA [®] MOUNT		200mm x 200mm
WEIGHT	Net	72.6 lb. (33.0 kg) (with stand) 28.3 kg (without stand)
	Gross	88.0 lb. (40.0 kg) (with stand)
REGULATIONS	51000	cUL, NOM, CB, FCC-B
PACKAGE CONTENTS		LCD TV display, power cable, remote control with batteries,
		RCA A/V cable, Quick Start Guide, User Guide



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789



the choice of professionals

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com *Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [13112-00B-08/06] N4060w-1

For more product information, visit us on the web at ViewSonic.com

Download from Www.Somanuals.com. All Manuals Search And Download.

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com