# **Pro8400**

010

nom

TEXAS INSTRUMENTS

# HIGH BRIGHTNESS

**PROFESSIONAL GRADE INSTALLATION** 

Pro8400

## See it all in any venue.

The ViewSonic<sup>®</sup> Pro8400 is an advanced high brightness DLP<sup>®</sup> installation projector which includes BrilliantColor<sup>™</sup> technology to produce more vibrant colors. The Pro8400 delivers 4000 lumens with a 1920x1080 (1080p) superb image resolution, allowing it to shine in virtually any lighting situation. The Pro8400 provides maximum mounting flexibility with a wide 1.5X optical zoom adjustment and a multitude of connectivity options including Network Display, USB, and WiFi. The filter-less design and long lamp life provide for easy maintenance and low total cost of ownership.

### **OPTIMIZE YOUR OPTIONS**

- > Bright in virtually any setting with 4,000 lumens Ultra-bright 4,000 lumen output makes this the perfect choice for large boardrooms, conference halls and auditoriums.
- > BrilliantColor<sup>™</sup> technology

Latest BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.

#### > Advanced connectivity

With dual HDMI, component, composite and S-video inputs.

#### > Connect anywhere

Present up to 8 projectors at the same time or allow up to 4 presenters to connect to a single projector over wireless or RJ45 network.

> Stay connected

Supports multiple video timing formats from SD (NTSC, PAL & SECAM) to HD 1080p.

> Network control through RJ45

#### > Give Greener presentations and save

Use the Eco mode to achieve lower power consumption, reduce overall noise and extend lamp life.

> Closed captioning

Integrated closed captioning decoder for the hearing impaired.



VIEWSONIC PRODUCTS, PROGRAMS, AND SERVICES



# **Pro8400**

## HIGH BRIGHTNESS 1080P PROJECTOR – PROFESSIONAL GRADE INSTALLATION







#### **Optional Accessories**

> Replacement Lamp	RLC-059
> Universal Ceiling Mount Kit	WMK-005

- > Wireless G Presentation Gateway WPG-360
- > USB Wireless Adapter (802.11 b/g/n) WPD-100
- > Extended Express Exchange® PRJ-EE-08-03

Projection		4:3 Aspect					
Distance		Wide			Tele		
Μ	Feet	Μ	Inches		Μ	Inches	
1.5	4.92	1.22	47.8		0.81	31.8	
1.8	5.90	1.49	57.4		0.97	38.1	
2	6.56	1.62	63.7		1.08	42.4	
3	9.84	2.44	95.8		1.61	63.7	
5	16.40	4.05	159.5		2.69	106.0	
10	32.80	8.11	319.0		5.39	212.1	



DISPLAY	Туре	0.7" Digital Micromirror Device (DLP™)				
	Resolution	1920x1080 (1080p)				
	Lens	1.5× Manual optical zoom / Manual optical focus				
	Keystone	Vertical digital keystone correction: +/- 20 degrees				
	Size	30"–300" / 0.76m–7.6m				
	Throw Distance	0.9m-10m / 3ft-32.8ft 1.4 - 2.14:1				
	Throw Ratio					
	Lamp	280 watt				
	Lamp Life (Normal / Eco-mode)					
	Brightness					
	Contrast Ratio					
	Aspect Ratio					
INPUT SIGNAL	Color Gamut Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N,				
		60), SECAM (B, D, G, K, K1, L), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i and 1080p (24fps, 25pfs and 30fps)				
	Ere en rener					
COMPATIBILITY	Frequency	Fh: 31–91KHz, Fv: 48–85Hz				
	PC	VGA to 1080p				
CONNECTOR	Mac <sup>®</sup>	Up to 1080p				
CONNECTOR	RGB Input	15-pin mini D-sub (x2)				
	RGB Output	15-pin mini D-sub				
	Digital Input	HDMI 1.3 (x2) RCA (x3)				
	Component					
	Composite Input	RCA jack				
	S-video Input	4-pin mini-DIN				
	USB	Mini-B for direct presentation from computer				
		Type A supports JPEG, BMP, TIFF, PNG, GIF from USB flash driv 3.5mm mini jack 3.5mm mini jack				
	Audio Input					
	Audio Output					
	Control	RS-232 (DB-9)				
	Network	RJ-45				
	Screen Trigger	0.35 plug (12V/1A)				
AUDIO	Speaker	10W (x2)				
POWER	Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)				
	Consumption	360W (max) / <1W (stand-by mode)				
CONTROLS	Basic	Power, keystone/arrow keys, left/blank, menu/exit,				
		right/panel key lock, auto, mode/enter, source				
	OSD	Picture: Brightness, Contrast, Color Setting, Keystone,				
		Aspect Ratio, Image, White Intensity, Gamma				
		Computer Image: Frequency, Tracking, H Position, V Position				
		Video Image: Saturation, Sharpnes, Tint				
		Setting: Menu Position, Projection, Signal Type, Lamp				
		Hour, Lamp Hour Reset, Filter Mode, Filter Hours, Filter				
		Hours Reset, Power Saving, Auto Source, Eco-mode, High				
		Altitude, OSD Timeout				
		Advance: Blank Screen, Password Word, Screen Capture,				
		Start up Screen, Digital Zoom, DCR, Close Captions				
OPERATING	Temperature	32°F–104°F (0°C–40°C)				
CONDITIONS		10%–90% (non-condensing)				
CONDITIONS	Humidity Altitude	0~6,000 ft (1,800m), operational up to 10,000 ft (3048m)				
	Normal / Eco-mode	33dB / 29dB				
DIMENSIONS		13.1 × 4.8 × 10.4 (in) / 332.7× 121.9 × 264.2 (mm)				
	Physical Packaging					
	Packaging	16.3 × 7.5 × 14.8 (in) / 414 ×190.5 × 375.9 (mm)				
WEIGHT	Net	8.5 lb (3.86 kg)				
	Gross	11.8 lb (5.36 kg)				
REGULATIONS		CB, RoHS, SVHC, WEEE, UL/cUL, FCC-B, ICES-004, TUV-S				
		(Argentina), NOM, PSB, C-tick, KC, CE, GOST-R, Hygienic,				
		UKrSEPRO, CCC				
PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, HDMI cable				
		remote control/laser with batteries, lens cap, Quick Start				
		Guide, ViewSonic Wizard DVD (with User Guide)				
		3-year limited warranty on parts, 1-year limited warranty				
WARRANTY		s year minited warranty on parts, if year minited warranty				

#### Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

\*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications and availability subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved [15241-00B-09/10] Pro8400-1



For more product information, visit us on the web at ViewSonic.com

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com