PJD7382 ULTRA-SHORT THROW PROJECTOR

Small budget-big presentations

The powerful PJD7382 120Hz 3D-ready projector combines powerful features with RJ45 network capability. The projector offers an extreme short throw ratio - producing a large 80-inch image at a distance of only 39 inches away. With its short throw lens, the PJD7382 saves space by allowing you to place it at the front of your table and still display large, crisp images.

With 3,000 lumens and a 3000:1 contrast ratio, your images look great in a classroom, meeting room or virtually any setting. All these features are packed into an attractive, compact design weighing only 7.7 lb. Multiple preset presentation modes, an increased 40 degree digital vertical keystone correction and digital zoom ensure the best possible image regardless of location. Choose the PJD7382 for up to 6,000 hours of lamp life, low cost replacement lamps, filter-free design and a non-degrading DLP® light engine for the best warranty and low total cost of ownership.
















The short throw lens enables large images to be projected from short distances in small rooms with short throw distances.

A screen size of 80-inch is possible from just 39



Latest BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video.

The sophisticated 6-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.

Off-to-Go feature

This feature allows the busy presneter to simply unplug the projector and go without waiting for the usual cool down phase.

This feature also protects lamp life from sudden power blackout.

Bright in virtually any setting with 3.000 lumens

Packs 3,000 ANSI lumens in just 7.7 pounds, and with a high 3000:1 contrast ratio (typ), your presentations are guaranteed to be vibrant even in the brightest office environment.

Network control through RJ45

Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector lamp status. Use the unique integrated clock to perform commands even when the host PC is powered down.

Crestron RoomView


Worldwide first Crestron RoomView control with management remote contrel software system

Eco-mode extends lamp life

Extend the life of your lamp up to 6,000 hours and reduce noise output.



** Running ECO-mode exclusively can extend lamp life.



PJD7382

Small budget-big presentations





Optional Accessories

Replacement Lamp	···· KLC-05/
Short throw mount	- WMK-025
Wireless G Presentation Gateway	WPG-350
3D goggle	PGD-150

Projec	ction Distance	4:3	Screen Size
М	Feet	М	inch
0.5	1.6	1.0	40
0.7	2.3	1.5	60
1.0	3.3	2.0	80
1.2	3.9	2.5	100
1.5	4.9	3.0	120
1.9	6.2	3.8	150
2.5	8.2	5.1	200
3.	10.2	6.4	250
3.7	7 12.1	7.6	300











ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Model Name		PJD7382
Display	Туре	0.55" Digital Micromirror Device (DLP™)
-1/	Resolution	XGA 1024x768 (Native) / UXGA 1600x1200 (compressed)
	Lens	Fixed Lens / Digital Zoom / Manual Focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Throw Distance	0.5m-3.7m / 1.6ft-12.1ft
		0.61:1
	Throw Ratio	
	Zoom factor	FIXED
	Lamp	210 watt
	Lamp Life (Normal / Eco Mode)	4000 / 6000 hours
	Brightness (Maximum)	3000 Lumens
	Contrast Ratio (Typical)	3000:1
	Colour Depth	24 bits, 16.7M color (8+8+8)
	Colour Wheel	6-Segment RGBCYW / 7200rpm
	Colour Gamut	90% NTSC 1931 CIE
Audio	Speaker	10Wx1
Input Signal	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N,60), SD 480 and 576i (24fps, 25fps and 30fps), ED 480pand 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps,25fps and 30fps)
	F	
Competibilit	Frequency	Fh: 31–100KHz, Fv: 48–120Hz
Compatibility	PC	VGA to UXGA
	Mac	Up to 1400x1050 (may require Mac adapter)
Connector	RGB	Input: 15-pin mini D-sub (x2), Output: 15-pin mini D-sub
	Composite Input	1x RCA jack
	S-Video Input	1x 4-pin mini-DIN
	Audio Input	1x 3.5mm mini jack, 1x RCA (L/R)
	Microphone Input	1x 3.5mm mini Mono jack
	Audio Output	1x 3.5mm mini jack
	Control	RS-232 (9-pin mini-DIN)/RJ-45
	USB	1x Type B
	DC Output	12V
Power	Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)
Power		329W (typ) / 1W (stand-by mode)
1	Power Consumption	
Language		English/ Dutch/French/ Spanish/ Italian/ Korean/
		Thai/Portuguese/ T. Chinese/ S. Chinese/ Japanese/
		Russian/Germany/ Swedish/ Turkish/ Finnish /Polish/ Czech
Controls	Basic	Power, keystone/arrow keys, left/blank,
		menu/exit,right/panel key lock, auto, mode/enter, source
	OSD	(1)Picture: Brightest, contrast, color setting, keystone,
		aspectratio, image, white intensity, gamma, 3D sync, 3D sync invert
		(2)Computer Image Picture: Brightest, contrast, color
		setting, keystone, aspect ratio, image, white intensity, gamma, 3Dsync, 3D sync invert
		(3)Computer Image: Frequency, tracking, H position, V
		position
		(4)Video Image: Saturation, sharpness, tint
		(5)Setting: Menu position, projection, signal type, lamp
		hour,lamp hour reset, filter mode, filter hours, filter hours
		reset, power saving, auto source, Eco-mode, high altitude,
		OSD timeout
Operating	Temperature	0°C-40°C
Condition	Humidity	10%-90% (non-condensing)
Noise Level	Normal / Eco Mode	32dB / 27dB
Dimensions	Physical (W×H×D)	290mm x 126mm x 254mm
Weight	Net	3.5 kg (7.71bs)
Regulations	1101	CB, UL, CUL, FCC (including ICES-003), CE, UL-Argentina, NOM, TUV-GS, GOST-R, SASO, Ukraine, PSB, C-Tick,
		Korean-eK, CCC, Hygiene, WEEE, RoHS
		ViewSonic projector, power cable, VGA cable, laser
Packing Contents		



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com