




# *Personal Systems Reference Lenovo® Consumer Monitors 2005 -2012 Withdrawn*

*Last Update: April 2014 - Version 452*



Lenovo L2363d Wide Monitor


Visit [www.lenovo.com/psref](http://www.lenovo.com/psref) for the latest version

<p>Name <b>LI1962 Wide Flat Panel Monitor</b>                  Case color <b>Black</b>                  Type-model <b>3737-US1</b>                  Panel <b>TFT-LCD, twisted nematic (TN), white LED backlight</b>                  Viewable image size <b>19" (481mm) diagonal</b>                  Max view area (W x H) <b>16.07" x 10.05" / 408.2mm x 255.2mm</b>                  Optimum resolution <b>1440x900</b>                  Max pixel rate <b>205MHz (VGA), 165MHz (DVI)</b>                  Aspect ratio <b>16:10</b>                  Pixel pitch (mm) <b>.284mm</b>                  Dot/Pixel per Inch <b>89 dpi</b>                  Brightness <b>200 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>500:1 (typical)</b>                  Dynamic contrast ratio <b>10,000,000:1</b>                  Pixel response time <b>5ms (typical)</b>                  Viewing angle at 10:1 CR <b>180° (+/- 90°) horizontal, 130° (+/- 65°) vertical</b>                  Stand <b>Tilt adjustable stand</b>                  Bezel width <b>Sides: 0.41" (10.5mm)</b>                  Dimensions (HxWxD) <b>14.08" H x 17.60" W x 7.78" D;                  357.6mm H x 447.0mm W x 197.6mm D</b>                  Power supply <b>27 watts typical, 30 watts maximum,                  &lt;0.5 watts standby/suspend, universal,                  integrated (no external brick-like power supply)</b>                  Weight <b>6.55 lb; 2.97kg</b>                  Limited warranty<sup>4</sup> <b>1 year</b>                  Available date <b>August 2012</b></p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 19-inch monitor</li> <li>• HD support, HDCP-compliant</li> <li>• Built-in VGA and DVI connectors for attachment to two systems concurrently</li> <li>• Compliance with ENERGY STAR 5.1</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows 7 certified</li> </ul>				
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, EDID 1.3A, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR® 5.1</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>FCC Class B</b>                  Environmental <b>TCO (TCO Displays 5.2)                  WEEE (EU Directive 2002/96/EC),                  RoHS (EU Directive 2002/95/EC)</b></p>	 <p style="text-align: center;"><b>LI1962 Wide Monitor</b></p>				
<p>Preset resolutions <b>VGA: 640x350, 640x480, 720x400                  SVGA: 800x600, 832x624                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1280x800, 1366x768                  WXGA+: 1440x900</b>                  Presets / user settings <b>Presets: 24;                  user settings: 20</b></p>					
<p>Viewing adjustments <b>Tilt: 18° back, -4° forward</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (control buttons on front) for automatic image setup, dual input and NOVO vision</b>                  Multiple input <b>Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog, blue                  (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b></b>                  Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>					
<p>Ship group <b>Monitor, attached Stand and Base, Warranty information, setup guide,                  1 CD with multilingual User's Guide, setup test pattern and monitor installation files,                  1.8 meter analog signal cable, 1.8 meter black power cord</b></p>					
<p style="text-align: center;"><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>⇒ <b>1 year limited warranty<sup>4</sup></b></li> <li>⇒ <b>Advanced Exchange Service at 1-877-453-6686</b></li> <li>⇒ <b>Replacement normally arrives in five business days, excluding holidays</b></li> <li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<p style="text-align: center;"><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>                  See all monitors at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				


See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014

<p>Name <b>L2062 Wide Flat Panel Monitor</b>                  Case color <b>High gloss black with metal gray</b>                  Type-model <b>1173-US1</b>                  Panel <b>TFT-LCD, twisted nematic (TN), white LED backlight</b>                  Viewable image size <b>20.0" / 508mm</b> (diagonal)                  Max view area (W x H) <b>17.4" x 9.8" / 443mm x 249mm</b>                  Optimum resolution <b>1600x900</b>                  Max pixel rate <b>153 MHz</b>                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>0.277mm</b>                  Dot/Pixel per Inch <b>92 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Dynamic contrast ratio <b>5,000,000:1</b>                  Pixel response time <b>5ms (typical)</b>                  Color gamut <b>72%</b>                  Anti-reflective <b>Anti-reflective, anti-glare</b>                  Viewing angle at 10:1 CR <b>170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</b>                  Stand <b>Tilt adjustable stand</b>                  Bezel width <b>Sides: 0.63" (16mm);</b>                  Dimensions (HxWxD) <b>14.3" H x 18.9" W x 6.9" D;                  362.5mm H x 480.0mm W x 174.8mm D</b>                  Power supply <b>17 watts typical, 22 watts maximum,                  &lt;1 watts standby/suspend, universal,                  integrated (no external brick-like power supply)</b>                  Weight <b>7.99 lb; 3.63 kg</b>                  Limited warranty<sup>4</sup> <b>1 year</b>                  (includes backlight)                  Available date <b>May 2011</b></p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 20-inch monitor</li> <li>• View images in a 16x9 wide aspect ratio</li> <li>• High-bandwidth Digital Content Protection (HDCP)-compliant</li> <li>• Tilt and cable management stand</li> <li>• Compliance with ENERGY STAR 5.0</li> <li>• Mercury-free and Arsenic-free panel glass</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows® 7 certified</li> </ul>				
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR® 5.0</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>FCC Class B</b>                  Environmental <b>TCO (TCO Displays 5.2),                  WEEE (EU Directive 2002/96/EC),                  RoHS (EU Directive 2002/95/EC)</b></p>	<div style="text-align: center;">  <p><b>Lenovo L2062 Wide Monitor</b></p> </div>				
<p>Preset resolutions <b>VGA: 640x350, 640x480, 720x400                  SVGA: 800x600, 832x624                  XGA: 1024x768, 1152x864                  WXGA: 1366x768                  SXGA: 1280x1024                  WXGA+: 1440 x 900, 1600x900</b>                  Presets / user settings <b>Standard presets: 24; user settings: 20</b></p>					
<p>Viewing adjustments <b>Tilt: 20° back, -5° forward; detachable stand</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (control buttons on front) for automatic image setup</b>                  USB hub <b>None</b>                  Multiple input <b>Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog, blue                  (2) Digital Visual Interface (DVI-D) for digital attach [white], <b>HDCP-compliant</b></b>                  Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>	<p><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>                  More information at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington® MicroSaver® Cable Lock		73P2582			
Kensington Twin Head Cable Lock	45K1620				
<p>Ship group <b>Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, analog signal cable, 1.8m power cord</b></p>					
<p style="text-align: center;"><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>↪ <b>1 year limited warranty<sup>4</sup></b></li> <li>↪ <b>Advanced Exchange Service at 1-877-453-6686</b></li> <li>↪ <b>Replacement normally arrives in five business days, excluding holidays</b></li> <li>↪ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>↪ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>					


See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014

<p>Name <b>LI2031 Wide Flat Panel Monitor</b>                  Case color <b>High gloss black</b>                  Type-model <b>3728-US1</b>                  Panel <b>TFT-LCD, twisted nematic (TN), white LED backlight</b>                  Viewable image size <b>20" (508mm) diagonal</b>                  Max view area (W x H) <b>18.22" x 10.71" / 462.8mm x 272.0mm</b>                  Optimum resolution <b>1600x900</b>                  Max pixel rate <b>205MHz (VGA), 165MHz (DVI)</b>                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>.277mm</b>                  Dot/Pixel per Inch <b>92 dpi</b>                  Brightness <b>200 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>500:1 (typical)</b>                  Dynamic contrast ratio <b>10,000,000:1</b>                  Pixel response time <b>5ms (typical)</b>                  Viewing angle at 10:1 CR <b>160° (+/- 80°) horizontal, 160° (+/- 80°) vertical</b>                  Stand <b>Tilt adjustable stand</b>                  Bezel width <b>Sides: 0.40" (10.2mm)</b>                  Dimensions (HxWxD) <b>13.78" H x 18.83" W x 7.78" D;                  350.0mm H x 478.2mm W x 197.6mm D</b>                  Power supply <b>27 watts typical, 30 watts maximum,                  &lt;0.5 watts standby/suspend, universal,                  integrated (no external brick-like power supply)</b>                  Weight <b>6.79 lb; 3.08kg</b>                  Limited warranty<sup>4</sup> <b>1 year</b>                  Available date <b>July 2012</b></p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 20-inch monitor</li> <li>• HD support, HDCP-compliant</li> <li>• Built-in VGA and DVI connectors for attachment to two systems concurrently</li> <li>• Compliance with ENERGY STAR 5.1</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows 7 certified</li> </ul>				
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, EDID 1.3A, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR® 5.1</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>FCC Class B</b>                  Environmental <b>TCO (TCO Displays 5.2)                  WEEE (EU Directive 2002/96/EC),                  RoHS (EU Directive 2002/95/EC)</b></p>	 <p style="text-align: center;"><b>LI2031 Wide Monitor</b></p>				
<p>Preset resolutions <b>VGA: 640x350, 640x480, 720x400                  SVGA: 800x600, 832x624                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1280x800, 1366x768                  WXGA+: 1440x900, 1600x900</b>                  Presets / user settings <b>Presets: 24;                  user settings: 20</b></p>					
<p>Viewing adjustments <b>Tilt: 18° back, -4° forward</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (control buttons on front) for automatic image setup, dual input and NOVO vision</b>                  Multiple input <b>Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog, blue                  (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b></b>                  Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>	<p><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>⇒ <b>1 year limited warranty<sup>4</sup></b></li> <li>⇒ <b>Advanced Exchange Service at 1-877-453-6686</b></li> <li>⇒ <b>Replacement normally arrives in five business days, excluding holidays</b></li> <li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>				
<p>Ship group <b>Monitor, attached Stand and Base, Warranty information, setup guide,                  1 CD with multilingual User's Guide, setup test pattern and monitor installation files,                  1.8 meter analog signal cable, 1.8 meter black power cord</b></p>		<p><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>                  See all monitors at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock
Kensington MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				


See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014

<p>Name <b>LI2221s Wide Flat Panel Monitor</b>                  Case color <b>High gloss black</b>                  Type-model <b>3708-US1 / 3708-US2</b>                  Panel TFT-LCD, In-Plane Switching (IPS), <b>white LED backlight</b>                  Viewable image size <b>21.5" (546mm) diagonal</b>                  Max view area (W x H) <b>18.77" x 10.56" / 476.6mm x 268.1mm</b>                  Optimum resolution <b>1920x1080</b>                  Max pixel rate <b>205MHz (VGA), 165MHz (DVI)</b>                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>.248mm</b>                  Dot/Pixel per Inch <b>103 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Dynamic contrast ratio <b>10,000,000:1</b>                  Pixel response time <b>14ms (typical)</b>                  Viewing angle at 10:1 CR <b>178° (+/- 89°) horizontal, 178° (+/- 89°) vertical</b>                  Stand <b>Tilt adjustable stand</b>                  Bezel width <b>Sides: 0.65" (16.5mm)</b>                  Dimensions (HxWxD) <b>15.08" H x 20.08" W x 6.77" D; 383.0mm H x 510.0mm W x 172.0mm D</b>                  Power supply <b>27 watts typical, 37 watts maximum, &lt;0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)</b>                  Weight <b>7.05 lb; 3.20kg</b>                  Limited warranty<sup>4</sup> <b>1 year</b>                  Available date <b>October 2012</b></p>	<p style="text-align: center;"><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 21.5-inch monitor</li> <li>• 1080p full HD support, HDCP-compliant</li> <li>• Built-in VGA and DVI connectors for attachment to two systems concurrently</li> <li>• Compliance with ENERGY STAR</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows 7 certified</li> </ul>				
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, EDID 1.3, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR<sup>®3</sup> qualified</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>FCC Class B</b>                  Environmental <b>TCO (TCO Displays 5.2)                  WEEE (EU Directive 2002/96/EC),                  RoHS (EU Directive 2002/95/EC)</b></p>	<div style="text-align: center;">  <p><b>LI2221s Wide Monitor</b></p> </div>				
<p>Preset resolutions <b>VGA: 640x350, 640x480, 720x400                  SVGA: 800x600, 832x624                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1366x768                  WXGA+: 1440x900, 1600x900                  WSXGA+: 1680x1050                  WUXGA: 1920x1080</b>                  Presets / user settings <b>Presets: 24;                  user settings: 24</b></p>					
<p>Viewing adjustments <b>Tilt: 20° back, -5° forward</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (control touch buttons on front) for automatic image setup, dual input and NOVO vision</b>                  Multiple input <b>Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog                  (2) Digital Visual Interface (DVI-D), digital, <b>HDCP-compliant</b></b>                  Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI<sup>®</sup> (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>	<p>Ship group <b>Monitor, attached stand, setup guide,                  1 CD with multilingual User's Guide, setup test pattern and monitor installation files,                  1.8 meter analog signal cable, 1.8 meter black power cord</b></p>				
<p style="text-align: center;"><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>⇒ <b>1 year limited warranty<sup>4</sup></b></li> <li>⇒ <b>Advanced Exchange Service at 1-877-453-6686</b></li> <li>⇒ <b>Replacement normally arrives in five business days, excluding holidays</b></li> <li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<p style="text-align: center;"><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>                  See all monitors at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				


See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014

<p>Name <b>LI2231 Wide Flat Panel Monitor</b>                  Case color <b>High gloss black</b>                  Type-model <b>4374-US1</b>                  Panel <b>TFT-LCD, twisted nematic (TN), white LED backlight</b>                  Viewable image size <b>21.5" (546mm) diagonal</b>                  Max view area (W x H) <b>18.77" x 10.56" / 476.6mm x 268.1mm</b>                  Optimum resolution <b>1920x1080</b>                  Max pixel rate <b>205MHz (VGA), 165MHz (DVI)</b>                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>.284mm</b>                  Dot/Pixel per Inch <b>89 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Dynamic contrast ratio <b>10,000,000:1</b>                  Pixel response time <b>5ms (typical)</b>                  Viewing angle at 10:1 CR <b>170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</b>                  Stand <b>Tilt adjustable stand</b>                  Bezel width <b>Sides: 0.62" (15.8mm)</b>                  Dimensions (HxWxD) <b>14.45" H x 20.06" W x 7.78" D;                  367.1mm H x 509.6mm W x 197.6mm D</b>                  Power supply <b>38 watts typical, 42 watts maximum,                  &lt;0.5 watts standby/suspend, universal,                  integrated (no external brick-like power supply)</b>                  Weight <b>7.05 lb; 3.20kg</b>                  Limited warranty<sup>4</sup> <b>1 year</b>                  Available date <b>July 2012</b></p>	<p style="text-align: center;"><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 21.5-inch monitor</li> <li>• 1080p full HD support, HDCP-compliant</li> <li>• Built-in VGA and DVI connectors for attachment to two systems concurrently</li> <li>• Compliance with ENERGY STAR 5.1</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows 7 certified</li> </ul>				
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, EDID 1.3A, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR® 5.1</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>FCC Class B</b>                  Environmental <b>TCO (TCO Displays 5.2)                  WEEE (EU Directive 2002/96/EC),                  RoHS (EU Directive 2002/95/EC)</b></p>	<div style="text-align: center;">  <p><b>LI2231 Wide Monitor</b></p> </div>				
<p>Preset resolutions <b>VGA: 640x350, 640x480, 720x400                  SVGA: 800x600, 832x624                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1280x800, 1366x768                  WXGA+: 1440x900,                  WUXGA: 1920x1080</b>                  Presets / user settings <b>Presets: 24;                  user settings: 20</b></p>					
<p>Viewing adjustments <b>Tilt: 18° back, -4° forward</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (control buttons on front) for automatic image setup, dual input and NOVO vision</b>                  Multiple input <b>Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog, blue                  (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b></b>                  Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>					
<p>Ship group <b>Monitor, attached Stand and Base, Warranty information, setup guide,                  1 CD with multilingual User's Guide, setup test pattern and monitor installation files,                  1.8 meter analog signal cable, 1.8 meter black power cord</b></p>					
<p style="text-align: center;"><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>↪ <b>1 year limited warranty<sup>4</sup></b></li> <li>↪ <b>Advanced Exchange Service at 1-877-453-6686</b></li> <li>↪ <b>Replacement normally arrives in five business days, excluding holidays</b></li> <li>↪ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>↪ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<p style="text-align: center;"><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				

See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014


<p>Name <b>L2262 Wide Flat Panel Monitor</b>                  Case color <b>High gloss black with metal gray</b>                  Type-model <b>0560-US1</b>                  Panel <b>TFT-LCD, twisted nematic (TN), white LED backlight</b>                  Viewable image size <b>21.5" (546mm) diagonal</b>                  Max view area (W x H) <b>18.8" x 10.6" / 476.6mm x 268.1mm</b>                  Optimum resolution <b>1920x1080</b>                  Max pixel rate <b>VGA: 205MHz; DVI: 165MHz</b>                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>.248mm</b>                  Dot/Pixel per Inch <b>103 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Dynamic contrast ratio <b>5,000,000:1</b>                  Pixel response time <b>5ms (typical)</b>                  Color gamut <b>72%</b>                  Vertical frequency <b>50 to 76Hz</b>                  Horizontal frequency <b>30 to 83kHz</b>                  Viewing angle at 10:1 CR <b>170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</b>                  Stand <b>Tilt adjustable stand</b>                  Bezel width <b>Sides: 0.75" (19.0mm); top: 0.72" (18.2mm); bottom: 1.07" (27.3mm)</b>                  Dimensions (HxWxD) <b>15.08" H x 20.31" W x 7.07" D; 383mm H x 516mm W x 179.6mm D</b>                  Power supply <b>23 watts typical, 27 watts maximum, &lt;1 watts standby/suspend, universal, integrated (no external brick-like power supply)</b>                  Weight <b>9.13 lb; 4.14 kg</b>                  Limited warranty<sup>4</sup> <b>1 year (includes backlight)</b>                  Available date <b>June 2011</b></p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 21.5-inch monitor with white LED backlight</li> <li>• View images in a 16x9 wide aspect ratio</li> <li>• High-bandwidth Digital Content Protection (HDCP)-compliant</li> <li>• Tilt and cable management stand</li> <li>• Compliance with ENERGY STAR 5.0</li> <li>• Touch sensitive control buttons can give user new comfortable experiences</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows® 7 certified</li> </ul>				
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR<sup>®</sup> 5.0</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>FCC Class B</b>                  Environmental <b>TCO (TCO Displays 5.1), WEEE (EU DIRECTIVE 2002/96/EC), RoHS (EU DIRECTIVE 2002/95/EC)</b></p>	<div style="text-align: center;">  <p><b>Lenovo L2262 Wide Monitor</b></p> </div>				
<p>Preset resolutions <b>VGA: 640x350, 640x480                  SVGA: 800x600, 832x624                  XGA: 1024x768,                  XGA+: 1152x864                  SXGA: 1280x1024                  HD: 1366x768                  WXGA+: 1440x900                  WSXGA+: 1680x1050                  Full HD: 1920x1080</b>                  Presets / user settings <b>Standard presets: 26; user settings: 20</b></p>					
<p>Viewing adjustments <b>Tilt: 20° back, -5° forward; detachable stand</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (touch sensitive buttons on front) for automatic image setup, dual input, brightness, and NOVO vision</b>                  USB hub <b>None</b>                  Camera <b>None</b>                  Multiple input <b>Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog, blue                  (2) Digital Visual Interface (DVI-D) for digital attach [white], <b>HDCP-compliant</b></b>                  Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI<sup>®</sup> (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>	<p>Ship group <b>Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter black power cord</b></p>				
<p style="text-align: center;"><b>Limited Warranty</b></p> <p>↪ <b>1 year limited warranty<sup>4</sup></b>                  ↪ <b>Advanced Exchange Service at 1-877-453-6686</b>                  ↪ <b>Replacement normally arrives in five business days, excluding holidays</b>                  ↪ <b>Lenovo pays all shipping costs for valid warranty claims<sup>5</sup></b>                  ↪ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></p>	<p style="text-align: center;"><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>                  More information at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington® MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				

See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014

<p>Name <b>LI2321s Wide Flat Panel Monitor</b>                  Case color <b>High gloss black</b>                  Type-model <b>4373-US1 / 4373-US2</b>                  Panel <b>TFT-LCD, In-Plane Switching (IPS), white LED backlight</b></p> <p>Viewable image size <b>23.0" (584mm) diagonal</b>                  Max view area (W x H) <b>20.05" x 11.28" / 509.2mm x 286.4mm</b>                  Optimum resolution <b>1920x1080</b>                  Max pixel rate <b>205MHz (VGA), 165MHz (HDMI/DVI)</b>                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>.265mm</b>                  Dot/Pixel per Inch <b>96 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Dynamic contrast ratio <b>10,000,000:1</b>                  Pixel response time <b>14ms (typical)</b>                  Viewing angle at 10:1 CR <b>178° (+/- 89°) horizontal, 178° (+/- 89°) vertical</b></p> <p>Stand <b>Tilt adjustable stand</b>                  Bezel width <b>Sides: 0.72" (18.4mm)</b>                  Dimensions (HxWxD) <b>15.87" H x 21.57" W x 7.27" D;                  403.1mm H x 548.0mm W x 184.6mm D</b></p> <p>Power supply <b>35 watts typical, 42 watts maximum,                  &lt;0.5 watts standby/suspend, universal,                  integrated (no external brick-like power supply)</b></p> <p>Weight <b>7.56 lb; 3.43kg</b>                  Limited warranty<sup>4</sup> <b>1 year</b>                  Available date <b>October 2012</b></p>	<p style="text-align: center;"><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 23-inch monitor</li> <li>• 1080p full HD support, HDCP-compliant</li> <li>• Built-in VGA, DVI and HDMI 1.3 connectors for attachment to three systems concurrently</li> <li>• Compliance with ENERGY STAR</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows 7 certified</li> </ul>				
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, EDID 1.3, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR<sup>®3</sup> qualified</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>FCC Class B</b>                  Environmental <b>TCO (TCO Displays 5.2)                  WEEE (EU Directive 2002/96/EC),                  RoHS (EU Directive 2002/95/EC)</b></p>	<div style="text-align: center;">  <p><b>LI2321s Wide Monitor</b></p> </div>				
<p>Preset resolutions <b>VGA: 640x350, 640x480, 720x400                  SVGA: 800x600, 832x624                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1366x768                  WXGA+: 1440x900, 1600x900                  WSXGA+: 1680x1050                  WUXGA: 1920x1080</b></p> <p>Presets / user settings <b>Presets: 24;                  user settings: 24</b></p>					
<p>Viewing adjustments <b>Tilt: 20° back, -5° forward</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (control touch buttons on front) for automatic image setup, change input and NOVO vision</b>                  Multiple input <b>Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog                  (2) Digital Visual Interface (DVI-D), digital, <b>HDCP-compliant</b>                  (3) HDMI (1.3), digital, <b>HDCP-compliant</b></b></p> <p>Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI<sup>®</sup> (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>	<p>Ship group <b>Monitor, attached stand, setup guide,                  1 CD with multilingual User's Guide, setup test pattern and monitor installation files,                  1.8 meter analog signal cable, 1.8 meter black power cord</b></p>				
<p style="text-align: center;"><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>⇒ <b>1 year limited warranty<sup>4</sup></b></li> <li>⇒ <b>Advanced Exchange Service at 1-877-453-6686</b></li> <li>⇒ <b>Replacement normally arrives in five business days, excluding holidays</b></li> <li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>5</sup></b></li> <li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<p style="text-align: center;"><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>                  See all monitors at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				


See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014



<p>Name <b>LI2331 Wide Flat Panel Monitor</b>                  Case color <b>High gloss black</b>                  Type-model <b>3686-US1</b>                  Panel <b>TFT-LCD, twisted nematic (TN), white LED backlight</b>                  Viewable image size <b>23.0" (584mm) diagonal</b>                  Max view area (W x H) <b>20.05" x 11.28" / 509.2mm x 286.4mm</b>                  Optimum resolution <b>1920x1080</b>                  Max pixel rate <b>205MHz (VGA), 165MHz (HDMI/DVI)</b>                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>.265mm</b>                  Dot/Pixel per Inch <b>96 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Dynamic contrast ratio <b>10,000,000:1</b>                  Pixel response time <b>5ms (typical)</b>                  Viewing angle at 10:1 CR <b>170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</b>                  Stand <b>Tilt adjustable stand</b>                  Bezel width <b>Sides: 0.62" (15.8mm)</b>                  Dimensions (HxWxD) <b>15.34" H x 21.60" W x 8.31" D;                  389.6mm H x 548.4mm W x 211.2mm D</b>                  Power supply <b>38 watts typical, 42 watts maximum,                  &lt;0.5 watts standby/suspend, universal,                  integrated (no external brick-like power supply)</b>                  Weight <b>8.16 lb; 3.70kg</b>                  Limited warranty<sup>4</sup> <b>1 year</b>                  Available date <b>July 2012</b></p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 23-inch monitor</li> <li>• 1080p full HD support, HDCP-compliant</li> <li>• Built-in VGA, DVI and HDMI 1.4 connectors for attachment to three systems concurrently</li> <li>• Compliance with ENERGY STAR 5.1</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows 7 certified</li> </ul>
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/C1, EDID 1.3A, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR® 5.1</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>FCC Class B</b>                  Environmental <b>TCO (TCO Displays 5.2)                  WEEE (EU Directive 2002/96/EC),                  RoHS (EU Directive 2002/95/EC)</b></p>	 <p style="text-align: center;"><b>LI2331 Wide Monitor</b></p>
<p>Preset resolutions <b>VGA: 640x350, 640x480, 720x400                  SVGA: 800x600, 832x624                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1280x800, 1366x768                  WXGA+: 1440x900,                  WUXGA: 1920x1080</b>                  Presets / user settings <b>Presets: 24;                  user settings: 20</b></p>	
<p>Viewing adjustments <b>Tilt: 18° back, -4° forward</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (control buttons on front) for automatic image setup, change input and NOVO vision</b>                  Multiple input <b>Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog, blue                  (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>                  (3) HDMI (1.4), digital, black, <b>HDCP-compliant</b></b>                  Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>	
<p>Ship group <b>Monitor, attached Stand and Base, Warranty information, setup guide,                  1 CD with multilingual User's Guide, setup test pattern and monitor installation files,                  1.8 meter analog signal cable, 1.8 meter black power cord</b></p>	


<p style="text-align: center;"><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>↪ <b>1 year limited warranty<sup>4</sup></b></li> <li>↪ <b>Advanced Exchange Service at 1-877-453-6686</b></li> <li>↪ <b>Replacement normally arrives in five business days, excluding holidays</b></li> <li>↪ <b>Lenovo pays all shipping costs for valid warranty claims<sup>5</sup></b></li> <li>↪ <b>24x7<sup>6</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<p style="text-align: center;"><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				

See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014


<p>Name <b>LI2361d Wide Flat Panel Monitor</b>                  Case color <b>High gloss black with metal gray</b>                  Type-model <b>1192-US1</b>                  Panel <b>TFT-LCD, twisted nematic (TN), white LED backlight</b>                  Viewable image size <b>23.0" (584mm) diagonal</b>                  Max view area (W x H) <b>20.04" x 11.28" / 509.2mm x 286.4mm</b>                  Optimum resolution <b>1920x1080</b>                  Max pixel rate <b>205MHz (VGA), 165MHz (HDMI/DVI)</b>                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>.265mm</b>                  Dot/Pixel per Inch <b>96 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Dynamic contrast ratio <b>10,000,000:1</b>                  Pixel response time <b>5ms (typical)</b>                  Viewing angle at 10:1 CR <b>170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</b>                  Stand <b>Tilt adjustable stand</b>                  Bezel width <b>Sides: 0.74" (18.7mm)</b>                  Dimensions (HxWxD) <b>16.18" H x 21.61" W x 7.47" D;                  411.0mm H x 549.0mm W x 189.8mm D</b>                  Power supply <b>40 watts typical, 45 watts maximum,                  &lt;1 watts standby/suspend, universal,                  integrated (no external brick-like power supply)</b>                  Weight <b>11.0 lb; 5.0kg</b>                  Limited warranty<sup>4</sup> <b>1 year</b>                  Available date <b>January 2012</b></p>	<p style="text-align: center;"><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 23-inch monitor</li> <li>• 1080p full HD support, HDCP-compliant</li> <li>• Lenovo's 3D monitor, supports new FPR 3D technology (FPR: Film-type Patterned Retarder)</li> <li>• Built-in VGA, DVI and HDMI 1.4 connectors for attachment to three systems concurrently</li> <li>• Compliance with ENERGY STAR 5.1</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows 7 certified</li> </ul>
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, EDID 1.4A, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR® 5.1</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>FCC Class B</b>                  Environmental <b>WEEE (EU Directive 2002/96/EC),                  RoHS (EU Directive 2002/95/EC)</b></p> <p>Preset resolutions <b>VGA: 640x350, 640x480, 720x400                  SVGA: 800x600, 832x624                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1280x768, 1280x800, 1366x768                  WXGA+: 1440x900, 1600x900                  WSXGA+: 1680x1050                  WUXGA: 1920x1080</b></p> <p>Presets / user settings <b>Presets: 26 (VGA), 24 (HDMI);                  user settings: 20</b></p>	 <p style="text-align: center;"><b>LI2361d Wide Monitor</b></p>
<p>Viewing adjustments <b>Tilt: 20° back, -5° forward</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (control buttons on front) for automatic image setup and adjustment for brightness</b>                  Multiple input <b>Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>                  (2) HDMI (1.4), digital, black, <b>HDCP-compliant</b>                  (3) VGA 15-pin D-shell, analog, blue</b>                  Signal cables <b>detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>	
<p>Ship group <b>Monitor, attached Stand and Base, 3D glasses, 3D poster, Monitor shopping bag, Warranty information,                  1 CD with multilingual User's Guide, quick setup guide and monitor installation files,                  1.8 meter analog signal cable, 1.8 meter black power cord</b></p>	

<p style="text-align: center;"><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>↪ <b>1 year limited warranty<sup>4</sup></b></li> <li>↪ <b>Advanced Exchange Service at 1-877-453-6686</b></li> <li>↪ <b>Replacement normally arrives in five business days, excluding holidays</b></li> <li>↪ <b>Lenovo pays all shipping costs for valid warranty claims<sup>5</sup></b></li> <li>↪ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<p style="text-align: center;"><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				

See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014


<p>Name <b>L2362p Wide Flat Panel Monitor</b>                  Case color <b>High gloss black with metal gray</b>                  Type-model <b>0559-US1</b>                  Panel <b>TFT-LCD, twisted nematic (TN), white LED backlight</b>                  Viewable image size <b>23.0" (584mm) diagonal</b>                  Max view area (W x H) <b>20.0" x 11.3" / 509.2mm x 286.4mm</b>                  Optimum resolution <b>1920x1080</b>                  Max pixel rate <b>VGA: 205MHz; HDMI: 165MHz</b>                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>.265mm</b>                  Dot/Pixel per Inch <b>96 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Dynamic contrast ratio <b>5,000,000:1</b>                  Pixel response time <b>5ms (typical)</b>                  Color gamut <b>72%</b>                  Vertical frequency <b>50 to 75Hz</b>                  Horizontal frequency <b>30 to 83kHz</b>                  Viewing angle at 10:1 CR <b>170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</b>                  Stand <b>Tilt and swivel adjustable stand</b>                  Bezel width <b>Sides: 0.74" (18.7mm); top: 1.05" (26.7mm); bottom: 1.06" (26.8mm)</b>                  Dimensions (HxWxD) <b>16.18" H x 21.61" W x 7.47" D; 411mm H x 549mm W x 189.8mm D</b>                  Power supply <b>40 watts typical, 45 watts maximum, &lt;1 watts standby/suspend, universal, integrated (no external brick-like power supply)</b>                  Weight <b>11.79 lb; 5.35 kg</b>                  Limited warranty<sup>4</sup> <b>1 year (includes backlight)</b>                  Available date <b>July 2011</b></p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 23-inch monitor with white LED backlight</li> <li>• View images in a 16x9 wide aspect ratio</li> <li>• 1080p full HD support, HDCP-compliant</li> <li>• Tilt, swivel, and cable management stand</li> <li>• Compliance with ENERGY STAR 5.0</li> <li>• Integrated camera (0.3 megapixel) and digital microphone</li> <li>• Internal speaker (3 watts x 2) on bottom</li> <li>• Integrated USB 2.0 Hub (1 port into PC, 4 ports for accessories)</li> <li>• Touch sensitive control buttons can give user new comfortable experiences</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows® 7 certified</li> </ul>				
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR<sup>®</sup> 5.0</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>FCC Class B</b>                  Environmental <b>TCO (TCO Displays 5.1), WEEE (EU DIRECTIVE 2002/96/EC), RoHS (EU DIRECTIVE 2002/95/EC)</b></p>	 <p><b>Lenovo L2362p Wide Monitor</b></p>				
<p>Preset resolutions (VGA) <b>VGA: 640x480                  SVGA: 800x600                  XGA: 1024x768                  XGA+: 1152x864                  SXGA: 1280x1024                  HD: 1366x768                  WXGA+: 1440x900, 1600x900                  WSXGA+: 1680x1050                  Full HD: 1920x1080</b></p> <p>Presets / user settings <b>Standard presets: VGA: 26; HDMI: 24; user settings: 20</b></p>					
<p>Viewing adjustments <b>Tilt: 20° back, -5° forward; swivel: +/-150°; detachable stand</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (touch sensitive buttons on front) for volume up/down, mute, automatic image setup, dual input, brightness, and NOVO vision</b>                  USB hub <b>USB 2.0 Hub (1 port into PC, 4 ports for accessories)</b>                  Camera <b>Integrated camera (0.3 megapixel) and digital microphone</b>                  Speaker <b>Internal speaker (3 watts x 2) on bottom, audio in jack (3.5mm) and audio out jack (3.5mm) on rear</b>                  Multiple input <b>Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog, blue                  (2) HDMI (1.3), digital, black, <b>HDCP-compliant</b></b>                  Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter                  (2) detachable, HDMI at each end, digital, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI<sup>®</sup> (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>	<p>Viewing adjustments <b>Tilt: 20° back, -5° forward; swivel: +/-150°; detachable stand</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (touch sensitive buttons on front) for volume up/down, mute, automatic image setup, dual input, brightness, and NOVO vision</b>                  USB hub <b>USB 2.0 Hub (1 port into PC, 4 ports for accessories)</b>                  Camera <b>Integrated camera (0.3 megapixel) and digital microphone</b>                  Speaker <b>Internal speaker (3 watts x 2) on bottom, audio in jack (3.5mm) and audio out jack (3.5mm) on rear</b>                  Multiple input <b>Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog, blue                  (2) HDMI (1.3), digital, black, <b>HDCP-compliant</b></b>                  Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter                  (2) detachable, HDMI at each end, digital, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI<sup>®</sup> (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>				
<p>Ship group <b>Monitor, attached stand, Setup poster, Warranty Information, CD with multilingual User's Guide and monitor installation files, clean cloth, 1.8 meter analog signal cable, 1.8 meter HDMI cable, 1.8 meter USB cable, 1.8 meter power cord, 1.8 meter audio cable</b></p>	<p><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>                  More information at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington® MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				
<p><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>↪ <b>1 year limited warranty<sup>4</sup></b></li> <li>↪ <b>Advanced Exchange Service at 1-877-453-6686</b></li> <li>↪ <b>Replacement normally arrives in five business days, excluding holidays</b></li> <li>↪ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>↪ <b>24x7<sup>7</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>					

See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014

<p>Name <b>L2363d Wide Flat Panel Monitor</b>                  Case color <b>High gloss black with metal gray</b>                  Type-model <b>4452-US1</b>                  Panel TFT-LCD, twisted nematic (TN), CCFL backlight                  Viewable image size <b>23.0" (584mm)</b> diagonal                  Max view area (W x H) 20.04" x 11.28" / 509.2mm x 286.4mm                  Optimum resolution <b>1920x1080</b>                  Max pixel rate 290MHz (DVI), 165MHz (HDMI)                  Aspect ratio 16:9                  Pixel pitch (mm) .265mm                  Dot/Pixel per Inch 96 dpi                  Brightness 400 nits or cd/m<sup>2</sup> (typical)                  Contrast ratio 1000:1 (typical)                  Dynamic contrast ratio 20000:1                  Pixel response time 5ms (typical)                  Anti-reflective Anti-reflective, anti-glare                  Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical                  Stand Tilt adjustable stand                  Bezel width <i>Sides:</i> 1.13" (28.7mm)                  Dimensions (HxWxD) 16.69" H x 22.40" W x 6.57" D;                  423.8mm H x 569.0mm W x 167.0mm D                  Power supply 55 watts typical, 60 watts maximum,                  &lt;2 watts standby/suspend, universal,                  integrated (no external brick-like power supply)                  Weight 13.2 lb; 6.0kg                  Limited warranty<sup>4</sup> <b>1 year</b> (includes backlight)                  Available date April 2011</p>	<p style="text-align: center;"><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 23-inch monitor</li> <li>• 1080p full HD support, HDCP-compliant</li> <li>• Lenovo's first 3D monitor, supports NVIDIA® 3D Vision™ (requires selected NVIDIA graphics card configurations)</li> <li>• Supports 120Hz refresh rate</li> <li>• Integrated 3D Web Camera to record 3D images</li> <li>• Built-in DVI and HDMI 1.3 connectors for attachment to two systems concurrently</li> <li>• 10-60 degree easily adjustable stand and VESA mount</li> <li>• Compliance with ENERGY STAR 5.0</li> <li>• Arsenic free glass</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows 7 certified</li> </ul>
<p>VESA-compliant<sup>2</sup> VESA DDC2B/CI, EDID 1.3, VESA DPMS-compliant                  Power management ENERGY STAR<sup>®</sup> 5.0                  Ergonomics ISO 9241-307                  Emission standards FCC Class B                  Environmental WEEE (EU Directive 2002/96/EC),                  RoHS (EU Directive 2002/95/EC)</p>	<div style="text-align: center;">  <p><b>L2363d Wide Monitor</b></p> </div>
<p>Preset resolutions                  VGA: 640x350, 640x480, 720x400                  SVGA: 800x600, 832x624                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1366x768                  WXGA+: 1440x900, 1600x900                  WSXGA+: 1680x1050                  WUXGA: 1920x1080 (support 120Hz refresh rate for 3D display mode)                  Presets / user settings Presets: 29 (DVI), 24 (HDMI);                  user settings: 20</p>	
<p>Viewing adjustments <i>Tilt:</i> 10°-60° back, 0° forward; adjustable stand                  Rotating screen None                  On screen display On screen display with digital user controls (8 languages)                  Control features Direct access (control buttons on front) for automatic image setup and adjustment for brightness                  USB hub USB 2.0 Hub (1 port into PC, 3 ports for accessories)                  Camera module Integrated camera (3D, 0.3 megapixel) and dual array microphone                  3D Vision kit NVIDIA 3D Vision kit includes GeForce 3D Vision active shutter glasses, 3D Vision USB controller/IR emitter                  Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)                  Monitor connectors (1) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>                  (2) HDMI (1.3), digital, black, <b>HDCP-compliant</b>                  Signal cables (1) detachable, dual-link DVI-D at each end, digital, 1.8 meter                  (2) detachable, HDMI at each end, digital, 1.8 meter                  Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)                  Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	
<p>Ship group Monitor, attached stand, cable cover, Setup poster, Health and Safety Information and 3D Camera Setup Guide, 2 CDs with multilingual User's Guide, quick setup guide and monitor installation files, NVIDIA 3D vision kit, 1.8 meter dual-link DVI-D cable, 1.8 meter HDMI cable, 1.8 meter USB cable, 1.8 meter black power cord</p>	

<p style="text-align: center;"><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>↪ 1 year limited warranty<sup>4</sup></li> <li>↪ Rapid Replacement Service at 1-877-453-6686</li> <li>↪ Replacement normally arrives in two business days, excluding holidays</li> <li>↪ Lenovo pays all shipping costs for valid warranty claims<sup>5</sup></li> <li>↪ 24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></li> </ul>	<p style="text-align: center;"><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				

See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014

<p>Name <b>L2364 Wide Flat Panel Monitor</b>                  Case color <b>High gloss black with metal gray</b>                  Type-model <b>1187-US1</b>                  Panel <b>TFT-LCD, twisted nematic (TN), white LED backlight</b>                  Viewable image size <b>23.0" (584mm) diagonal</b>                  Max view area (W x H) <b>20.0" x 11.3" / 509.2mm x 286.4mm</b>                  Optimum resolution <b>1920x1080</b>                  Max pixel rate <b>VGA: 205MHz; HDMI/DVI: 165MHz</b>                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>.265mm</b>                  Dot/Pixel per Inch <b>96 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Dynamic contrast ratio <b>5,000,000:1</b>                  Pixel response time <b>5ms (typical)</b>                  Color gamut <b>72%</b>                  Vertical frequency <b>50 to 75Hz</b>                  Horizontal frequency <b>30 to 83kHz</b>                  Viewing angle at 10:1 CR <b>170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</b>                  Stand <b>Tilt adjustable stand</b>                  Bezel width <b>Sides: 0.71" (18.0mm); top: 0.71" (18.0mm); bottom: 0.89" (22.5mm)</b>                  Dimensions (HxWxD) <b>15.90" H x 21.57" W x 7.20" D; 403.9mm H x 547.8mm W x 183mm D</b>                  Power supply <b>30 watts typical, 35 watts maximum, &lt;0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)</b>                  Weight <b>7.28 lb; 3.30 kg</b>                  Limited warranty<sup>4</sup> <b>1 year (includes backlight)</b>                  Available date <b>July 2011</b></p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 23-inch monitor with white LED backlight</li> <li>• View images in a 16x9 wide aspect ratio</li> <li>• Built-in VGA, DVI-D, and HDMI 1.3 connectors</li> <li>• 1080p full HD support, HDCP-compliant</li> <li>• Tilt and cable management stand</li> <li>• Compliance with ENERGY STAR 5.0</li> <li>• Mercury free panel</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows® 7 certified</li> </ul>				
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, EDID 1.4A, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR<sup>®</sup> 5.0</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>FCC Class B</b>                  Environmental <b>TCO (TCO Displays 5.2), WEEE (EU DIRECTIVE 2002/96/EC), RoHS (EU DIRECTIVE 2002/95/EC)</b></p>	<div style="text-align: center;">  <p><b>Lenovo L2364 Wide Monitor</b></p> </div>				
<p>Preset resolutions (VGA) <b>VGA: 640x350, 640x480, 720x400</b>  <b>SVGA: 800x600, 832x624</b>  <b>XGA: 1024x768</b>  <b>XGA+: 1152x864</b>  <b>WXGA: 1280x768, 1280x800</b>  <b>SXGA: 1280x1024</b>  <b>WXGA+: 1440x900, 1600x900</b>  <b>WSXGA+: 1680x1050</b>  <b>Full HD: 1920x1080</b>                  Presets / user settings <b>Standard presets: VGA: 29; HDMI: 26; user settings: 20</b></p>					
<p>Viewing adjustments <b>Tilt: 20° back, -5° forward; detachable stand</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (buttons at the middle bottom of the front bezel) for volume up/down, mute, automatic image setup, dual input, brightness, and NOVO vision</b>                  USB hub <b>None</b>                  Multimedia <b>Audio in jack (3.5mm) and audio out jack (3.5mm) on rear</b>                  Multiple input <b>Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog, blue</b>  <b>(2) HDMI (1.3), digital, black, <b>HDCP-compliant</b></b>  <b>(3) Digital Visual Interface (DVI-D) for digital attach [white], <b>HDCP-compliant</b></b>                  Signal cable <b>Detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI<sup>®</sup> (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>					
<p>Ship group <b>Monitor, attached stand, base, Setup poster, Warranty Information, CD with multilingual User's Guide and monitor installation files, shopping bag, 1.8 meter analog signal cable, 1.8 meter power cord</b></p>					
<p style="text-align: center;"><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>⇒ <b>1 year limited warranty<sup>4</sup></b></li> <li>⇒ <b>Advanced Exchange Service at 1-877-453-6686</b></li> <li>⇒ <b>Replacement normally arrives in five business days, excluding holidays</b></li> <li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>5</sup></b></li> <li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<p style="text-align: center;"><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>                  More information at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington® MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				

See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014

<p>Name <b>LI2721s Wide Flat Panel Monitor</b>                  Case color <b>High gloss black</b>                  Type-model <b>4371-US1 / 4371-US2</b>                  Panel <b>TFT-LCD, In-Plane Switching (IPS), white LED backlight</b></p> <p>Viewable image size <b>27.0" (685.8mm) diagonal</b>                  Max view area (W x H) <b>23.54" x 13.24" / 597.9mm x 336.3mm</b>                  Optimum resolution <b>1920x1080</b>                  Max pixel rate <b>205MHz (VGA), 165MHz (HDMI/DVI)</b>                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>.265mm</b>                  Dot/Pixel per Inch <b>96 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Dynamic contrast ratio <b>10,000,000:1</b>                  Pixel response time <b>14ms (typical)</b>                  Viewing angle at 10:1 CR <b>178° (+/- 89°) horizontal, 178° (+/- 89°) vertical</b>                  Stand <b>Tilt adjustable stand</b>                  Bezel width <b>Sides: 0.21" (5.26mm)</b>                  Dimensions (HxWxD) <b>17.53" H x 24.63" W x 7.47" D; 445.4mm H x 625.6mm W x 189.8mm D</b></p> <p>Power supply <b>35 watts typical, 42 watts maximum, &lt;0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)</b></p> <p>Weight <b>12.79 lb; 5.80kg</b>                  Limited warranty<sup>4</sup> <b>1 year</b>                  Available date <b>October 2012</b></p>	<p style="text-align: center;"><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 27-inch monitor</li> <li>• 1080p full HD support, HDCP-compliant</li> <li>• Built-in VGA, DVI and HDMI 1.3 connectors for attachment to three systems concurrently</li> <li>• Compliance with ENERGY STAR</li> <li>• Kensington® lock slot ready for enhanced security</li> <li>• Microsoft® Windows 7 certified</li> </ul>				
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, EDID 1.3, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR<sup>®3</sup> qualified</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>FCC Class B</b>                  Environmental <b>TCO (TCO Displays 5.2)                  WEEE (EU Directive 2002/96/EC),                  RoHS (EU Directive 2002/95/EC)</b></p> <p>Preset resolutions <b>VGA: 640x350, 640x480, 720x400                  SVGA: 800x600, 832x624                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1366x768                  WXGA+: 1440x900, 1600x900                  WSXGA+: 1680x1050                  WUXGA: 1920x1080</b></p> <p>Presets / user settings <b>Presets: 24;                  user settings: 24</b></p>	 <p style="text-align: center;"><b>LI2721s Wide Monitor</b></p>				
<p>Viewing adjustments <b>Tilt: 20° back, -5° forward</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (control touch buttons on front) for automatic image setup, change input and NOVO vision</b>                  Multiple input <b>Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog                  (2) Digital Visual Interface (DVI-D), digital, <b>HDCP-compliant</b>                  (3) HDMI (1.3), digital, <b>HDCP-compliant</b></b></p> <p>Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI<sup>®</sup> (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>					
<p>Ship group <b>Monitor, attached stand, setup guide,                  1 CD with multilingual User's Guide, setup test pattern and monitor installation files,                  1.8 meter analog signal cable, 1.8 meter black power cord</b></p>					
<p style="text-align: center;"><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>⇒ <b>1 year limited warranty<sup>4</sup></b></li> <li>⇒ <b>Advanced Exchange Service at 1-877-453-6686</b></li> <li>⇒ <b>Replacement normally arrives in five business days, excluding holidays</b></li> <li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>5</sup></b></li> <li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<p style="text-align: center;"><b>Accessories</b></p> <table border="0"> <tr> <td>Kensington MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>                  See all monitors at <a href="http://www.lenovo.com/support/monitors">www.lenovo.com/support/monitors</a></p>	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				

See footnotes for important warranty information  
 US model(s) withdrawn effective March 2014

**Availability:** All offers subject to availability. Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo is not responsible for photographic or typographic errors.

**Warranty:** For a copy of applicable product warranties, go to: [http://support.lenovo.com/en\\_US/product-service/warranty-status/WarrantyPolicies.page](http://support.lenovo.com/en_US/product-service/warranty-status/WarrantyPolicies.page). Lenovo makes no representation or warranty regarding third party products or services.

- <sup>1</sup> **ISO-compliant:** Compliance with ISO 9241 Part 3, ISO Part 7, ISO Part 8, and/or ISO 13406 Part 2 is dependent on a complete ISO-capable platform of a system unit, monitor, video subsystem, operating system and fonts.
- <sup>2</sup> **VESA:** Requires attachment to suitably configured system with similarly enabled operating system.
- <sup>3</sup> **ENERGY STAR:** As an ENERGY STAR partner, Lenovo has determined that this product meets the ENERGY STAR 4.0 or 4.1 guidelines for energy efficiency. Requires attachment to suitably configured system.
- <sup>4</sup> **Limited warranty:** Support unrelated to a warranty issue may be subject to additional charges.
- <sup>6</sup> **Lenovo pays all shipping costs** for warranty repairs during limited warranty period.
- <sup>8</sup> **Telephone support** may be subject to additional charges, even during the limited warranty period. In the United States call 877-453-6686. Response times may vary. May exclude some holidays.



**Trademarks:** Lenovo, the Lenovo logo, New World. New Thinking., Access Connections, Rescue and Recovery, ThinkCentre, ThinkPad, ThinkStation, ThinkVantage, and ThinkVision are trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Other company, product, or service names may be trademarks or service marks of others.

This publication was developed for products and services offered in the United States. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to alter specifications and other product information at any time without prior notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore this disclaimer may not apply to you. This publication was developed in the US.

Visit [www.lenovo.com/safecomputing](http://www.lenovo.com/safecomputing) periodically for the latest information on safe and effective computing.

Visit [www.lenovo.com/psref](http://www.lenovo.com/psref) for the latest version of Personal Systems Reference.

© Lenovo, 2012.  
All rights reserved.

Lenovo  
1009 Think Place  
Morrisville, NC 27560  
U.S.A.

October 2012  
cmbook.pdf

Flat Panel Monitors - US model		FEATURES
Name	<b>Lenovo L195 Wide Flat Panel Monitor</b>	<ul style="list-style-type: none"> <li>• All-purpose 19-inch wide flat panel LCD monitor</li> <li>• View images in a 16x10 wide aspect ratio</li> <li>• Slim 14.3mm (0.56") side bezel</li> <li>• High-bandwidth Digital Content Protection (HDCP)-compliant</li> <li>• Resolution of 1440x900 provides crisp screen images</li> <li>• Stand tilts for comfortable viewing</li> <li>• Rear stand cover to hide cables for easy cable management</li> <li>• Soundbar with stereo speakers for daily audio usage</li> <li>• Direct access for automatic image setup, input selection, and NovoVision</li> <li>• NovoVision offers four modes (text, Internet, video, and split demo) and provides automatic contrast, brightness, color correction, and color enhancement</li> <li>• Integrated power supply eliminates the bulky power adapter for improved cable management</li> <li>• Matching design to IdeaCentre® systems</li> <li>• Microsoft® Windows® Vista™ Premium certified</li> </ul>
Case color	<b>High gloss black</b>	
Part number	<b>18002904</b>	
Stand	<b>Tilt stand</b>	
Screen	LCD Active Matrix TFT (Thin Film Transistor)	
Viewable image size	<b>19.0" / 481mm</b> (diagonal)	
Aspect ratio	16:10	
Pixel pitch (mm)	0.282mm	
Max view area (inches)	16.2" x 10.1" (horizontal x vertical)	
Max view area (mm)	410mm x 257mm (horizontal x vertical)	
Viewing angle at 5:1 CR	176° vertical, 176° horizontal	
Viewing angle at 10:1 CR	160° vertical, 160° horizontal	
Video input	<b>Digital or analog (two separate connectors)</b>	
Dual input	<b>Dual input</b> (two different PCs attach to two different connectors; one PC shows image; select via button)	
Rotating screen	None	
Soundbar	Installed on bottom of monitor, volumn control knob, two stereo speakers (3 watts), powered by monitor, microphone input jack, headphone jack	
Optimum resolution	<b>1440x900</b> at 60Hz	
Maximum resolution	1440x900 at 75Hz (137MHz maximum pixel rate)	
Vertical frequency	50 to 76Hz	
Horizontal frequency	30 to 81kHz	
Display colors (maximum)	16.7 million simultaneous colors	
Preset display modes	VGA: 640x480 60, 72, 75Hz SVGA: 800x600 56, 60, 72, 75Hz XGA: 1024x768 60, 70, 75Hz SXGA: 1280x1024 60, 70, 72, 76Hz WXGA+: 1440x900 60, 75Hz	
Presets / user settings	Standard presets: 17; user settings: 15	
Brightness	300 nits or cd/m <sup>2</sup> (typical)	
Contrast ratio	1000:1 (typical)	
Pixel response time	5ms (typical)	
Scaling	Automatically expands image of lower resolution to full screen of 1440x900	
On screen display	On screen display with digital user controls (7 languages)	
Control features	Direct access (buttons on front) for auto adjustment, input select, and NovoVision (4 preload modes, optimize visual experience for different usages); brightness; contrast; image horizontal and vertical position; user color settings (3 preset + 1 user); on screen display (OSD) language selection; menu position; information screen; image setup; reset of geometry and color point to factory default settings; lockable settings	
Monitor connectors	Two connectors: (1) analog 15-pin D-shell [blue] (2) Digital Visual Interface (DVI-D) for digital attach [white], <b>HDCP-compliant</b>	
Signal cable	Two cables: (1) detachable, 15-pin D-shell at each end (for analog connector), 1.8 meter, matches color of monitor (2) detachable, DVI-D at each end (for digital connector), 1.8 meter, matches color of monitor	
Anti-reflective / anti-glare	Anti-reflective / anti-glare	
Dimensions	14.67" H x 17.36" W x 7.09" D / 373mm height x 441mm width x 180mm depth	
Weight	10.2 lb / 4.6 kg	
Viewing adjustments	Tilt: 20° back, 5° forward / no swivel / no lift / detachable stand	
Mounting features	None	
Security	Security keyhole for attachment of optional cable lock (such as Kensington® Microsaver® lock)	
VESA DDC <sup>2</sup>	DDC/CI	
VESA DPMS-compliant	DPMS	
Power management	ENERGY STAR <sup>®</sup> 4.0	
Ergonomics	ISO 13406 Part 2 <sup>1</sup>	
Pixel defect	ISO 13406-2 Class II pixel defect standard	
Emission standards	MPR-2 / MPR-3A / FCC Class B	
Environmental label	WEEE / RoHS (EU Directive 2002/95/EC)	
Ship group	Monitor, attached stand, customer installable base, soundbar, Setup Guide, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, analog signal cable, digital signal cable, 1.8m black power cord	
Power supply	100-240Vac (universal) / integrated (no external brick-like power supply) / 48 watts maximum (with soundbar), <2 watts for "active off"	
Limited warranty <sup>4</sup>	<b>1 year</b> (includes backlight)	
Available date	August 2008	
<b>LIMITED WARRANTY</b>		
<ul style="list-style-type: none"> <li>↪ <b>1-year limited warranty<sup>4</sup></b></li> <li>↪ <b>Rapid Replacement Service at 1-877-453-6686</b></li> <li>↪ <b>Replacement normally arrives in two business days, excluding holidays</b></li> <li>↪ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>↪ <b>24x7<sup>5</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>		



Lenovo L195 Wide

See footnotes for important warranty information  
 US model announced August 5, 2008  
 US model withdrawn effective April 2010



Flat Panel Monitors - US model		FEATURES																											
Name	<b>Lenovo L195 Wide Flat Panel Monitor</b>	<ul style="list-style-type: none"> <li>All-purpose 19-inch wide flat panel LCD monitor</li> <li>View images in a 16x10 wide aspect ratio</li> <li>Slim 14.3mm (0.56") side bezel</li> <li>High-bandwidth Digital Content Protection (HDCP)-compliant</li> <li>Resolution of 1680x1050 provides crisp screen images</li> <li>Stand tilts for comfortable viewing</li> <li>Rear stand cover to hide cables for easy cable management</li> <li>Soundbar with stereo speakers for daily audio usage</li> <li>Direct access for automatic image setup, input selection, and NovoVision</li> <li>NovoVision offers four modes (text, Internet, video, and split demo) and provides automatic contrast, brightness, color correction, and color enhancement</li> <li>Integrated power supply eliminates the bulky power adapter for improved cable management</li> <li>Matching design to IdeaCentre® systems</li> <li>Microsoft® Windows® Vista™ Premium certified</li> </ul>																											
Case color	<b>High gloss black</b>																												
Type-model	<b>4418-HC1   4419-HC1</b>																												
Stand	<b>Tilt stand</b>																												
Screen	LCD Active Matrix TFT (Thin Film Transistor)																												
Viewable image size	<b>19.0" / 481mm</b> (diagonal)																												
Aspect ratio	16:10																												
Pixel pitch (mm)	0.243mm																												
Max view area (inches)	16.1" x 10.0" (horizontal x vertical)																												
Max view area (mm)	408mm x 255mm (horizontal x vertical)																												
Viewing angle at 10:1 CR	160° vertical, 170° horizontal																												
Video input	<b>Digital or analog (two separate connectors)</b>																												
Dual input	<b>Dual input</b> (two different PCs attach to two different connectors; one PC shows image; select via button)																												
Rotating screen	None																												
Soundbar	Installed on bottom of monitor, volume control knob, two stereo speakers (3 watts), powered by monitor, microphone input jack, headphone jack																												
Optimum resolution	<b>1680x1050</b> at 60Hz																												
Maximum resolution	1680x1050 at 60Hz (137MHz maximum pixel rate)																												
Vertical frequency	50 to 76Hz																												
Horizontal frequency	30 to 81kHz																												
Display colors (maximum)	16.7 million simultaneous colors																												
Preset display modes	<table border="0"> <tr> <td>640x350</td> <td>70Hz</td> </tr> <tr> <td>PAL VGA: 640x480</td> <td>50Hz</td> </tr> <tr> <td>VGA: 640x480</td> <td>60, 66, 72, 75Hz</td> </tr> <tr> <td>720x400</td> <td>70Hz</td> </tr> <tr> <td>SVGA: 800x600</td> <td>56, 60, 72, 75Hz</td> </tr> <tr> <td>832x624</td> <td>75Hz</td> </tr> <tr> <td>XGA: 1024x768</td> <td>60, 70, 75Hz</td> </tr> <tr> <td>1152x864</td> <td>75Hz</td> </tr> <tr> <td>1280x720</td> <td>60Hz</td> </tr> <tr> <td>1280x768</td> <td>60Hz</td> </tr> <tr> <td>1280x960</td> <td>60Hz</td> </tr> <tr> <td>SXGA: 1280x1024</td> <td>60, 70, 75, 76Hz</td> </tr> <tr> <td>WXGA+: 1440x900</td> <td>60, 75Hz</td> </tr> <tr> <td>WSXGA+: 1680x1050</td> <td>60Hz</td> </tr> </table>	640x350	70Hz	PAL VGA: 640x480	50Hz	VGA: 640x480	60, 66, 72, 75Hz	720x400	70Hz	SVGA: 800x600	56, 60, 72, 75Hz	832x624	75Hz	XGA: 1024x768	60, 70, 75Hz	1152x864	75Hz	1280x720	60Hz	1280x768	60Hz	1280x960	60Hz	SXGA: 1280x1024	60, 70, 75, 76Hz	WXGA+: 1440x900	60, 75Hz	WSXGA+: 1680x1050	60Hz
640x350	70Hz																												
PAL VGA: 640x480	50Hz																												
VGA: 640x480	60, 66, 72, 75Hz																												
720x400	70Hz																												
SVGA: 800x600	56, 60, 72, 75Hz																												
832x624	75Hz																												
XGA: 1024x768	60, 70, 75Hz																												
1152x864	75Hz																												
1280x720	60Hz																												
1280x768	60Hz																												
1280x960	60Hz																												
SXGA: 1280x1024	60, 70, 75, 76Hz																												
WXGA+: 1440x900	60, 75Hz																												
WSXGA+: 1680x1050	60Hz																												
Presets / user settings	Standard presets: 26; user settings: 27																												
Brightness	300 nits or cd/m <sup>2</sup> (typical)																												
Contrast ratio	1000:1 (typical)																												
Pixel response time	5ms (typical)																												
Scaling	Automatically expands image of lower resolution to full screen of 1680x1050																												
On screen display	On screen display with digital user controls (7 languages)																												
Control features	Direct access (buttons on front) for auto adjustment, input select, and NovoVision (4 preload modes, optimize visual experience for different usages); brightness; contrast; image horizontal and vertical position; user color settings (3 preset + 1 user); on screen display (OSD) language selection; menu position; information screen; image setup; reset of geometry and color point to factory default settings; lockable settings																												
Monitor connectors	Two connectors: (1) analog 15-pin D-shell [blue]																												
Signal cable	Two cables: (2) Digital Visual Interface (DVI-D) for digital attach [white], <b>HDCP-compliant</b> (1) detachable, 15-pin D-shell at each end (for analog connector), 1.8 meter, matches color of monitor (2) detachable, DVI-D at each end (for digital connector), 1.8 meter, matches color of monitor																												
Anti-reflective / anti-glare	Anti-reflective / anti-glare																												
Dimensions	14.67" H x 17.36" W x 7.09" D / 373mm height x 441mm width x 180mm depth																												
Weight	10.1 lb / 4.6 kg																												
Viewing adjustments	Tilt: 20° back, 5° forward / no swivel / no lift / detachable stand																												
Mounting features	None																												
Security	Security keyhole for attachment of optional cable lock (such as Kensington® Microsaver® lock)																												
VESA DDC <sup>2</sup>	DDC/CI																												
VESA DPMS-compliant	DPMS																												
Power management	ENERGY STAR <sup>®3</sup> 4.0																												
Ergonomics	ISO 13406 Part 2 <sup>1</sup>																												
Pixel defect	ISO 13406-2 Class II pixel defect standard																												
Emission standards	MPR-2 / MPR-3A / FCC Class B																												
Environmental label	WEEE / RoHS (EU Directive 2002/95/EC)																												
Ship group	Monitor, attached stand, customer installable base, soundbar, Setup Guide, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, analog signal cable, digital signal cable, 1.8m black power cord																												
Power supply	100-240Vac (universal) / integrated (no external brick-like power supply) / 48 watts maximum (with soundbar), <2 watts for "active off"																												
Limited warranty <sup>4</sup>	<b>4418-HC1: 1 year</b> (includes backlight); <b>4419-HC1: 3 year</b> (includes backlight)																												
Available date	September 2008																												



Lenovo L195 Wide

LIMITED WARRANTY	
↪	<b>1-year or 3-year limited warranty<sup>4</sup></b>
↪	<b>Rapid Replacement Service at 1-877-453-6686</b>
↪	<b>Replacement normally arrives in two business days, excluding holidays</b>
↪	<b>Lenovo pays all shipping costs for valid warranty claims<sup>5</sup></b>
↪	<b>24x7<sup>3</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b>


See footnotes for important warranty information  
 US models announced September 2, 2008  
 US models withdrawn effective April 2010

Flat Panel Monitors - US model		FEATURES
Name	<b>Lenovo L222 Wide Flat Panel Monitor</b>	<ul style="list-style-type: none"> <li>• All-purpose 22-inch wide flat panel LCD monitor</li> <li>• View images in a 16x10 wide aspect ratio</li> <li>• Slim 15 mm (0.59") side bezel</li> <li>• High-bandwidth Digital Content Protection (HDCP)-compliant</li> <li>• Resolution of 1680x1050 provides crisp screen images</li> <li>• Stand tilts and swivels for comfortable viewing</li> <li>• Rear stand cover to hide cables for easy cable management</li> <li>• One key release stand for wall mounting</li> <li>• Touch-sensitive buttons for all monitor control features</li> <li>• Direct access for automatic image setup, input selection, and NovoVision</li> <li>• NovoVision offers four modes (text, Internet, video, and split demo) and provides automatic contrast, brightness, color correction, and color enhancement</li> <li>• Integrated power supply eliminates the bulky power adapter for improved cable management</li> <li>• Matching design to IdeaCentre® systems</li> <li>• Microsoft® Windows® Vista™ Premium certified</li> </ul>
Case color	<b>High gloss black</b>	
Part number	<b>18002819</b>	
Stand	<b>Tilt and swivel stand</b>	
Screen	LCD Active Matrix TFT (Thin Film Transistor)	
Viewable image size	<b>22.0" / 559mm</b> (diagonal)	
Aspect ratio	16:10	
Pixel pitch (mm)	0.282mm	
Max view area (inches)	18.7" x 11.6" (horizontal x vertical)	
Max view area (mm)	474mm x 296mm (horizontal x vertical)	
Viewing angle at 5:1 CR	176° vertical, 176° horizontal	
Viewing angle at 10:1 CR	160° vertical, 160° horizontal	
Video input	<b>Digital or analog (two separate connectors)</b>	
Dual input	<b>Dual input</b> (two different PCs attach to two different connectors; one PC shows image; select via button)	
Rotating screen	None	
Soundbar	Installed on bottom of monitor, volumn control knob, two stereo speakers (3 watts), powered by monitor, microphone input jack, headphone jack	
Optimum resolution	<b>1680x1050</b> at 60Hz	
Maximum resolution	1680x1050 at 60Hz (146MHz maximum pixel rate)	
Vertical frequency	56 to 76Hz	
Horizontal frequency	30 to 83kHz	
Display colors (maximum)	16.7 million simultaneous colors	
Preset display modes	VGA: 640x480 60, 72, 75Hz 720x400 70Hz SVGA: 800x600 56, 60Hz, 75Hz 832x624 75Hz XGA: 1024x768 60, 70, 75Hz 1152x864 75Hz SXGA: 1280x1024 60, 70, 75, 76Hz WXGA+: 1440 x 900 60, 75Hz WSXGA+: 1680x1050 60Hz	
Presets / user settings	Standard presets: 17; user settings: 17	
Brightness	300 nits or cd/m <sup>2</sup> (typical)	
Contrast ratio	1000:1 (typical)	
Pixel response time	5ms (typical)	
Scaling	Automatically expands image of lower resolution to full screen of 1680x1050	
On screen display	On screen display with digital user controls (7 languages), touch-sensitive control buttons	
Control features	Direct access (touch buttons on front) for auto adjustment, input select, and NovoVision (4 preload modes, optimize visual experience for different usages); brightness; contrast; image horizontal and vertical position; user color settings (3 preset + 1 user); on screen display (OSD) language selection; menu position; information screen; image setup; reset of geometry and color point to factory default settings; lockable settings	
Monitor connectors	Two connectors: (1) analog 15-pin D-shell [blue], (2) Digital Visual Interface (DVI-D) for digital attach [white], <b>HDCP-compliant</b>	
Signal cable	Two cables: (1) detachable, 15-pin D-shell at each end (for analog connector), 1.8 meter, matches color of monitor (2) detachable, DVI-D at each end (for digital connector), 1.8 meter, matches color of monitor	
Anti-reflective / anti-glare	Anti-reflective / anti-glare	
Dimensions	16.13" H x 19.89" W x 7.48" D / 410mm height x 505mm width x 190mm depth	
Weight	12.8 lb / 5.8 kg	
Viewing adjustments	Tilt: 20° back, 5° forward / swivel: +/-175° / no lift / detachable stand	
Mounting features	Wall or desk mounting using or third-party accessories meeting the VESA FPMPI® (100mm mount)	
Security	Security keyhole for attachment of optional cable lock (such as Kensington® Microsaver® lock)	
VESA DDC <sup>2</sup>	DDC/CI	
VESA DPMS-compliant	DPMS	
Power management	ENERGY STAR® 4.0	
Ergonomics	ISO 13406 Part 2 <sup>1</sup>	
Pixel defect	ISO 13406-2 Class II pixel defect standard	
Emission standards	MPR-2 / MPR-3A / FCC Class B	
Environmental label	WEEE / RoHS (EU Directive 2002/95/EC)	
Ship group	Monitor, attached stand, customer installable base, soundbar, Setup Guide, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, analog signal cable, digital signal cable, 1.8m black power cord	
Power supply	100-240Vac (universal) / integrated (no external brick-like power supply) / 56 watts maximum (with soundbar), <2 watts for "active off"	
Limited warranty <sup>4</sup>	<b>1 year</b> (includes backlight)	
Available date	August 2008	
<b>LIMITED WARRANTY</b>		
<ul style="list-style-type: none"> <li>↪ <b>1-year limited warranty<sup>4</sup></b></li> <li>↪ <b>Rapid Replacement Service at 1-877-453-6686</b></li> <li>↪ <b>Replacement normally arrives in two business days, excluding holidays</b></li> <li>↪ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>↪ <b>24x7<sup>5</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>		



Lenovo L222 Wide

See footnotes for important warranty information  
 US model announced August 5, 2008  
 US model withdrawn effective April 2010

Flat Panel Monitors - US model		FEATURES
Name	<b>Lenovo L222 Wide Flat Panel Monitor</b>	<ul style="list-style-type: none"> <li>• All-purpose 22-inch wide flat panel LCD monitor</li> <li>• View images in a 16x10 wide aspect ratio</li> <li>• Slim 15 mm (0.59") side bezel</li> <li>• High-bandwidth Digital Content Protection (HDCP)-compliant</li> <li>• Resolution of 1920x1200 provides crisp screen images</li> <li>• High Definition (HD) ready; supports 1080p video</li> <li>• Stand tilts and swivels for comfortable viewing</li> <li>• Rear stand cover to hide cables for easy cable management</li> <li>• One key release stand for wall mounting</li> <li>• Touch-sensitive buttons for all monitor control features</li> <li>• Direct access for automatic image setup, input selection, and NovoVision</li> <li>• NovoVision offers four modes (text, Internet, video, and split demo) and provides automatic contrast, brightness, color correction, and color enhancement</li> <li>• Matching design to IdeaCentre® systems</li> <li>• Microsoft® Windows® Vista™ Premium certified</li> </ul>
Case color	<b>High gloss black</b>	
Type-model	<b>4432-HF1</b>	
Stand	<b>Tilt and swivel stand</b>	
Screen	LCD Active Matrix TFT (Thin Film Transistor)	
Viewable image size	<b>22.0" / 559mm</b> (diagonal)	
Aspect ratio	16:10	
Pixel pitch (mm)	0.247mm	
Max view area (inches)	18.7" x 11.6" (horizontal x vertical)	
Max view area (mm)	474mm x 296mm (horizontal x vertical)	
Viewing angle at 10:1 CR	160° vertical, 170° horizontal	
Video input	<b>Digital or analog (two separate connectors)</b>	
Dual input	<b>Dual input</b> (two different PCs attach to two different connectors; one PC shows image; select via button)	
Rotating screen	None	
Soundbar	Installed on bottom of monitor, volume control knob, two stereo speakers (3 watts), powered by monitor, microphone input jack, headphone jack	
Optimum resolution	<b>1920x1200</b> at 60Hz	 <p style="text-align: center;"><b>Lenovo L222 Wide</b></p>
Maximum resolution	1920x1200 at 60Hz (205MHz maximum pixel rate)	
Vertical frequency	50 to 75Hz	
Horizontal frequency	30 to 83kHz	
Display colors (maximum)	16.7 million simultaneous colors	
Preset display modes	VGA: 640x480 60Hz SVGA: 800x600 56, 60Hz XGA: 1024x768 60Hz SXGA: 1280x1024 60Hz WXGA+: 1440 x 900 60Hz WSXGA+: 1680x1050 60Hz WSXGA+: 1680x1050 60Hz WUXGA: 1920x1200 60Hz	
Presets / user settings	Standard presets: 8; user settings: 10	
Brightness	300 nits or cd/m <sup>2</sup> (typical)	
Contrast ratio	1000:1 (typical)	
Pixel response time	5ms (typical)	
Scaling	Automatically expands image of lower resolution to full screen of 1920x1200	
On screen display	On screen display with digital user controls (7 languages), touch-sensitive control buttons	
Control features	Direct access (touch buttons on front) for auto adjustment, input select, and NovoVision (4 preload modes, optimize visual experience for different usages); brightness; contrast; image horizontal and vertical position; user color settings (3 preset + 1 user); on screen display (OSD) language selection; menu position; information screen; image setup; reset of geometry and color point to factory default settings; lockable settings	
Monitor connectors	Two connectors: (1) analog 15-pin D-shell [blue], (2) Digital Visual Interface (DVI-D) for digital attach [white], <b>HDCP-compliant</b>	
Signal cable	Two cables: (1) detachable, 15-pin D-shell at each end (for analog connector), 1.8 meter, matches color of monitor (2) detachable, DVI-D at each end (for digital connector), 1.8 meter, matches color of monitor	
Anti-reflective / anti-glare	Anti-reflective / anti-glare	
Dimensions	16.13" H x 19.89" W x 7.48" D / 410mm height x 505mm width x 190mm depth	
Weight	12.8 lb / 5.8 kg	
Viewing adjustments	Tilt: 20° back, 5° forward / swivel: +/-175° / no lift / detachable stand	
Mounting features	Wall or desk mounting using or third-party accessories meeting the VESA FPMPI® (100mm mount)	
Security	Security keyhole for attachment of optional cable lock (such as Kensington® Microsaver® lock)	
VESA DDC <sup>2</sup>	DDC/CI	
VESA DPMS-compliant	DPMS	
Power management	ENERGY STAR® 4.0	
Ergonomics	ISO 13406 Part 2 <sup>1</sup>	
Pixel defect	ISO 13406-2 Class II pixel defect standard	
Emission standards	MPR-2 / MPR-3A / FCC Class B	
Environmental label	WEEE / RoHS (EU Directive 2002/95/EC)	
Ship group	Monitor, attached stand, customer installable base, soundbar, Setup Guide, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, analog signal cable, digital signal cable, 1.8m black power cord	
Power supply	100-240Vac (universal) / integrated (no external brick-like power supply) / 56 watts maximum (with soundbar), <2 watts for "active off"	
Limited warranty <sup>4</sup>	<b>1 year</b> (includes backlight)	
Available date	September 2008	
<b>LIMITED WARRANTY</b>		
<ul style="list-style-type: none"> <li>↪ <b>1-year limited warranty<sup>4</sup></b></li> <li>↪ <b>Rapid Replacement Service at 1-877-453-6686</b></li> <li>↪ <b>Replacement normally arrives in two business days, excluding holidays</b></li> <li>↪ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>↪ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>		

See footnotes for important warranty information  
 US model announced September 2, 2008  
 US model withdrawn effective April 2010

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>