

VSX-1015TX-K

DTS-ES DISCRETE/DTS 96/24/WMA9 PRO/THX™ SELECT2™ CERTIFIED AUDIO/VIDEO RECEIVER WITH ADVANCED DIRECT ENERGY MOSFET & AUTO MCACC

- Advanced Direct Energy MOSFET Construction
- Auto MCACC with 5-Band EQ
- Video Up Conversion (up to Component)
- Equal High Power for All Seven Channels (120W x 7)
- The World's First THX™ Select 2 Certified*1
- Built-in DTS*2-ES Discrete/DTS 96/24/NEO:6/Dolby*3 Digital EX/Dolby Pro Logic IIx Decoder
- WMA9 Pro*4 Compatible
- Virtual Surround Back Mode
- Double-Precision 48-bit Motorola DSP
- 5.1-Channel Input (DVD)
- DVD-Audio/SACD Ready
- 192kHz/24-bit DAC
- Advanced Surround (8 Modes)
- Dialog Enhancement
- Auto Surround
- 7-Channel Stereo
- Midnight Listening Mode
- 5 Digital Inputs (2 Coaxial, 2 Optical, 1 Front Optical) and 1 Digital Optical Output
- Component Video Terminal (3 Inputs, 1 Output)
- S-Video Terminal (5 Inputs, 2 Outputs)
- Front A/V Inputs with S-Video Input and Optical Digital Input
- 7.1-Channel Preamp Output
- Audio (Tuner included)/Video inputs: 3A/5AV
- Audio/Video outputs: 1A/1AV+1V
- SR+ (Smart Remote) Terminal Out
- FL Dimmer (4 Steps)
- Large Banana Speaker Terminal (L/R/C/LS/RS/SBL/SBR)
- On-Screen Display
- Pre-programmed and Learning LCD Remote
- Stylish Black Aluminum Panel
- Power Requirements: AC 120V/60Hz
- Standby Power Consumption: 0.43W
- Dimensions (W x H x D): 16-9/16 x 6-13/16 x 18-5/16 inches/420 x 173 x 465mm
- Weight: 33 lbs. 14 oz./15.4kg



Setup Microphone



VSX-1015TX-K Rear panel

*1 THX and Select2 are trademarks of THX Ltd. THX may be registered in some jurisdictions. All rights reserved.

*2 DTS, DTS-ES, NEO:6 and DTS 96/24 are trademarks of Digital Theater Systems, Inc.

*3 Dolby, Pro Logic, Dolby Digital, Surround EX and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.

*4 Windows Media® Audio 9 Professional, Microsoft, Windows Media and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries. Proprietary driver is required for WMA9 Pro playback on computer.

• Stereo: Continuous average power output of 120 watts at 8 ohms, from 20 to 20kHz with no more than 0.2% total harmonic distortion
 • Surround: 120W + 120W (8 ohms, 20Hz to 20kHz, 0.2% THD) (front); 120W (8 ohms, 20Hz to 20kHz, 0.2% THD) (center); 120W + 120W (8 ohms, 20Hz to 20kHz, 0.2% THD) (surround); 120W + 120W (8 ohms, 20Hz to 20kHz, 0.2% THD) (surround back)

• Measured pursuant to the Federal Trade Commission's Trade Regulation Rule on Power Output Claims for Amplifiers.
 • The impedances indicated in the specifications are actual values that speakers can present to an amplifier while playing back music. They do not refer to the nominal rated impedances of speakers you use.
 • Specifications and design subject to modification without notice.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>