


Overview

At A Glance

- Intel® 815E chipset
- 133 MHz Front Side Bus
- One Intel® Pentium® III processor up to 1.2 GHz
- High-performance 10,000 rpm and optional 15,000 rpm Ultra160 SCSI and Quiet Seek 7200 rpm Ultra ATA hard drives
- Choice of graphics controllers: Matrox Millennium G450 dual, NVIDIA Quadro2 EX, ELSA Synergy II, or NVIDIA Quadro2 MXR
- Multi-display support
- Convertible minitower form factor with external drives that rotate 90°, easily converting from minitower to desktop
- Compaq Intelligent Manageability
- Windows 2000 or Windows NT 4.0 pre-installed
- Easy Access Keyboard
- Protected by Compaq Services, including a three-year, limited warranty – Terms and conditions vary by country. Certain restrictions and exclusions apply.



1. V710 Monitor (sold separately)
2. Three-button Mouse
3. Easy Access Keyboard
4. LED
5. Dual-State Power Button
6. Expansion Slots

7. SMART III Ultra ATA or SCSI Hard Drive
8. 1.44-MB diskette drive
9. CD-ROM
10. Expansion Bays
11. 200-Watt Power Supply

Standard Features – Pre Configured Models

Chipset – Intel 815E

Processor and Speed	Intel Pentium III Processors	Standard L2 Cache	256-KB Integrated ECC
<i>One of the following</i>	1 GHz	Front Side Bus	133 MHz

Hard Drives

<i>One of the following</i>	20-GB 7200 rpm SMART III Ultra ATA/100 with Drive Protection System
	20-GB 7200 rpm SMART III Ultra ATA/100 with Drive Protection System <i>(Quite Seek and Idle HDD (EMEA Only))</i>
	40-GB 7200 rpm SMART III Ultra ATA/100 with Drive Protection System
	18-GB Ultra160/10K RPM SCSI HDD
	Adaptec 29160 U160 SCSI Controller on SCSI models

Memory	Standard	128 MB (PC133MHz SDRAM Memory)
<i>One of the following</i>	Standard	256 MB (PC133MHz SDRAM Memory)
	Maximum	512 MB (PC133MHz SDRAM Memory)

Removable Storage	1.44-MB Diskette Drive
--------------------------	------------------------

Optical Storage	48X CD-ROM Drive
<i>One of the following</i>	8X/4X/32X CD-RW

Keyboard/Mouse	Easy Access Keyboard
	3-Button Mouse

Audio	Integrated Intel Audio with Premium Internal Speaker
--------------	--

Network Controller	Integrated Intel PRO/100 VM Network Connection
---------------------------	--

Graphics	Matrox G450 AGP
<i>One of the following:</i>	ELSA Synergy II (AGP)
	NVIDIA Quadro2 EX
	NVIDIA Quadro2 MXR

Expansion Capability	Memory Expansion Slots (DIMMS)	3 DIMMS
	Memory Type	SDRAM
	Maximum Memory	512MB

Expansion Slots	(Total/Available)	6/4
	AGP	1/ up to 1 depending on model
	PCI	5/ up to 4 depending on model

Expansion Bays	(Total/Available)	5/2
	Internal	2/1
	External	3/1

Operating System	Dual Installation Windows 2000 with selectable Service Pack 1/Windows NT 4.0 with Service Pack 6a
	<i>Note: Dual Installation- End-user must make a one-time selection between Windows 2000 and Windows NT 4.0. If end-user desires the rejected product(s) after selection is made, the end-user must acquire and pay for rejected product separately.</i>

Standard Features – Pre Configured Models

Chipset – Intel 815E (continued)

Interfaces	I/O Chip	Socket 370, Coppermine 128K/256K FC-PGA 66/100/133 FSB
	Serial Port / UART Type	Yes
	Parallel Port	Yes
	USB	2 ports
	Infrared Port	No
	Network	RJ-45 (with integrated LEDs)
	Keyboard	Yes
	Mouse	Yes; PS/2
	Video	Yes
	Audio	Yes

Power Conservation ‘Energy Saver’	Energy Star Compliant	Yes (on select models)
	Power Consumption in ES Mode	http://www.eng.hou.compaq.com/-agency/e-star.htm Note: This Web site is available in English only.
	APM Support	Version 1.2
	Screen Blanking	Yes
	Hard Disk “Idle” Mode	Yes
	System Idle Mode	Yes
	Cache Memory Power-Down	No
	CD-Rom Down	Yes
	System Environmental Specifications Temperature, Acoustics, Shock, Vibration, and Altitude	http://envwebserver.eng.hou.compaq.com/envtestlab/prod02.htm Note: This Web site is available in English only.

Boot Support	Local Diskette Boot	Yes (Windows 95, Windows 98.DOS)
	Remote Diskette Boot	No
	Network Boot	Yes

Initial Configuration and Deployment	Alliris eXpress	http://www.compaq.com/im
	PC Transplant/PC Transplant PRO	http://www.compaq.com/im
	System Software Management ver 1.4	http://www.compaq.com/im
	Novel ZenWorks 2.0	http://www.compaq.com/im
	IM LC ver 1.6	http://www.compaq.com/im
	Support Software CD	http://www.compaq.com/im Note: These Web sites are available in English only.
	Compaq OS Restore CD	Yes

Asset Control	Asset Tag	Yes
	DIMM Serial Presence Detect	Yes
	Hard drive serial number, model, and manufacturer	Yes
	Monitor serial number, model and manufacturer	Yes
	System serial number, model, and manufacturer	Yes
	ROM revision levels	Yes
	Systemboard revision level	Yes
	Compaq Fingerprint Identification Technology	Yes/Optional
	Configuration Control Hardware	No
	DMI BIOS	Yes
	Memory Change Alert	Yes
	Ownership Tag	Yes
	Kensington Lock Support	Yes

Standard Features – Pre Configured Models

Chipset – Intel 815E (continued)

Standard Security Features	Cable Lock Provision	Yes
	Power-On Password	Yes
	QuickBlank/QuickLock	No
	Serial, Parallel, USB Port Control	Yes
	Removable Media Write/Boot Control	Yes
	Setup Password	Yes
Software Updating and Management	Compaq Info Messenger	Yes
	Remote Security Management	Yes
	Remote ROM Flash	Yes, requires CPQRS driver
	Remote Wakeup/Remote Shutdown	Yes
	ROM-Based Setup and Diagnostics	Yes
	Support Software CD and WWW site	Yes
Fault Notification and Recovery	DMI BIOS	Yes
	SMART Hard Drives, Fault Notification, and Prefailure Warranty	Yes
	Proactive Backup	Yes
	ECC Memory, Fault Notification, and Prefailure Warning	Not Supported; 815E does not support ECC memory
	Processor Fault Notification and Prefailure Warranty	Yes
	Surge Tolerant Power Supply	Yes
	Thermal Sensor	Yes
	Ultra ATA Integrity Monitoring	Yes
Other Features	ACPI-Ready Hardware	Yes
	Compaq Insight Manager LC and XE Agents	Yes
	Altiris agent	Yes
	Compaq Management Solutions Partners Program	Yes
	Dual-State Power Button	Yes
	Compaq Management Solutions Partners Program	Yes
	Wired for Management Support	Yes

Intelligent Manageability Compaq Intelligent Manageability, a key component of PC Lifecycle Solutions, is the broad set of manageability features found on all Compaq Deskpro desktops, *Armada*™ portables, Deskpro Workstation, *Professional Workstation*™, and *ProLiant*™ server products. These best-in-class features on PC clients comply with industry standards, such as DMI and Wired for Management, while pioneering new ground in client manageability. Compaq introduced the industry's first line of manageable clients in 1995 and has been driving the industry ever since. With Compaq's lifecycle management philosophy, enterprises have all of the pieces for end-to-end management and proven tools for hassle-free management of PCs and significantly lower total cost of ownership.

Intelligent Manageability offers solutions in the areas of Initial Configuration and Deployment, Asset Tracking and Security, Software Updating and Management, and Fault Notification and Recovery. For more information, visit our Web site: www.compaq.com/im. Note: This Web site is available in English only.

Standard Features – Pre Configured Models

Chipset – Intel 815E (continued)

Software	Windows 3.1	No
	Windows NT 4.X	Yes
	Windows 2000	Yes
	Windows NT 4.X/Windows 2000	Yes
	Computer Setup Utility	Yes
	Insight Personal Edition	Yes
	Diagnostics for Windows	Yes
	Microsoft Internet Explorer	Yes
	Compaq Information Center	No
	Intelligent Manageability Agent	Yes

Power Supply **Convertible Minitower**
200 Watts

Service and Support

On-site Warranty and ServiceNo ^{Note 1:} This three-year, limited warranty and service offering delivers three years of on-site, next business-day^{Note 2} service for parts and labor and includes free telephone support ^{Note 3} 24 x 7. Global coverage ^{Note 2} ensures that any product purchased in one country and transferred to another, non-restricted country will remain fully covered under the original warranty and service offering.

Note 1: Terms and conditions may vary by country. Certain restrictions and exclusions apply.

Note 2: On-site service may be provided pursuant to a service contract between Compaq and an authorized Compaq third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.

Note 3: Technical telephone support applies only to Compaq-configured, Compaq and Compaq-qualified, third-party hardware and software. Toll-free calling and 24 x 7 support may not be available in some countries.

Standard Features – Pre Configured Models

D23/1.0/20A/256/2+C 470012-811	Processor	1GHz Pentium III w/ 133MHz FSB
	Cache Memory	256-KB Integrated ECC
	Memory	256MB PC133 SDRAM (1x256)
	Optical Drive	48X CD-ROM
	Hard Drive	20-GB Ultra ATA 7200 rpm
	Controller	Integrated Ultra ATA/100
	Graphics	nVIDIA Quadro2 MXR
	Audio	Integrated AC97 <i>Premier•Sound</i>
	OS	Dual Windows NT 4.0 SP6a/Windows 2000 SP1 pre-install

D23/1.0/18S/256/2XC 470012-856	Processor	1GHz Pentium III w/ 133MHz FSB
	Cache Memory	256-KB Integrated ECC
	Memory	256MB PC133 SDRAM (1x256)
	Optical Drive	48X CD-ROM
	Hard Drive	18.2-GB Ultra 160 SCSI (10,000 rpm)
	Controller	Integrated Ultra ATA/100 and Ultra160 SCSI PCI
	Graphics	Matrox Millennium G450 (AGP)
	Audio	Integrated AC97 <i>Premier•Sound</i>
	OS	Dual Windows NT 4.0 SP6a/Windows 2000 SP1 pre-install

D23/1.0/20A/256/2+C 470014-563	Processor	1GHz Pentium III w/ 133MHz FSB
	Cache Memory	256-KB Integrated ECC
	Memory	256MB PC133 SDRAM (1x256)
	Optical Drive	48X CD-ROM
	Hard Drive	20-GB Ultra ATA 7200 rpm
	Controller	Integrated Ultra ATA/100
	Graphics	ELSA Synergy II
	Audio	Integrated AC97 <i>Premier•Sound</i>
	OS	Dual Windows NT 4.0 SP6a/Windows 2000 SP1 pre-install

Standard Features – Custom Configuration Models

Deskpro Workstation AP230-Flexible Solutions Configured to Order

Order the Compaq Deskpro Workstation the way the customer wants it by selecting the processor, hard drive, memory, graphics controller, and more. Purchase directly from Compaq or a Compaq Authorized Agent. Configurable components and Options change frequently. Check the Compaq Product Bulletin or www.compaq.com for the latest options available from Compaq. **Note:** This Web site is available in English only.

Chipset – Intel 815E

Processor and Speed	Intel Pentium III Processors	Standard L2 Cache	256-KB Integrated ECC
<i>One of the following</i>	1.2GHz	Front Side Bus	133 MHz
	1 GHz	Maximum Memory	512MB
	933 MHz		

Hard Drive

<i>One of the following</i>	18.2-GB 10,000 rpm Ultra160 SCSI with PCI Ultra160 Controller
	18.2-GB 15,000 rpm Ultra160 SCSI with PCI Ultra160 Controller
	20-GB 7200 rpm SMART III Ultra ATA/100 with Drive Protection System
	20-GB 7200 rpm SMART III Ultra ATA/100 with Drive Protection System (<i>Quite Seek and Idle HDD (EMEA ONLY)</i>)
	40-GB 7200 rpm SMART III Ultra ATA/100 with Drive Protection System

Memory

<i>One of the following</i>	128-MB SDRAM (PC133) (utilizes one DIMM slot)
	256-MB SDRAM (PC133) (utilizes one DIMM slot)
	384-MB SDRAM (PC133) (utilizes two DIMM slots)
	512-MB SDRAM (PC 133) (utilizes two DIMM slots)

Removable Storage

1.44-MB Diskette Drive

Optical Storage

48X CD-ROM Drive
16X DVD-ROM Drive
8X/4X/32X CD-RW Drive

Keyboard/Mouse

Easy Access Keyboard

Audio

Integrated Intel Audio with Premium Internal Speaker

Network Controller

Integrated Intel PRO/100 VM Network Connection
V.90 56K PCI Modem

Graphics

One of the following:

Matrox G450 Dual Head 32-MB AGP
ELSA Synergy II 32-MB AGP
NVIDIA Quadro2 EX
NVIDIA Quadro2 MXR

Expansion Slots

(Total/Available)	
AGP	1/ up to 1 depending on model
PCI	5/ up to 4 depending on model

Expansion Capability

Memory Expansion Slots (DIMMS)	3 DIMMS
Memory Type	SDRAM
Maximum Memory	512MB

Expansion Bays

(Total/Available)	5/2
Internal	2
External	3

Standard Features – Custom Configuration Models

Chipset – Intel 815E (continued)

Operating System Dual Installation Windows 2000 with selectable Service Pack 1/Windows NT4.0 with Service Pack 6a

Note: Dual Installation- End-user must make a one-time selection between Windows NT 4.0 and Windows 2000. If end-user desires the rejected product(s) after selection is made, the end-user must acquire and pay for rejected product separately.

Interfaces	I/O Chip	Socket 370, Coppermine 128K/256K FC-PGA 66/100/133 FSB
	Serial Port/UART Type	Yes
	Parallel Port	Yes
	USB	2 ports
	Infrared Port	No
	Network	RJ-45 (with integrated LEDs)
	Keyboard	Yes
	Mouse	Yes; PS/2
	Video	Yes
	Audio	Yes

Power Conservation “Energy Saver”	Energy Star Compliant	Yes (on select models)
	Power Consumption in ES Mode	http://www.eng.hou.compaq.com/-agency/e-star.htm Note: This Web site is available in English only.
	APM Support	Version 1.2
	Screen Blanking	Yes
	Hard Disk ‘Idle’ Mode	Yes
	System Idle Mode	Yes
	Cache Memory Power-Down	No
	CD-ROM Down	Yes
	System Environmental Specifications Temperature, Acoustics, Shock, Vibration, and Altitude	http://envwebserver.eng.hou.compaq.com/envtestlab/prod02.htm Note: This Web site is available in English only.

Boot Support	Local Diskette Boot	Yes (Windows 95, Windows 98.DOS)
	Remote Diskette Boot	No
	Network Boot	Yes

Initial Configuration and Deployment	Altiris eXpress	http://www.compaq.com/im
	PC Transplant/PC Transplant PRO	http://www.compaq.com/im
	System Software Management ver 1.4	http://www.compaq.com/im
	Novel ZenWorks 2.0	http://www.compaq.com/im
	IM LC ver 1.6	http://www.compaq.com/im
	Support Software CD	http://www.compaq.com/im Note: These Web sites are available in English only.
	Compaq OS Restore CD	Yes

Standard Features – Custom Configuration Models

Chipset – Intel 815E (continued)

Asset Control	Asset Tag	Yes
	DIMM Serial Presence Detect	Yes
	Hard drive serial number, model, and manufacturer	Yes
	Monitor serial number, model and manufacturer	Yes
	System serial number, model, and manufacturer	Yes
	ROM revision levels	Yes
	Systemboard revision level	Yes
	Compaq Fingerprint Identification Technology	Yes/Optional
	Configuration Control Hardware	No
	DMI BIOS	Yes
	Memory Change Alert	Yes
	Ownership Tag	Yes
	Kensington Lock Support	Yes

Standard Security Features	Cable Lock Provision	Yes
	Power-On Password	Yes
	QuickBlank/QuickLock	No
	Serial, Parallel, USB Port Control	Yes
	Removable Media Write/Boot Control	Yes
	Setup Password	Yes

Software Updating and Management	Compaq Info Messenger	Yes
	Remote Security Management	Yes
	Remote ROM Flash	Yes, requires CPQRS driver
	Remote Wakeup/Remote Shutdown	Yes
	ROM-Based Setup and Diagnostics	Yes
	Support Software CD & WWW site	Yes

Fault Notification and Recovery	DMI BIOS	Yes
	SMART Hard Drives, Fault Notification, & Prefailure Warranty	Yes
	Proactive Backup	Yes
	ECC Memory, Fault Notification, and Pre-failure Warning	Not Supported: 815E does not support ECC memory
	Processor Fault Notification and Prefailure Warranty	Yes
	Surge Tolerant Power Supply	Yes
	Thermal Sensor	Yes
	Ultra ATA Integrity Monitoring	Yes

Standard Features – Custom Configuration Models

Chipset – Intel 815E (continued)

Other Features	ACPI-Ready Hardware	Yes
	Compaq Insight Manager LC and XE Agents	Yes
	Altiris agent	Yes
	Compaq Management Solutions Partners Program	Yes
	Dual-State Power Button	Yes
	Compaq Management Solutions Partners Program	Yes
	Wired for Management Support	Yes

Intelligent Manageability

Compaq Intelligent Manageability, a key component of PC Lifecycle Solutions, is the broad set of manageability features found on all Compaq Deskpro desktops, *Armada* portables, Deskpro Workstation, *Professional Workstation*, and *ProLiant* server products. These best-in-class features on PC clients comply with industry standards, such as DMI and Wired for Management, while pioneering new ground in client manageability. Compaq introduced the industry's first line of manageable clients in 1995 and has been driving the industry ever since. With Compaq's lifecycle management philosophy, enterprises have all of the pieces for end-to-end management and proven tools for hassle-free management of PCs and significantly lower total cost of ownership.

Intelligent Manageability offers solutions in the areas of Initial Configuration and Deployment, Asset Tracking and Security, Software Updating and Management, and Fault Notification and Recovery. For more information, visit our Web site: www.compaq.com/im. Note: This Web site is available in English only.

Software	Windows 3.1	No
	Windows NT 4.X	Yes
	Windows 2000	Yes
	Windows NT 4.X/Windows 2000	Yes
	Computer Setup Utility	Yes
	Insight Personal Edition	Yes
	Diagnostics for Windows	Yes
	Microsoft Internet Explorer	Yes
	Compaq Information Center	No
	Intelligent Manageability Agent	Yes

Power Supply 200 Watts

Service and Support

On-site Warranty and Service ^{Note 1}: This three-year, limited warranty and service offering delivers three years of on-site, next business-day ^{Note 2} service for parts and labor and includes free telephone support ^{Note 3} 24 x 7. Global coverage ^{Note 2} ensures that any product purchased in one country and transferred to another non-restricted country will remain fully covered under the original warranty and service offering.

Note 1: Terms and conditions may vary by country. Certain restrictions and exclusions apply.

Note 2: On-site service may be provided pursuant to a service contract between Compaq and an authorized Compaq third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.

Note 3: Technical telephone support applies only to Compaq-configured, Compaq and Compaq-qualified, third-party hardware and software. Toll-free calling and 24 x 7 support may not be available in some countries.

After-Market Options

Memory (DIMMs)	133-MHz SDRAM DIMMs		
	256-MB Memory Kit (1 x 256-MB SDRAM DIMM, 133 MHz)	174225-B21	
	128-MB Memory Kit (1 x 128-MB SDRAM DIMM, 133 MHz)	174224-B21	
	Bulk		
	256-MB Memory Kit (1 x 256-MB SDRAM DIMM, 133-MHz)	174233-B21	
	128-MB Memory Kit (1 x 128-MB SDRAM DIMM, 133-MHz)	174232-B21	
	Monitors	TFTs	
		Compaq TFT8020 Monitor (18-inch, Opal)	326100-001
Compaq TFT8020 Monitor (18-inch, Carbon)		159244-001	
Compaq TFT5010 Monitor (15-inch, Opal)		104741-001	
Compaq TFT5010 Monitor (15-inch, Carbon)		154486-001	
Compaq TFT5005 Monitor (15-inch, Opal)		201431-001	
Compaq TFT5005 Monitor (15-inch, Carbon)		201430-001	
CRTs			
Professional Series			
Compaq P1210 CRT Monitor (21-inch, Opal)		210290-001	
Compaq P910 CRT Monitor (19-inch, Opal)		210254-001	
Compaq P710 CRT Monitor (17-inch, Opal)		210189-001	
Value Series			
Compaq V1100 CRT Monitor (21-inch, Opal)		386472-001	
Compaq V710 CRT Monitor (17-inch, Opal)		187895-001	
Standard Series			
Compaq S910 CRT Monitor (19-inch, Opal)		138485-001	
Compaq S710 CRT Monitor (17-inch, Opal)		152991-001	
Compaq M710 CRT Monitor (17-inch, Opal)		154499-005	
Compaq S710 CRT Monitor (17-inch, Carbon)		154499-002	
Compaq S510 CRT Monitor (15-inch, Carbon)		168636-002	
Graphics		Controller Cards	
		Matrox G450 32-MB AGP	202389-B21
	ELSA Synergy II 32-MB AGP	103382-B21	
	NVIDIA Quadro2 EX	232090-B21	
	NVIDIA Quadro2 MXR	221412-B21	
Tape Drives	33/66 GB VXA-1 SCSI Tape Drive (Opal)	237108-B21	
	33/66 GB VXA-1 IDE Tape Drive (Opal)	237109-B21	
	33/66 GB VXA-1 Media (2-Pack)	237111-B21	
	VXA-1 Cleaning Cartridge	237110-B21	

After-Market Options

Optical Drives	<i>DVD-ROM Drives</i>	
	16X/40X DVD-ROM Drive	211055-B21
	<i>CD-ROM Drives</i>	
	48X CD-ROM Drive	187217-B21
	<i>CD-RW Drives</i>	
	8X/4X/32X CD-RW Drive	294407-B21
Hard Drives	<i>Ultra ATA/100 Hard Drives with Drive Protection System (DPS)</i>	
	20-GB Ultra ATA 100 (7200 rpm) Hard Drive w/DPS - Quiet Seek and Quiet Idle	176275-021
	20-GB Ultra ATA 100 (7200 rpm) Hard Drive w/DPS - Quiet Seek	176272-B21
	40-GB Ultra ATA 100 (7200rpm) Hard Drive w/DPS - Quiet Seek and Quiet Idle	201066-B21
	<i>SCSI Hard Drives</i>	
	18-GB 10K rpm Ultra 160 SCSI Hard Drive	159764-B21
	18GB 15K rpm Ultra 160 SCSI Hard Drive	191188-B21
	Controllers/Cables/Adapters	Adaptec 29160N Ultra 160 Single Channel SCSI Controller
Multimedia	Premier•Sound™ PS330 Speakers	160992-001
	Altec Lansing ACS21 Speakers	194839-001
	Altec Lansing ACS33 Speakers	203621-001
Communications	Compaq V.90 56K PCI Modem	171914-001
Input/Output Devices	Compaq Easy Access Keyboard	122660-006
Support Software CD	Annual Subscription	183426-001
	Single CD-ROM (current month)	272505-001
Other	Rack Mount Conversion Kit, fixed Rails	303606-B21
	Sliding Shelf Kit	332564-B21
	Depth Adjustable Rails	332558-B21

Memory

815E chipset (128 MB)

133-MHz SDRAM DIMM MEMORY

STANDARD MEMORY

128-MB DIMM Standard

STANDARD MEMORY PLUS OPTIONAL MEMORY

Support for up to 512 MB of DIMM memory is available with the installation of optional SDRAM Memory Kits.

STANDARD MEMORY REPLACED WITH OPTIONAL MEMORY

Support for up to 512 MB of DIMM memory is available with the removal of the standard 128-MB DIMM and the installation of optional SDRAM Memory Kits.

Memory		Slot		
		1	2	3
Standard	128 MB	128 MB	Empty	Empty
Optional	512 MB	128 MB	128 MB	256 MB
Maximum	512 MB	256 MB	256 MB	Empty

Note: All Compaq Deskpro Workstation AP230 series contain three DIMM slots, but can only be upgraded to a maximum of 512 MB. The limitation of 512 MB maximum is a limitation of the memory controller in the 815E chipset.

Note: It is not necessary to add memory in pairs or kits. Memory upgrades are accomplished by adding single or multiple DIMMs of the same or varied sizes. This chart does not represent all possible memory configurations.

Memory

815E chipset (256 MB)

133-MHz SDRAM DIMM MEMORY

STANDARD MEMORY

256-MB DIMM Standard

STANDARD MEMORY PLUS OPTIONAL MEMORY


Support for up to 512 MB of DIMM memory is available with the installation of optional SDRAM Memory Kits.

Memory		Slot	
		1	2
Standard	256 MB	256 MB	Empty
Optional	512 MB	256 MB	256 MB

Note: All Compaq Deskpro Workstation AP230 series contain three DIMM slots, but can only be upgraded to a maximum of 512 MB. The limitation of 512 MB maximum is a limitation of the memory controller in the 815E chipset.

Note: It is not necessary to add memory in pairs or kits. Memory upgrades are accomplished by adding single or multiple DIMMs of the same or varied sizes. This chart does not represent all possible memory configurations.

Storage



DESKPRO WORKSTATION AP230 SERIES DRIVE SUPPORT

	Quantity Supported	Position Supported	Controller
CONVERTIBLE MINITOWER			
Diskette Drives	1	3	Floppy
Floppy Drives	1	3	IDE
CD-ROM Drives	2	1,2	IDE
DVD-ROM Drives	2	1,2	IDE
CD-RW Drives	2	1,2	IDE
SMART III Ultra ATA Hard Drives	Up to 2	4,5	Ultra ATA
SCSI Hard Drives	Up to 2	4,5	SCSI

Technical Specifications

System Unit	Chassis	Color	Opal
		Architecture	PCI/AGP
		System Board Form Factor	Standard ATX wit custom power supply
		Flash ROM	Yes
Dimensions (HxWxD)		17.65 x 6.6 x 17.11 in/44.83 x 16.76 x 43.46 cm	
Weight (approximate)		26 lbs/11.8 kg	
Weight Supported		100 lbs/45.5 kg	
Power Supply	Operating Voltage Range	90 to 132 VAC/180 to 264 VAC	
	Rated Voltage Range	100 to 127 VAC/200 to 240 VAC	
	Rated Line Frequency	50 to 60 Hz	
	Rated Input Current	6A/3A	
	Maximum Rated Power	200W	
	Power Supply Fan	Variable speed fan integrated into power supply	
	Processor Fan	Fixed Speed	
	Chassis Fan	Variable speed fan mounted to chassis (Convertible Minitower and Slim Desktop only)	
Temperature	Operating	50° to 95°F/10° to 35°C	
	Non-operating	-4° to 140°F/-20° to 60°C	
Humidity	Operating	20% to 80%	
	Non-operating	10% to 90%	
Maximum Altitude	Operating	0 to 10,000 ft/0 to 3,048 m	
	Non-operating	0 to 30,000 ft/0 to 9,144 m	
	Maximum Rate of Change	1500 feet per minute/457 meters per minute	

Technical Specifications

Compaq Easy Access Keyboard	Dimensions (HxWxD)	18.3 x 6.3 x 1.4 in/465 x 160 x 36 mm	
	Weight	Approximately 2 lbs/0.9 kg	
Electrical	Operating Voltage	+5VDC \pm 5%	
	Power Consumption	50 mA maximum (with 3 LEDs on)	
	System Interface	PS/2 mini-din connector	
	ESD	CE level 4, 15 kV air discharge	
	EMI-RFI	Conforms to FCC rules for a Class B computing device	
	PC98	Functionally compliant	
	Mechanical	Languages	30+ available
Keycaps		Low-profile design	
Switch Actuation		55 g nominal peak force with tactile feedback	
Switch Life		20 million keystrokes (using Hasco modified tester)	
Switch Type		Contamination resistant membrane	
Key Leveling Mechanism		For all double wide and greater length keys	
Cable Length		6 ft/1.8 m	
PC98-99		Mechanically compliant	
Acoustics		50 dBA maximum sound pressure level	
Environmental	Operating Temperature	50° to 122° F/10° to 50° C	
	Non-operating Temperature	-22° to 140° F/-30° to 60° C	
	Operating Humidity	10% to 90% (non condensing at ambient)	
	Non-operating Humidity	20% to 80% (non condensing at ambient)	
	Operating Shock	40 g, 6 surfaces	
	Non-operating Shock	80 g, 6 surfaces	
	Operating Vibration	2 g peak acceleration	
	Non-operating Vibration	4 g peak acceleration	

Technical Specifications

Compaq 3-Button Mouse	Dimensions/Weight	Height	1.42 in/3.6 cm
		Length	4.17 in/10.7 cm
		Width	2.87 in/7.4 cm
		Weight	5.20 oz/150 g
Environmental	Operating Temperature	32° to 104° F/0°C to 40° C	
	Non-operating Temperature	-4° to 140° F/-20° to 60°C	
	Operating Humidity	10% to 90% (non condensing at ambient)	
Mechanical	Resolution	400 ± 20% DPI	
	Tracking Speed	10 in/s Maximum	
	Tracking Mechanism Life	300 miles/483 km at average speed of 10 in/s	
	Switch Life	1,000,000 operations (using Hasco modified tester)	
	Switch Life	1,000,000 operations (using Hasco modified tester)	
	Switch Type	Micro-switches	
	Tracking Mechanism Life	155 miles/250 km at average speed of 10 in/s	
	Cable Length	6 ft/1.8 m	
	PC98-99	Mechanically compliant	
Regulatory Approvals	Compliant	UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick	

Technical Specifications

1.44-MB Diskette Drive	Diskette Size	3.5 in	
	LED Indicators (front panel)	Green	
	Read/Write Capacity per Diskette (high/low density)	1.44 MB/720 KB	
	Drive Supported	One	
	Drive Height	One-third	
	Drive Rotation	300 rpm	
	Transfer Rate (high/low)	500/250 Kb/s	
	Bytes/Sector	512	
	Sectors/Track (high/low)	18/9	
	Tracks/Side (high/low)	80/80	
	Access Times	Track-to-Track (high/low)	3/6 ms
		Average (high/low)	169/94 ms
		Settling Time	15 ms
		Latency Average	100 ms
Cylinders (high/low)	80/80		
Read/Write Heads	Two		

Technical Specifications

Ultra 160 SCSI Hard Drives	18.2 GB 10K	Capacity	18,200 MB		
		Height	1 in/25.4 mm		
		Width	3.5 in/88.9 mm		
		Interface	Ultra 160 SCSI		
		Transfer Rate Synchronous (Maximum)	160 MB/s		
		Seek Time (typical reads, including settling)	Single Track	0.6 ms	
			Average	4.7 ms	
			Full-Stroke	12 ms	
		Rotational Speed	10,000 rpm		
		Physical Configuration	Logical Blocks	35,566,000	
Operating Temperature	50° to 95°F/10° to 35°C				
<hr/>					
	18.2 GB	Capacity	18,200 MB		
		Height	1 in/25.4 mm		
		Width	3.5 in/88.9 mm		
		Interface	Ultra 160 SCSI		
		Transfer Rate Synchronous (Maximum)	160 MB/s		
		Seek Time (typical reads, including settling)	Single Track	0.8 ms	
			Average	4.1 ms	
			Full-Stroke	7.7 ms	
		Rotational Speed	15,000 rpm		
		Physical Configuration	Logical Blocks	35,566,000	
	Operating Temperature	50° to 95°F/10° to 35°C			
<hr/>					
SMART III Ultra ATA/100 Hard Drives	40 GB	Capacity	40,000 MB		
		Height	1 in/25.4 mm		
		Width	3.5 in/88.9 mm		
		Interface	Ultra ATA/100		
		Transfer Rate Synchronous (Maximum)	100 MB/s		
		Seek Time (typical reads, including settling)	Single Track	1.2 ms (2.7 ms quiet seek)	
			Average	8 ms (10.1 ms quiet seek)	
			Full-Stroke	18 ms (21.1 ms quiet seek)	
		Rotational Speed	7200 rpm		
		Physical Configuration	Logical Blocks	78,165,360	
Operating Temperature	41° to 131°F/5° to 55°C				
<hr/>					
20-GB 7200rpm drives shipping in EMEA with Quiet Seek also have Quiet Idle technology, which reduces acoustic levels by approximately 5 decibels	20 GB	Capacity	20,000 MB		
		Height	1 in/25.4 mm		
		Width	3.5 in/88.9 mm		
		Interface	Ultra ATA/100		
		Transfer Rate Synchronous (Maximum)	100 MB/s		
		Seek Time (typical reads, including settling)	Single Track	1.2 ms (2.7 ms quiet seek)	
			Average	8 ms (10.1 ms quiet seek)	
			Full-Stroke	18 ms (21.1 ms quiet seek)	
		Rotational Speed	7200 rpm		
		Physical Configuration	Logical Blocks	39,102,336	
Operating Temperature	41° to 131°F/5° to 55°C				

Technical Specifications

48X CD-ROM Drive		
Bus		
Data Buffer	16.6 MB/s	
Data Transfer Rate Rate (1 KB = 1,024 bytes)	Sustained Variable	150 KB/s Minimum (audio) CD: 3,000 to 7200 KB/s
Disk Rotation Technology	CAV-Constant Angular Velocity	
Access Time (ms)	Random	< 100 ms
	Full-Stroke Seek	< 150 ms
Access Seek Time		
Cache Buffer Standard/Maximum	128 KB	
Interface	ATAPI	
Disk Formats Read	Photo-CD/Multi-session, CD-ROM, Multi Read, CD TEXT, Audio CD, CD-I, CD-RW and CD-R CD-EXTRA and CD-ROM XA	
Disk Formats Written	None	
Disk	Capacity	CD: 650 MB
	Block Size	Mode 1 – 2,048 bytes Mode 2 – 2,340, 2,336 bytes CD-DA – 2,352 bytes CD-XA – 2,328 bytes
	Diameter	12 cm; 8 cm
	Thickness	1.2 mm
	Track Pitch	1.6 µm
Audio Output Level	Line-out	0.7 V @ 47 Kohm
	Headphone	0.6 V @ 32 ohm
Startup Time	< 7 seconds (typical); < 30 seconds with multi-session	
Operating Conditions	Temperature	41° to 113°F/5° to 45°C
	Humidity	10% to 80% relative humidity
Dimensions	(HxWxD, maximum)	1.7 x 5.9 x 8.2 in/42.9 x 150.1 x 208 mm
	Weight	2.6 lbs/1200 g
Approvals/Environmentals		
OS support	Windows NT 3.51/4.0 Windows 3.51/95/98/2000 OS/2	
MPEG playback graphics solution support	None	
Compaq Products Supported	Deskpro 2000, 4000, 6000, and Deskpro EP and EN Series	
Other	Operates in horizontal or vertical position	

Technical Specifications

16X DVD-ROM Drive	Bus	Ultra DMA 33
	Data Transfer Rate (1 KB = 1024 bytes)	Sustained DVD = 8.1 MB/s to 21.6 MB/s CD-ROM = 2.55 KB/s to 6.00 KB/s
	Disk Rotation Technology	DVD: CAV - Constant Angular Velocity CD: CAV - Constant Angular Velocity
	Access Time (ms)	Random DVD = <100 ms; CDROM = < 80 ms Full Stroke Seek DVD = <240 ms; CDROM = <160 ms
	Cache Buffer Standard / Max	512 KB
	ATAPI Interface	ATAPI
	Disk Formats Read	DVD-ROM Yes DVD-Video Yes DVD-R Yes DVD-RW Yes DVD-RAM No Photo-CD/Multi-session Yes CD-ROM Yes CD TEXT Yes Audio CD Yes CD-I Yes CD-RW Yes CD-R Yes CD-DA Yes Video CD Yes CD EXTRA Yes CD-ROM XA Yes MPEG Yes MPC Level 2 Yes
	Disk Formats Written	None
	Disk	Capacity CD = 650 MB DVD: 4.7 GB, 8.5 GB, 9.4 GB Block Size Mode 0 2352 (bytes) Mode 1 2352, 2340, 2336, 2048 (bytes) Mode 2 2352, 2340, 2336, 2048 (bytes) DVD – 2048 (bytes) Diameter 12 cm, 8 cm Thickness 1.2 mm (CD-ROM) 1.2 mm (DVD) Track Pitch 1.6 µm (CD-ROM) 0.74 µm (DVD)
	Audio Output Level	Line Out 0.7± 0.1 Vrms Headphones 0.45 ± 0.2 Vrms
	Operating Conditions	Temperature 41° to 113°F/5° to 45°C Humidity 5% to 85% relative humidity

Technical Specifications

16X DVD-ROM Drive <i>(continued)</i>	Dimensions (HxWxD)	1.67 x 5.83 x 8.18 in/4.23 x 14.8 x 20.75 cm
	Weight	2.22 lbs/1 kg
	Agency Approvals / Environmentals	UL, CSA, TUV, FDA, FCC, CE, EMI
	OS Support	Windows 98/98SE, Windows ME, Windows 2000, and Windows NT 4.0 (for data applications only)
	MPEG Video playback Compatibility	Please refer to the platform for support
	RPC2 (Regional Protection Control)	Yes
	Minimum CPU Supported	Pentium II 400 MHz or Celeron 466 MHz
	Mounting Orientation	Operates in horizontal or vertical position.
	Kit Contents	DVD-ROM Drive, MPEG playback software, IDE Cable, audio cable, installation instructions, and warranty card.

Technical Specifications

8X CD-RW Drive	Interface	ATAPI EIDE	
	Media formats read	CD-RW	CD-RW High-Speed
	CD-ROM	Yes	Yes
	CD-R	Yes	Yes
	CD-Digital Audio	Yes	Yes
	CD-Extra	Yes	Yes
	CD-ROM XA	Yes	Yes
	CD-I	Yes	Yes
	Audio CD	Yes	Yes
	Video CD	Yes	Yes
	Photo CD	Yes	Yes
	Multi Read	Yes	Yes
	Multi-session	Yes	Yes
	CD-Text	Yes	Yes
	Media formats written	32X Max CD-R and 8X Max CD-RW	Disc at once, Track at once, Fixed packet, Variable packet
	Media Capacity	650 MB	
	Data Transfer Rates Read	Sustained	CD-R Write: 1,200 Kb/s (8X) CD-RW Write: 600 Kb/s (4X) CD-RW Read: 1,200 Kb/s (8X) CD-ROM and CD-R Read: up to 4,800 Kb/s (32X)
		Variable	
	Access Times	Random	120 ms (typical)
		Full Stroke Seek	200 ms (typical)
	Disk Diameter	12 cm, 8 cm (read only)	
	Disk loading mechanism	Tray	
	Operating Conditions	Temperature	5° to 45°C
		Relative Humidity	10% to 80%
	Dimensions	Fits in a Standard 5.25 inch Drive Bay	
	Mounting	Horizontal or Vertical	
	Weight	2.4 lbs	
	Approvals/Environmental	FCC	Yes
		UL	Yes
		CSA	Yes
		CE	Yes
		FDA	Yes
		EN60 950	Yes
	Operating Systems Supported	Windows 98/98SE and Windows NT 4.0	
	Kit Contents	CD-RW Drive, IDE Cable, High-Speed CD-R Media, CD-RW Media, Roxio Software (Easy CD Creator and Direct CD), Install Guide, Warranty Card	

Technical Specifications

Integrated Intel Audio with Premier Internal Speakers	Card Type	PCI
	Plug and Play	Yes
	Stereo Codec	Yes
	OPL3 FM Synthesis	128 WaveTable Synthesizer
	Compatibility	Sound Blaster Sound Blaster Pro Full DOS Game Compatibility
	Ports	Microphone in (10 Kohm) Line-in (10 Kohm) Line-out/Headphone-out (33 ohm) <i>(Note: Line out cannot drive external passive speakers.)</i> MIDI (playback only) CD In TAD TV Tuner
	Sampling	48 KHz
	Compression	ADPCM, CCITT A-law, CCITT u-law
	OS support	Windows NT 4.0 Windows 95 Windows 98 DOS
	Wavetable Syntheses (software)	Yes
3D Positional Sound	Yes	
Analog Audio	<i>Premier•Sound™</i>	
Number of Channels (mono/stereo)	Mono	
Internal Audio Power Amp Rating	Nominal: 1.5 Watts RMS @ 8 ohms Maximum: 5 Watts RMS @ 8 ohms	
Number of Fixed Equalization Stages	6	
Speaker (Internal)	1.57 x 2.76 in/40 mm x 70 mm	

Technical Specifications

Integrated Intel PRO/100 VM Network Connection	Connectors	RJ-45		
	Expansion Bus Architecture	PCI 2.2		
	Network Transfer Rate	10Base-T (Half-Duplex)	10 Mb/s	
		10Base-T (Full-Duplex)	20 Mb/s	
100Base-TX (Half-Duplex)		100 Mb/s		
100Base-TX (Full-Duplex)		200 Mb/s		
Standards Compliance	IEEE VLAN Support (802.1A)			
	IEEE 802.2			
	IEEE 802.3 & IEEE 802.3u (100-Mb/s Ethernet)			
	IEEE Intel Priority Packet (801.1p)			
OS Driver Support	Microsoft Windows NT 3.51 and 4.0			
	Microsoft Windows 95, 98 and 2000 Beta			
	Novell Netware 3.11, 3.12 & 4.1x,			
	5 Server Sun Solaris™			
	SCO UnixWare			
	OpenDesktop OpenServer			
Remote Wakeup	Yes, (PME# and WAKE signals) - no cable required on 810 or 820 chipset platforms			
Proactive Alert Technology	Yes, alert on LAN (transmit functionality only) requires management console software, such as HP OpenView. It also requires alert utilities for the management console, proxy client software, and client configuration software.			
Boot PROM support	Yes, Intel PRO/100 Boot Agent (PXE 2.0, RPL)			
F12 BIOS Support	Yes			
Environmental Requirements				
Operating	Temperature	32° to 131° F/0° C to 55° C		
	Humidity (non-condensing)	85% at 131° F/55° C		
	Altitude	10,000 ft/3,048 m		
Non-Operating	Temperature	-40° to 158° F/-40° to 70° C		
	Humidity (non-condensing)			
	Altitude	5,000 ft/15,240 m		

Technical Specifications

Matrox Millennium G450 DualHead Graphics Controller	Form Factor	ATX
	Bus Type	AGP 1X, 2X, 4X
	Standard Memory	AGP: 32 MB
	DAC Speed	360 MHz (secondary DAC: 200 MHz)
	Data Path	External 64-bit DDR Internal 256-bit
	Internal Bus Width	256-bit DualBus
	Memory Interface	64-bit DDR Memory
	Frame Buffer	AGP: 32 MB
	Two Integrated RAMDACs	Yes
	Color Space Conversion	Yes
	Scaling	Yes
	Quick Draw Support	Yes
	DCI & DirectX Video Playback	Yes
	MS DirectDraw Support	Yes
	3D Support	Yes
	Engine Acceleration	3 ROP bitBLT Line Draw Text Color Expansion Basic Video Color Conversion and Scaling Triangle Setup Engine
	Output	Analog, 2 ports
	OS Support	Windows 2000/Windows NT 4.0, Windows 98, Linux, OS/2 Warp, and the upcoming Windows Millennium Edition
	Other	Texture mapping support Flat and Gouraud shading Direct 3D support Anisotropic Filter Perspective texture Specular highlighting Wireframe Dithering Full-scene anti-aliasing OpenGL support Vertex fog Dual Texture Mapping Environment-Mapped Bump Mapping Plug-and-Play AGP 2X and AGP 4X0.18-micron technology (lower heat/power consumption) High-quality DVD playback with full access to Windows

Technical Specifications

Matrox Millennium G450 DualHead Graphics Controller <i>(continued)</i>	3D Features	Single-cycle multi-texturing	Yes
		Environment-Mapped Bump Mapping	Yes
		Internal Rendering	32-bit
		Source Textures	Up to 32-bit
		Maximum Texture Size	2048 x 2048
		Hardware non-power-of- 2 textures	Yes
		32-bit Color Output	Yes
		32-bit Independent Z-buffer	Yes
		Stencil Buffering	Yes
		AGP Texturing	Yes
		Trilinear Filtering	Yes
		DirectX Support	Yes
		OpenGL Support	Yes
DualHead Display Features	Multi-Display Mode	Yes	
	DVD Max Mode	Yes	
	DualHead Zoom Mode	Yes	
	DualHead Clone Mode	Yes	
	DualHead TV Output Mode	Yes	
Supported Modes	This list assumes setup to be DualHead multi-display running Microsoft Windows 98. If using Windows NT 4.0 or Windows 2000 while in multi-display, primary CRT is limited to modes supported by second CRT.		
	Primary CRT Color	Color Depths (bpp)	Refresh Rates
	Depths		
	640 x 480	8, 16, 24, 32	60 Hz, 72 Hz, 75 Hz, 85 Hz
	800 x 600	8, 16, 24, 32	60 Hz, 72 Hz, 75 Hz, 85 Hz
	1024 x 768	8, 16, 24, 32	60 Hz, 70 Hz, 75 Hz, 85 Hz
	1152 x 864	8, 16, 24, 32	75 Hz
	1280 x 960	8, 16, 24, 32	60 Hz, 75 Hz, 85 Hz
	1280 x 1024	8, 16, 24, 32	60 Hz, 75 Hz, 85 Hz
	1600 x 1200	8, 16, 24, 32	60 Hz, 65 Hz, 70 Hz, 75 Hz, 85 Hz
	1800 x 1440	8, 16, 24,	60 Hz, 72 Hz, 75 Hz, 85 Hz
	1856 x 1392	8, 16, 24	60 Hz, 75 Hz, 85 Hz
	1920 x 1440	8, 16, 24	60 Hz, 75 Hz, 85 Hz
	2048 x 768	8, 16	60 Hz, 75 Hz
Secondary CRT Color	Color Depths (bpp)	Refresh Rates	
Depths			
640 x 480	16,32	60 Hz, 72 Hz, 75 Hz, 85 Hz	
800 X 600	16,32	60 Hz, 72 Hz, 75 Hz, 85 Hz	
1024 x 768	16,32	60 Hz, 72 Hz, 75 Hz, 85 Hz	
1152 x 864	16,32	75 Hz	
1280 x 960	16,32	60 Hz, 72 Hz, 75 Hz, 85 Hz	
1280 x1024	16,32	60 Hz, 72 Hz, 75 Hz, 85 Hz	
1600 x 1200	16,32	60 Hz, 65 Hz, 70 Hz, 75 Hz, 85 Hz	

Technical Specifications

ELSA Synergy II Graphics Controller	Dimensions (HxW)	3.25 x 6.25 in/8.3 x 15.9 cm		
	Resolution	Maximum Colors Supported	Maximum Refresh Rate	Memory Dedicated to Texture Support
	640 x 480	16.7M	120 Hz	29.1 MB
	800 x 600	16.7M	120 Hz	27.1 MB
	1024 x 768	16.7M	120 Hz	23.5 MB
	1152 x 864	16.7M	120 Hz	21.1 MB
	1280 x 1024	16.7M	120 Hz	17.9 MB
	1600 x 1000	16.7M	75 Hz	14 MB
	1600 x 1000	65K	85 Hz	14 MB
	1600 x 1200	16.7M	75 Hz	10.2 MB
	1600 x 1200	65K	85 Hz	10.2 MB
	1600 x 1280	16.7M	75 Hz	8.7 MB
	1600 x 1280	65K	85 Hz	8.7 MB
	1920 x 1080	16.7M	75 Hz	8.4 MB
	1920 x 1080	65K	85 Hz	8.4 MB
	1920 x 1200	16.7M	75 Hz	5.7 MB
	1920 x 1200	65K	75 Hz	5.7 MB
3D/2D Controller	Nvidia TNT 2			
VGA Controller	Integrated			
Bus Type	AGP 2X/4X			
RAMDAC	Integrated 300 MHz			
Memory Type	SDRAM			
Memory Amount	32 MB (Maximum)			
Memory Speed	143 MHz			
Controller Clock Speed	125 MHz			
Color Planes	24 bits double buffered			
Stencil Planes	8 bit			
Alpha Planes	0			
Z-buffer	24 bit			
Total bits/pixel	96			
Maximum Vertical Refresh Rate	120 Hz			
Maximum Pixel Clock	300 MHz			
Multi-display Support	No			
Operating Systems	Windows 2000, Windows NT 4.0, Windows 98			

Note: All drivers and enhanced software, including *POWERdraft*, *ELSAview*, and *MAXtreme*, can be found on the Compaq Web site at: www.compaq.com/support/files/workstations/us/index.html.

Technical Specifications

NVIDIA Quadro2 MXR Graphics Controller	Dimensions (LxHxW)	Approximately 6.5 x 3.8 x 0.6 in/16.51 x 9.65 x 1.52 cm		
	Resolution	Maximum Colors Supported	Maximum Refresh Rate	Memory Dedicated to Texture Support
	640 x 480	16.7 M	240 Hz	28.4 MB
	800 x 600	16.7 M	240 Hz	26.4 MB
	1024 x 768	16.7 M	200 Hz	22.8 MB
	1152 x 864	16.7 M	170 Hz	20.3 MB
	1280 x 1024	16.7 M	150 Hz	16.6 MB
	1600 x 1000	64 K	120 Hz	22.6 MB
	1600 x 1000	16.7 M	120 Hz	13.3 MB
	1600 x 1200	64 K	100 Hz	20.8 MB
	1600 x 1200	16.7 M	100 Hz	9.5 MB
	1600 x 1280	64 K	100 Hz	20 MB
	1600 x 1280	16.7 M	100 Hz	8 MB
	1920 x 1080	64 K	85 Hz	19.9 MB
	1920 x 1080	16.7 M	85 Hz	7.7 MB
	1920 x 1200	64 K	85 Hz	18.5 MB
	1920 x 1200	16.7 M	85 Hz	5 MB
3D/2D Controller	Integrated Quadro2 MXR 2D/3D 128-bit graphics processor unit (GPU)			
VGA Controller	Integrated into the Quadro2 MXR GPU			
Bus Type	AGP 2X, 4X Graphics Bus			
RAMDAC	350 MHz			
Memory Type	183 MHz SDR 2Mx32			
Memory Amount	32 MB			
Memory Speed	183 MHz			
Controller Clock Speed	200 MHz			
Color Planes	32-bit color buffer			
Overlay Planes	1 16-bit Video overlay plane, software emulation for OpenGL overlay planes			
Stencil Planes	8-bit stencil buffer			
Alpha Planes	8-bit alpha buffer			
Z-buffer	24-bit Z buffer			
Total bits/pixel	64-bits			
Maximum Vertical Refresh Rate	240 Hz			
Maximum Pixel Clock	350 MHz			
Multi-display support	Yes			
Operating Systems	Microsoft® Windows® 2000, Windows NT 4.0 available from Compaq			

Note: All drivers and enhanced software, including ELSA POWERdraft, ELSA MAXtreme, and NVIDIA QuadroView, can be found on the Compaq web site at: www.compaq.com/support/files/workstations/us/index.html.

Technical Specifications

NVIDIA Quadro2 EX Graphics Controller	Resolution	Maximum Colors Supported	Maximum Refresh Rate	Memory Dedicated to Texture Support
	640 x 480	16.7 M	240 Hz	28.4 MB
	800 x 600	16.7 M	240 Hz	26.4 MB
	1024 x 768	16.7 M	200 Hz	22.8 MB
	1152 x 864	16.7 M	170 Hz	20.3 MB
	1280 x 1024	16.7 M	150 Hz	16.6 MB
	1600 x 1000	64 K	120 Hz	22.6 MB
	1600 x 1000	16.7 M	120 Hz	13.3 MB
	1600 x 1200	64 K	100 Hz	20.8 MB
	1600 x 1200	16.7 M	100 Hz	9.5 MB
	1600 x 1280	64 K	100 Hz	20 MB
	1600 x 1280	16.7 M	100 Hz	8 MB
	1920 x 1080	64 K	85 Hz	19.9 MB
	1920 x 1080	16.7 M	85 Hz	7.7 MB
	1920 x 1200	64 K	85 Hz	18.5 MB
	1920 x 1200	16.7 M	85 Hz	5 MB
Dimensions (LxHxW)	Approximately 6.5 x 3.8 x 0.6 in/16.51 x 9.65 x 1.52 cm			
3D/2D Controller	Integrated Quadro2 EX 2D/3D 128-bit graphics processor unit (GPU)			
VGA Controller	Integrated into the Quadro2 EX GPU			
Bus Type	AGP 2X, 4X Graphics Bus			
RAMDAC	350 MHz			
Memory Type	183 MHz SDR 2Mx32			
Memory Amount	32 MB			
Memory Speed	183 MHz			
Controller Clock Speed	200 MHz			
Color Planes	32-bit color buffer			
Overlay Planes	1 16-bit Video overlay plane, software emulation for OpenGL overlay planes			
Stencil Planes	8-bit stencil buffer			
Alpha Planes	8-bit alpha buffer			
Z-buffer	24-bit Z buffer			
Total bits/pixel	64-bits			
Maximum Vertical Refresh Rate	240 Hz			
Maximum Pixel Clock	350 MHz			
Multi-display support	No			
Operating Systems	Microsoft® Windows® 2000, Windows NT 4.0 available from Compaq			

Note: All drivers and enhanced software, including ELSA POWERdraft, , can be found on the Compaq web site at: www.compaq.com/support/files/workstations/us/index.html.

Compaq PCs use genuine Microsoft® Windows®

www.microsoft.com/piracy/howtotell

Compaq, Deskpro, registered United States Patent and Trademark Office.

Intel, the Intel Inside Logo, and Pentium are registered trademarks of Intel Corporation.

Microsoft, MS, Windows and Windows NT are registered trademarks of the Microsoft Corporation in the U.S. and other countries.

Other product names mentioned herein may be trademarks and/or registered trademarks of their respective companies.

©2001 Compaq Computer Corporation.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>