
Overview



Introduction

The highly available HP StorageWorks SAN Switch 2/8V and 2/8V Power Pack offer 2 Gb connectivity for an entry-level storage area network (SAN), and the ability to grow to a core-to-edge infrastructure. The simplicity and ease-of-use advantages of the SAN Switch 2/8V and 2/8V Power Pack can help increase administrator productivity and lower the cost of management. This can be especially beneficial for organizations with limited IT expertise.

The Switch delivers eight high performance Auto Sensing 1 and 2 Gb Fibre Channel ports. In addition, the SAN Switch 2/8V and 2/8V Power Pack are fully non-blocking and provide 16 Gb switching (2 Gb full duplex) capacity for un-congested sustained, 2 Gb full duplex throughput. The SAN Switch 2/8V scales to a maximum fabric configuration of two switches and can be upgraded to full SAN configurations by purchasing a full fabric upgrade license. Small-form-factor-pluggable optical transceivers (SFPs) must be ordered separately.

The Power Pack provides the SAN administrator with the necessary tools to monitor the health and performance of the network, while also ensuring the highest levels of security, scalability and manageability. Available pre-configured on the switch or as an upgrade, Power Pack also provides the foundation for integration into HP OpenView Storage Area Manager (SAM), enabling infrastructure management through a single-pane-of-glass. The Power Pack tools can be ordered separately, as well.

Key Features and Benefits

- Reduced Total Cost of Ownership for SAN Infrastructure
 - Enables storage consolidation, simplified management of data center SAN environment
 - Interoperability with the more than 1 MILLION port HP SAN Switch installed base
- Highest integration with HP Open View Storage Area Manager via:
 - SAN Switch API
 - SAN Switch element managers
 - HP StorageWorks Fabric Manager
 - Broadest range of compatibility with SAN products
 - Multi-vendor server and storage environment
 - $\,\circ\,\,$ Widest range of HP SAN solutions
 - Backward compatible with previously installed 1Gb SAN Switches
- HP Power Pack (Optional) highest supported modular functionality
 - Trunking highest throughput between switches (8Gb/sec)
 - HW enforced WWN Zoning (Advanced Zoning)
 - Proactive threshold monitor (Fabric Watch)
 - Advanced Performance Monitor
 - Per Switch element manager (WebTools)
 - O Support for extended distance (Extended Fabrics)
 - Support for multi-protocol gateways (Remote Switch)
- Broadest Range of HP Packaged SAN Services
 - Mission critical SAN Services SAN-ES
 - $\,\circ\,\,$ Assessment and installation services for security
- Flexible storage connectivity
 - The only SAN solutions providing the complete HP SAN Switch functionality from Embedded to Enterprise. The HP SAN Switch value line
 products allows the capability to apply the complete SAN Switch functionality to an affordable entry level SAN deployment and then to grow
 that deployment to the largest SAN fabric solutions supported by HP.



HP StorageWorks SAN Switch 2/8V and 2/8V Power **Pack B-Series Family**

Models

HP StorageWorks SAN	HP StorageWorks SAN Switch 2/8V	AA979A
Switch 2/8V SAN Switch 2/8V Power Pack Models	HP StorageWorks SAN Switch 2/8V 2-Switch to Full Fabric Upgrade License	AA975A
	HP StorageWorks SAN Switch 2/8V Power Pack	AA980A
	SAN Switch Power Pack Software Bundle (optional)	T3573A



HP StorageWorks SAN Switch 2/8V and 2/8V Power Pack B-Series Family

Product Highlights

8 non-blocking ports	Eight auto-sensing 1 and 2 Gb universal, self-configuring ports (F, FL, E). Can be programmed to fixed 1 Gb or 2 Gb speed. Full 16 Gb switching capacity for un-congested fully sustained, 2 Gb full duplex throughput.				
Configuration support	SAN Switch 2/8V Power Pack will interoperate with 1Gb and 2Gb B-Series SAN Switches running the firmware version defined in the SAN Design Guide http://h18000.www1.hp.com/products/storageworks/san/documentation.html				
High-availability features	Hot Code Load Activation				
Advanced Fabric Services	 ISL Trunking (optional) Hardware Enforced Zoning WebTools Remote Switch (optional) Fabric Watch (optional) End-to-End Performance Analysis (optional) 				
Manageability	 WebTools OpenView API IP SNMP 				
Scalability	 SAN Switch 2/8V has a two switch SAN scaling limit (standard) Optional full SAN scaling license 				

Software Components, Standard

Frame Filtering	An ASIC based capability in the 2Gb family of switches that enables new applications and features. The switch now has the ability to "view" the first 64 bytes of the Fibre Channel frame. At this time, Frame Filtering enables advanced capabilities such as Advanced Zoning and Advanced Performance Monitoring.		
Advanced Zoning	In the 2 Gb generation of switches, WWN Zoning and Access Control are enforced by hardware that provides the same simple administration previously enforced only with software. Administrators can organize a physical fabric into logical groups and prevent unauthorized access by devices outside the Zone.		
WebTools	Enables organizations to monitor and manage single Fibre Channel switches and small SAN fabrics. Tasks can be performed through a Java-capable Web browser from a standard laptop, desktop PC or workstation from any location within the enterprise.		

Software Components, Optional

SAN Switch 2/8V Power Includes bundled license for: Pack Software Bundle ISL Trunking

- Advanced Performance Monitoring
- Fabric Watch
- Extended Fabric
- Remote Switch



Product Highlights

ISL Trunking	For high performance enhanced Trunking, this optional license logically groups up to four E-ports to provide a high bandwidth trunk between two switches. Each 2 Gb switch needs its own license. The switch operating system views the trunk as a single, high bandwidth resource (up to 8 Gb) when routing connections between switches. Connections are load- balanced across the individual links, which comprise the logical trunk group. Each 8-port switch can have a total of two separate 4-port Trunk groups.
Advanced Performance Monitor	This enabling technology helps administrators monitor and watch specific fabric metrics from a SID (Source ID) to a DID (Destination ID), so they can fine-tune and scale the fabric more efficiently. Plus, Advanced Performance Monitoring includes the ability for early warning detection of hot spots within the fabric, a powerful tool for maintaining overall balanced performance.
Fabric Watch	Fabric Watch enables each switch to monitor the SAN for potential faults-and automatically alert network managers to problems before they become failures. Fabric Watch tracks a variety of SAN fabric elements, events, and counters. Monitoring fabric-wide events, ports, SFPs, and environmental parameters permits early fault detection and isolation as well as performance measurement. Each switch in the SAN needs its own Fabric Watch license.
Extended Fabric	Extends all of the scalability, reliability, and performance benefits of Fibre Channel Storage Area Networks (SANs) beyond the native 10 km distance specified by the Fibre Channel standard. Required with future use of Very Long Distance SFPs and/or wavelength division multiplexing (WDM or DWDM).
Remote Switch	Remote switch fabric functions with the aid of a bridging device or network bridge. The network bridge supports both Fibre Channel physical interfaces, as well as secondary non-Fibre Channel FCIP physical interface.
Fabric Manager (v4.1.1)	Fabric Manager is a highly scalable, Java-based application that manages multiple switches and multiple fabrics (up to eight) in real time, helping SAN administrators with SAN configuration, monitoring, dynamic provisioning, and daily management. SAN administrators gain rapid access to critical SAN information across multiple personality fabrics.
Secure Fabric OS	Secure Fabric OS [™] is a comprehensive security solution for SAN fabrics, providing policy-based security protection for more predictable change management, assured configuration integrity and reduced risk of downtime. Secure Fabric OS protects the network by using the strongest, enterprise-class security methods available, including digital certificates and digital signatures, multiple levels of password protection, strong password encryption and Public Key Infrastructure (PKI)-based authentication, and 128-bit encryption of the switch's private key used for digital signatures. With its flexible design, Secure Fabric OS enables organizations to customize SAN security to meet specific policy requirements. In addition, Secure Fabric OS works in conjunction with Advanced Zoning to further secure access to the SAN, simplify storage management, and reduce provisioning time.
Full Fabric License for 2/8V	Expands connectivity from 2 switch scaling to full fabric scaling. Please see the following web site for further information: http://h18006.www1.hp.com/products/storageworks/san/documentation.html



Service and Support, HP Care Pack and Warranty Information

Warranty	(1-1-1) Hardware Warranty - One-year on-site warranty, 8x5, next business day response, installation not included. NOTE: The hardware warranty covers firmware and embedded non-saleable software. Saleable software carries its own warranty, see below. Software Warranty - HP warrants only that the software media will be free of physical defects for a period of ninety (90) days from delivery. EXCLUSIVE REMEDY. The entire liability of HP and its suppliers and your exclusive remedy for software that does not conform to this Limited Warranty shall be the repair or replacement of the defective media. This warranty and remedy are subject to your returning the defective media during the warranty period to HP in the country in which you obtained the software.				
HP Service & Warranty Support	HP Service & Warranty Support Additional Warranty protection and/or HP Installation packages can be purchased. NOTE: Certain restrictions and exclusions apply. Consult the Customer Support Center for details. HP provides a one-year, hardware limited warranty, fully supported by a worldwide network of resellers and service providers. In addition, available service offerings include a full range of HP Care Pack packaged hardware and software services: Installation				
	 Extended coverage hours and enhanced response times System management and performance services 				
	For more information on warranty and support options, please visit our Web site at: http://www.hp.com/hps/tech/storage/supp/.				
Software Product Services	 Stand-alone telephone support Rights to new license version Media and documentation updates 				
Hardware Product Services	 Installation services On-site maintenance (includes warranty support) Response time upgrades during the warranty period Post-warranty coverage 				
HP Care Pack Services Warranty Upgrade Options	 Service offerings include a full range of Customer HP Care Pack services for both hardware and software services: Response - Upgrade on-site response from next business day to same day 4-hours Coverage - Extend hours of coverage from 5 days x 9 hours to 7 days x 24 hours Duration - Select duration of coverage for a period of 1, 3, or 5 years Additional Warranty protection and/or HP Installation packages can be purchased. NOTE: Certain restrictions and exclusions apply. Consult the HP Customer Support Center for details. 				
HP Care Pack Information	HP Care Pack is defined as an upgrade to the product warranty attribute, available for a specific duration and hours of coverage.				
	 HP Care Pack is not available for less than the product's warranty duration. HP Care Pack is available for sale anytime during the warranty period for most products, but the commencement date will be the same as the Warranty Start Date (delivery date to end user customer). Proof of purchase may be required. HP Care Pack services are prepaid. For additional HP Care Pack (hardware & software) information, as well as orderable part numbers, please refer to the URL 				
	listed below: http://h18005.www1.hp.com/services/carepaq/index.html				
Additional Services	Implementation service, SAN Architecture service. For more information on service options, please visit our Web site at: http://www.hp.com/go/san.				



Family Information

Features	MSA SAN Switch 2/8 (embedded switch)	SAN Switch 2/8V and SAN Switch 2/8V Power Pack Workgroups,	SAN Switch 2/16V Workgroups,	SAN Switch 2/16N FF and SAN Switch 2/16N Power Pack Departments,	SAN Switch 2/32 and SAN Switch 2/32 Power Pack Departments,	Core 2/64 and Core 2/64 Power Pack Data Centers	SAN Director 2/128 and Director 2/128 Power Pack Data Centers
Targeted Environment	Workgroups, Departments	Departments	Departments	Departments, Data Centers	Departments, Data Centers	Dala Ceniers	Data Centers
Port Bandwidth	2 Gbit/sec	2 Gbit/sec	2 Gbit/sec	2 Gbit/sec	2 Gbit/sec	2 Gbit/sec	2 Gbit/sec
Aggregate device bandwith	32 Gbit/sec end-to-end	32 Gbit/sec end-to-end	64 Gbit/sec end-to-end	64 Gbit/sec end-to-end	128 Gbit/sec end-to-end	256 Gbit/sec end-to-end	512 Gbit/sec end-to-end
OS Support				SAN Design Guide			
	ļ		/ww.compaq.com/p	, in the second s	Y		
Storage system support	MSA 1000	MA8000 EMA12000/ EMA16000 EVA v2.0, XP, VA	MA8000 EMA12000/ EMA16000 EVA v2.0, XP, VA	MA8000 EMA12000/ EMA16000 EVA v2.0, XP, VA	MA8000 EMA12000/ EMA16000 EVA v2.0, XP, VA	MA8000 EMA12000/ EMA16000 EVA v2.0, XP, VA	MA8000 EMA12000/ EMA16000 EVA v2.0, XP, VA
Ports	7 external/1 internal	8 SFP	16 SFP	16 SFP	32 SFP	32 SFP Base 64 Total	32 SFP Base 128 Total
Cascading support	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Advanced Trunking	Optional Upgrade	Included with Power Pack or Optional Upgrade	Optional Upgrade	Included with Power Pack or Optional Upgrade	Included with Power Pack or Optional Upgrade	Included with Power Pack or Optional Upgrade	Included with Power Pack or Optional Upgrade
Form factor	Embedded	10	10	10	1.50	14U	14U
Zoning Software	Yes (Included)	Yes (Included)	Yes (Included)	Yes (Included)	Yes (Included)	Yes (Included)	Yes (Included)
Hot plug, redundant power supplies	No	No	No	No	Yes	Yes	Yes
Hot plug fans	No	No	No	No	Yes	Yes	Yes
Enterprise Backup Solution (EBS) support**	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	s correct Host Bus A	dapter. Not all Ope	rating Systems Supp	orted.	R	R	n



Configuration Information

Step 1 – Base Configuration

Select one:		
Model Name	Model Description	Part Numbe
	8-port Fibre Channel Fabric Switch, licenses, docs, and rack rails.	AA979
	NOTE: Requires optical transceivers listed below.	
StorageWorks SAN Switch 2/8	8-port Fibre Channel Fabric Switch with bundled software and rack rails.	AA980/
Power Pack	NOTE: Requires optical transceivers listed below.	
Add Software		
Power Pack Software Bundle for SAN Switch 2/8V	Fabric Watch, ISL Trunking, Extended Fabric, Remote Switch, Advanced Performance Monitoring	T3573.
Optional Software:	Fabric Watch	324504-B2
	ISL Trunking	324506-B2
	Advanced Performance Monitor	324507-B2
	Remote Switch	325891-B2
	Extended Fabric	324505-B2
	Secure Fabric OS for 8 & 16 port switches (v3.x firmware or higher)	332924-B2
	Fabric Manager v4.1.1	345690-B2
	Fabric Manager Upgrade License (v3.x to v4.1)	345691-B2
Step 2 – Additiona Optical Transceivers	I Options Short Wave Short Wave	221470-B2 300834-B2
	I Options Short Wave	300834-B2 300835-B2
Optical Transceivers	I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km)	300834-B2 300835-B2
Optical Transceivers	I Options Short Wave Short Wave Long Wave (10 km)	300834-B2 300835-B2 300836-B2
Optical Transceivers	I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km) LC-LC for between two 2 Gb devices	300834-B2 300835-B2 300836-B2 221692-B2
Optical Transceivers	I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km) LC-LC for between two 2 Gb devices 2 m LC-LC Multi-Mode Fibre Channel Cable	300834-B2 300835-B2 300836-B2 221692-B2 221692-B2 221692-B2
Optical Transceivers	I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km) IC-LC for between two 2 Gb devices 2 m LC-LC Multi-Mode Fibre Channel Cable 5 m LC-LC Multi-Mode Fibre Channel Cable	
Optical Transceivers	I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km) IC-LC for between two 2 Gb devices 2 m LC-LC Multi-Mode Fibre Channel Cable 5 m LC-LC Multi-Mode Fibre Channel Cable 15 m LC-LC Multi-Mode Fibre Channel Cable	300834-B2 300835-B2 300836-B2 221692-B2 221692-B2 221692-B2 221692-B2 221692-B2
Optical Transceivers	I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km) LC-LC for between two 2 Gb devices 2 m LC-LC Multi-Mode Fibre Channel Cable 5 m LC-LC Multi-Mode Fibre Channel Cable 15 m LC-LC Multi-Mode Fibre Channel Cable 30 m LC-LC Multi-Mode Fibre Channel Cable	300834-B2 300835-B2 300836-B2 221692-B2 221692-B2 221692-B2 221692-B2 221692-B2
Optical Transceivers	I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km) IC-LC for between two 2 Gb devices 2 m LC-LC Multi-Mode Fibre Channel Cable 5 m LC-LC Multi-Mode Fibre Channel Cable 15 m LC-LC Multi-Mode Fibre Channel Cable 30 m LC-LC Multi-Mode Fibre Channel Cable 50 m LC-LC Multi-Mode Fibre Channel Cable	300834-B2 300835-B2 300836-B2 221692-B2 221692-B2 221692-B2 221692-B2 221692-B2 221692-B2
Optical Transceivers	I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km) LC-LC for between two 2 Gb devices 2 m LC-LC Multi-Mode Fibre Channel Cable 5 m LC-LC Multi-Mode Fibre Channel Cable 15 m LC-LC Multi-Mode Fibre Channel Cable 30 m LC-LC Multi-Mode Fibre Channel Cable 50 m LC-LC Multi-Mode Fibre Channel Cable LC-SC for between a 1 Gb and a 2 Gb device	300834-B2 300835-B2 300836-B2 221692-B2 221692-B2 221692-B2 221692-B2 221692-B2 221691-B2
Optical Transceivers	I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km) LC-LC for between two 2 Gb devices 2 m LC-LC Multi-Mode Fibre Channel Cable 5 m LC-LC Multi-Mode Fibre Channel Cable 15 m LC-LC Multi-Mode Fibre Channel Cable 30 m LC-LC Multi-Mode Fibre Channel Cable 50 m LC-LC Multi-Mode Fibre Channel Cable LC-SC for between a 1 Gb and a 2 Gb device 2 m LC-SC Multi-Mode Fibre Channel Cable	300834-B2 300835-B2 300836-B2 221692-B2 221692-B2 221692-B2
Optical Transceivers	I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km) IC-LC for between two 2 Gb devices 2 m LC-LC Multi-Mode Fibre Channel Cable 5 m LC-LC Multi-Mode Fibre Channel Cable 15 m LC-LC Multi-Mode Fibre Channel Cable 30 m LC-LC Multi-Mode Fibre Channel Cable 50 m LC-LC Multi-Mode Fibre Channel Cable LC-SC for between a 1 Gb and a 2 Gb device 2 m LC-SC Multi-Mode Fibre Channel Cable 5 m LC-SC Multi-Mode Fibre Channel Cable	300834-B2 300835-B2 300836-B2 221692-B2 221692-B2 221692-B2 221692-B2 221692-B2 221691-B2 221691-B2
	I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km) IC-LC for between two 2 Gb devices 2 m LC-LC Multi-Mode Fibre Channel Cable 5 m LC-LC Multi-Mode Fibre Channel Cable 15 m LC-LC Multi-Mode Fibre Channel Cable 30 m LC-LC Multi-Mode Fibre Channel Cable 50 m LC-LC Multi-Mode Fibre Channel Cable LC-SC for between a 1 Gb and a 2 Gb device 2 m LC-SC Multi-Mode Fibre Channel Cable 5 m LC-SC Multi-Mode Fibre Channel Cable 15 m LC-SC Multi-Mode Fibre Channel Cable	300834-B2 300835-B2 300836-B2 221692-B2 221692-B2 221692-B2 221692-B2 221692-B2 221691-B2 221691-B2 221691-B2
Optical Transceivers	 I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km) LC-LC for between two 2 Gb devices 2 m LC-LC Multi-Mode Fibre Channel Cable 5 m LC-LC Multi-Mode Fibre Channel Cable 15 m LC-LC Multi-Mode Fibre Channel Cable 30 m LC-LC Multi-Mode Fibre Channel Cable 30 m LC-LC Multi-Mode Fibre Channel Cable 50 m LC-LC Multi-Mode Fibre Channel Cable 2 m LC-SC for between a 1 Gb and a 2 Gb device 2 m LC-SC Multi-Mode Fibre Channel Cable 5 m LC-SC Multi-Mode Fibre Channel Cable <td>300834-B2 300835-B2 300835-B2 200836-B2 221692-B2 221692-B2 221692-B2 221692-B2 221691-B2 221691-B2 221691-B2 221691-B2 221691-B2</td>	300834-B2 300835-B2 300835-B2 200836-B2 221692-B2 221692-B2 221692-B2 221692-B2 221691-B2 221691-B2 221691-B2 221691-B2 221691-B2
Optical Transceivers	I Options Short Wave Short Wave Long Wave (10 km) Long Wave (35 km) LC-LC for between two 2 Gb devices 2 m LC-LC Multi-Mode Fibre Channel Cable 5 m LC-LC Multi-Mode Fibre Channel Cable 15 m LC-LC Multi-Mode Fibre Channel Cable 30 m LC-LC Multi-Mode Fibre Channel Cable 50 m LC-LC Multi-Mode Fibre Channel Cable 50 m LC-LC Multi-Mode Fibre Channel Cable 2 m LC-SC for between a 1 Gb and a 2 Gb device 2 m LC-SC Multi-Mode Fibre Channel Cable 5 m LC-SC Multi-Mode Fibre Channel Cable 30 m LC-SC Multi-Mode Fibre Channel Cable 30 m LC-SC Multi-Mode Fibre Channel Cable 50 m LC-SC Multi-Mode Fibre Channel Cable 50 m LC-SC Multi-Mode Fibre Channel Cable 50 m LC-SC Multi-Mode Fibre Channel Cable	300834-B2 300835-B2 300836-B2 221692-B2 221692-B2 221692-B2 221692-B2 221691-B2 221691-B2 221691-B2 221691-B2 221691-B2 221691-B2



Technical Specifications

Fibre Channel ports	8 universal ports				
Scalability	Full fabric architecture:				
	http://h18006.www1.hp.com/	'products/storageworks/san/c	documentation.html		
Certified maximum	Refer to SAN Design Guide: http://h18006.www1.hp.com/products/storageworks/san/documentation.html				
Interoperability	http://ii8006.wwwi.np.com/products/storageworks/san/documentation.html SAN Switch 8, SAN Switch 16, SAN Switch 8-EL, SAN Switch 16-EL, Integrated /32, Integrated /64, SAN Switch2/16, SAN Switch 2/16-EL, SAN Switch 2/				
Performance	2.125 Gbit/sec line speed, full duplex				
Switch core	Non-blocking				
Fabric latency	${<}2\mu$ sec. with no contention,	cut-through routing			
Maximum frame size	2112-byte payload				
Classes of service	Class 2, Class 3, Class F (inte	r-switch frames)			
Port types	FL_Port, F_Port, and E_Port; s	elf-discovery based on switch	type (U_Port)		
Data traffic types	Fabric switches support unicas	st, multicast (256 groups), an	d broadcast		
Media types	Small Form-Factor Pluggable	(SFP)			
Laser	Short-wave up to 1,640 ft (30	0 m); long-wave up to 6.2 m	i (10 km) when available		
Fabric services	Simple Name Server, Registered State Change Notification (RSN), Alias Server (multicast); and Zoning, WebTools. Optional Fabric Watch, Extended Fabrics, and Remote Switch				
Options	SFP media				
Supported software	Telnet, SNMP, WebTools, Adv	anced Zoning, Fabric Watch	, Extended Fabrics, Remote Switch		
Management access	10/100 Ethernet (RJ-45), serial port				
Diagnostics	POST and embedded online/offline diagnostics				
Back-to-front airflow, power from rear	1 υ, 19-in.–EIA compliant				
Dimensions	Width	10.4 in/26.4 cm			
	Height	1.71 in/4.2 cm			
	Depth	16.9 in/42.8 cm			
	Weight	8.5 lb/3.9 kg			
Environment	Temperature	Operating	50° to 104° F (10° to 40° C)		
		Non-operating	-13° to 158° F (-25° to 70° C)		
	Humidity	Operating	5% to 85%		
		Non-operating	104° F (40° C)		
	Altitude	Up to 9,800 ft (3,000 m)			
	Shock	80 G, 2.5 ms, half sine			
	Vibration	Operating	.5 G, 5-500-5 Hz		
		Non-operating	10 G, 0-5 kHz		
Power	Supported power range	Nominal	100 to 240 VAC contiguous, 0.5 A for each power supply		
		Operational	90 to 264 VAC		
	Frequency	47 to 63 Hz			

© Copyright 2004 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com