NEW MODEL INFORMATION

DTS-ES and Dolby Digital EX A/V Receiver

DENON AVR-1804



DENON's Basic Design for High-Quality Sound Reproduction Power Transformer for High Power Driven

The chassis that supports the large transformer has been designed to absorb vibration, and the transformer is housed inside a highly rigid frame to secure it more solidly to the chassis. In addition, a cushioning material has been placed around the core of the transformer to minimize interference on the signal and enable more faithful reproduction of the original sound. DENON's higher-end models incorporate these low-noise designs, such as the use of short rings.



• Twin Drive Rectifier

DENON's Twin Drive Rectifier design uses two rectifying diodes in parallel to bring out the maximum potential of the large transformer. Since the rectifiers power the large block capacitors at low impedance, they are able to supply ample current to reproduce deep basses as well as sudden bursts of sound from percussion or other musical instruments.

Large Aluminum Extruded Heatsink

DENON uses large heatsink made of extruded aluminum. They have been placed in a design that ensures mostly uniform temperatures throughout the heatsink so that the output transistors for all channels can be driven under uniform conditions. This in turn ensures that all channels respond with equal performance to the demands of the audio signals.



■ Fully Discrete, Equal Power Six Amplifier Channels, 90 Watts Each

Front	90 W + 90 W	(8 ohms, 20 Hz - 20 kHz, 0.08 % THD)
Center	90 W	(8 ohms, 20 Hz - 20 kHz, 0.08 % THD)
Surround	90 W + 90 W	(8 ohms, 20 Hz - 20 kHz, 0.08 % THD)
Surround Back	90 W	(8 ohms, 20 Hz - 20 kHz, 0.08 % THD)

For optimum Dolby Digital and DTS reproduction, the AVR-1804 features high quality, wideband audio amplification, providing 90 watts power output for each of the six main channels. A large capacity power supply includes a high current power transformer along with discrete power output devices on all six amplifier channels for highest dynamic range and superb reproduction clarity.

Single-Channel Surround Back Power Amp for 6.1 Surround and 2 Speaker Terminals for 7.1 Surround

The AVR-1804 is equipped with a total of 6 power amps including one for the Surround Back speaker to give you more clearly defined sound localization at the rear for 6.1-channel surround sources such as DTS-ES Discrete 6.1, DTS-ES Matrix6.1, Dolby Digital EX, and DTS-ES NEO:6. The AVR-1804 also provides you with 2 speaker terminals for the Surround Back channels, allowing for the ultimate home theater experience in amazing 7.1-channel Surround.

■ 32 bit High Quality DSP

A-high -quality 32-bit DSP "MELODY 32" from Analog Devices has been used in the DSP processor, placing the AVR-1804 at a higher rank than other models of this class in its ability to accurately decode and reproduce the superior quality of surround sources.

■ 24 bit, 96 kHz High Resolution D/A Conversion

Wide-Range Play Capability for DVD-Audio and SACD

The power amp circuits of the AVR-1804 have been meticulously designed to reproduce the exceptionally high sound quality with wide frequency response from 10 Hz to 100 kHz.

Cinema Equalizer

The sound from movie sources recorded in Dolby Digital, DTS or other formats emphasizes high-frequency range due to a theater's front speakers being placed behind the movie screen. If this sound is reproduced in the home theater without correction, the high-frequency range is too strong. The AVR-1804 features a Cinema Equalizer to correct these high-frequency components so that the sound is clearer and easier to listen to. (For Dolby Digital, Dolby Pro Logic II, Dolby Digital EX and DTS surround modes)

Personal Memory Plus, for Easy Operation

The AVR-1804 includes the Personal Memory Plus function that automatically remembers the surround mode you last used for each program source, so that you do not need to select the mode again for that program.

On Screen Display

The AVR-1804 lets you make system settings via diaplays on your TV scren from the comfort of your chair.

Acclaimed Customization Feature

As with all of DENON's high-grade A/V receiver, the AVR-1804 lets you adjust delay times and other parameters so that you can customize the performance of the AVR-1804 to suit your own home theater and enhance operating ease. The adjustments are easy to make via a dialog format on the fluorescent display on the front panel. These customized features are then stored, for each source input and surround mode, in Personal Memory Plus so constant readjustments are not required.

■ Multi-Function Preset Memory Remote Controller with Glow-keys

The supplied system remote controller features a large selection of remote control codes to operate other components in your home theater system, including codes for selected DENON models, along with remote control codes from other manufacturers. The most frequently used buttons are laid out separately for TV, VCR and DVD, for maximum ease-of-use.

Remote control codes cannot be used with the products of other manufacturers and some DENON products.

■ DTS-ES (Discrete 6.1 / Matrix 6.1) and DTS NEO:6 Decoder

Dolby Digital, Dolby Pro Logic II and Dolby Digital EX Decoder

■ 6 Channel Stereo Mode

DENON's popular 6 Channel Stereo mode transforms your favorite 2-channel sources such as CD, tape, stereo radio and stereo video sources into exciting surround sound, free of delay effects and unnatural artifacts, from all six speakers. This 6 Channel Stereo mode was originally developed by DENON to enhance music lovers' enjoyment of home theater ambience.

Virtual Surround Mode

Surround yourself with sensational 3D soundfield envelopment using just one pair of speakers. The AVR-1804's Virtual Surround mode provides a dramatic psychoacoustic surround sound effect, using two speakers with all sources.

DENON DSP Surround Modes Add Listening Excitement

Put yourself in the middle of your favorite concert hall and music environments with DENON's DSP acoustic environment simulation modes. These DSP modes add spacious surround sound enhancements to your favorite music and video sources.

Adjustable Cross-Over Switching

The AVR-1804 supports subwoofer cross-over switching with a choice of 4 cross-over frequencies: 80, 100, 120 and 150. This lets you more accurately match the performance characteristics of the subwoofer to the main speaker system.

Support for Multi-Zone Configurations

The AVR-1804 provides a Multi Zone Output function and a Select function that let you output different surces to multiple zones. Sources can be selected for output to an additional zone, in addition to the main room.

Multi Zone Power Amplifier Assign

The AVR-1804's Power Amplifier Assign function lets you assign the Surround Back (SB) amplifier channel when the system is not configured for 6.1 to instead drive the Multi-room Zone 2 speaker (mono), with 90 Watts per channel output power, while still providing 5 discrete amplifier channels to drive all speakers in a 5.1 configured home theater room

REC OUT Selector

- High-guality Component Video In/Out Terminals
- Video Conversion
- Digital Optical Output
- Front Panel Inputs (with S-Video, Digital Optical Input)
- Front A/B Speaker Terminals
- High-grade Speaker Terminals (except speakers B)
- Frequency Synthesis Tunina
- 40-Station AM/FM Random Preset Memory Tuning
- Auto Preset Memory



Specifications

Input/Output Terminals For Every A/V System

•	Audio Inputs	
	9 Analog Inputs	PHONO, CD, TUNER, DVD/VDP, TV/DBS,
	6 Analog EXT. Input	VCR-1, VCR-2, CDR/TAPE, V.AUX(FRONT) FRONT L/R, CENTER, SURROUND L/R, SUBWOOFER
	1 Digital (Optical) Input	
	1 Digital (Coaxial) Input	
•	Audio Outputs	
	1 Analog PRE OUT Terminals	SUBWOOFER
	3 Analog REC OUT Terminals	VCR-1, VCR-2, CDR/TAPE
	1 Analog Multi Zone 2 Output	L/R
	1 Digital (Optical) Output	OPTICAL x 1

Video Inputs

2 Component Video Input	VIDEO1, VIDEO2
5 Composite Inputs	DVD/VDP, TV/DBS, VCR-1, VCR-2,
	V.AUX(FRONT)
5 S-Video Inputs	DVD/VDP, TV/DBS, VCR-1, VCR-2,
	V.AUX(FRONT)

Video Outputs

1 Component Video Output MONITOR		
3 Composite Outputs	VCR-1, VCR-2, MONITOR	
3 S-Video Outputs	VCR-1, VCR-2, MONITOR	

Power Amplifier Section

Rated output	*THD figures a	re power amp stage values.
Front	. 90 W + 90 W	(8 ohms, 20 Hz - 20 kHz, 0.08 % THD)
	125 W + 125 W	(6 ohms, 1 kHz, 0.7 % THD)
Center	. 90 W	(8 ohms, 20 Hz - 20 kHz, 0.08 % THD)
	125 W	(6 ohms, 1 kHz, 0.7 % THD)
Surround	. 90 W + 90 W	(8 ohms, 20 Hz - 20 kHz, 0.08 % THD)
	125 W + 125 W	(6 ohms, 1 kHz, 0.7 % THD)
Surround Back	. 90 W	(8 ohms, 20 Hz - 20 kHz, 0.08 % THD)
	125 W	(6 ohms, 1 kHz, 0.7 % THD)

Preamplifier Section

Input sensitivity/Impedance PHONO(MM) 2.5 mV/47 kohms CD, DVD/VDP, TV/DBS, VCR-1, VCR-2, CDR/TAPE, V.AUX(FRONT) 200 mV/47 kohms Output level/Load impedance SUBWOOFER 1.2 V/10 kohms CDR/TAPE, VCR-1, VCR-2, ZONE2 Frequency response 10 Hz - 100 kHz (+1, -3 dB) (Tone Defeat On) Signal-to-noise ratio 100 dB (IHF-A weighted) (Tone Defeat On) Tone control Treble: ±12 dB at 10 kHz Bass: ±12 dB at 100 Hz

FM Section

Tuning frequency range	87.5 - 107.9 MHz
Usable sensitivity	1.0 µV (11.2 dBf)

AM Section

Tuning frequency range 520 - 1710 kHz Usable sensitivity 18 µV

General

Power supply	AC 120 V, 60 Hz
Power consumption	4.5 A
Dimensions	434 (W) x 171 (H) x 416 (D) mm
	17.1" (W) x 6.7" (H) x 16.4" (D)
Weight	11.9 kg, 28.6 lbs

*Design and specifications are subject to change without notice. *"Dolby", "Dolby Digital", "Pro Logic II", "Dolby Digital EX" and the double-D device are registered trademarks of Dolby Laboratories Licensing Corporation. *DTS is registered trademarks of DTS Technology.

DENON ELECTORONICS (USA), INC. 19 CHAPIN ROAD BLDG#C, PINE BROOK, NJ 07058, U.S.A. TEL : 973-396-0810 www.usa.denon.com

DENON CANADA INC. 505 APPLE CREEK BLVD. UNIT 5 MARKHAM, ONTARIO L3R5B1, CANADA TEL : 905-475-4085 www.denon.ca

DENON, LTD. 3-16-11, YUSHIMA, BUNKYO-KU, TOKYO 113-0034, JAPAN

AVR18043.QXD 03.7.11 10:04 AM Page 3

.11 10:04 AM Page 3



Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com