802.11b/g MIMO Wireless LAN PCI Card

Caution

This Quick Installation is meant to help you install the product quickly and easily. For detailed instructions on installation, configuration, and further setup options please consult the User Manual.





Quick Install

There are two modes for you to choose in this screen, either choose WiFi mode or Performance mode (Tx Burst mode). This mode selection screen is set for the default mode shown in the utility screen. You can still change its mode later in the utility screen. Click Next to



Click Continue Anyway to proceed with the Installation.

When the following screen appears, click **Finish** to



Installation Verification

Download from Www.Somanuals.com. All Manuals Search And Download.



Utility Configuration

All settings are categorized into SIX tabs, including **Profile Tab**, Link Status Tab, Site Survey Tab, Statistics Tab, Advanced Tab and About Tab

Profile Tab

The **Profile** screen enables you to create, edit, delete, activate, de-activate and raise/lower priorities of the profiles, which are used by the station to connect to WLAN networks.

Infrastructure

Link Status Tab

The Link Status screen displays the Link Quality, Signal Strength and some other current linking information.

Status: AirLive (→ 00 £0 9812/3456 Extra Info : Link is Up [TxPower:100%] Channel : [6 <→ 2437000 KHz Link Speed : Tx (Mbps) 12.0 Rx (Mbps) 1.0 Throughput: Tx (Mbps) 0.0 Rx (Mbps) 3.5 Normal 65% dBm 5 Link Quality: Weak 26% dBm Signal Strength: Weak 23% 5 Normal 70% 100 100	ofile Link Status 9	Site Survey S	tatistics	Advanced	About	
Extra Info : Link is Up [TxPower100%] Channel : 6 <→ 2437000 KHz Link Speed : Tx (Mbps) 12.0 Rx (Mbps) 1.0 Throughput: Tx (Kbps) 0.0 Rx (Kbps) 3.5 Normal 55% Link Qualty : Weak 26% dBm Signal Strength : Weak 23% Signal Strength : Weak 70%	Status :	AirLive <>	00-E0-9	8-12-34-56		
Link Speed: Tx (Mbps) 120 Rx (Mbps) 1.0 Throughput: Tx (Kbps) 0.0 Rx (Kbps) 3.5 Normal 65% Link Quality: Weak 26% dBm Signal Strength: Weak 23% Signal Strength: Weak 23%	Extra Info :	Link is Up [TxPower	r:100%]	Channel : 6 <>	2437000 KHz
Throughput: Tx (Kbps) 0.0 Rx (Kbps) 3.5 Normal 65% 0.0 Rx (Kbps) 3.5 Link Quality: Weak 26% 0.0 0.0 Signal Strength: Weak 23% 0.0 0.0 Signal Strength: Weak 23% 0.0 0.0 Normal 70% 0.0 0.0 0.0	Link Speed :	Tx (Mbps)		12.0	Rx (Mbps)	1.0
Normal 65% Link Quality: Week 25% View 25% dBm Signal Strength Week 23% Signal Strength Week 23%	Throughput :	Tx (Kbps)		0.0	Rx (Kbps)	3.5
Link Quality: Weak 26% / dBm Signal Strength: Weak 23% Signal Strength: Weak 23% Signal Strength: Normal 70%		Normal	65%			
Weak 26% dBm Signal Strength : Weak 23% Signal Strength : Normal 70%	Link Quality :					
Signal Strength : Weak 23% Signal Strength 2 Normal 70%		Weak	26%			dBm
Signal Strength2 Normal 70%	Signal Strength :					
Signal Strength2 Normal 70%		Weak	23%			
Normal 70%	Signal Strength2					
Noire Level		Normal	70%			
TRONG LEVEL.	Noise Level :		ПТ			
					0	

Site Survey Tab

The **Site Survey** screen displays a list of infrastructure and ad-hoc networks available for connection.

SSID	BSSID	Sig	C	Encrypt	Authent	Network T.
cc-11g	00-0A-79-6E-20	47%	5	TKIP;A	WPA-P	Infrastruct
AirLive	00-E0-98-12-34	23%	6	None	Unknown	Infrastruct
B055-11g	00-0F-66-EE-16	23%	8	TKIP	WPA-P	Infrastruct
00-11g	00-20-A6-4F-2E	26%	10	TKIP	WPA-P	Infrastruct
\$]						>

Statistics Tab

The **Statistics** screen displays the statistics on your current network settings.

file Link Status Site Survey Statistics Advanced ,	About	
Transmit Statistics		
Frames Transmitted Successfully	=	379
Frames Transmitted Successfully Without Retry	=	367
Frames Transmitted Successfully After Retry(s)	=	12 2 0
Frames Fail To Receive ACK After All Retries	-	
RTS Frames Successfully Receive CTS	=	
RTS Frames Fail To Receive CTS	=	0
Receive Statistics		
Frames Received Successfully		31
Frames Received With CRC Error		50811
Frames Dropped Due To Out-of-Resource	-	0
Duplicate Frames Received	=	0
		Reset Count

Advanced Tab

The **Advanced** screen lets you configure the advanced wireless settings including wireless security settings.

Wireless mode 802.11 B/G	mix Select Your Country Region Code
B/G Protection Auto	
Tx Rate Auto	LEAP turn on CCKM
	Enable Radio Measurement
-	Non-Serving Channel Measurements
Enable TCP Window Size	Limit 250 milliseconds (0-2000)
Fast Roaming at 70 dBm	
Turn off RF	Apply

AboutTab

The About screen displays the basic version information about the Config Version, Driver Version, EEPROM Version and Firmware Version.

Config Version :	0.9.5.0	Date :	12-12-2005
Driver Version :	1.0.3.0	Date :	10-27-2005
EEPROM Version :	1.0	Firmware Version :	0.8
IP Address :	169.254.97.119	Phy_Address: 0	0-E0-98-12-54-08
C. A. Marila	255 255 0.0	Default Gatewau :	

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com