

# F-Series F-315/F-317

VALUE CHOICE *PLUS*

## AG Neovo F-Series *PLUS* Displays

Made for those who want an excellent value display with added multimedia and video power



### Elegant & Rugged Design

Smart exterior with exceptional strength

### Enhanced Audio Delivery

Built-In speakers providing an improved soundstage utilizing SRS™3D and WOW™ technologies

### Ease of Use

A host of video options, including analog, s-video, CVBS and component video

### Picture-In-Picture

Simultaneous computer display and video signal playback

### Desk/Arm/Wall Flexibility

VESA Compatible LCD display arm or wall mount kit both available

### Features

15"/17" TFT Active Matrix Screen  
1024x768/1280x1024 Resolution  
Analog and Video Inputs  
Built-In Speakers with SRS™ Audio Effects  
Ultra Slim & Lightweight

**AG neovo**

A Different Class Of Display

## F-Series Displays



### Video In Port

Connect DVD, VCR or other video devices directly via a video in port.



### Picture-In-Picture

Watch computer display and DVD, VCR or other video simultaneously.



### Built-in Speakers

Eliminate the need for external speakers, and enjoy a rich multimedia experience.



### WOW Technology

Produces a taller and wider soundstage with enhanced bass performance (F-317).



### SRS 3D Technology

Delivers a panoramic 3D soundstage from ordinary audio input (F-315).



### Auto-Adjustment

Automatically adjusts screen settings for an optimal image, without changing settings manually.



### OSD

On-Screen Display (OSD) makes adjusting the display settings quick and convenient.



### Cable Management

Built In cable management system promotes a clutter-free and more organized desktop.



### LCD Display Arm

Advanced gas-spring suspension guarantees smooth stable operation, and flexibility of use.



### Wall Mount Kit

Mount the LCD display on the wall to save even more valuable desktop space.



### Security Lock

Increase security by anchoring the LCD display to an immovable object. Compatible with Kensington® security locks.



## Specifications

## F-315

## F-317

<b>Panel</b>	Panel Type	TFT LCD	TFT LCD
	Panel Size	15.0" (381mm)	17.0" (432 mm)
<b>VGA Analogue Input Signal</b>	Max. Resolution	XGA 1024 x 768	WXGA 1280 x 1024
	Pixel Pitch	0.297mm	0.264mm
	Brightness	350cd/m <sup>2</sup> (Typical)	250cd/m <sup>2</sup> (Typical)
	Contrast Ratio	500:1 (Typical)	500:1 (Typical)
	Surface Treatments	Hard Coating (3H), Anti-glare treatment, Anti-static	Hard Coating, Anti-glare treatment, Anti-static
	Viewing Angle (H/V)	170°/170° (Minimum)	170°/170° (Minimum)
	Wide Viewing Angle	Yes	Yes
	Display Color	16.7M	16.7M
	Response Time	15ms /10ms (Typical)	15ms /10ms (Typical)
	CCFL	4	4
Life Time (Hours)	50,000 (typical)	50,000 (min)	
<b>Video Input</b>	Signal System	NTSC, PAL, SECAM	NTSC, PAL, SECAM
	Input Level	1Vp-p @ 7ohm	1Vp-p @ 7ohm
	Input Level	1Vp-p @ 7ohm	1Vp-p @ 7ohm
<b>Connector</b>	Analog	15-Pin Mini D-Sub	15-Pin Mini D-Sub
	Video (Option)	4-Pin Mini Din S-Video CVBS Jack Component Video	4-Pin Mini Din S-Video CVBS Jack Component Video
<b>Speaker Power</b>	Speaker	Yes (2W)	Yes (2W)
	Power	3-Pin AC Plug	3-Pin AC Plug
<b>Audio</b>	Input Level	Max: 1 Vp-p rms	Max: 1 Vp-p rms
	Audio-In	3.5mm audio line-in	3.5mm audio line-in
	Audio-Out	3.5mm headphone jack	3.5mm headphone jack
	Speakers	Two 2 watt built-in speakers	Two 2 watt built-in speakers
	Amplifier	1.5W at 1kHz	1.5W at 1kHz
SRS™ Audio Processor Effects	SRS™ 3D Stereo	WOW™ by SRS	
<b>Tilt/Swivel</b>	Tilt Angle / Swivel	0°~ 20° (Tilt)	0°~ 20° (Tilt)
<b>Mounting</b>	VESA FPM/PMI	Yes (100mm)	Yes (100mm)
<b>Dimensions</b>	Net (W x H x D)	416 x 364 x 160mm (16.4" x 14.3" x 6.3")	474 x 408 x 187mm (18.6" x 16.1" x 7.4")
	Packing (W x H x D)	465 x 420 x 150mm (18.3" x 16.5" x 5.9")	565 x 522 x 178mm (22.2" x 20.5" x 7.1")
<b>Weight</b>	Net Weight	3.7Kg (8.2lb)	4.9Kg (10.8lb)
	Gross Weight	5.9Kg (13.0lb)	6.9Kg (15.2lb)
<b>Regulation Approval</b>	Safety & EMI	FCC, UL/CUL, EPA, TUV/GS, CE, NORDIC, NUTEK, BSMI, VCCI, CCIB, CB, ISO13406, TCO95 or TCO99 (depends on color)	FCC, UL/CUL, EPA, TUV/GS, CE, NORDIC, NUTEK, BSMI, VCCI, CCIB, CB, ISO13406, TCO95 or TCO99 (depends on color)
	VESA	DDC1/2B, DPMS	DDC1/2B, DPMS
<b>Power</b>	Power AC	100~240V, 50~60Hz	100~240V, 50~60Hz
	Consumption	< 48W (On) < 5W (Stand-by) < 5W (Off)	< 48W (On) < 5W (Stand-by) < 5W (Off)

All specifications are subject to change without prior notice. © 2003 Associated Industries China Inc. The name AG Neovo is a trademark of AIC. All other trademarks are the property of their respective owners.

## Optional Accessories



WIRELESS R/F KEYBOARD & MOUSE

LCD DISPLAY ARM

TV TUNER FRAME

WALL MOUNT KIT

**AG neovo**  
A Different Class Of Display



## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>