



# RX-W19



► FEATURES

- High 1440 x 900 WXGA<sup>+</sup> resolution and high contrast ratio 1000:1
- Image sticking (burn-in) prevention function added to secure your investment
- Quick signal-switching time (≤ 0.8 sec.)
- Real-time displaying the image upon signal connection
- Video input settings will resume when power re-plug
- Looping video inputs for multiple connections
- Auto termination
- Supports NTSC/PAL/SECAM video system
- Supports color and B/W picture
- Selectable signal source
- PC & Mac compatible
- Auto-adjustment for optimal settings when VGA input is selected
- NeoV Optical Glass™
- Slim border & bezel design
- Distinctive metal alloy housing for added strength
- Kensington® security socket
- VESA standard wall mount

► SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD
	<b>Panel Size</b>	19" (481mm)
	<b>Max. Resolution</b>	WXGA <sup>+</sup> 1440 x 900
	<b>Pixel Pitch</b>	0.285mm
	<b>Brightness</b>	380cd/m <sup>2</sup> (Typical)
	<b>Contrast Ratio</b>	1000:1 (Typical)
	<b>Viewing Angle (H/V)</b>	170°/160° (Typical)
	<b>Display Color</b>	16.7M
	<b>Response Time</b>	5ms (GTG)
	<b>Frequency (H/V)</b>	H: 24kHz – 80kHz V: 56Hz – 75Hz
Input Connector	<b>Max. Pixel Clock</b>	150MHZ
	<b>Life Time</b>	50,000hrs (Minimum)
	<b>Analog</b>	15-Pin D-Sub
Input Signal	<b>Digital</b>	24-Pin DVI-D
	<b>BNC Security</b>	BNC Connector
	<b>Auto Composite System</b>	NTSC/PAL/SECAM
Output Connector	<b>BNC Security</b>	BNC Connector
	<b>NeoV Optical Glass</b>	
Tilt	<b>Thickness</b>	3.0mm (0.18")
	<b>Reflection Rate</b>	<1%
	<b>Transmission Rate</b>	>96%
Mounting	<b>Hardness</b>	>6H (MOH's Rating)
	<b>Tilt</b>	0° ~ +20°
	<b>VESA FPMPI</b>	Yes (100mm)
Regulation Approval	<b>Certifications &amp; Compliance</b>	FCC, UL/CUL, NOM, CB, CE, TUV/Baurt, BSMI, NORDIC, GOST, WEEE, RoHS
	<b>VESA</b>	DDC 1/2B, DDC-CI
	<b>Power Source Consumption</b>	100 - 240V, 50 - 60Hz <48W (On) <1W (Off)
Temperature	<b>Operation</b>	0°C ~ 40°C
	<b>Storage</b>	-20°C ~ 60°C
Dimensions	<b>Net (W x H x D)</b>	448 x 351 x 155 mm (17.6" x 13.8" x 6.1")
	<b>Packing (W x H x D)</b>	534 x 472 x 195 mm (21.0" x 18.6" x 7.7")
Weight	<b>Net Weight</b>	5.4kg (11.8 lbs)
	<b>Gross Weight</b>	7.9kg (17.5 lbs)
Packing	<b>1 Pallet</b>	48 Sets
	<b>20' Container</b>	480 Sets
	<b>40' Container</b>	960 Sets

All specifications are subject to change without prior notice

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>