

AS 4+3 Automixer



### Description

The AS 4+3 is an easy to use and affordable gating automixer that can easily be integrated into any sound reinforcement, teleconferencing or recording application. The AS 4+3 has four balanced mic inputs and three unbalanced line inputs, as well as, one balanced line output and one unbalanced record/line output.

Each of the four mic inputs have integrated and adjustable compressor/levelers making the AS 4+3 an automatic level control system. The compressor/levelers can help maintain consistent audio level despite various signal strengths that may be present at the microphone inputs. NOM attenuation decreases by 3dB every time the number of in-use mics doubles. A switcheable ducking function will attenuate all other inputs by 12dB when signal is present at mic input #1. Dipswitches on the rear panel allow for the line inputs to be exempted from the automix and/or ducking functions in the mixer.

The AS 4+3 was designed to operate with various types of microphones. Dip switches on the rear panel allow for 24 volt phantom powering of condenser microphones. The preamp gain range for the mic input signal are switcheable on the rear panel while front panel controls provide fine adjustment of input and output signals for an exact match into whatever component follows the AS 4+3.

More than one AS 4+3 may be daisy chained via expansion port connection incorporating the automix functions so that all will work together as one unit.

### **Features**

- Four automatic microphone inputs, three line inputs
- Integrated compressor/leveler for consistent levels
- Ducking/priority function
- Expansion ports for larger systems
- Low and high frequency shelving controls on master line output
- Balanced line output and unbalanced record output

# Architects and Engineers Specifications

The mixer shall be an automatic mixer capable of being daisychained, with four gated microphone inputs and three line inputs. The microphone inputs shall provide 24-V phantom power and a compressor limiter separately adjustable for each channel. The device shall be fitted with microphone inputs and a line output on 3-pin XLR connectors and line inputs and recording outputs on

RCA jacks. A switchable ducking function shall cause all other channels to be attenuated while there is activity in the MIC 1 channel. The mixer shall be fitted with a two-band equalizer (bass and treble) affecting only the main output signal. The automatic mixer shall be the AKG Acoustics Model AS 4+3.

## **Specifications**

| Microphone Inputs  |                                                                                                                                                                   |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Туре:              | balanced and RF filtered                                                                                                                                          |
| Impedance:         | approx. 2.4 k $\Omega$ at any level                                                                                                                               |
| Nominal level:     | -50 to -10 dBu adjustable<br>in two sub-ranges                                                                                                                    |
| S/N ratio:         | 75 dB (20 Hz to 22 kHz, rms)                                                                                                                                      |
| Max. input level:  | +5 dBu                                                                                                                                                            |
| Turn-on threshold: | -32 to 0 dB re nominal input level                                                                                                                                |
| Hold time:         | 1/4/8/12 secs. ±20%                                                                                                                                               |
| Gate attenuation:  | 14 to 26 dB, adjustable                                                                                                                                           |
| Compression ratio: | linear to 2:1, adjustable                                                                                                                                         |
| Audio bandwidth:   | 20 Hz to 35 kHz                                                                                                                                                   |
| NOM attenuation:   | 1 microphone:0 dB2 microphones:-2.1 dB3 microphones:-4 dB4 microphones:-5.5 dB5 microphones:-7.2 dB6 microphones:-8.6 dB7 microphones:-9.9 dB8 microphones:-11 dB |
| Phantom power:     | 24 V, switchable on each channel ( $Bi = 2 \times 1.2 \text{ kg}$ )                                                                                               |

| Line Inputs       |                              |
|-------------------|------------------------------|
| Туре:             | unbalanced and RF filtered   |
| Impedance:        | >35 kΩ                       |
| Nominal level:    | -10 dBu                      |
| S/N ratio:        | 75 dB (20 Hz to 22 kHz, rms) |
| Audio bandwidth:  | 20 Hz to 45 kHz              |
| Max. input level: | +5 dBu                       |
|                   |                              |

| System:              |                                      |
|----------------------|--------------------------------------|
| Max. gain:           | 55 dB (input to main output)         |
| Ducking attenuation: | 9 dB to 20 dB, adjustable            |
| THD:                 | <0.1%; at any level setting          |
| IM distortion:       | <0.1%; at any level setting          |
| Power requirement:   | 5 W max. at 12 V AC                  |
| Weight:              | 5.5 lbs. (2.5 kg )                   |
| Size:                | 19 x 1.7 x 7 in. (483 x 44 x 180 mm) |
|                      |                                      |

 $(Ri = 2 \times 1.2 \text{ k}\Omega)$ 

#### **Limited Warranty**

Valid only in the United States. AKG Acoustics warrants AKG products against defects in material or workmanship for a period of two years from the date of original purchase for use, and agrees to repair or, at our option, replace any defective unit without charge for either parts or labor. Important: This warranty does not cover damage resulting from accident, misuse or abuse, lack of reasonable care, the affixing of any attachment not provided with the product, loss of parts or connecting the product to any but the specified receptacles. This warranty is void unless service or repairs are performed by an authorized service center. No responsibility is assumed for any special, incidental

or consequential damages. However, the limitation of any right or remedy shall not be effective where such is prohibited or restricted by law. Simply take or ship your AKG product prepaid to our service department. Be sure to include your sales slip as proof of purchase date. (We will not repair transit damage under the no-charge terms of this warranty.) Note: No other warranty, written or oral is authorized by AKG Acoustics, Inc. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Some states do not allow the exclusion or limitation of incidental or consequential damages or limitation on how long an implied warranty lasts, so the above exclusions and limitation may not apply to you.

#### Microphones · Headphones · Wireless Microphones · Wireless Headphones · Headsets · Electroacoustical Components



Specifications subject to change without notice.

AKG Acoustics GmbH Lemböckgasse 21-25, P.O.B. 158, A-1230 Vienna/AUSTRIA Tel: (43 1) 86 654-0\*, Fax: (43 1) 86 654-516 Internet: http://www.akg.com

AKG Acoustics; A Division of Harman Pro Germany Bodenseestraße 228, D-81243 München/GERMANY Tel: (089) 87 16-0, Fax: (089) 87 16-200

Arbiter Pro Audio Wilberforce Road, London NW9 6AX/ENGLAND Tel: (0181) 202 1199, Fax: (0181) 202 7076

AKG ACOUSTICS, U.S. 914 Airpark Center Drive Nashville, TN 37217, U.S.A Tel: (615) 620-3800, Fax: (615) 620-3875

Studer Japan Ltd. 2-43-7, Uehara, Shibuya-ku, Tokyo 151-0064/JAPAN Tel: (813) 3465-2211, Fax: (813) 3465-2214

Erikson Pro Audio 620 McCaffrey, St-Laurent, Quebec, H4T 1N1, CANADA Tel: (514) 738-3000, Fax: (514) 737-5069 Internet: www.iam-ind.com/eriksonpro

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com