



## AT-2971SX/LC

### Gigabit Ethernet PCI Extended Server Interface Card

#### AT-2971SX/LC

PCI-x 64-bit fiber Gigabit interface card

#### High Performance

A high performance interface card with a 32-bit or 64-bit (33/66/1000/133 Mhz) bus, line speed and jumbo frames support, Allied Telesis' AT-2971SX/LC supports the calculation of TCP, UDP and IP checksums through the hardware platform without time loss by the MAC controller for both transmission and receiving paths—a capability that leads to improvements on overall system performance. To reduce the load on the CPU, Allied Telesis' AT-2971SX/LC uses interrupt moderation to group the huge amounts of interrupts caused by small packets transferred at Gigabit speed, enabling the handling of several data packets per interrupt.

#### High Reliability

The AT-2971SX/LC Gigabit Ethernet interface card comes with a variety of reliability features that maintain the longest-possible connection through link aggregation, redundant switch failover and PCI hot plug. The on-board sensors and driver functions monitor the health of interface cards and their ports, enabling proactive network management.

#### Comprehensive Software Support

The AT-2971SX/LC interface cards feature a set of software programs that assist you with your network set-up and configuration. The offline user diagnostic program provides system administrators and engineers with a tool to analyze Network Interface Cards and check specific data. The network control program for Windows 2K, Windows XP and Windows Vista Server 2003 allows you to easily control and configure all your AT-2971SX/LC interface cards.

#### Key Features

##### Management Software

- VLAN support
- Link aggregation LACP
- Failover

##### Advance Properties

- Jumbo frames
- Checksum offloading
- Sensor support
- PCI-x (PCI Extended) 64-bit
- Windows Vista
- IEEE 802.1x flow control
- IEEE 802.1p-based traffic prioritization
- TCP segmentation (large send)
- PXE 2.1 remote root support
- Low-profile and standard height brackets included
- Microsoft certified drivers
- RoHS compliant
- Dynamic interrupt moderation
- Compliant with Trade Agreement Act
- IPv6

# AT-2971SX/LC | Gigabit Ethernet PCI Extended Server Interface Card

## Specifications

### Management Features

WMI  
ACPI 2.0/w01  
PXE 2.1 Boot ROM

### Bus Type

PCI-x 64-bit

### Ethernet Standards

IEEE 802.1p	Quality of Service
IEEE 802.1Q	VLANs
IEEE 802.2	LLC
IEEE 802.3ac	MAC
IEEE 802.3az	1000SX
IEEE 802.3x	Flow control, auto-negotiation

### Drivers Supported

Vista  
Vista 64-bit  
Windows XP  
Windows XP 64-bit  
Windows 2003  
Windows 2003 64-bit  
Windows 2000  
NDIS2  
NetWare 6.x  
Linux 2.4  
Linux 2.6

### Available

Windows NT 4  
Solaris x86  
Solaris Sparc 32-bit  
Solaris Sparc 64-bit  
Free BSD  
AIX  
NetWare 5.x

### Compliance

RoHS  
cUL  
UL  
FCC/EN55022 Class B  
TUV  
EN55024  
CE  
C-TICK  
VCCI

### Connectors

SC  
LC  
Transmit optical power (min/max) -9.5/-1.5dBm

### Environmental Specifications

Operating temperature 0°C to 50°C  
Storage temperature -25°C to 70°C  
Relative humidity 5% to 90% non-condensing

### Power

Power consumption 3 Watts (max)  
Signaling voltage 3.3/5V

### Status Indicators

LED	2 ports
1000	ON 1000Mbps link up OFF 1000Mbps link down
ACT	ON Receiving/transmitting OFF Not receiving/ not transmitting

### Physical Characteristics

Dimensions 16.8cm x 6.4cm  
(W x H) (6.7") x (2.5")  
Weight 65g

Ships with standard bracket attached to interface card.  
Low-profile bracket is included in packaging.

### Network Type

1000SX

### Network Speed

Auto-negotiation

### Network Controller

Marvell 88E8022

## Ordering Information

### AT-2971SX/LC-yyy

PCI-x 64-bit fiber Gigabit interface card

Where yyy = 001 for single pack  
020 for 20-pack  
901 for single pack, Federal and Government  
920 for 20-pack, Federal and Government

Ships with standard bracket attached to interface card.  
Low-profile bracket is included in packaging.

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

[www.alliedtelesis.com](http://www.alliedtelesis.com)

© 2007 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000232 Rev D

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>