

AT-WCU201 Series Wireless USB2.0 Adapters



AT-WCU201G

IEEE802.11g, 108Mbps High Speed
Wireless USB2.0 Adapter

Higher Speed and Longer Reach

Allied Telesis' AT-WCU201G equips the mobile users with better access to the wireless network with higher speed and longer reach. With the Super GTM Technology, the connection speed can get up to 108Mbps, double what a normal 802.11g card can give you. It's suitable for wireless applications where delivery of digital images, videos, and MP3 files are required. Dynamic data rate scaling also helps to achieve the fastest possible connections.

Securer

The security on AT-WCU201G backed up by the latest industry compliance WPA and WPA2, and 802.1x authentications ensure that you get the best security measures possible in the market. It guarantees network access from permit users only, and give you a peace of mind that your data will be safe.

Flexibility and Convenience

AT-WCU201G is ideal for use either at home, in the office or on the road. Users can use AT-WCU201G on either their laptops or desktop PCs without opening the PC for installation. With the USB cable shipped along with AT-WCU200G, it provides the convenience for placing the device wherever it's easier to reach and with better reception. The ad-hoc mode will allow the users with 802.11b/g enabled computers to share files and transfer data wirelessly between themselves.

Interoperability

Allied Telesis Inc.'s AT-WCU201G is Wi-Fi certified. The certification provides users with the freedom and confidence of choosing Wireless LAN Access Points and client devices, knowing that these products are interoperable with products from other Wi-Fi certified vendors. Customers can use the same AT-WCU200G across multiple environments—in their offices, homes and in public areas where Wi-Fi LANs are deployed. They no longer risk being locked into a single vendor solution.

Key Features

- Compatible with IEEE 802.11g standard with speeds up to 108Mbps data rate for the turbo mode
- Dynamic data rate scaling at 54, 48, 36, 24, 18, 12, 9 and 6Mbps for 802.11g
- Dynamic data rate scaling at 11, 5.5, 2 and 1Mbps for 802.11b
- Maximum reliability, throughput and connectivity with automatic data rate switching
- Support Ad-hoc mode (peer-to-peer) as well as Infrastructure mode
- Supports WPA and AES enhanced security
- Supports wireless data encryption with 64/128/152-bit WEP standard for security
- Friendly user configuration
- High speed USB 2.0 interface with data rates up to 12Mbps full speed and 480Mbps high speed

Radio Characteristics

Data Rate with Automatic Fallback

1 6, 9, 12, 24, 36, 48, 54 Mbps for 802.11g and 1, 2, 5.5, and 11 Mbps for 802.11b

Receiver Sensitivity

Typical Sensitivity at Which Frame (1000-byte PDUs)

Error Rate = 10%

-88dBm at 6Mbps

-86dBm at 9Mbps

-84dBm at 12Mbps

-82dBm at 18Mbps

-78dBm at 24Mbps

-74dBm at 36Mbps

-69dBm at 48Mbps

-66dBm at 54Mbps

Modulation Schemes

BPSK, QPSK, 16QAM, 64QAM, and OFDM

Frequency Range

2400 ~ 2497 MHz ISM band (channels 1 ~ 14)

Operating Channels

USA: 11

Europe: 13

Transmit Output Power

Typical RF Output Power at each Data Rate

+15dBm at 54 and 48Mbps

+16dBm at 36 Mbps

+17dBm at 24, 18, 12, 9, and 6Mbps

Standards Capability

IEEE 802.11b

IEEE 802.11g

Media Access Protocol

CSMA/CA with ACK

Antenna

Integrated antenna

Security

64/128/152-bits WEP encryption/decryption

with up to four WEP keys

Support EAP-TLS, EAP-TTLS, and EAP-PEAP for 802.1X

Support WPA-PSK, WPA-EAP and Cipher Mode AES

and TKIP

LED Status Indicators

Link: Green — Link established

Act: Blinking Amber — Activity

BUS Interface

Universal Serial Bus (USB 2.0)

Driver Support

Windows 2000

Windows XP

Windows 2003

Technical Specifications

Power Characteristics

Operating Voltage: 5V +/- 5% I/O supply voltage

Transmit Output Power

Typical RF Output Power at each Data Rate

+15dBm at 54 and 48Mbps

+16dBm at 36 Mbps

+17dBm at 24, 18, 12, 9, and 6Mbps

Continuous Current Consumption

472 mA at transmit mode

290 mA at receive mode

Environmental Specifications

Operating Temperature: 0 to 55°C

Storage Temperature: -20 to 75°C

Operating Humidity: 10 to 90 % no condensation

Physical Characteristics

Dimensions: 81 x 25 x 12 mm (L x W x H)

Weight: 0.05 lbs (25g)

Standards Compliance

IEEE Std 802.11b

IEEE Std 802.11g

Electrical/Mechanical Approvals

FCC/EN55022 Class B

TUV

CE

Ghost

Wi-Fi

Ordering Information

AT-WCU201G-XXX

IEEE802.11g, 108Mbps High-Speed

Wireless USB2.0 Adapter

Where XXX = 001 for single pack

= 020 for 20 pack

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2006 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000100 Rev. C

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>