American Standard

HAMPTON[™] 5' DROP-IN WHIRLPOOL

HIGH GLOSS ACRYLIC

HAMPTON™ 5' DROP-IN WHIRLPOOL

2425.018W Whirlpool featuring System I

- · Acrylic with fiberglass reinforcement
- Pre-leveled tub bottom
- Form-fitted backrest
- Dual, molded-in arm rests
- 1.5 HP single speed, self-draining pump/motor
- Factory-installed power cord with plug
- Eight multi-directional and flow-adjustable jets including:
 - Two Ideal-flow jets
 - Four body massage jets
 - Two recessed back-rest jets
- Deck-mounted air switch On/Off
- Two silent air volume controls
- Quick Connect Safe-T-Heater connection system
- · Factory installed and tested whirlpool system

Whirlpool Massage featuring System I

- Question 2425.018WC StayClean™ Whirlpool Massage featuring System I:
 - Same as above except with the StayClean[™] whirlpool system featuring Antimicrobial AlphaSan®

Nominal Dimensions: 60" x 32" x 21-1/2" (1524 x 813 x 546mm)

Compliance Certifications -Meets or Exceeds the Following Specifications:

- Underwriters Laboratories Hydromassage Bathtubs UL 1795
- ASME A112.19.7M for Whirlpool Appliances
- ANSI Z124.1 for Plastic Bathtubs
- ASTM E162 for Flammability
- NFPA 258 for Smoke Density

NOTE: Roughing-in dimensions and product specifications shown on reverse side of page.



To Be Specified - Required:

- Color:
- Bath Faucet: (specify finish)
- Bath Drain: 1583.470 (specify finish)

To Be Specified - Optional:

- □ Safe-T-Heater*: 9075.120
- Bath Caddie: 9533.100 (in Chrome only)
- Jet Trim Ring Kit: 9860.200-two per kit (specify finish)


For color/finish availability and other faucet choices, please see the Product Selector and Pricing Guide.

* **NOTE:** the Safe-T-Heater is designed to maintain water temperature during operation. It will not heat cold water to desired bathing temperature.

American Standard

HAMPTON[™] 5' DROP-IN WHIRLPOOL

HIGH GLOSS ACRYLIC



GENERAL SPECIFICATIONS FOR 2425 WHIRLPOOL
INSTALLED SIZE 60 x 32 x 21-1/2 (1524 x 813 x 546mm)
WEIGHT 115 Lbs. (52 Kg.)
WEIGHT w/WATER 574 Lbs. (258 Kg.)
GAL. TO OVERFLOW55 Gal. (208 L.)
WHIRLPOOL MIN. OPERATING VOL45 Gal. (171 L.)
BATHING WELL AT SUMP16-1/4 x 38-1/4 (413 x 972mm)
BATHING WELL AT RIM 26-1/4 x 52-1/2 (667 x 1334mm)
WATER DEPTH TO OVERFLOW 15 (381mm)
FLOOR LOADING 43 Lbs./Sq.Ft. (208 Kgs./Sq.m)
(PROJECTED AREA)
PTS 15.6
CUBE (FT ³)35.3
WHIRLPOOL ELECTRICAL SPECIFICATIONS
PUMP1.6 HP, 9.7 AMPS,120V.

NOTES:

BATH CAN BE INSTALLED EITHER ABOVE OR BELOW FLOOR LINE AS PIER, ISLAND, OR PENINSULA TYPE INSTALLATION. SUPPORT OF BATH BY INTEGRAL FEET. NO ADDITIONAL SUPPORT REQUIRED. SUPPORT AND ENCLOSING MATERIAL BY OTHERS.

REFER TO INSTALLATION INSTRUCTIONS SUPPLIED WITH WHIRLPOOL FOR ADDITIONAL INFORMATION.

OPTIONAL 3 WALL TILING BEAD. KIT No. TILE-BEAD AND APRON No. WBURG5-APRON AVAILABLE AND MUST BE ORDERED SEPARATELY.

FITTINGS NOT INCLUDED AND MUST BE ORDERED SEPARATELY.

PROVIDE SUITABLE REINFORCEMENT FOR ALL SUPPORTS.

IMPORTANT:

Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard Z124.1 These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided leaflet.

© 2003 American Standard Inc.

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com