



# APM CO., LTD

## AAM-50100DU



### Features

- For IEEE802.11a
- Fixed TX/RX Gain
- Outdoor Use
- Transmit P1dB: +33dBm
- High switching speed
- TX/RX LED Indication

### Specification

Output Power	+29 dBm $\pm$ 1.5dB/yields 36Mbps for OFDM
Operating Range	5100-5900 MHz
Operating Mode	Bi-Directional TDD
Transmit Gain	10dB $\pm$ 2dB
Frequency Response	$\pm$ 2dB
Signal Type	IEEE802.11a
TX/RX Switch Time	<500 nSec
TX Input Power	2dBm Min/18dBm Max
Receiver Gain	12dB $\pm$ 2dB
Noise Figure	<3.5dB typical
Connectors	N Type, 50Ohm
Power Consumption	Tx: <1.3A / Rx: <50mA @ 9-12 VDC
LED Indication	Transmit: Green/Receive: Red
AMP Dimensions	112L * 60W * 31H ( mm )
Operating Temperature	-20 ~ +70°C

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>