



APM CO., LTD

AAL-9606 Pan / Tilt IP Camera MPEG4 / MJPEG / 3GPP

Features

- Pan range 0°~ 325°
- Tilt range 0°~ 90°
- 5 camera tours and 16 preset numbers
- Color 1/3" CCD sensor
- Remote surveillance via IE
- Motion detection with video notice
- Support static or dynamic IP
- MPEG4 / MJPEG dual codec



Specifications

| | |
|------------------------|---|
| P/T control | |
| Pan range | 0° ~ 325° |
| Tilt range | 0° ~ 90° |
| Auto pan | Yes |
| Camera tour | 5 |
| Preset numbers | 16 |
| Sensor | |
| Sensor type | Color 1/3" CCD sensor |
| Scan method | Interlace |
| Minimum illumination | 0.2 Lux @ F 2.0 |
| S/N ration | More than 48dB |
| Gamma characteristic | 0.45 |
| Lens | f3.6 @ F2.0 board lens, full glasses |
| Auto white balance | Yes |
| Auto gain control | Yes |
| Backlight compensation | Yes |
| Video | |
| Video compression | MPEG4 / MJPEG dual codec, 3GPP (H.263) |
| Video frame rate | Up to 30 fps for all video resolutions |
| Compression rate | 5 levels: best, better, normal, faster, fastest |
| Frame rate setting | NTSC: 1, 2, 3, 4, 5, 6, 7, 10, 15, 30 fps PAL: 1, 2, 3, 4, 5, 6, 12, 25 fps |
| Video resolution | NTSC: 704x480, 640x480, 320x240, 176x112 PAL: 704x576, 640x480, 352x288, 176x144 |
| Image rotation | Mirror / Up side down |
| Digital zoom | 4X, 2X, 1X, 0.5X |



APM CO., LTD

AAL-9606 Pan / Tilt IP Camera MPEG4 / MJPEG / 3GPP

| | |
|------------------------------|--|
| Motion detection | 3 windows |
| Alarm notification | Send image e-mail / Upload video file to ftp server / Save video file to network share / Send notification to TCP/HTTP server / Control camera to a preset location / Turn on alarm output |
| Audio | |
| Internal microphone | Sensitivity: 62dB |
| Communication | |
| LAN port | RJ-45, 10/100M auto-sensed, auto crossover |
| Communication protocol | 3GPP, RTSP, TCP/IP, HTTP, FTP, SMTP, PPPoE, DHCP, DNS, DDNS, UPnP, UDP, ARP, ICMP, SAMBA, NTP |
| Video streaming | Multicasting / RTSP / Over HTTP |
| IP filter | Yes |
| I/O | |
| Alarm input | 2 |
| Alarm output | 1 |
| Analog video output | 1 |
| Analog audio output | 1 |
| Software | |
| Browser | Internet Explorer 6.0 or above |
| Application software | CentaView application software |
| OS supported | Microsoft Windows 2000, XP |
| Power | |
| Power | DC 12V 1.5A, switching type power supply |
| Power consumption | 10W (800mA x 12V), maximum |
| LED | |
| Link LED | Green color |
| Alert LED | Green color |
| Size | |
| Main body | 159mm (W) x153mm (D) x140mm (H) |
| Operating environment | |
| Operating temperature | 5°C ~ 40°C |
| Storage temperature | -20°C ~ 50°C |
| Humidity | 10% ~ 80% non-condensing |
| EMI | |
| | FCC / CE class B |

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>