



# APM CO., LTD

## AAM-2405gM

### 2.4GHz IEEE802.11g Bi-Directional Amplifier

#### Features




- For IEEE 802.11g
- Easy to monut
- High Gain Antenna
- High switching speed
- Indoor Use
- DC jack built-in



#### Specification

Output Power	27 dBm $\pm$ 1dBm
Operating Range	2400-2500 MHz
Operating Mode	Bi- Directional TDD
Transmit Gain	up to 12dBm
Frequency Response	$\pm$ 1dBm
TX/ RX Switch Time	< 1 uSec
TX Input Power	2dBm Min/18dBm Max
Receiver Gain	Up to 10dBm
Noise Figure	3.0dBm typical
Connectors	In:SMA(F); Out:SMA(F)RP, 50 Ohm
Power Consumption	Tx:<0.6A/ Rx:<80mA @ 5.0 VDC
LED Indication	DC Power In
AC Adapter	AC 100V~240V In/DC 5.0V $\pm$ 5% 2A Out
AMP Dimensions	92L * 60W * 29H (mm)
Operating Temperature	0°C to +60°C
*5dBi Rubber Antenna*	

#### Standard Accessories

		
Switch Adaptor	Antenna	Cable

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>