

Proxima Pro AV 9300 Projector

Technical and Functional Specifications

- Computer Compatibility**
 - Sun, SGI, IBM, HP, DEC, and X-terminals graphics modes up to 135 MHz
 - IBM PC, PS/2, Pentium, and compatibles
 - Apple Macintosh, Power Macintosh and PowerBook
- Video Compatibility**
 - NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
- Input Sources**
 - 2 computer input channels (optional connector modules available):
Channel 1: (5) BNC (R, G, B, H, V)
Channel 2: (1) HD15
 - Each channel includes:
RCA type stereo audio (R, L-mono), mouse control port, USB port
 - 2 video input channels:
3 BNC (for component, composite)
1 mini DIN 4-pin (for S-Video)
1 RCA type audio (R, L-mono)
- Output Sources:**
 - 1 monitor output
HD15 + RCA type audio (R, L-mono)
(optional connector modules available)
 - 1 video output:
3 BNC (for component, composite)
1 mini DIN 4-pin (for S-Video)
1 RCA type audio (R, L-mono)
- Control Input Sources**
 - RS232C (DB9)
- H-Sync Range**
 - 15-81 kHz
- V-Sync Range**
 - 50-100 Hz
- Brightness**
 - 1600 ANSI lumens (typical)
- Brightness Uniformity**
 - 85% typical
- Contrast Ratio**
 - 100:1 ANSI; 250:1 full-on, full-off
- Display Technology/No. of Colors**
 - 1.8" polysilicon LCD / 16.7 million colors
- Resolution**
 - XGA (1024 x 768)
- Resolutions Supported**
 - VGA (640x480, Fit-to-View®)
 - SVGA (800x600, Fit-to-View)
 - XGA (1024x768)
 - SXGA, (1280x1024, Fit-to-View), wide format (16:9 aspect) capable
- Image Diagonal (Std Lens)**
 - 2.5 ft. to 50 ft. (0.8 m to 15.2 m)
- Projection Lens**
 - Power zoom and focus. 1.6:1 ratio, F2.6 ~3.5, focal length 67~107mm (long and wide lens options)
- Projection Distance (Std Lens)**
 - 3.6 ft. to 70.8 ft. (1.1 m to 21.6 m)
- Lens Shift**
 - Power lens shift +12 to -12° (keystone corrected)
- Lamp (Life)**
 - 400 watt metal halide (1,000 hours)
- Audio**
 - Two 3-watt stereo speakers
- Remote Control**
 - Wireless IR with mouse control
 - Wired projector (w/o mouse control) via mini-jack
- Approvals**
 - FCC Class A, UL, cUL, CE
- Power Consumption**
 - 630 watts
- Power Requirements**
 - 90-264 volts (110~120/200~240V + 10%) at 50/60 Hz
- Operating Temperature (Sea Level)**
 - 41-95° F (5-35° C)
- Weight**
 - 37.4 lb. (17.0 kg)

Copyright © 1997-2004 InFocus Corporation.
All Rights Reserved.

Dimensions	<ul style="list-style-type: none">● 15.4 in. (W) x 22.9 in. (L) x 9.2 in. (H) 23.3 cm (W) x 58.2 cm (L) x 39.0 cm (H)
Projection Method	<ul style="list-style-type: none">● front/rear, desktop/ceiling
On-screen Menu Languages	<ul style="list-style-type: none">● English, German, French, Italian, Spanish
Audible Noise	<ul style="list-style-type: none">● < 42db
Dot Clock	<ul style="list-style-type: none">● Up to 135 MHz
Horizontal Resolution	<ul style="list-style-type: none">● 800 video lines
Warranty	<ul style="list-style-type: none">● Two years on parts and labor (excluding lamp)

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>