

Proxima Pro AV 9410 Projector

Technical and Functional Specifications

Native Resolution	<ul style="list-style-type: none">● SXGA (1280 x 1024)
Resolution Supported	<ul style="list-style-type: none">● SXGA (1280 x 1024, 1152 x 864); Fit-to-View display of XGA (1024 x 768), SVGA (800 x 600), VGA (640 x 480, 720 x 400, 640 x 400), UXGA (1600 x 1200)● Apple Macintosh 21 in. (1152 x 870), Mac 12 in. (512 x 384), 13 in. (640 x 480), 16 in. (832 x 624), 19 in. (1024 x 768)● PC98 (1120 x 750, 1280 x 1024), PC98 (1024 x 768, 800 x 600, 640 x 480, 640 x 400), UXGA (1600 x 1200), PC98NX (1600 x 1200), Fit-to-View mode of 16:9 aspect capable
Brightness	<ul style="list-style-type: none">● 3700 ANSI lumens
Brightness Uniformity	<ul style="list-style-type: none">● 85% typical
Contrast Ratio	<ul style="list-style-type: none">● 200:1 ANSI; 600:1 full on, full off
Computer Compatibility	<ul style="list-style-type: none">● Sun, SGI, IBM, HP, DEC, and X-terminal graphics modes up to 200 MHz, IBM PC, PS/2, Pentium, and compatibles● Apple Macintosh, Power Macintosh and PowerBook, G3
Video Compatibility	<ul style="list-style-type: none">● NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, HDTV (1080i, 1035i, 720p)
Display Technology	<ul style="list-style-type: none">● 1.8 in. polysilicon LCD x 3 with Microlens
Number of Colors	<ul style="list-style-type: none">● 16.7 million
Input Sources	<ul style="list-style-type: none">● 2 computer input channels Channel 1: RGB (HDI5) / DFP (Digital Panel Link Interface) Channel 2: BNC (R, G, B, H, V)● Each channel includes: RCA type stereo audio (R, L-mono), mouse control port, USB port● 2 video input channels Each channel includes: 3 BNC for component [Video/Y, C/Cb (B-Y), Cr (R-Y)] and composite], 1 mini DIN 4-pin (for S-Video), 1 RCA type stereo audio (R, L-mono)
Output	<ul style="list-style-type: none">● 1 monitor output HD15 (RGBHV) + RCA type stereo audio (R, L-mono)● 1 video output 3 BNC (for component and composite) 1 mini DIN 4-pin (for S-Video) 1 RCA type stereo audio (R, L-mono)
H-Sync Range	<ul style="list-style-type: none">● 15-100 kHz
V-Sync Range	<ul style="list-style-type: none">● 50-120 Hz
Dot Clock	<ul style="list-style-type: none">● 220 MHz
Keystone Correction	<ul style="list-style-type: none">● Power +12 to -12° (keystone corrected)
Projection Lens	<ul style="list-style-type: none">● Std lens—power zoom and focus. F=2.0-2.3, focal length f=75.7-97.5 mm
Projection Distance/Image Width	<ul style="list-style-type: none">● 2.0–2.6:1 Minimum Projection Distance • 5.2 ft. (1.6 m)
Minimum Projection Distance	<ul style="list-style-type: none">● 5.2 ft. (1.6 m)
Zoom	<ul style="list-style-type: none">● 1.3:1
Aspect Ratio	<ul style="list-style-type: none">● 5:4, supports 4:3 and 16:9
Image Size	<ul style="list-style-type: none">● 3.3 ft. to 50 ft. (1.0 m to 15.2 m)
Projection Method	<ul style="list-style-type: none">● front/rear, desktop/ceiling
Audio	<ul style="list-style-type: none">● Two 3-watt speakers
Audible Noise	<ul style="list-style-type: none">● <45 dB
Remote Control	<ul style="list-style-type: none">● 1 wireless remote with mouse
Control Communication	<ul style="list-style-type: none">● RS-232C control and laser pointer; 1 remote with hardwire capability and no mouse control
Lamp (Life)	<ul style="list-style-type: none">● 440 watt DC metal halide (estimated 1,000 hours)
Dimensions	<ul style="list-style-type: none">● 15.4 in. (W) x 22.9 in. (L) x 9.2 in. (H) 39 cm (W) x 58.2 cm (L) x 23.3 cm (H)
Weight	<ul style="list-style-type: none">● 39.2 lb. (17.8 kg)

Copyright © 1997-2004 InFocus Corporation.
All Rights Reserved.

- Power Consumption** ● 650 watts
- Power Requirements** ● 100–120, 200–240 VDC
- Operating Temperature** ● 41-95° F (5-35° C)
- On-Screen Menu Languages** ● English, German, French, Italian, Spanish, Japanese
- Approvals** ● FCC Class A, UL, cUL, CE
- Warranty** ● Two years on parts and labor (excluding lamp), 90-days on lamp

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>