

## AMERICAN TECHNOLOGIES NETWORK, CORP.

## NVM14-3A

## MULTI PURPOSE NICHT

- Lightweight
- · Compact, rugged design
- Waterproof
- Weapon mountable
- · Head or helmet mountable for hands-free usage
- · Left or right eye use
- Easy of operation
- Auto Brightness Control
- Bright Light Cut-off
- Ergonomic, Simple, Easy to operate controls
- · Utilizes either CR123A lithium battery or AA Alkaline. (Adapter included)
- Compatible with most IR lasers
- Adaptable for use with cameras
- Total Darkness Technology with built-in Infrared Illuminator and flood lens
- Optional Patented Life Tracker System available for measuring hours of operation
- Limited Two-year Warranty

## HIGH QUALITY 3A GEN IMAGE INTENSIFIER TUBE

DESCRIPTION	Select Alpha
GENERATION	3
PHOTOCATHODE TYPE	Thin Film GaAs
RESOLUTION, LP/MM *	64 - 72
SIGNAL-TO-NOISE RATIO*	26 typical
EXPORT	N/A for export
FIGURE OF MERIT	1800 typical

<sup>\*</sup> Specifications are provided for informational purposes only. Actual values may vary







The NVM14-3A is a high performance, versatile night vision monocular. It is designed to be multifunctional: hand-held as a monocular, head-mounted/ helmet-mounted as a single-eye goggle, or weapon- mounted as a night scope.

The NVM14-3A utilizes a single 3rd gen image intensifier tube combined with specially designed optics to provide crisp, clear images under the darkest of conditions.

The NVM14-3A has an optional flip-up headset or helmet mount with an automatic off-feature. The automatic off-feature turns the unit off when it is flipped-up out of the viewing position.

The NVM14-3A has a host of additional features such as a built-in IR illuminator with rotary lens to select between IR Spot or Flood Beam as well as a built-in automatic highlight cutoff to protect the image intensifier. The NVM-14 also includes a bright light and low battery warning indicators built into the viewing area of the eyepiece.

The NVM14-3A is compatible with most weapons, IR laser aiming/illuminating devices and standard collimated reflex sights.

Optional: System/IIT service life recorder-feature that lets you measure the hours of operation (within one minute) that have been used on the system.

Magnification	. 1X
Lens system Element	. F1.2, 25 mm
Exit Pupil	
Eye Relief	. 25 mm
Eye use	
FOV	
Range of focus	
Diopter Adjustment	
ABC- Automatic Brightness	
Control Cut-off to Protect	
Image Intensifier Tube	Yes
Bright Light Indicator	
Controls	. Digital
	Built-in Rotary Select - Flood & Spot
IR Illumination Range	20 meters
IR Indicator	LED ON/ Battery Low
Weight w/ Battery	0.34 kg
Dimensions	
Environmental rating	. Waterproof 20 m, 1 hr.
Operation Temperature	-40 to +50 C
Storage Temperature	-50 to +70 C
Flip Up Headset	
w/ Automatic System Off	Yes
	. 30 hrs. (AA), 60 hrs. (3 V, Lithium)
Battery Life w/ IR ON	. 30 hrs. (3 V, Lithium) Continous
Power supply	(1) 3 V Lithium, or (1) AA Alkaline
Mil-Spec 810 Standards	Complies
Waterproof	
Warranty	

Export Warning: These products are subject to one or more of the export control laws and regulations of the U.S. Government. Pending the model these products are under the control jurisdiction of either the US Department of State or the US Bureau of Industry and Security US Department of Commerce. Export without proper licensing or consent is strictly prohibited.

American Technologies Network Corp. 1341 San Mateo Avenue, South San Francisco, CA 94080 800-910-2862 650-989-5100 FAX 650-875-0129





E-mail: info@atncorp.com, sales@atncorp.com

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com