



SCM300ASL PRO : 3 - way active

- Features
- 34mm soft dome tweeter.
 - Twin full spec "SL" 15"/375mm bass drivers.
 - ATC 75mm "Super Dome" mid driver.
 - Rack-mount ATC 4 way grounded plane 850W amplifier.
 - Clip indication.
 - 6 year warranty.

Specifications

Drivers : HF 34mm, Mid 75mm, LF 2 x 375mm **Amplitude Linearity (±2dB) :** 50Hz-12kHz **Cut-off Frequencies (-6dB) :** 25Hz, 20kHz (free standing) 20Hz, 20kHz (soffit mounted)
Horizontal Dispersion : ±80°, Coherent **Vertical Dispersion :** ±10°, Coherent **Max. Continuous SPL (1 metre) :** 121 dB **Crossover Frequencies :** 380Hz, 3.5kHz
Input Connectors : Male XLR **Input Sensitivity :** 2V **Input Impedance :** Balanced > 10kΩ **Amplifier Output :** Bass 275+275W, Mid 200W, High 100W
Filters : Even Order Critically Damped **Overload Protection :** Active FET momentary gain reduction plus thermal tweeter protection
Front Panel Indicators : Power On indicator, Gain Reduction warning **Dimensions (HxWxD) :** 884 x 925 x 460mm (34.8" x 36.4" x 18.7") **Weight :** 140kg / 308lbs

Passive versions available. ATC reserves the right to vary products and specifications without prior notice.



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>