
IPM515 | Slim-Grip[™] with Mini Windshield Suction and Dashboard Mount for Apple iPhone[®] and iPod touch[®]




Windshield Mounting

Step 1. Find a safe location on the interior of the vehicle's windshield to mount the pedestal. Firmly push the suction base (A) against the windshield and flip the base lever down (B) to the locked position. See diagram below.



Install the Support Legs to the Holder

Step 1. Insert the holder support legs (A) by sliding them into the support leg grooves (B) on the top and bottom of the holder.



Package Contents:

(1) SM050-HPB-2 - Slim-Grip[™] holder for Apple iPhone and iPod touch[®]
(1) GN015-HPB-2 - Mini Windshield Suction and Dashboard Mount
(1) AP013 - Circular Adhesive Dashboard Disc


Compatible with the following devices:

- Apple iPhone[®] 4
- Apple iPhone[®] 3GS
- Apple iPhone[®] 3G
- Apple iPhone[®] Original
- Apple iPod touch[®] All models

*Apple[®], iPhone[®], and iPod touch[®] are trademarks of Apple Computer, Inc. Arkon Resources, Inc. is not affiliated with Apple Computer, Inc.


Connecting the Slim-Grip[™] Holder to Dual T-Tab Pedestal

Step 1. Connect the dual T-slots (A) on holder to the dual T-tabs (B) on the pedestal head.



Insert Phone into Holder

 Secure holder with your hand for support, as spring-loaded mechanism requires significant force to operate. Hold your phone and insert into universal holder by pushing down on the bottom spring-loaded support legs with moderate amount of pressure (C). Slide the top of the device under the top support legs (D) until it fits snuggly in the holder.



Continued on other side...



Safety Precautions

Do not install Arkon products over an air bag cover or within the air bag deployment zone. Arkon Resources, Inc. assumes no responsibility of liability for injury or death as a result of car crashes and / or air bag deployment.

Arkon is not responsible for any damages caused to your car, your device, or yourself due to the installation or use of this pedestal mount.




Consumer Hotline: USA (800) 841-0884 INT'L (626) 254-9005 Monday - Friday 9 am - 5 pm, PST www.arkon.com

Arcadia, CA 91006 USA Designed in USA | Made in China © Copyright 2010 Arkon Resources, Inc.

IPM515 Slim-Grip[™] with Mini Windshield Suction and Dashboard Mount for Apple iPhone[®] and iPod touch[®]


Adjusting Holder to Fit Phone




Step 1. If necessary, adjust the support legs (E) on top and bottom by sliding them laterally to avoid any buttons or ports that may be on your phone.

Dashboard or Console Mounting Instructions

- Step 1. Choose a suitable location for disc (and pedestal) installation. Do not place mount in or near an air bag deployment zone or where it will obstruct view of the road or hinder vehicle operation.
- Step 2. Clean the dashboard or console surface area thoroughly with the included alcohol pad. Allow the area dry before applying the mounting disc.



- Step 3. Remove the paper backing of the disc and place on the cleaned surface. Press the top of the disc down firmly to allow the adhesive to stick to the surface. Allow 24 hours for the adhesive to cure to the surface before applying any pressure.
- Step 4. Place the suction cup of the pedestal firmly down on the center of the mounting disc and lower the securing lever.



Continued in next column...



Safety Precautions

Do not install Arkon products over an air bag cover or within the air bag deployment zone. Arkon Resources, Inc. assumes no responsibility of liability for injury or death as a result of car crashes and/or air bag deployment.

Arkon is not responsible for any damages caused to your car, your device, or yourself due to the installation or use of this pedestal mount.

ARKON[®] **RESOURCES INC.** The Mobile Mounting Specialists™

Consumer Hotline: USA (800) 841-0884 INT'L (626) 254-9005 Monday - Friday 9 am - 5 pm, PST www.arkon.com Arcadia, CA 91006 USA Designed in USA | Made in China © Copyright 2010 Arkon Resources, Inc.

Step 5. Push the pedestal suction cup (A) down onto the disk (C). Flip the lever (B) down to secure the suction cup. Adjust the angle of the pedestal head as needed.

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com