
CHORUS SPACE-C CC300

Analog 3-Dimensional Sound Effects Pedal

Thank you for showing your confidence in us by purchasing the BEHRINGER CHORUS SPACE-C CC300. This ultimate effects pedal comes with 4 dedicated space presets that let you add a breathtaking third dimension to your sound or instrument. Experience the secret weapon of professional recording studios.

The chorus effect adds a shifting detuned signal to the original, similar to playing in unison in a group of instruments, and it is often used for dispersing sounds.

1. Controls



- The **MODE SELECTOR** switches let you choose between 4 dedicated space presets. Use these presets in any combination or even activate them at the same time. This results in 16 combinations giving you a wide range of spacious effects. The effect gets deeper from the left to the right.
- The ON/BATT LED illuminates when the effect is activated. It also serves as a battery level indicator.
- 3 Use the footswitch to activate/deactivate the effect.
- 4 Use this ¼" TS **IN** connector to plug in the instrument cable.
- The two ¼" TS **OUT A** and **OUT B** connectors send the signal to your amp. Use both connectors if you want to achieve full stereo chorus effect. For mono use plug in OUT A only.

Use the **DC IN** connection to plug in a 9 V power supply (not included).

The **BATTERY COMPARTMENT** is located underneath the pedal cover. To install or replace the 9 V battery (not included), press the hinges with a ballpoint pen and remove the pedal cover. Be careful not to scratch the unit.

The CC300 has no on/off switch. As soon as you insert the plug into the in connector, the CC300 is on. When not in use, remove the plug from the in connector. This extends the life of the battery.

The **SERIAL NUMBER** is located at the underside.

2. Safety Instructions

Do not use near water, or install near heat sources. Use only authorized attachments/accessories. Do not service product yourself. Contact our qualified servicing personnel for servicing or repairs, especially when power supply cord or plug is damaged.

3. Warranty

Please register your new BEHRINGER equipment right after your purchase by visiting http://behringer.com and read the terms and conditions of our warranty carefully.

4. Specifications

In	
Connector	1⁄4" TS
Impedance	500 kΩ
Out A	
Connector	1⁄4" TS
Impedance	1 kΩ
Out B	
Connector	1⁄4" TS
Impedance	1 kΩ
Power Supply	
	9 V≕, 100 mA regulated
BEHRINGER PSU-S	В
USA/Canada	120 V∼, 60 Hz
Europe/U.K./	230 V~, 50 Hz
Australia	
China	220 V~, 50 Hz
Korea	220 V~, 60 Hz
Japan	100 V~, 50/60 Hz

Power connector	2 mm DC jack,
	negative center
Battery	9 V type 6LR61
Power consumption	30 mA
Physical/Weight	

approx. 2 1/8 x 2 3/4 x 4 4/5"
approx. 54 x 70 x 123 mm
approx. 0.73 lbs / 0.33 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may therefore differ from those listed or shown.



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com