

COLORdash™ Block



CONTROL FEATURES

- 3, 4, 5, 9, 11, or 12-channel RGB LED wash light
- Operating modes
 - 3-channel: RGB control
 - 4-channel: RGB, dimmer
 - 4-channel: RGBW control
 - 5-channel: RGBW, dimmer
 - 9-channel: RGB, ID addressing, dimmer, macro, strobe, auto/custom
 - 11-channel: RGBW, ID addressing, dimmer, module selection, macro, strobe, auto/ custom
 - 12-channel: RGB for individual block control
- RGBW color mixing with or without DMX controller
- Built-in automated programs via master/slave, COLOR-CON, or DMX
- Recall custom programs via master/slave or DMX
- Adjustable fan speeds

ADDITIONAL FEATURES

- Double-bracket yoke doubles as floor stand
- LCD display with password protection
- Transfer custom programs between fixtures
- Additional (IEC) power output: max 20 units @ 120 V (see manual for details)
- Includes 6.6 ft (2 m) power extension cable

SPECIFICATIONS

- 18° optics
 - Beam angle: 17°
 - Field angle: 32°
 - Lux: 1,690 @ 2 m
- Light source: 28 x 1 W LEDs, 50,000 hrs (8 x 350 mA red, 8 x 350 mA green, 8 x 350 mA blue, 4 x 350 mA white)
- Power and current: 120 V, 60 Hz; 41.2 W, 0.35 A (operating), 0.3 A (inrush)
230 V, 50 Hz; 40.2 W, 0.18 A (operating), 0.4 A (inrush)
- AC power: Auto-ranging 100 V ~ 240 V 50/60 Hz
- Weight: 4.4 lbs / 1.9 kg
- Size: 9.8 x 7.6 x 5.9 in / 249 x 192 x 149 mm



www.chauvetlighting.com
info@chauvetlighting.com
t: 954.929.1115
3000 North 29th Court
Hollywood, FL 33020

CHAUVET[®]
Value • Innovation • Performance

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>