



CHRISTIE Mirage S+4K

Fast, Detailed 3D Images From a Small, Lightweight Package

Uses

- Automotive
- Oil & gas exploration
- Scientific research
- Aerospace
- Engineering
- Manufacturing
- Museums and education
- Architecture
- Entertainment
- Medical/pharmaceutical

The Christie Mirage S+4K produces phenomenal image quality and clarity from a small, light package with increased processing power and internal edge-blending and optional warping – perfect for front and rear stereo projection.

Using next generation 3-chip DLP™ technology, high-quality optics and 10-bit image processing, the Christie Mirage S+4K delivers 5000 lumens and SXGA+ resolution. This quiet yet powerful package offers unique features such as high-bandwidth signal processing, higher stereo sync, internal scaling of stereo signals, Picture in Picture and seamless switching between sources.

On-board ChristieNET™ connectivity makes monitoring and control as simple as plugging in an Ethernet cable. And the Mirage S+4K operates on 110V – 240V for powerful 3D images anywhere. With a full suite of SXGA+ lenses and compatibility with legacy lenses and modules, the Christie Mirage S+4K easily fits into any 3D application.

Christie Mirage – recreate reality!

Christie Mirage S+4K

Specifications



All new 10-bit processing in the Christie Mirage S+4K offers high bandwidth signal processing, optional warping capability, superior edge-blending and much more.

IMAGE

- 5000 ANSI lumens (+/- 10%)
- 90% brightness uniformity
- 450–600:1 ANSI, 1500–2000:1 full field (adjustable internal aperture)

DISPLAY TECHNOLOGY AND RESOLUTION

- 3D 3-chip 0.95" Darkchip2™ DMD
- True SXGA+ 1400 x 1050 resolution

INPUT SIGNAL COMPATIBILITY

- VGA to QXGA (2048 x 1536)
- All current HDTV/DTV formats
- Multi-standard video decoder
- Horizontal and vertical scaling, all inputs

LENS MOUNT

- Motorized horizontal and vertical offset
- Tool-free lens insertion system
- Scheimpflug (tilt) adjustment
- Built-in light shutter
- Internal electromechanical iris

LAMP

- 1.0kW CERMAX® Xenon pre-aligned lamp module
- 1000 hours (typical) lifetime

LIGHT OUTPUT CONTROL (LITELOC™)

- "Auto Brightness" (Intensity), "Lamp Conserve" (Power), "Max Brightness" modes



Specifically designed SXGA+ lenses and compatibility with competitive lenses give you the fullest resource flexibility.



A user-replaceable, pre-aligned Xenon lamp features LiteLOC™ for constant brightness.

SCAN RATES

- Horizontal – 15 kHz to 120 kHz
- Vertical – 23.97 Hz to 150 Hz

PIXEL CLOCK

- 220 MHz
- 115 Hz refresh rate at SXGA+ resolution
- 120 Hz refresh rate at SXGA resolution

INPUTS, CONTROL & NETWORKING

- RGBHV/YPbPr: 5 BNC
- DVI-I: digital/analog RGB/YPbPr (HDCP)
- One composite video, one S-Video
- Two option slots for analog/digital modules
- 2 RS-232 ports and 1 RS-422 port
- On-board ChristieNET™ connectivity (RJ45)
- Built-in backlit keypad and IR remote control

ADVANCED FEATURE SET

- Stereo Sync Harness
- Built-in edge-blending
- Comprehensive Color Adjustment (CCA™)
- Dark Interval Adjustment (DIA™)
- Minimum Delay Feature
- Picture in Picture
- Seamless switching
- Auto set-up, power-up feature
- Menus in five languages
- On-screen help
- 50 channel memories

POWER REQUIREMENTS

- 100 VAC to 240 VAC +/- 10% @ 50/60 Hz
- Power consumption: 1600W maximum
- Thermal dissipation: 5460 BTU/hr
- Operating current: 12A @ 100V / 8A @ 200V

DIMENSIONS

- Weight: 72 lb (32.7 kg) (excluding lens)
- Shipping weight: 115 lb (52 kg)
- Size: 26" W x 22.3" L x 12.3" H (660mm W x 566mm L x 313mm H) (excluding lens)

STANDARD ACCESSORIES

- IR keypad (w/batteries)
- Line cord
- Stereo Sync Harness
- User manual

OPTIONAL ACCESSORIES

- Fixed lenses: 0.73:1, 1.2:1
- Zoom lenses: 1.45-1.8:1, 1.8-2.5:1, 2.5-4.5:1, 4.5-7.3:1
- ChristieTWIST™ Image Warping and Edge-Blending module
- Dual SD/HD-SDI, DVI and legacy interface modules
- Wired remote control and RS-422 Two Way Controller
- Remote IR sensor
- Ethernet, RS-232, RS-422 cables

- Service manual
 - KoRET™ 10-bit librarian
 - Lens adapter (for competitive lenses)
- ### OPERATING ENVIRONMENT
- Temp: 40 to 95° F (5 to 35° C)
 - Humidity: 20 – 80% non-condensing

REGULATORY APPROVALS

- UL/CSA/IEC 60950 (3rd edition)
- FCC Class A, CE, CCC (pending)
- This product conforms to all relevant European directives, standards, safety, health and environmental concerns

WARRANTY

- 2 years parts and labor (including light engine)



Corporate Offices

USA
10550 Camden Drive
Cypress, CA 90630
PH: 714-236-8610
FX: 714-503-3385
Toll free: 866-880-4462 (NA only)
sales-us@christiedigital.com

CANADA

809 Wellington Street North
Kitchener, Ontario N2G 4Y7
PH: 519-744-8005
FX: 519-749-3136
Toll free: 800-265-2171 (NA only)
sales-canada@christiedigital.com

Worldwide Offices

UNITED KINGDOM
PH: +44 118 977 8000
FX: +44 118 977 8100
sales-europe@christiedigital.com

GERMANY

PH: +49 2161 664540
FX: +49 2161 664546
sales-europe@christiedigital.com

FRANCE

PH: +33 (0) 1 47 48 28 07
FX: +33 (0) 1 47 48 26 06
Mobile: +33 (0) 6 76 47 43 62
sales-france@christiedigital.com

SINGAPORE

PH: +65 6877 8737
FX: +65 6877 8747
sales-singapore@christiedigital.com

SHANGHAI

PH: +86 21 6278 7708
FX: +86 21 6270 5816
sales-china@christiedigital.com

BEIJING

PH: +86 10 6561 0240
FX: +86 10 6561 0546
sales-china@christiedigital.com

JAPAN

PH: +81 3 3559 7481
FX: +81 3 3599 7482
sales-japan@christiedigital.com

For the most current specification information, please visit www.christiedigital.com

Copyright 2005 Christie Digital Systems, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or trademarks of their respective holders. Canadian manufacturing facility is ISO 9001:2000 certified. The DLP™ logo and DLP™ Medallion are trademarks of Texas Instruments. Printed in Canada. 1280
Apr 05-NA

Performance specifications are typical. Due to constant research, specifications are subject to change without notice.



Download from www.Somanuals.com. All Manuals Search And Download.

WWW.CHRISTIEDIGITAL.COM

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>