

CHRISTIE Mirage S+14K

Brightest, Highest Resolution 3D Projector Available

Uses

Entertainment
Theme parks
Large venues
Automotive
Oil & gas exploration
Scientific research
Aerospace
Manufacturing
Museums and education
Architecture

With the Christie Mirage S+14K, Christie offers the widest brightness range of any active stereo projectors on the market. A stunning 14000 lumens, SXGA+ resolution and 1500-1800:1 contrast ratio deliver brilliantly crisp images from a rugged, powerful package. With increased processing power and built-in edge-blending and optional warping – your 3D displays create impact.

Next generation 3-chip DLP™ technology high-quality optics and 10-bit image processing designed in a compact package, the Mirage S+14K offers high-bandwidth signal processing, higher stereo sync, internal scaling of stereo signals, Picture in Picture and seamless switching between sources – enabling large format and tradeshow active stereo presentations.

On-board ChristieNET™ connectivity and a full suite of SXGA+ lenses give you ultimate control over your image.

Christie Mirage – recreate reality!



Christie Mirage S+14K

Specifications



Designed with built-in handles, an optimized airflow design and multiple rigging points, the Christie Mirage S+14K is easy to install, easy to use and easy to maintain.

IMAGE

- 14,000 ANSI lumens (+/- 10%)
- 90% brightness uniformity
- Contrast: 450-600:1 ANSI, 1500-1800:1 full field (adjustable internal aperture)

DISPLAY TECHNOLOGY AND RESOLUTION

- 3D 3-chip 0.95" Darkchip2™ DMD
- True SXGA+ 1400 x 1050 resolution

INPUT SIGNAL COMPATIBILITY

- VGA to QXGA (2048 x 1536)
- Accepts all current HDTV/DTV formats
- Multi-standard video decoder
- Horizontal and vertical scaling, all inputs

SCAN RATES

- Horizontal – 15 kHz to 120 kHz
- Vertical – 23.97 Hz to 150 Hz

LENS MOUNT

- Motorized horizontal and vertical offset
- Tool-free lens insertion system
- Scheimpflug (tilt) adjustment
- Built-in light shutter
- Internal electromechanical iris

LAMP

- 2.4kW Xenon Bubble lamp
- 1250 hours (typical) lifetime

LIGHT OUTPUT CONTROL (LITELOCT™)

- "Auto Brightness" (Intensity), "Lamp Conserve" (Power), "Max Brightness" modes

POWER REQUIREMENTS

- 200 VAC to 240 VAC +/- 10% @ 50/60 Hz
- Power consumption: 4000W maximum
- Thermal dissipation: 13,648 BTU/hr
- Operating current: 20A @ 200V



Built-in LCD text display shows status and error messages. The graphic user interface enables full and easy control of the projector.



Built-in stacking points make rigging and aligning the Christie Mirage S+14K simple.

PIXEL CLOCK

- 220 MHz
- 115 Hz refresh rate at SXGA+ resolution
- 120 Hz refresh rate at SXGA resolution

INPUTS, CONTROL & NETWORKING

- RGBHV/YPbPr: 5 BNC
- DVI-I: digital/analog RGB/YPbPr (HDCP)
- One Composite video, one S-Video
- Two option slots – analog/digital modules
- 2 RS-232 ports and 1 RS-422 port
- On-board ChristieNET™ connectivity (RJ45)
- Built-in backlit keypad and IR remote control

ADVANCED FEATURE SET

- Stereo Sync Harness
- Built-in edge-blending
- Comprehensive Color Adjustment (CCA™)
- Dark Interval Adjustment (DIA™)
- Minimum Delay Feature
- Picture in Picture
- Seamless switching
- Auto set-up, power-up feature
- Menus in five languages
- On-screen help
- 50 channel memories

DIMENSIONS

- (excludes lens, feet, stacking points)
- Weight: 140 lb (63.6 kg)
- Shipping weight: 160 lb (72.7 kg)
- Size: 24.5" W x 32.1" L x 15.1" H (631.4mm W x 814.8mm L x 384mm H)

STANDARD ACCESSORIES

- IR keypad (w/batteries)
- Line cord
- Stereo Sync Harness
- User manual

OPTIONAL ACCESSORIES

- Fixed Lenses: 0.73:1, 1.2:1
- Zoom Lenses: 1.45-1.8:1, 1.8-2.5:1, 2.5-4.5:1, 4.5-7.3:1
- Manual "Legacy" lens mount
- ChristieTWIST™ Image Warping and Edge-Blending module
- Dual SD/HD-SDI, DVI and legacy interface modules
- Wired remote control and RS-422 Two Way Controller
- Remote IR sensor
- Ethernet, RS-232 and RS-422 cables
- Service manual
- KoRET™ 10-bit librarian
- Lens adapter (for competitive lenses)

OPERATING ENVIRONMENTS

- Temp: 40 to 95° F (5 to 35° C)
- Humidity: 20 – 80% non-condensing

REGULATORY APPROVALS

- UL/CSA/IEC 60950 (3rd edition)
- FCC Class A, CE, CCC (pending)
- This product conforms to all relevant European directives, standards, safety, health and environmental concerns

WARRANTY

- 2 years parts and labor (including light engine)



Corporate Offices

USA
10550 Camden Drive
Cypress, CA 90630
PH: 714-236-8610
FX: 714-503-3385
Toll free: 866-880-4462 (NA only)
sales-us@christiedigital.com

CANADA
809 Wellington Street North
Kitchener, Ontario N2G 4Y7
PH: 519-744-8005
FX: 519-749-3136
Toll free: 800-265-2171 (NA only)
sales-canada@christiedigital.com

Worldwide Offices

UNITED KINGDOM
PH: +44 118 977 8000
FX: +44 118 977 8100
sales-europe@christiedigital.com

GERMANY
PH: +49 2161 664540
FX: +49 2161 664546
sales-europe@christiedigital.com

FRANCE
PH: +33 (0) 1 47 48 28 07
FX: +33 (0) 1 47 48 26 06
Mobile: +33 (0) 6 76 47 43 62
sales-france@christiedigital.com

SINGAPORE
PH: +65 6877 8737
FX: +65 6877 8747
sales-singapore@christiedigital.com

SHANGHAI
PH: +86 21 6278 7708
FX: +86 21 6270 5816
sales-china@christiedigital.com

BEIJING
PH: +86 10 6561 0240
FX: +86 10 6561 0546
sales-china@christiedigital.com

JAPAN
PH: +81 3 3559 7481
FX: +81 3 3559 7482
sales-japan@christiedigital.com

For the most current specification information, please visit www.christiedigital.com

Copyright 2005 Christie Digital Systems, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Canadian manufacturing facility is ISO 9001:2000 certified. The DLP™ logo and DLP™ Medallion are trademarks of Texas Instruments. Printed in Canada. 1280
Apr 05-NA

Performance specifications are typical. Due to constant research, specifications are subject to change without notice.



Download from www.Somanuals.com. All Manuals Search And Download.



WWW.CHRISTIEDIGITAL.COM

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>