





Residential Energy Saver High Input Direct Vent Water Heater

Features:

-  Bradford White is ISO registered to the 9001 standard.
- All residential storage models meet or exceed efficiency requirements of the Department of Energy. ASHRAE Standard 90.1 b (current standard) and the National Appliance Energy Conservation Act of 1987 recent amendment effective January 20, 2004 which supercedes all state and local efficiency requirements.
 - **1" Non-CFC foam insulation**—surrounds the tank surface, saving energy by retarding loss of heat.
 - **Closed combustion**—all air for combustion is taken directly from the outside. The co-axial vent pipe (pipe inside a pipe) draws combustion air in through the outer pipe (6"), and exhausts the products of combustion through the inner pipe (4").
 - **Co-axial**—rotational venting at top of unit.
 - **Heat Traps**—factory installed, minimizes heat loss through piping.
 - **Water Connections**—3/4" NPT factory installed true dielectric fittings. Extends water heater life and eases installation.
 - **No electrical power necessary.**
 - **Piezo igniter**—for ease of lighting the pilot.
 - **Vitraglas® lined tank**—Bradford White water heater tanks are protected from the corrosive effects of hot water by an exclusive ceramic porcelain-like coating. The Bradford White high silica Vitraglas® lining provides a tough interior surface for our water heater tanks.
 - **Factory installed Hydrojet® Total Performance System**—cold inlet sediment reducing device. Helps prevent sediment build up in tank. Increases first hour delivery of hot water while minimizing temperature build up at top of tank.
 - **Protective magnesium anode rod**—provides added protection against corrosion for long trouble-free service.
 - **Brass drain valve.**
 - **T&P relief valve**—included.
 - **Side Tappings**—for space heating purposes.
 - **Fully automatic controls**—automatic temperature selection at your fingertips. Built-in energy cut-off switch prevents abnormally high water temperature for extra safety. Built-in gas pressure regulation. Fast-acting thermostat starts heat recovery cycle sooner.
 - **Optional vent kits**—allow for up to 8 foot max vertical and 8 foot max horizontal (2.4 meters). All DH-1 models must be terminated horizontally
 - **Six or ten year limited warranty on steel tank**—heavy gauge steel automatically formed, rolled and welded to assure a continuous seam for glass lining.
 - **Six year limited warranty on parts.**
 - **Design certified by CSA International. (formerly AGA and CGA)**

MANUFACTURED UNDER ONE OR MORE OF THE FOLLOWING U.S. PATENTS: 7,063,133 B2; 5,954,492; 5,954,492; 5,761,379; 5,943,984; 5,081,696; 5,988,117; 6,142,216; 5,199,385; 5,574,822; 5,372,185; 5,485,879; 5,277,171; (B1)5,341,770; 5,660,165; 5,596,952; 5,682,666; 4,904,428; 5,023,031; 5,000,893; 4,669,448; 4,829,983; 4,808,356; 5,115,767; 5,092,519; 5,052,346; 4,416,222; 4,628,184; 4,861,968; 4,672,919; Re. 34,534. OTHER U.S. AND FOREIGN PATENT APPLICATIONS PENDING. CURRENT CANADIAN PATENTS: 1,272,914; 1,280,043; 1,289,832; 2,045,862; 2,112,515; 2,108,186; 2,107,012; 2,092,105.5.





Horizontal Installation Only

Optional Kits:

Part Number	Description
243-42516-00	Kit F – Telescopes from 4 $\frac{3}{4}$ " to 5 $\frac{1}{16}$ "
243-42517-00	Kit G – Telescopes from 6 $\frac{1}{2}$ " to 9 $\frac{3}{16}$ "
243-42514-00	Kit H – Telescopes from 13 $\frac{3}{4}$ " to 23 $\frac{1}{16}$ "
243-42512-00	Kit I – Telescopes from 49 $\frac{3}{16}$ " to 95 $\frac{1}{16}$ "

The standard vent kit (239-42979-00) is ordered and shipped separately. The components are as follows: 4" vent tube*, 6" Air Intake Tube, Vent Terminal, Inner Wall Term Mounting Flange, Outer Wall Term. Mounting Flange, Vent Terminal Hardware, RTV Silicone Sealant, 4" Vent Elbow and a 6" Air Intake Elbow. The vent tube and air intake tube telescopes from 13 3/4" to 23 11/16".

		Horizontal "X"				
		16 1/4	18	25 1/4	37 3/4	61 5/16
		17 3/16	20 11/16	35 3/16	57 7/8	107 5/16
Vertical "Y"	11 9/16	order kit F	order kit G	no add'l kit req'd	order kit H	order kit I
	16 5/16	*order kit F (2)	order kit G & F	order kit F	order kit H & F	order kit F & I
	17 1/4					
	18 1/16	order	order	order	order	order
	20 3/4	kit F & G	kit G (2)	kit G	kit G & H	kit G & I
	25 5/16	order	order	order	order	order
	35 1/4	kit F	kit G	kit H	kit H (2)	kit I
	38 1/16	order	order	order	order	order
	57 15/16	kit H & F	kit H & G	kit H (2)	kit H (3)	kit H & I
	61 3/8	order	order	order	order	order
107 3/8	kit I & F	kit I & G	kit I	kit I & H	kit I (2)	

* (2) = Order two of the kits referenced.

* (3) = Order three of the kits referenced.

The bold text above show what kit(s) are needed in addition to the standard vent and air intake tubes. If the standard vent and air intake tubes are not used in the venting system (those that do not have bold text) they can be discarded or saved.

For vent distances not found in the selection chart above, please contact the Product Management Department for sizing recommendations.

Energy Saver Direct Vent Models

CEC listed.

78% Recovery Efficiency for all models.

NATURAL GAS					A	B	C	D	E	F	G						
Model Number	Imp. Gal. Cap.	U.S. Gal. Cap.	Liters	Input BTU	KW	GPH Rec. 50°C/90°F Rise			Ht. to Center Line of Vent in. mm.	Jacket Dia. in. mm.	Ht. to Top of Heater in. mm.	Ht. to Gas Conn. in. mm.	Ht. to T&P Conn. in. mm.	Space Htg. Outlet in. mm.	Space Htg. Inlet in. mm.	Vent Dia. in. mm.	Approx. Shpg. Wt. Lbs. Kg.
						Imp. Gal.	US GPH	LPH									
DH1-504T6BN ^(LP)	40	48	182	50,000	14.7	43	53	201	75 $\frac{1}{4}$ 1911	20 508	58 $\frac{3}{4}$ 1492	15 $\frac{1}{4}$ 387	52 $\frac{1}{4}$ 1327	52 $\frac{1}{4}$ 1327	15 $\frac{3}{4}$ 400	4/6 102/152	197/89.4
DH1-65T6BN	54	65	246	55,000	16.1	47	58	220	78 $\frac{1}{4}$ 1988	22 559	62 1557	15 $\frac{3}{8}$ 387	56 1422	56 1422	15 $\frac{3}{4}$ 400	4/6 102/152	243/110
DH1-75S6BN ^(LP)	62	75	284	60,000	17.6	51	63	238	75 $\frac{1}{2}$ 1918	24 $\frac{1}{2}$ 622	59 1499	15 $\frac{3}{8}$ 387	52 1321	52 1321	16 $\frac{1}{2}$ 419	4/6 102/152	281/127

For 10 year models, change suffix from "6" to "10".

All propane gas heaters are equipped with Cast Iron Burner. Change suffix "BN" to "CX".

Suitable for Water (Potable) Heating and Space Heating

Toxic chemicals, such as those used for boiler treatment, shall NEVER be introduced into this system. This unit may NEVER be connected to any existing heating system or component(s) previously used with a non-potable water heating appliance.

General

All gas water heaters are certified at 300 PSI (2068 kPa) test pressure and 150 PSI (1034 kPa) working pressure. All water connections are 3/8" (19mm) NPT on 11" (703mm) centers on top of unit, all gas connections 1/2" (13mm). All models design certified by CSA International (formerly AGA and CGA). Recovery based on rated efficiency.

Meets NAECA requirements. All natural gas models meet SCAQMD requirements.

Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.

6-Year Limited Warranty on Component Parts

BRADFORD WHITE CORPORATION has a 6-year warranty on replaceable parts—thermostat, burner, dip tube, drain valve and piezo igniter. These quality components are manufactured for us by industry leaders and will be replaced in the event of failure during the parts warranty period (exclusive of shipping and re-installation cost).§

6 or 10-Year Limited Tank Warranties

BRADFORD WHITE CORPORATION LIMITED WARRANTY: Protects your investment in a quality glass-lined heater. If the tank leaks for reasons of faulty materials, workmanship, or corrosion within the warranty period, the heater will be replaced with a comparable heater of our manufacture (exclusive of shipping and re-installation cost).§

§ Some states do not allow limitations on warranties. See complete copy of the warranty included with this product. Indicated warranties apply to USA, Canada and Puerto Rico installations.

Vitraglas® and Hydrojet® are registered trademarks of Bradford White® Corporation. ©2006, Bradford White Corporation. All rights reserved.

105-B-HIDV-1106-A

^(LP) Propane Gas Inputs			Recovery at 50°C Rise and 90°F Rise		
	Imp. GPH	U.S. GPH	Liters/Hr.		
DH1-504T6CX	48,000 BTU/H	14.1 KW	41	50	189
DH1-75S6CX	57,000 BTU/H	16.7 KW	48	60	227

BRADFORD WHITE
CORPORATION
Ambler, PA

For U.S. and Canada field service, contact your professional installer or local Bradford White sales representative.

Sales/800-523-2931
Fax/215-641-1670

Technical Support/800-334-3393
Fax/269-795-1089

Warranty/800-531-2111
Fax/269-795-1089

International:
Telephone/215-641-9400
Telefax/215-641-9750

Fax on Demand:
888-538-7833

www.bradfordwhite.com

BRADFORD WHITE-CANADA INC.
Mississauga, ON

Sales/Technical Support
866-690-0961
905-238-0100

Fax/905-238-0105

www.bradfordwhitecanada.com

Count On Bradford White

For Everything Hot Water

Printed in U.S.A.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>