

# First Alert

## USER'S MANUAL

### 120V PLUG-IN CARBON MONOXIDE ALARM WITH SILENCE FEATURE



120V AC ~ 60 Hz  
.085A Standby .087A Alarm

M08-0016-000 P 06/02



Model FCD2N

#### IMPORTANT! PLEASE READ CAREFULLY AND SAVE.

This user's manual contains important information about your Carbon Monoxide (CO) Alarm's operation. If you are installing this CO Alarm for use by others, you must leave this manual—or a copy of it—with the end user.

THIS USER'S MANUAL HAS BEEN RESIZED TO  
PRINT OUT ON 8-1/2 x 11" PAGES.

BLACK page numbers reference the original printed document.

RED page numbers reference this web version.

## TABLE OF CONTENTS

Introduction	1
Basic Safety Information	1
How Your CO Alarm Works	1
What the Lights and Alarm Tones Mean	2
Installation	2
Where to Install CO Alarms	2
Where CO Alarms Should NOT Be Installed	2
How to Install Your CO Alarm	3
If Your CO Alarm Sounds	3
If the Alarm Signal Sounds	3
Finding the Source of CO After an Alarm	3 & 4/3
Using the Silence Feature	3
Testing and Maintenance	3
What You Need to Know About CO	4
What is CO?	4
Symptoms of CO Poisoning	4
Potential Sources Of CO In The Home	4
How Can I Protect My Family?	4
Underwriters Laboratories Inc. UL2034	5-6/5
General Limitations Of CO Alarms	5-6/5
Troubleshooting Guide	5-6/6
Five-Year Limited Warranty	5-6/6

All Rights Reserved. © 2002 BRK Brands, Inc.  
BRK Brands, Inc., 3901 Liberty Street Road, Aurora, IL 60504-8122  
Consumer Affairs: (800) 323-9005  
www.firstalert.com

## INTRODUCTION

### BASIC SAFETY INFORMATION

#### IMPORTANT!

- Dangers, Warnings, and Cautions alert you to important operating instructions or to potentially hazardous situations. Pay special attention to these items.
- **THIS IS NOT A SMOKE ALARM!** This CO Alarm is designed to detect carbon monoxide from ANY source of combustion. It is NOT designed to detect smoke, fire, or any other gas.
- This CO Alarm is approved for use in single-family residences. It is NOT designed for marine use.

#### CAUTION!

- This CO Alarm will only indicate the presence of carbon monoxide gas at the sensor. Carbon monoxide gas may be present in other areas.

#### WARNING!

- The Silence Feature is for your convenience only and will not correct a CO problem. Always check your home for a potential problem after any alarm. Failure to do so can result in injury or death.
- This CO Alarm cannot operate without continuous electricity. It does not operate during a power failure.
- NEVER ignore your Carbon Monoxide Alarm if it alarms. Refer to "If Your CO Alarm Sounds" for more information. Failure to do so can result in injury or death.
- Test the CO Alarm once a week. If the CO Alarm ever fails to test correctly, have it replaced immediately! If the CO Alarm is not working properly, it cannot alert you to a problem.
- This product is intended for use in ordinary indoor locations of family living units. It is not designed to measure CO levels in compliance with Occupational Safety and Health Administration (OSHA) commercial or industrial standards. Individuals with medical conditions that may make them more sensitive to carbon monoxide may consider using warning devices which provide audible and visual signals for carbon monoxide concentrations under 30 ppm. For additional information on carbon monoxide and your medical condition contact your physician.

## HOW YOUR CO ALARM WORKS

### GENERAL INFORMATION

#### CAUTION!


Leave your CO Alarm plugged in year-round. CO problems can occur any time during the year, and this Alarm can only alert you if it is plugged in and receiving power.

This CO Alarm is intended for use in a standard, unswitched 120V AC wall outlet. It is not intended for use in extension cords, power strips, or outlets controlled by a switch or dimmer. These may not provide continuous power to the unit.

When fully powered, it samples the air and takes a new reading about every second. A microchip inside the unit stores each reading, and remembers the levels of CO it has been exposed to over time. The unit goes into alarm mode when it has been exposed to a "critical" level of CO (measured in parts per million or "ppm") within a specified time (measured in minutes).

This Carbon Monoxide Alarm features a permanently installed sensor, three colored indicator lights, and an 85dB alarm horn. It also has a Silence Feature to temporarily quiet the alarm horn.

### THE COVER OF YOUR CO ALARM




- 1 Test/Silence Button
- 2 POWER Light (Green)
- 3 SERVICE Light (Yellow)
- 4 ALARM Light (Red)
- 5 Air Vents
- 6 (Behind the Cover) Alarm Horn: 85dB audible alarm for test, alarm, and unit malfunction warning.

### MALFUNCTION WARNING

This unit performs self-diagnostic tests approximately every second. If the Alarm malfunctions, it should be replaced immediately.


## WHAT THE LIGHTS AND ALARM TONES MEAN

### During Power Up (or After Power Outage)




Green light ON. Yellow & red lights OFF. Horn "chirps" once.

### During an Alarm




Green light ON. Yellow light OFF. Red light FLASHES. Repeating horn pattern: 4 beeps, then a pause, 4 beeps, then a pause.

### During Normal Operation




Green light ON. Yellow & red lights OFF. Horn silent.

### During Alarm Malfunction




Green light ON. Yellow light ON. Red light FLASHES. Horn "chirps" about twice a minute.

### During Normal Test



All three lights flash briefly. Horn pattern repeats twice: 4 beeps, then a pause, 4 beeps, then a pause.

### Using the Silence Feature in Alarm




Green light ON. Yellow light OFF. Red light FLASHES. Horn silent for 4 minutes. Refer to "Using The Silence Feature" for details.

## INSTALLATION

### WHERE TO INSTALL CO ALARMS

The National Fire Protection Association (NFPA) recommends that a CO Alarm should be centrally located outside of each separate sleeping area in the immediate vicinity of the bedrooms. For added protection, install additional CO Alarms in each separate bedroom, and on every level of your home.

If your bedroom hallway is longer than 40 feet, install a CO Alarm at BOTH ends of the hallway.



◇ REQUIRED TO MEET NFPA RECOMMENDATIONS

◆ SUGGESTED AREAS FOR INSTALLING ADDITIONAL CO ALARMS

### In a Single-level Home:

- Install at least one CO Alarm near or within each separate sleeping area.
- For added protection, install an additional CO Alarm at least 20 feet (6 meters) away from the furnace or fuel burning heat source.

### In a Multi-level Home:

- Install at least one CO Alarm near or within each separate sleeping area.
- For added protection, install at least one CO Alarm on each level of the home. If you have a basement, install that CO Alarm at the top of the basement stairs.
- For added protection, install an additional CO Alarm at least 20 feet (6 meters) away from the furnace or fuel burning heat source.

### ⚠ WARNING!

This unit does not work without power. Choose an outlet where it can't be accidentally unplugged or switched off by children. Keep small children away from the unit. Teach them not to play with it or unplug it. Explain what the alarms mean.

## WHERE CO ALARMS SHOULD NOT BE INSTALLED

### DO NOT LOCATE THIS CO ALARM:

- In garages, kitchens, furnace rooms, or in any extremely dusty, dirty or greasy areas.
- Closer than 20 feet from a furnace or other fuel burning heat source, or fuel burning appliances like a water heater.
- Within 5 feet of any cooking appliance.
- In extremely humid areas. This alarm should be at least 10 feet from a bath or shower, sauna, humidifier, vaporizer, dishwasher, laundry room, utility room or other source of high humidity.
- In areas where temperature is colder than 40°F (4°C) or hotter than 100°F (38°C). These areas include unconditioned crawl spaces, unfinished attics, uninsulated or poorly insulated ceilings, porches, and garages.
- In turbulent air, like near ceiling fans, heat vents, air conditioners, fresh air returns, or open windows. Blowing air may prevent CO from reaching the sensors.
- In direct sunlight.
- In outlets covered by curtains or other obstruction.

### ⚠ WARNING!

This CO Alarm is designed for use inside a single-family home or apartment. It is not meant to be used in common lobbies, hallways, or basements of multi-family buildings unless working CO Alarms are also installed in each family living unit. CO Alarms in common areas may not be heard from inside individual family living units.

### ⚠ WARNING!

This CO Alarm alone is not a suitable substitute for complete detection systems in places which house many people, like hotels or dormitories, unless a CO Alarm is also placed in each unit.

### ⚠ WARNING!

DO NOT use this CO Alarm in warehouses, industrial or commercial buildings, special-purpose non-residential buildings, RVs, boats, or airplanes. This CO Alarm is specifically designed for residential use, and may not provide adequate protection in non-residential applications.

## HOW TO INSTALL YOUR CO ALARM

### ⚠ WARNING!

This CO Alarm cannot operate without continuous electricity. It does not operate during a power failure. Do not use in an extension cord, or outlet controlled by a dimmer or switch—unit must have a constant power supply.

### ⚠ CAUTION!

Leave your CO Alarm plugged in year-round. CO problems can occur any time during the year, and this alarm can only alert you if it is plugged in and receiving power.

1. Plug the unit into a standard UNSWITCHED 120V AC outlet. In horizontally or vertically positioned wall outlets, mount unit with Test/Silence button facing upward.
2. Make sure green light shines when you plug in the unit. It will shine continuously when unit is receiving power. The horn will “chirp” once during power up, or when power is restored after an outage.
3. Test by pressing the Test/Silence button firmly until the unit sounds: four loud beeps, pause, 4 beeps. The sequence should last 5-6 seconds. During testing, the green, yellow, and red lights flash. This is normal.
4. While testing the unit, have a family member check that the horn can be easily heard from the sleeping areas. The unit should be located where it can wake you if it alarms at night.
5. Find the pair of self-adhesive labels included with this CO Alarm.
  - On each label write in the phone number of your emergency responder (like 911) and a qualified appliance technician.
  - Place one label near the CO Alarm, and the other label in the “fresh air” location you plan to go if the alarm sounds.

**NOTE:** A qualified appliance technician is defined as “a person, firm, corporation, or company that either in person or through a representative, is engaged in and responsible for the installation, testing, servicing, or replacement of heating, ventilation, air conditioning (HVAC) equipment, combustion appliances and equipment, and/or gas fireplaces or other decorative combustion equipment.”


## IF YOUR CO ALARM SOUNDS

Actuation of your CO alarm indicates the presence of carbon monoxide (CO) which can kill you. In other words, when your CO Alarm sounds, you must not ignore it!

### IF THE ALARM SIGNAL SOUNDS:

1. Operate the Test/Silence button.
2. Call your emergency services, fire department or 911. Write down the number of your local emergency service here:  
  
\_\_\_\_\_
3. Immediately move to fresh air—outdoors or by an open door or window. Do a head count to check that all persons are accounted for. Do not re-enter the premises, or move away from the open door or window until the emergency services responder has arrived, the premises have been aired out, and your CO Alarm remains in its normal condition.
4. After following steps 1-3, if your CO Alarm reactivates within a 24-hour period, repeat steps 1-3 and call a qualified appliance technician to investigate for sources of CO from fuel-burning equipment and appliances, and inspect for proper operation of this equipment. If problems are identified during this inspection have the equipment serviced immediately. Note any combustion equipment not inspected by the technician, and consult the manufacturers’ instructions, or contact the manufacturers directly, for more information about CO safety and this equipment. Make sure that motor vehicles are not, and have not, been operating in an attached garage or adjacent to the residence. Write down the number of a qualified appliance technician here:  
  
\_\_\_\_\_

**IF IN ALARM EVERYONE  
MOVE TO FRESH AIR**



**“ALARM-MOVE TO FRESH AIR”**

If you hear the alarm horn and the red light is flashing, move everyone to a source of fresh air.  
**DO NOT unplug the CO Alarm!**

POWER/ALARM

### FINDING THE SOURCE OF CO AFTER AN ALARM

Because CO may dissipate by the time an investigator arrives, it may be difficult to locate the source of CO. See “What You Need to Know About CO.” BRK Brands, Inc. shall not be obligated to pay for any carbon monoxide investigation or service call.

## USING THE SILENCE FEATURE

### ⚠ WARNING!

The Silence Feature is for your convenience only and will not correct a CO problem. Always check your home for a potential problem after any alarm. Failure to do so can result in injury or death.

### ⚠ WARNING!

**NEVER unplug your CO Alarm to silence the horn. Use the silence feature. Unplugging the CO Alarm removes your protection!** See “If Your CO Alarm Sounds” for details on responding to an alarm.

The Silence Feature is intended to temporarily silence your CO Alarm’s alarm horn while you correct the problem—it will not correct a CO problem. While the alarm is silenced, it will continue to monitor the air for CO.

When CO reaches alarm levels, the alarm will sound—repeating horn pattern: 4 beeps, a pause, 4 beeps, etc. Press and hold the Test/Silence button until the horn is silent. The initial Silence cycle will last approximately 4 minutes.

### NOTE:

After initial 4-minute Silence cycle, the CO Alarm re-evaluates present CO levels and responds accordingly. If CO levels remain potentially dangerous—or start rising higher—the horn will start sounding again.

### While the detector is silenced:

If the CO Alarm...	This means...
Is silent for only 4 minutes, then starts sounding loudly—4 beeps, then a pause, 4 beeps, then a pause. Red light continues flashing...	CO levels are still potentially dangerous.
Remains silent. Only the green light is on...	Unit has returned to normal operation.

## TESTING AND MAINTENANCE

### WEEKLY TESTING

#### ⚠ WARNING!

**Test the CO Alarm once a week. If the CO Alarm ever fails to test correctly, have it replaced immediately! If the CO Alarm is not working properly, it cannot alert you to a problem.**

Push and hold the Test/Silence button on the cover until a loud alarm sounds—4 beeps, a pause, then 4 beeps. The alarm sequence should last for 5-6 seconds. If the CO Alarm ever fails to test properly, replace it immediately.

If the CO Alarm is not working properly, refer to the “Limited Warranty” at the end of this manual.

#### ⚠ WARNING!

**The Test/Silence button is the only proper way to test the CO Alarm. NEVER use vehicle exhaust! Exhaust may cause permanent damage and voids your warranty.**

#### ⚠ WARNING!

**DO NOT stand close to the CO Alarm when the horn is sounding. Exposure at close range may be harmful to your hearing. When testing, step away when horn starts sounding.**

### REGULAR MAINTENANCE

To keep the CO Alarm in good working order:

- Test it every week using the Test/Silence button.
- Vacuum the CO Alarm cover at least twice a year, using the soft brush attachment. Test the CO Alarm again after vacuuming.

#### ⚠ CAUTION!

**DO NOT spray cleaning chemicals or insect sprays directly on or near the CO Alarm. DO NOT paint over the CO Alarm. Doing so may cause permanent damage.**

### IMPORTANT!

Household cleaners, aerosol chemicals and other contaminants can affect the sensor. When using any of these materials near the CO Alarm, make sure the room is well ventilated.

#### IMPORTANT!

If your home is being fumigated, unplug the unit temporarily and put it where it will not be exposed to chemicals or fumes. When fumigation is complete and all traces of fumes clear, plug the unit back in and retest it.

# WHAT YOU NEED TO KNOW ABOUT CO

## WHAT IS CO?

CO is an invisible, odorless, tasteless gas produced when fossil fuels do not burn completely, or are exposed to heat (usually fire). Electrical appliances typically do not produce CO.

**These fuels include:** Wood, coal, charcoal, oil, natural gas, gasoline, kerosene, and propane.

Common appliances are often sources of CO. If they are not properly maintained, are improperly ventilated, or malfunction, CO levels can rise quickly. CO is a real danger now that homes are more energy efficient. "Air-tight" homes with added insulation, sealed windows, and other weatherproofing can "trap" CO inside.

## SYMPTOMS OF CO POISONING

These symptoms are related to CO POISONING and should be discussed with ALL household members.

### Mild Exposure:

Slight headache, nausea, vomiting, fatigue ("flu-like" symptoms).

### Medium Exposure:

Throbbing headache, drowsiness, confusion, fast heart rate.

### Extreme Exposure:

Convulsions, unconsciousness, heart and lung failure. Exposure to carbon monoxide can cause brain damage, death.

## ⚠WARNING!

**Some individuals are more sensitive to CO than others, including people with cardiac or respiratory problems, infants, unborn babies, pregnant mothers, or elderly people can be more quickly and severely affected by CO. Members of sensitive populations should consult their doctors for advice on taking additional precautions.**


## FINDING THE SOURCE OF CO AFTER AN ALARM

Carbon monoxide is an odorless, invisible gas, which often makes it difficult to locate the source of CO after an alarm. These are a few of the factors that can make it difficult to locate sources of CO:

- House well ventilated before the investigator arrives.
- Problem caused by "backdrafting."
- Transient CO problem caused by special circumstances.

**BRK Brands, Inc. shall not be obligated to pay for any carbon monoxide investigation or service call.**

## POTENTIAL SOURCES OF CO IN THE HOME



**Fuel-burning appliances like:** portable heater, gas or wood burning fireplace, gas kitchen range or cooktop, gas clothes dryer.

**Damaged or insufficient venting:** corroded or disconnected water heater vent pipe, leaking chimney pipe or flue, or cracked heat exchanger, blocked or clogged chimney opening.

**Improper use of appliance/device:** operating a barbecue grill or vehicle in an enclosed area (like a garage or screened porch).

**Transient CO Problems:** "transient" or on-again-off-again CO problems can be caused by outdoor conditions and other special circumstances.

The following conditions can result in transient CO situations:

1. Excessive spillage or reverse venting of fuel appliances caused by outdoor conditions such as:
  - Wind direction and/or velocity, including high, gusty winds. Heavy air in the vent pipes (cold/humid air with extended periods between cycles).
  - Negative pressure differential resulting from the use of exhaust fans.
  - Several appliances running at the same time competing for limited fresh air.
  - Vent pipe connections vibrating loose from clothes dryers, furnaces, or water heaters.
  - Obstructions in or unconventional vent pipe designs which can amplify the above situations.
2. Extended operation of unvented fuel burning devices (range, oven, fireplace).
3. Temperature inversions, which can trap exhaust close to the ground.
4. Car idling in an open or closed attached garage, or near a home.

These conditions are dangerous because they can trap exhaust in your home. Since these conditions can come and go, they are also hard to recreate during a CO investigation.

## HOW CAN I PROTECT MY FAMILY?

A CO Alarm is an excellent means of protection. It monitors the air and sounds a loud alarm before carbon monoxide levels become threatening for average, healthy adults.

**A CO Alarm is not a substitute for proper maintenance of home appliances.**

To help prevent CO problems and reduce the risk of CO poisoning:

- Clean chimneys and flues yearly. Keep them free of debris, leaves, and nests for proper air flow. Also, have a professional check for rust and corrosion, cracks, or separations. These conditions can prevent proper air movement and cause backdrafting. Never "cap" or cover a chimney in any way that would block air flow.
- Test and maintain all fuel-burning equipment annually. Many local gas or oil companies and HVAC companies offer appliance inspections for a nominal fee.
- Make regular visual inspections of all fuel-burning appliances. Check appliances for excessive rust and scaling. Also check the flame on the burner and pilot lights. The flame should be blue. A yellow flame means fuel is not being burned completely and CO may be present. Keep the blower door on the furnace closed. Use vents or fans when they are available on all fuel-burning appliances. Make sure appliances are vented to the outside. Do not grill or barbecue indoors, or in garages or on screen porches.
- Check for exhaust backflow from CO sources. Check the draft hood on an operating furnace for a backdraft. Look for cracks on furnace heat exchangers.
- Check the house or garage on the other side of shared wall.
- Keep windows and doors open slightly. If you suspect that CO is escaping into your home, open a window or a door. Opening windows and doors can significantly decrease CO levels.

**In addition, familiarize yourself with all enclosed materials. Read this manual in its entirety, and make sure you understand what to do if your CO Alarm sounds.**

# UNDERWRITERS LABORATORIES INC. UL2034

## WHAT LEVELS OF CO CAUSE AN ALARM?

Underwriters Laboratories Inc. UL2034 defines 3 specific alarm points by which all residential CO Alarms must alarm. They are measured in parts per million (ppm) of CO over time (in minutes).

### UL2034 Required Alarm Points\*:

- If the alarm is exposed to 400 ppm of CO, IT MUST ALARM BETWEEN 4 and 15 MINUTES
- If the alarm is exposed to 150 ppm of CO, IT MUST ALARM BETWEEN 10 and 50 MINUTES.
- If the alarm is exposed to 70 ppm of CO, IT MUST ALARM BETWEEN 60 and 240 MINUTES.

\* Approximately 10% COHb exposure at levels of 15% to 95% Relative Humidity (RH).

The unit is designed not to alarm when exposed to a constant level of 30 ppm for 30 days.

## IMPORTANT!

CO Alarms are designed to alarm before there is an immediate life threat. Since you cannot see or smell CO, never assume it's not present.

- An exposure to 100 ppm of CO for 20 minutes may not affect average, healthy adults, but after 4 hours the same level may cause headaches.
- An exposure to 400 ppm of CO may cause headaches in average, healthy adults after 35 minutes, but can cause death after 2 hours.

## IMPORTANT!

This CO Alarm measures exposure to CO over time. It alarms if CO levels are extremely high in a short period of time, or if CO levels reach a certain minimum over a long period of time. The CO Alarm generally sounds an alarm before the onset of symptoms in average, healthy adults.

Why is this important? Because you need to be warned of a potential CO problem while you can still react in time. In many reported cases of CO exposure, victims may be aware that they are not feeling well, but become disoriented and can no longer react well enough to exit the building or get help. Also, young children and pets may be the first affected. The average healthy adult might not feel any symptoms when the CO Alarm sounds. However, people with cardiac or respiratory problems, infants, unborn babies, pregnant mothers, or elderly people can be more quickly and severely affected by CO. If you experience even mild symptoms of CO poisoning, consult your doctor immediately!

## GENERAL LIMITATIONS OF CO ALARMS

**This CO Alarm is intended for residential use. It is not intended for use in industrial applications where Occupational Safety and Health Administration (OSHA) requirements for carbon monoxide detectors must be met.**

**CO Alarms will not work without power.** This CO Alarm requires a continuous supply of AC power. Plug into an unswitched 120V AC outlet only.

**This CO Alarm will not sense carbon monoxide that does not reach the sensor.** This CO Alarm will only sense CO at the sensor. CO may be present in other areas. Doors or other obstructions may affect the rate at which CO reaches the CO Alarm. For this reason, if bedroom doors are usually closed at night, we recommend you install a CO Alarm in each bedroom and in the hallway between them.

**CO Alarms may not sense CO on another level of the home.** For example, a CO Alarm on the second level, near the bedrooms, may not sense CO in the basement. For this reason, one CO Alarm may not give adequate warning. Complete coverage is recommended. Place CO Alarms on each level of the home.

**CO Alarms may not be heard.** The alarm horn loudness meets or exceeds current UL standards of 85 dB at 10 feet. However, if the CO Alarm is installed outside the bedroom, it may not wake up a sound sleeper or one who has recently used drugs or has been drinking alcoholic beverages. This is especially true if the door is closed or only partly open. Even persons who are awake may not hear the alarm horn if the sound is blocked by distance or closed doors. Noise from traffic, stereo, radio, television, air conditioner, or other appliances may also prevent alert persons from hearing the alarm horn. This CO Alarm is not intended for people who are hearing impaired.

**Standards:** Underwriters Laboratories Inc. Single and Multiple Station carbon monoxide alarms UL2034.

According to Underwriters Laboratories Inc. UL2034, Section 1-1.2: "Carbon monoxide alarms covered by these requirements are intended to respond to the presence of carbon monoxide from sources such as, but not limited to, exhaust from internal-combustion engines, abnormal operation of fuel-fired appliances, and fireplaces. CO Alarms are intended to alarm at carbon monoxide levels below those that could cause a loss of ability to react to the dangers of Carbon Monoxide exposure." This CO Alarm monitors the air at the Alarm, and is designed to alarm before CO levels become life threatening. This allows you precious time to leave the house and correct the problem. This is only possible if Alarms are located, installed, and maintained as described in this manual.

**Gas Detection at Typical Temperature and Humidity Ranges:** The CO Alarm is not formulated to detect CO levels below 30 ppm typically. UL tested for false alarm resistance to Methane (500 ppm), Butane (300 ppm), Heptane (500 ppm), Ethyl Acetate (200 ppm), Isopropyl Alcohol (200 ppm) and Carbon Dioxide (5000 ppm). Values measure gas and vapor concentrations in parts per million.

**Audible Alarm:** 85dB minimum at 10 feet.

**CO Alarms are not a substitute for a smoke alarm.** Although fire is a source of carbon monoxide, this CO Alarm does not sense smoke or fire. This CO Alarm senses CO that may be escaping unnoticed from malfunctioning furnaces, appliances, or other sources. Early warning of fire requires the installation of smoke alarms.

**CO Alarms are not a substitute for life insurance.** Though these CO Alarms warn against increasing CO levels, BRK Brands, Inc. does not warrant or imply in any way that they will protect lives from CO poisoning. Homeowners and renters must still insure their lives.

**CO Alarms have a limited life.** Although the CO Alarm and all of its parts have passed many stringent tests and are designed to be as reliable as possible, any of these parts could fail at any time. Therefore, you must test your CO Alarm weekly.

**CO Alarms are not foolproof.** Like all other electronic devices, CO Alarms have limitations. They can only detect CO that reaches their sensors. They may not give early warning to rising CO levels if the CO is coming from a remote part of the home, away from the CO Alarm.

## TROUBLESHOOTING GUIDE

PROBLEM...	THIS MEANS...	YOU SHOULD...
Green light is OFF. Unit will not alarm when you press the Test/Silence button.	CO Alarms may not be plugged all the way in, or is not receiving power.	Gently push unit all the way into outlet. Make sure it is not plugged into an outlet controlled by a switch.
Unit "chirps" about twice a minute. Green and Yellow lights are ON. Red light FLASHES	Malfunction. CO Alarm needs to be replaced.	Make sure unit is plugged in securely. CO Alarms under warranty should be returned to manufacturer for replacement. See "Limited Warranty" for details.
CO Alarm goes back into alarm 4 minutes after you press the Test/Silence button.	CO levels are still potentially dangerous.	Refer to "If Your CO Alarm Sounds" for details on how to respond to an alarm. If anyone is feeling ill, EVACUATE your home immediately.
CO Alarm sounds frequently even though no high levels of CO are revealed in an investigation.	The CO Alarm may be improperly located. Refer to "Where to Install CO Alarms."	Relocate your Alarm. If frequent alarms continue, have home rechecked for potential CO problems. You may be experiencing an intermittent CO problem.

If you have any questions that cannot be answered by reading this manual, call Consumer Affairs at 1-800-323-9005.

### FIVE-YEAR LIMITED WARRANTY

**Coverage:** BRK Brands, Inc. ("BRK") the maker of First Alert® brand products, warrants that for a period of 5 years from the date of purchase, this product will be free from defects in material and workmanship. BRK, at its option, will repair or replace this product or any component of the product found to be defective during the warranty period. Replacement will be made with a new or remanufactured product or component. If the product is no longer available, replacement may be made with a similar product of equal or greater value. This is your exclusive warranty.

This warranty is valid for the original retail purchaser from the date of initial retail purchase and is not transferable. Keep the original sales receipt. Proof of purchase is required to obtain warranty performance. BRK dealers, service centers, or retail stores selling BRK products do not have the right to alter, modify or any way change the terms and conditions of this warranty.

This warranty does not cover normal wear of parts or damage resulting from any of the following: negligent use or misuse of the product, use on improper voltage or current, use contrary to the operating instructions, disassembly, repair or alteration by anyone other than BRK or an authorized service center. Further, the warranty does not cover acts of God, such as fire, flood, hurricanes and tornadoes or any batteries that are included with this unit.

BRK shall not be liable for any incidental or consequential damages caused by the breach of any express or implied warranty. Except to the extent prohibited by applicable law, any implied warranty of merchantability or fitness for a particular purpose is limited in duration to the duration of the above warranty. Some states, provinces, or jurisdictions do not allow the exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above limitations or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state, or province to province.

**How to Obtain Warranty Service:**

**Service:** If service is required, do not return the product to your retailer. In order to obtain warranty service, contact the Consumer Affairs Division at 1-800-323-9005, 7:30 AM to 5:00 PM, Central Standard Time, Monday through Friday. To assist in serving you, please have the model number and date of purchase available when calling.  
3920 Enterprise Court, Aurora, IL 60504-8132.

**For your records, please record:**

**Date Purchased:** \_\_\_\_\_

**Where Purchased:** \_\_\_\_\_

First Alert® is a registered trademark of the First Alert Trust.

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>