




# Light Duty Commercial Wall Hung Energy Saver Electric Water Heater



Photo is of LD-WH6U3-1

#### The Light Duty Wall Hung Electric Models Feature:

- Fully Automatic Controls—Fast acting surface-mount thermostat for automatic temperature control. Factory installed sensitive manual reset energy cut-off for safety to prevent overheating.
- Direct Heat Transfer With a Single Immersed Element—Transfers heat directly and efficiently to the water. Screw-in style element.
- Vitraglas® Lining—Bradford White water heater tanks are protected from the corrosive effects of hot water by an exclusive ceramic porcelain-like coating. The Bradford White high silica Vitraglas® lining provides a tough interior surface for our hot water tanks.
- 1" Non-CFC Foam Insulation—Surrounds the tank surface, saving energy by retarding loss of heat (30 gallon model has 2").
- Factory Installed Heavy Duty Wall Mounting Bracket—no additional brackets or modifications required.
- Water Connections—3/4" NPT factory installed true dielectric fittings extend water heater life and eases installation. Located on the bottom for easier installation.
- Protective Magnesium Anode Rod—Provides added protection against corrosion for long trouble-free service.
- Steel Tank—Heavy gauge steel automatically formed, rolled, and welded.
- Voltages Available—120V, 208V, 240V, 277V, 480V.
- Single Phase Operation Only.
- T&P Relief Valve Opening—All models have special tapping on side of tank.











3 or 5-Year Limited Tank Warranties / 1-Year Limited Warranty on Component Parts.

For more information on warranty, please visit www.bradfordwhite.com For products installed in USA, Canada and Puerto Rico. Some states do not allow limitations on warranties. See complete copy of the warranty included with the heater.

### **Light Duty Wall Hung Energy Saver Models**

Meet or exceed ASHRAE 90.1b (current standard) C.E.C. Listed

Model Number	Capacity U.S. Imp.	Recovery 100°F Rise U.S.* Imp.*	A Height	B Jacket Dia.	C Wall to Front	D Height to Bracket	E Height to T&P Conn.	Approx. Shipping Weight
	U.S. Imp. Gal. Gal.	U.S.* Imp.* GPH GPH	in.	in.	in.	in.	in.	lbs.
LD-WH6U3-1†	6 5	6 5	153/4	14	145/8	113/4	117/8	33
LD-WH12U3-1†	12 10	6 5	163/8	18	185/8	123/4	121/2	48
LD-WH20L3-1	19 16	6 5	243/8	18	185/8	181/4	21	59
LD-WH30L3-1	30 25	6 5	291/4	22	225/8	23	253/4	82

Model Number	Capacity	Recovery 56°C Rise Liters/*	A Height	B Jacket Dia.	C Wall to Front	D Height to Bracket	E Height to T&P Conn.	Approx. Shipping Weight
	Liters	Hour	mm.	mm.	mm.	mm.	mm.	kg.
LD-WH6U3-1†	23	23	400	356	372	298	302	15
LD-WH12U3-1†	45	23	416	457	473	314	317	22
LD-WH20L3-1	72	23	619	457	473	464	533	27
LD-WH30L3-1	114	23	743	557	575	584	654	37

Specify wattage and voltage when ordering. Use chart to right for maximum wattages at certain voltages.


†Maximum wattage at any voltage is 3000W.


For 5 year models, change suffix "3" to "5".

Single element only.

\*Based on 1500W operation.

NSF Construction not available.





	Recovery GPH Temperature Rise °F					
Wattage	60	80	90	100	120	
1500W	10	8	7	6	5	
2000W	14	10	9	8	7	
2500W	17	13	11	10	9	
3000W	21	15	14	12	10	
3500W	24	18	16	14	12	
4000W	28	21	18	16	14	
4500W	31	23	21	19	15	
5000W	34	26	23	21	17	
5500W	38	29	25	23	19	
6000W	41	31	28	25	21	

Wattage	Voltage						
Limitations	120V	208V	240V	277V	480\		
1500W	yes	yes	yes	yes	yes		
2000W	yes	yes	yes	yes	yes		
2500W	yes	yes	yes	yes	yes		
3000W	yes	yes	yes	yes	yes		
3500W	no	yes	yes	no	no		
4000W	no	yes	yes	yes	yes		
4500W	no	yes	yes	yes	yes		
5000W	no	yes	yes	yes	yes		
5500W	no	yes	yes	no	no		
6000W	no	yes	yes	yes	yes		

#### Genera

All models UL and CUL listed. These heaters are wired Single Phase, 120V with one 1500W element, unless otherwise specified. All water and electrical connections are 3/4" (19mm)NPT.

All models certified at 300 psi test pressure (2068 kPa) and 150 psi working pressure (1034 kPa).

Applicable models CSA verified for energy performance in accordance with C191.1-M90.

Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.



Ambler, PA

For U.S. and Canada field service, contact your professional installer or local Bradford White sales representative.

Sales 800-523-2931 • Fax 215-641-1670 / Technical Support 800-334-3393 • Fax 269-795-1089 • Warranty 800-531-2111 • Fax 269-795-1089 International: Telephone 215-641-9400 • Telefax 215-641-9750 / www.bradfordwhite.com

BRADFORD WHITE-CANADA\* INC. Sales / Technical Support 866-690-0961 / 905-238-0100 • Fax 905-238-0105 / www.bradfordwhite.com

## Built to be the Best™

©2008, Bradford White Corporation. All rights reserved.

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com