

GREAT BEND® MID-MOUNT COMPACT LOADERS

Mid-Mount Loader Specifications	1045	2045	3045
Tractor HP Range	15-25	20-40	30-50
2WD/FWA	2WD/FWA	2WD/FWA	2WD/FWA
Max. Lift Height <i>Measured at Pivot Pin</i>	86"	103"	110"
Max. Lift Height <i>Under Level Bucket</i>	81"	96"	100"
Max. Dump Angle	45°	40°	45°
Digging Depth	5"	5"	5"
Lift Capacity <i>to Max. Height at Pivot Pin</i>	825 lbs.	1530 lbs.	2350 lbs.
Lift Capacity <i>to Max. Height 31.5" Forward of Pivot Pin</i>	570 lbs.	880 lbs.	1500 lbs.
Lift Capacity <i>to 59" Height at Pivot Pin</i>	940 lbs.	1730 lbs.	2700 lbs.
Lift Capacity <i>to 59" Height 31.5" Forward of Pivot Pin</i>	710 lbs.	1195 lbs.	1850 lbs.
Breakout Force <i>at Pivot Pin</i>	1335 lbs.	2370 lbs.	4000 lbs.
Breakout Force <i>31.5" Forward of Pivot Pin</i>	965 lbs.	1530 lbs.	2900 lbs.
Rollback Force <i>at Max. Height 31.5" Forward of Pivot Pin</i>	1935 lbs.	1625 lbs.	2300 lbs.
Rollback Force <i>at 59" Height 31.5" Forward of Pivot Pin</i>	2300 lbs.	2020 lbs.	3400 lbs.
Rollback Force <i>at Ground Level 31.5" Forward of Pivot Pin</i>	1700 lbs.	1680 lbs.	2800 lbs.
Specifications Based On Tractor System of	1875 psi hyd. pressure & 6 gpm pump capacity	2000 psi hyd. pressure & 10 gpm pump capacity	2500 psi hyd. pressure & 10 gpm pump capacity

GREAT BEND® FRONT-PUSH COMPACT LOADERS

Front-Push Loader Specifications	224	244	284
Tractor HP Range	12-25	15-35	25-50
2WD/FWA	2WD/FWA	2WD/FWA	2WD/FWA
Max. Lift Height <i>Measured at Pivot Pin</i>	76"	97"	107"
Max. Lift Height <i>Under Level Bucket</i>	71"	90"	101"
Max. Dump Angle	50°	50°	50°
Digging Depth	2.5"	4"	3"
Lift Capacity <i>to Max. Height at Pivot Pin</i>	725 lbs.	1150 lbs.	1970 lbs.
Lift Capacity <i>to Max. Height 31.5" Forward of Pivot Pin</i>	515 lbs.	875 lbs.	1270 lbs.
Lift Capacity <i>to 59" Height at Pivot Pin</i>	800 lbs.	1365 lbs.	2200 lbs.
Lift Capacity <i>to 59" Height 31.5" Forward of Pivot Pin</i>	595 lbs.	1085 lbs.	1570 lbs.
Breakout Force <i>at Pivot Pin</i>	1340 lbs.	1995 lbs.	2985 lbs.
Breakout Force <i>31.5" Forward of Pivot Pin</i>	960 lbs.	1525 lbs.	2005 lbs.
Rollback Force <i>at Max. Height 31.5" Forward of Pivot Pin</i>	1155 lbs.	2040 lbs.	2640 lbs.
Rollback Force <i>at 59" Height 31.5" Forward of Pivot Pin</i>	1330 lbs.	2410 lbs.	3220 lbs.
Rollback Force <i>at Ground Level 31.5" Forward of Pivot Pin</i>	1055 lbs.	1820 lbs.	2145 lbs.
Specifications Based On Tractor System of	1875 psi hyd. pressure & 4 gpm pump capacity	2000 psi hyd. pressure & 6 gpm pump capacity	2450 psi hyd. pressure & 9 gpm pump capacity

Great Bend®

More Performance For All Your Jobs

Great Bend®
 Manufactured by Bush Hog®, L.L.C.
 101 Bush Hog Boulevard
 Telford, TN 37690
 (423) 788-7100



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>