

# Bush Hog® TOUGH

## 2347QT Quick Attach Front-Push Loader

### Skid Steer Quick Attach System

#### BUSH HOG® TOUGH FEATURES

- TOUGH Boxed Boom Design
- TOUGH Large Diameter Cross Tubes
- TOUGH Robotic Welds
- TOUGH High Strength Chrome Plated Cylinder Rods
- TOUGH Bush Hog Made Buckets
- TOUGH Powder Coat Paint



MODEL	Specifications Based on 1997 ASAE STANDARDS	2347QT
<b>Tractor PTO HP Range</b>		25 - 50
<b>2WD/FWA</b>		2WD/FWA
<b>Maximum Lift Height</b> - Measured at Pivot Pin		107 inches
<b>Maximum Lift Height</b> - Under Level Bucket		101 inches
<b>Maximum Dump Angle</b>		50°
<b>Digging Depth</b>		3 inches
<b>Lift Capacity</b> to Maximum Height - At Pivot Pin		1970 lbs
<b>Lift Capacity</b> to Maximum Height - 31.5 inches Forward of Pivot Pin		1270 lbs
<b>Lift Capacity</b> to 59 inch Height - At Pivot Pin		2200 lbs
<b>Lift Capacity</b> to 59 inch Height - 31.5 inches Forward of Pivot Pin		1570 lbs
<b>Breakout Force</b> - At Pivot Pin		2985 lbs
<b>Breakout Force</b> - 31.5 inches - Forward of Pivot Pin		2005 lbs
<b>Rollback Force</b> at Maximum Height - 31.5 inches Forward of Pivot Pin		2640 lbs
<b>Rollback Force</b> at 59 inch Height - 31.5 inches Forward of Pivot Pin		3220 lbs
<b>Rollback Force</b> at Ground Level - 31.5 inches Forward of Pivot Pin		2145 lbs
<b>Raising Time</b> (Ground Level to Full Height)		4 seconds
<b>Lowering Time</b> (Full Height to Ground Level)		2 seconds
<b>Bucket Dumping Time</b> (Full Rollback to Full Dump)		4 seconds
<b>Bucket Rollback Time</b> (Full Dump to Full Rollback)		2 seconds
<b>Hydraulics</b>	Two 2.0 inch Bore, 22.50 inch Stroke Double Acting Bucket Cylinders and Two 2.0 inch Bore, 23.38 inch Stroke Double Acting Lift Cylinders	
<b>Specifications Based on Tractor System of</b>	2450 PSI hyd. Pressure & 9 GPM pump capacity	
<b>Bush Hog Quick Attach Buckets</b>	Available in 48, 60, 72 and 80 inch widths	
<b>Options</b>	Forklift Attachment (36 inch tines), Round Bale Spear, Bucket Tine Teeth, and Grill Guards	
<b>Warranty</b>	1 year limited warranty	
<b>FEATURES</b>	Available in major tractor colors	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>