

Bush Hog® TOUGH

2447QT Quick Attach Front-Push Loader

Skid Steer Quick Attach System

BUSH HOG® TOUGH FEATURES

- TOUGH Boxed Boom Design
- TOUGH Large Diameter Cross Tubes
- TOUGH Robotic Welds
- TOUGH High Strength Chrome Plated Cylinder Rods
- TOUGH Bush Hog Made Buckets
- TOUGH Powder Coat Paint



MODEL	Specifications Based on 1997 ASAE STANDARDS	2447QT
Tractor PTO HP Range		35 - 75
2WD/FWA		2WD/FWA
Maximum Lift Height - Measured at Pivot Pin		117 inches
Maximum Lift Height - Under Level Bucket		108 inches
Maximum Dump Angle		50°
Digging Depth		4.5 inches
Lift Capacity to Maximum Height - At Pivot Pin		2870 lbs
Lift Capacity to Maximum Height - 31.5 inches Forward of Pivot Pin		1985 lbs
Lift Capacity to 59 inch Height - At Pivot Pin		3220 lbs
Lift Capacity to 59 inch Height - 31.5 inches Forward of Pivot Pin		2390 lbs
Breakout Force - At Pivot Pin		3955 lbs
Breakout Force - 31.5 inches- Forward of Pivot Pin		2940 lbs
Rollback Force at Maximum Height - 31.5 inches Forward of Pivot Pin		3155 lbs
Rollback Force at 59 inch Height - 31.5 inches Forward of Pivot Pin		3880 lbs
Rollback Force at Ground Level - 31.5 inches Forward of Pivot Pin		3015 lbs
Raising Time (Ground Level to Full Height)		4 seconds
Lowering Time (Full Height to Ground Level)		3 seconds
Bucket Dumping Time (Full Rollback to Full Dump)		4 seconds
Bucket Rollback Time (Full Dump to Full Rollback)		2.5 seconds
Hydraulics	Two 2.25 inch Bore, 22.81 inch Stroke Double Acting Bucket Cylinders and Two 2.25 inch Bore, 23.19 inch Stroke Double Acting Lift Cylinders	
Specifications Based on Tractor System of	2450 PSI hyd. Pressure & 11 GPM pump capacity	
Bush Hog Quick Attach Buckets	Available in 60, 72 and 80 inch widths	
Bush Hog Quick Attach Heavy Duty Buckets	Available in 60, 72 and 84 inch widths	
Options	Forklift Attachment (42 inch tines), Round Bale Spear, Grapple Fork, Bucket Tine Teeth, Bolt-On Digging Teeth, Side Cutting Edges, Spill Guard Attachment, Hydraulic Self-Leveling, and Grill Guards	
Warranty	1 year limited warranty	
FEATURES	Available in major tractor colors	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>