

Bush Hog® TOUGH

Commercial Series Zero Turn Mowers

BUSH HOG® TOUGH FEATURES

TOUGH Commercial Grade Spindles Greased From The Top

TOUGH 7 Gauge Or 10 Gauge Welded Steel Decks

TOUGH Rolled Front Edge Deck With 3/8 Inch Bar For Extra Protection

TOUGH Fully Floating Deck

TOUGH Durable Anti-Scalp Rollers

TOUGH Long Lasting Electric Clutches



MODELS	Engines and Decks	Width x Length (deflector down)	Dry Weight* (*lbs. with standard seat)
CZ2149	21 HP Kawasaki®/49 inch deck	61 x 82	1,230
CZ2349	23 HP Kohler® Command™ Pro/49 inch deck	61 x 82	1,230
CZ2355	23 HP Kohler® Command™ Pro/55 inch deck	67 x 82	1,270
CZ2555	25 HP Kawasaki® FH72IV/55 inch deck	67 x 82	1,270
CZ2561	25 HP Kawasaki® FH72IV/61 inch deck	73 x 85	1,295

VEHICLE	
Drive System	Dual Hydro-Gear® variable displacement pumps and high efficiency Hydro-Gear® motors. 1.0 gallon reservoir. Cooling fans with each pump.
Brakes	Hydro provides dynamic braking; disc-type parking brake
Electrical System	12 volt, Rated at 230 CCA; electric start
Steering/Motor Control	Dampened twin levers, adjustable fore and aft and vertically
Front Caster Tires	13 x 5.0-6 4 ply tubeless on 49 inch and 55 inch decks 13 x 6.5-6 4 ply tubeless on 61 inch decks
Drive Tires	23 x 8.5-12 4 ply on 49 inch decks 24 x 9.5-12 4 ply on 55 inch decks 24 x 12-12 4 ply on 61 inch decks
Speed	Infinitely variable; 0-10 MPH forward
PTO Engagement	Mag Stop™ Electromagnetic clutch rated at 175 ft lbs
Fuel Capacity	12.5 gallons; twin fuel tanks
Seat Options	High-back, foam padded seat with flip-up arm rests and seat slides High-back full suspension seat with flip-up arm rests and seat slides
Features/Gauges	Tachometer/hour meter, low engine oil pressure warning light, low engine oil pressure audible alert, high engine temperature warning light and audible alert for Kohler® models, molded-in beverage holder, molded-in storage, large vented fuel caps and fuel tank Sitalines
Safety	Operator presence controls (OPC), Certified fold-down ROPS with seatbelt
Controls	Key ignition, throttle, choke, PTO switch, park brake lever

DECKS	
Style	7 gauge steel on 55 inch and 61 inch, 10 gauge steel on 49 inch, fully floating, 51/2 inch deep side discharge
Deck lift	Quick Foot™ height adjustment from the seat
Blades	1/4 inch thick, heat-treated high alloy steel, High Lift SM
Cutting Height Range	1 1/2 to 5 inches, adjustable in 1/4 inch increments
Blade Tip Speed	18,500 FPM
Accessories	Grass Mulching Kits, Stripping Roller, Canopy, Working Lights, Trailer Hitch Kit, Max Vac Grass Collection System and Bar tires.

WARRANTY	
	3 year limited warranty (third year parts only) includes drive train, electromagnetic clutch, deck and cutter spindles. See dealer for complete details. Engine warranty administered through engine manufacturer.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>