

## **Battery-Powered Wireless PresentationPro**

## Model PA150

- Ideal for mobile presenters, classroom and athletic uses
- Lightweight with built-in handle for easy mobility
- 16-channel UHF selectability for wireless mic
- Green, red and amber LEDs on front give visual confirmation of power, signal and reception
- Rechargeable 12V sealed lead-acid battery
- Separate bass, treble controls for quality sound
- Aux in and line inputs connect with LCD projectors, multimedia players, computers and whiteboards
- CE/C-UL approved safe for school, church, government uses
- Available wireless handheld (Q316), hands-free (M316 transmitter) and wired microphones
- Includes volume / mute remote control (not shown)



The battery-powered Wireless PresentationPro is an AC/DC powered, wireless PA system. With 16 selectable UHF channels and an internal battery, it can be used as a single, portable setup for presentations, emergency response situations, police needs, in meetings and for use by rental facilities.

"Project Intercept"

Please contact us immediately if you experience any difficulties with your PA150. Our "Project Intercept" customer service program will quickly repair or replace items under warranty. Simply contact us via phone or email warranty@califone.com

Visit our website at www.califone.com to learn more about the complete line of Califone® audio enhancing and visual technology products including: Wired and Wireless public address systems and lecterns, wireless microphones, headphones & headsets, group listening centers, multimedia players and computer peripheral products.

We are proud of helping teachers enhance student understanding and achievements since 1947, with your satisfaction as our first priority.

The PresentationPro carries a limited six-year warranty and service support available through authorized dealers nationwide. Its warranty covers school use - unlike some other PA products whose warranties would be voided if used in schools.

Distributed by:

## **Specifications**

Rated Power Output: Sensitivity for Rated Output:

Frequency Response: Dispersion Angle: Spėakers:

Crossover: Inputs:

Line Output:

Channels:

AC Power Requirements: Dimensions (HWD): **UHF** Receiver Specifications

Frequency: Oscillation: Modulation: Sensitivity: Frequency Response: Wireless Transmission Range: Dynamic Range:

Battery

Weight: Safety Approvals:

Warranty

15 watts RMS Line:125 mVrms Microphone: 4 mVrms Auxiliary: 250 mVi 60 Hz – 20 kHz ± 3dB 90° H x 120° V 250 mVrms

Woofer: 5-1/4" High efficiency 13mm mylar dome Tweeter:

Tweeter: I3mm myar dome L/C – 6dB/Octave @ 4 kHz Line inputs (2):Hi-Z, RCA (summing L+R) Balanced mic: Hi or lo-Z, with phantom power (+15 volts D.C.) Unbalanced mic: Lo –Z, 1/4"-phone Auxiliary: Hi-Z Mono 1/4"-phone

250mv constant 110 – 125 VAC, 50/60 Hz

6-1/4" x 10" x 8-1/2"

16 Selectable 740 - 801.80mHz Phase Lock Loop, Synthesized FM (Frequency Modulation) 7 microvolts

90 Hz - 17 KHz Approximately 160 ft. 100 dB

12V sealed lead-acid, rechargeable 4 hour run time, 6 hour recharge cycle

10 pounds, shipping weight 14 lbs. C-UL/CE approved safe for use in school, business, government and

church facilities
6 years from date of purchase (PA only, all other parts one year)

Califone® International Inc. 800-722-0500 www.califone.com Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com