

Canon



CORPORATE SOLUTIONS



imageRUNNER®
C6870U / C5870U

meap
POWERED BY

SETTING NEW STANDARDS FOR THE COLOR DIGITAL EXPERIENCE.

The color-enabled imageRUNNER® C6870U/C5870U devices are revolutionary digital multifunction solutions that are fast and versatile, and let you add color to your usual black-and-white work when you need it. Delivering high-speed, black-and-white output at up to 68/58 ppm (letter) respectively, and color output at 16 ppm (letter), they easily can handle the workload of several dedicated devices.

The imageRUNNER C6870U/C5870U devices offer a complete suite of functionality, including Internet-ready capabilities, advanced digital copying and Mail Box features, network printing and Universal Send™ functions, and the ability to distribute information across a dynamic landscape—all with the same industry-leading levels of performance, quality, and reliability you can expect only from Canon.

MAIN UNIT


Type:	Color Digital, Multifunction Imaging System
Imaging System:	Laser Dry Electrostatic Transfer
Developing System (B/W, Color):	Dry Monocomponent/Dual Component Developing System
Image Server Memory:	Standard 1GB RAM + 80GB HDD
First-Copy Time:	5.3 Seconds (B/W) 12.2 Seconds (Color)
Warm-Up Time:	9 Minutes or Less
Copy Speed (B/W, Color):*	68/58, 16 ppm (Letter) 34, 7.8 ppm (Legal) 28, 7.8 ppm (11" x 17") 25, 5.2 ppm (12" x 18"/13" x 19") 42, 7.8 ppm (Letter-R) 68/58, 16 ppm (Statement-R)
Acceptable Originals:	Sheets, Books, 3-Dimensional Items (Up to 4.4 lb.)
Max. Original Size:	11" x 17"
Max. Copy Size:	13" x 19"
Min. Copy Size:	3-15/16" x 5-7/8"
Max. Mail Boxes Supported:	100
Max. Copy Reservation:	5 Jobs
Copy/Scan Resolution:	600 x 600 dpi (256 Gradations) 8 Bit x 3 Colors
Engine Resolution:	600 x 600 dpi
Print Resolution:	2400 dpi x 600 dpi Interpolated
Copy Exposure:	Automatic or Manual (9 Levels)
Original Type:	Text, Photo, Printed Image, Text/Photo/Map
Halftones:	256 Gradations (Continuous-Tone)
Duplexing:	Standard Automatic Trayless Duplexing
Magnification:	25% to 400% (in 1% Increments)
Preset Reduction/Enlargement:	25%, 50%, 64%, 73%, 78%, 121%, 129%, 200%, 400%
Special Features:	Two-Page Separation, Cover/Sheet Insertion, Image Combination, Shift, Booklet, Transparency Interleaving, Job Done Notice, Margin, Different Size Originals, Job Build, Scan Image Check, Frame Erase, Image Creation, Sharpness, Image Adjustment, Area Designation, Form Composition, Page/Copy Set Numbering, Recall, Watermark/ Print Date, Mode Memory

Multiple Copies:	1 to 9,999
Network Scanning Utility:	Color Network ScanGear
Paper Sources Standard:	Dual Front-Loading Trays (1,500 Sheets Each) Dual Front-Loading Cassettes (550 Sheets Each) 100-Sheet Stack Bypass
Optional:	3,500-Sheet Paper Deck (Total: 7,700 Sheets)
Paper Weights:	17 lb. Bond to 110 lb. Index (Trays, Cassettes, Optional Paper Deck) 17 lb. Bond to 140 lb. Index (Manual Bypass Tray)
Dimensions (H x W x D):	46-7/8" x 26-3/4" x 33-1/2" (1191mm x 679mm x 852mm)
Installation Space (W x D):	57-3/4" x 33-1/2" (1468mm x 852mm) (with Stack Bypass Extended)
Weight:	498 lb. (226kg)
Power Requirements:	120V, 60Hz, 16A
Power Consumption:	1.75kW
Plug:	NEMA 5-20R
Drum:	Amorphous Silicon – Estimated Yield: 3,000,000 Impressions
Toner	
Black:	Magnetic Negative Toner Estimated Yield: 40,000 Images (at 6% Coverage)
Colors:	Non-Magnetic Negative Toners Estimated Yield: 9,500 Images (at 5% Coverage)
Color Universal Send (Standard)	
Sending Methods:	E-Mail, I-Fax, Super G3 Fax (Optional), File Server (IPX, FTP, SMB), User Inbox (Includes URL Send)
Address Book Capacity:	Max. 1,800 Destinations
File Formats:	Max. 5 LDAP Servers TIFF, JPEG, PDF, PDF (Compact)** PDF (OCR)**/**
Sending Sizes:	Statement to 11" x 17"
Automatic Document Feeder (Standard)	
Acceptable Originals:	Statement to 11" x 17"
Capacity:	100 Sheets (Letter/20 lb.)
Max. Paper Weights:	13 lb. to 32 lb. Bond (Simplex) 17 lb. to 32 lb. Bond (Duplex)

Original Scanning Speeds:	1-Sided: 50 Sheets/Minute (Letter in B/W and Color); 70 Sheets/Minute @ 300 x 300 dpi (Letter in B/W and Color) [†]
Original Feeding Method:	From First Page (Top of Original)
Power Source:	From Main Unit
Weight:	Approximately 32.4 lb. (14.7kg)

OPTIONAL ACCESSORIES

Finisher-R1/Saddle Finisher-R2	
Number of Trays:	2 Trays
Tray Capacity	
Non-Collate, Collate, and Group Mode:	1,000 Sheets (Letter, Statement, Statement-R, Executive) 500 Sheets (Legal, Letter-R, 11" x 17", 12" x 18", 13" x 19")
Staple Mode:	1,000 Sheets/30 Sets (Letter, Executive) 500 Sheets/30 Sets (Legal, Letter-R, 11" x 17")
Max. Stapling Capacity	
Corner, Double:	50 Sheets (Letter), 30 Sheets (Letter-R, Legal, 11" x 17"; 17 lb. to 20 lb. Bond)
Acceptable Paper Weights:	17 lb. Bond to 140 lb. Index
Saddle-Stitching ^{††}	
Acceptable Paper Sizes:	Letter-R, Legal, 11" x 17"
Tray Capacity:	1 to 5 Sheets/25 Sets 6 to 10 Sheets/15 Sets 11 to 15 Sheets/10 Sets
Max. Stapling Capacity/Set:	15 Sheets
Folding:	V-Fold
Additional Finisher Tray-A1^{†††}	
Capacity:	100 Sheets (Top Finisher Tray 1,000-Sheet Max. Decrease to 500)
Puncher Unit-M1[†]	
Max. Paper Weight:	Up to 140 lb. Index
Paper Sizes:	Letter, Legal, 11" x 17", Executive
Punch Method:	Sequential Processing System (One Sheet at a Time)
Punch Types:	2-Hole/3-Hole (Auto Change) 3-Hole (Letter, 11" x 17") 2-Hole (Legal, Letter-R, Executive)



Punch Waste Tray Capacity: Approximately 3,000 Sheets
 Punch Waste Tray Access: Front
 Power Source: From Finisher-R1 or Saddle Finisher-R2
 Dimensions (H x W x D): 32-3/4" x 4-1/4" x 24-1/4" (833mm x 107mm x 615mm)
 Weight: Approximately 15.9 lb. (7.2kg)

Side Paper Deck-U1

Number of Drawers: 1
 Paper Capacity: 3,500 Sheets (20 lb. Bond)
 Paper Size: Letter
 Paper Weight: 17 lb. Bond to 110 lb. Index
 Power Source: From Main Unit
 Dimensions (H x W x D): 22-3/8" x 12-7/8" x 23" (569.5mm x 326mm x 583mm)
 Weight: Approximately 101 lb. (46kg)

Color UFR II/PCL/PS Printer Kit-L1

Processor: Canon Custom Processor—Shared
 RAM: 1GB (Std./Max.)—Shared
 Hard Disk: 80GB—Shared
 PDL Support: PCL 5c, PostScript® 3™ Emulation, UFR II
 Interface Connections: 10/100Base-T (RJ-45), USB 2.0
 Network OS: Windows® 98/Me/2000/XP Windows NT® 4.0/Server 2003 Solaris™ 1.1x, 2.5x, or later, Mac OS 9.1 or later (PPD), Mac OS X (10.1.5 or later), Novell NetWare v.3.2, 4.1, 4.11, 4.2, 5, 5.1, 6, 6.5 (IPX/SPX™)

Print Service NetWare: NDS Pserver, Bindery Pserver, Nprinter, Rprinter
 TCP/IP: LPD/LPR, RAW (Port 9100), IPP 1.1, SMB, FTP
 AppleTalk: PAP (PostScript)
 Printer Drivers UFR II: Windows 2000/XP Windows Server 2003 Citrix MetaFrame Macintosh OS X (10.1.5 or later)
 PCL 5c: Windows 98/Me/2000/XP Windows NT 4.0/Server 2003 Citrix MetaFrame

PS 3 Emulation: Windows 98/Me/2000/XP Windows NT 4.0/Server 2003 Citrix MetaFrame Macintosh OS X (10.2 or later)

imagePASS-G1

Type: External Piggy-Back Controller
 Processor: Intel® Celeron® M 1.2GHz
 RAM: 256MB (Std.), 512MB (Max.)
 Hard Disk: 80GB
 PDL Support: Adobe PostScript 3, PCL 5c
 Interface Connections: 10/100/1000Base-T (RJ-45)
 Internal Fonts PS: 136 Fonts (117 Adobe® Type and 19 TrueType®)
 PCL 5c: 113 Roman
 Protocol Stacks: Ethernet 802.2, 802.3, Ethernet II, Ethernet SNAP
 IPX/SPX: Ethernet II
 AppleTalk: Ethernet SNAP
 Network OS: Novell NetWare v.5.x or later 5.1/6.0 (IPX/SPX) Windows 98/Me/2000/XP/ Server 2003 (TCP/IP), Solaris 2.5.1 or later, MacOS 9.2 or later, Mac OS X 10.2.4 or later

Dimensions (H x W x D): 13" x 11-1/4" x 3-1/2" (332mm x 287mm x 90mm)
 Weight: 10.9 lb. (5kg)
 Power Requirements: 100 to 240V, 50/60Hz, 2A
 Power Consumption: 35W

Additional Functions: Color Network ScanGear
 Fiery® Tools: WebTools™, Command WorkStation®, Fiery Downloader™, Fiery Remote Scan, ColorWise® Pro Tools (Calibrator, Color Editor, Profile Manager, Color Setup, Spot-On®)
 Optional: EFI Densitometer ED-100, Impose, Secure Erase

Super G3 Fax Board-U1

Applicable Line: Public Switched Telephone Network (PSTN)
 Connection Lines: One
 Sending/Original Size: Statement to 11" x 17" (from Document Feed)
 Recording/Printing Size: Statement to 11" x 17"

Other Optional Accessories and Utilities

- Accessibility Handle-A1
- Barcode Printing Kit-A1
- Braille Label Kit-A1
- Card Reader-C1
- Card Reader Attachment-C1
- Card Sets
- Cassette-AA1
- Copy Tray-K1
- Document Tray-K1
- eCopy Suite
- imageRUNNER Security Kit-A2**
- imageWARE™ Suite
- Key Switch Unit-A2
- NetSpot Suite
- Stamp Unit-A1
- PDF High Compression Kit-A1
- Remote Operator's Software Kit-A1
- Security Expansion Board-E1
- Universal Send PDF Enhancement Kit-C1**
- Voice Guidance Kit-A2
- Web Access Software Kit-D1***

* During printing, the engine may occasionally pause for internal adjustment.

** Requires PDF High Compression Kit-A1.

*** Requires Universal Send PDF Enhancement Kit-C1.

† 70 ipm @ 300 x 300 dpi available only for Send and Scan modes.

** Available on Saddle Finisher-R2 only.

*** Use of Additional Finisher Tray-A1 will alter top tray capacity when outputting Letter/Statement-R/Executive documents.

▲ Puncher Unit-M1 can only be installed with either the Finisher-R1 or Saddle Finisher-R2.

▲▲ Requires Security Expansion Board-E1.

▲▲▲ Requires Color UFR II/PCL/PS Printer Kit-L1 if printing PDF files.

Canon

*image*ANYWARE

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Windows and Windows NT are registered trademarks of Microsoft Corporation in the United States and/or other countries. Adobe, TrueType, and PostScript are registered trademarks of Adobe Systems Incorporated in the United States and/or other countries. Macintosh is a registered trademark of Apple Computer, Inc. Intel and Celeron are registered trademarks of Intel Corporation. eCopy ShareScan is a trademark of eCopy, Inc. Novell and NetWare are registered trademarks of Novell, Inc. in the United States and other countries. IPX/SPX is a trademark of Novell, Inc. Solaris is a trademark of Sun Microsystems, Inc. in the United States and other countries. EFI, Colorwise, Spot-On, Fiery, and Command WorkStation are registered trademarks of Electronics for Imaging, Inc. in the U.S. Patent and Trademark Office and certain other foreign jurisdictions. WebTools is a trademark of Electronics for Imaging Inc. CANON and IMAGERUNNER are registered trademarks, and UNIVERSAL SEND and the GENUINE logo are trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. REMOTE UI is a trademark of Canon U.S.A., Inc. IMAGEWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All other terms and product names may be trademarks or registered trademarks of their respective owners and are hereby acknowledged. Specifications subject to change without notice.
©2006 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Plaza
Lake Success, NY 11042



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>