DESCRIPTION

A return to simplicity, elegance and minimalism...Slender lines of unbroken light set in an architectural enviroment are what of essence of Straight and Narrow is all about. Accommodates most architectural lighting design applications.

- Features:
- Straight and Narrow embodies Neo-Ray's critical attention to architectural detail as well as lighting performance
- Continous and unbroken light
- Extruded aluminum housing offers precise in-line appearance
- Runs are provided to nearest foot

SPECIFICATION FEATURES

Construction

Extruded aluminum housing. Nominal 3', 4', 6' or 8' illuminated sections.

Shielding

Trimless, snap-in white high transmission acrylic diffuser. Snap-in high performance semi-specular or white parabolic louver.

Side mounted.



Electrical

120, 277, 347 or universal voltage, electronic ballast. Fixtures and electrical components certified to UL and CUL standards.

Mounting

Fixture mounts directly to

standard electrical box (not

supplied by Neo-Ray). Blocking


existing structure over a

provided by others.

Finish

Durable, low gloss, white powder coated acrylic. Optional custom finish.

Side mounted.



performance louver (S90)

Straight & Narrow 23DIW


23DW 23ADIW

T8, T5 or T5HO

WALL DIRECT-INDIRECT DIRECT

ORDERING INFORMATION

SAMPLE NUMBER: S23DIW/1X1T5/4/1EB-SI-EM-GLR-S90



Not all option combinations available, please consult your COOPER Lighting rep for additional information

performance louver (S90)





Catalog #	Туре
Project	
Comments	
Prepared by	Date


PHOTOMETRICS

23DW 2T5 lamp with White Louver (S90W)	Zonal Lumen Summary					Candela				
		Zone	Lumens	%Lamp	%Fixture		Angle	Along II	45°	Across
	Efficiency 68.1%	0-30	1546	26.7	39.1		0	2114	2114	2114
\ ! }	Test#13431	0-40	2358	40.6	59.7		5	2085	2087	2090
0 45 90		0-60	3495	60.3	88.4		15	1921	1971	2014
		0-90	3952	68.1	100.0		25	1623	1701	1774
	0	0-180	3952	68.1	100.0		35	1242	1280	1365
	45	Total Lur	Total Luminaire Efficiency = 68.1%					868	916	951
						55	406	506	516	
	50						65	249	263	311
							75	132	135	152
						85	36	36	39	
						90	0	0	0	
OUNTING INFOR	RMATION			ROWS						
47'	+ 71°									1/2'
	95"			(48	" 3FT INT); (72" 6FT INT) " 4FT INT); (96" 8FT INT) dd 0.188" for endcap	(36° 3FT INT); (7 (48° 4FT INT); (9		(48" 4FT	INT); (72" 6FT IN INT); (96" 8FT IN).188" for endcap	

- OVERALL LENGTH OF RUN (add 3/8' for end caps) -

mms smann

<u>us suummunu</u>



6-3/8" 8FT IND

FEATURES AND OPTIONS

OPTICAL OPTIONS







Regressed White Acrylic Diffuser



23 Direct/Indirect (Top View)



Staggered Lamps (DP T5 and T5HO only)

High Performance Louver

SERIES COMPANION PRODUCTS (Reference other spec sheets if necessary)





23DS

Surface





23DIP 23DP Direct/Indirect Pendant Direct Pendant

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com