

SETTING THE PREMIUM STANDARD FOR SUB-COMPACT BACKHOES.

The Sc2450 is the sub-compact tractor that performs in big ways, from performance to comfort. Innovative Shift-On-The-Go® technology lets you shift from high to low without stopping. Plus, its specially designed frame, curved boom attachments, powerful hydraulics and efficient engine deliver an all-around superior performance. And when you get an open, comfortable operator station with swivel seat and backhoe boom float control, you also get an experience way beyond the expected.

INNOVATIVE FEATURES FOR AN INCREDIBLE EXPERIENCE IS THE

CUB CADET YANMAR ADVANTAGE.



CURVED BOOM LOADER AND BACKHOE

Designed to get the most out of your tractor, the innovative backhoe with float control will take on any challenge. Plus, the curved boom loader offers the highest lift capacity in its class with greater visibility from behind the wheel. When you can dig deeper with more precision, you can effortlessly tackle the toughest jobs — that's a premium experience.



24 HP* DIRECT-INJECTION DIESEL ENGINE

This high-performance, 3-cylinder, liquid-cooled diesel engine burns cleaner and more efficiently. The advanced combustion chamber design allows for better fuel atomization and a longer stroke — creating better torque reserve so that you'll have power when you need it.

.....



DUAL HYDRAULIC PUMPS

Separate hydraulic pumps deliver a more efficient flow of hydraulic fluid for a smooth hydraulic response without compromising horsepower. Whether you're using the curved boom loader or accelerating through rough terrain with power steering, you'll have the power you need to handle demanding jobs with ease.

LOCATE A DEALER AT CUBCADETYANMAR.COM

YOUR INDEPENDENT DEALER CAN ANSWER ALL YOUR QUESTIONS ABOUT THE MANY BENEFITS OF OWNING A CUB CADET YANMAR.

Sc2450

MULTI-PURPOSE SUB-COMPACT TRACTOR

FEATURES

SELECTABLE 4WD WITH DIFFERENTIAL LOCK

SHIFT-ON-THE-GO®

HYDRAULIC POWER STEERING

BACKHOE BOOM FLOAT CONTROL

POP-UP SWIVEL SEAT

SHORT-STROKE BACKHOE CONTROLS

CRUISE CONTROL

ELECTRO-HYDRAULIC

REVERSE-OVERRIDE SWITCH FOR SAFE PTO OPERATION

ONE-PIECE HOOD FOR EASE OF MAINTENANCE

12-VOLT DC OUTLET

REVERSE-MOUNTED ENGINE

WIDE OPERATOR'S STATION

3-POINT HITCH POSITION CONTROL**

5-YEAR LIMITED POWERTRAIN WARRANTY[†]

*See Cub Cadet Yanmar Independent Dealer for warranty information

cubcadetyanmar.com



1,813 PSI

Sc2450 Specifications

POWERTRAIN	
Gross HP	24 HP* diesel
PTO HP (Hyd)	16.5 at 3,200 RPM
Rated RPM	3,200 RPM
Number of cylinders	3
Bore and stroke	72 x 74 mm
Total displacement	55.1 cu. in.
Ignition type	Indirect injection
Lubrication	Full pressure
Oil filter	Spin-on/full flow
Cooling system	Liquid cooled
Air cleaner	4" single dry
Preheat system	Glow plug
Alternator	40 amp.
Exhaust	Right side pointing down
CAPACITIES	
Fuel tank	5.8 gal.
Cooling system	3.4 qt.
Engine oil	2.5 qt.
Transmission case	2.0 gal.
DRIVETRAIN	
Transmission type	Hydrostatic
Number of ranges	2 Shift-On-The-Go®
4WD operations	2WD & 4WD selectable
Cruise control	Selectable
Rear differential lock	Foot pedal operation
PTO type	Independent
Mid PTO/RPM (standard)	2,100/3,338
Rear PTO/RPM (standard)	540/3,111
Brake	Wet disc
MAXIMUM TRAVELING SPEED	
Forward low	6.0 mph
Forward high	9.3 mph
Reverse low	3.6 mph
Reverse high	5.6 mph
	2.2
HYDRAULICS Type	Open center
Type Pump	Gear/Trochoid
Steering/SCV/backhoe/3-pt hitch	3.5 GPM at 3,200 RPM
Transmission/hydraulic PTO	3.4 GPM at 3,200 RPM
Maximum pump capacity	6.9 GPM at 3,200 RPM
3-point hitch**	Limited Category 1
3-point lift capacity at 24" behind	661 lbs.
Hydraulic control system	Position control
•	r datton control
DIMENSIONS	FF 411
Wheelbase	55.1"
Width	44.5"
Overall length w/ loader and backhoe	172.5"
Ground clearance	7.5" (w/R4)
Weight w/ROPS & fluids	2,525 lbs.
TIRE SIZE	10" 0 5" 10"
Front industrial/turf	18" x 8.5" – 10"
Rear industrial/turf	26" x 12.0" - 12"

Sc2450 Attachment Specifications

CL100 CURVED BOOM LOADER		
Maximum lift height at pivot point	71"	
Dump clearance	54"	
Reach at maximum height	27"	
Maximum dump angle	45°	
Reach w/bucket on ground	40"	
Maximum rollback angle	25°	
Digging depth	4"	
Overall height in carry position	37"	
Length of attachment (bucket bottom)	19.25"	
Maximum lift height under bucket	66"	
Bucket width/weight	48"/125 lbs.	
Bucket capacity	5 cu. ft.	
Lift capacity 500 mm forward of the pivot pins, maximum height	550 lbs.	
Lift capacity at pivot pins, maximum height	700 lbs.	
Breakout force at bucket pins	1,350 lbs.	
Breakout force at 500 mm forward of the pivot pins	1050 lbs.	
Raising time to full height w/o load	3.5 sec.	
Lowering time w/o load (power down)	2.5 sec.	
Attachment rollback time	2 sec.	
Attachment dumping time	1.5 sec.	
Rated flow	3.5 GPM	

CURVED BOOM BACKHOE

Relief valve

CONVED DOOM DACKING	
Maximum digging depth	76.5"
Digging depth (2' flat bottom)	74.5"
Swing arc	150°
Loading height (bucket at 60°)	60"
Reach from swing pivot	104"
Transport height	66"
Bucket rotation	180°
Loading reach	33"
Transport overhang	37"
Undercut	17"
Stabilizer spread (down)	74"
Bucket cylinder digging force	2,036 lbs.
Dipperstick cylinder digging force	1,187 lbs.
Weight (less bucket)	620 lbs.
Operating pressure	1,857 PSI
Ramp angle (w/industrial tires)	20.5°
Street pads	Optional
Bucket options	8", 12"

RESIDENTIAL/COMMERCIAL WARRANTY

Attachments	1-year limited warranty

RESIDENTIAL/COMMERCIAL **WARRANTY**[†]

Tractor	2-year or 2,000-hour limited warranty
Engine/drivetrain	5-year or 2,500-hour limited warranty

^{*}as rated by engine manufacturer

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the substitute for the sarety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications. Please visit cubcadetyanmar.com for more information.

773-04214 Printed in U.S.A. 12/10 © 2011 Cub Cadet Yanmar Download from Www.Somanuals.com. All Manuals Search And Download.

^{**3-}point hitch is optional

† See your local Cub Cadet Yanmar Independent Dealer for warranty details.

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com