

TANK™

COMMERCIAL ZERO-TURN RIDERS

- TANK™ 48
- TANK™ 60
- TANK™ M48
- TANK™ M54
- TANK™ M60
- TANK™ M72

FEATURES

48", 54", 60" OR 72"
FABRICATED DECK SIZE

ENGINE OPTIONS
UP TO 37 HP*

PIVOTING FRONT AXLE
FOLLOWS CONTOURS
OF THE GROUND

CUTS UP TO 6.5
ACRES PER HOUR

FOLDABLE ROPS

FOOT PEDAL DECK LIFT

GROUND SPEEDS
UP TO 12 MPH

PATENTED SMARTJET™
DECK WASH SYSTEM

2-YEAR AND 3-YEAR
LIMITED COMMERCIAL
WARRANTY†

COMMERCIAL



WE MEAN BUSINESS.™



YOUR CLIENTS WON'T JUST BE SATISFIED, THEY'LL BE SPEECHLESS.


If you're looking for a top-of-the-line commercial mower, you've found it. The TANK™ is designed to do it all. The Select Cut System™ deck can cut all types of grass in all types of conditions. Plus, it produces a high-quality cut at faster ground speeds. It easily handles attachments without sacrificing productivity, and has features that keep the operator comfortable in rough conditions. And with true commercial-grade toughness, it's no wonder that the TANK™ is the mower that all other mowers aspire to be.

SEE HOW THESE FEATURES HELP YOU GET THE JOB DONE RIGHT AT CUBCADETCOMMERCIAL.COM.



PIVOTING FRONT AXLE

Follows the contours of the ground for superior cutting, providing a smoother, more uniform look and versatility for different terrain.



SELECT CUT SYSTEM™ DECK

The innovative sloped-nose deck features a configurable inner baffle, offset and adjustable leading edges, ball wheels and the SmartJet™ deck washing system.



FULL SUSPENSION SEAT

This premium seat allows the operator to customize suspension settings for weight and personal preference. It also features foldable armrests and tilt capability for lower back support.

WHAT THAT MEANS TO YOU

Professional results every time and everywhere you mow.

You get premium cuts even in the toughest grass-cutting conditions from a deck that's easy to service.

Maximum comfort and support reduce fatigue, and make it easier and more enjoyable to work a long day.

* as rated by engine manufacturer † See specifications for warranty information

YOUR INDEPENDENT DEALER CAN ANSWER ALL YOUR QUESTIONS ABOUT THE MANY BENEFITS OF OWNING A CUB CADET.

LOCATE A DEALER AT
CUBCADETCOMMERCIAL.COM

Download from www.somanuals.com. All Manuals Search And Download.

TANK™ COMMERCIAL ZERO-TURN RIDERS

| ENGINE | TANK™ 48 | TANK™ 60 | TANK™ M48-KW | TANK™ M54-KH |
|--|--|---|---|---|
| Engine type | 23 HP* Kohler® V-Twin OHV | 25 HP* Kohler® V-Twin OHV | 23 HP* Kawasaki® V-Twin OHV | 27 HP* Kohler® Command® V-Twin OHV |
| Engine displacement/orientation | 674cc/vertical | 725cc/vertical | 675cc/vertical | 725cc/vertical |
| Engine fuel | Gas | | | |
| Ignition | Transistor controlled | | | |
| Lubrication/filter | Full pressure w/spin-on oil filter | | | |
| Cooling system | Air | | | |
| Air cleaner | Heavy-duty remote-mounted replacement dual element | | | |
| Alternator | 12V – 15 amp. regulated | | | |
| Fuel capacity | Twin 5-gallon tanks | Twin 5-gallon tanks | Twin 7-gallon tanks | Twin 7-gallon tanks |
| DRIVE SYSTEM | | | | |
| Drive system | Kanzaki DUP-10 pumps & White® wheel motors | Kanzaki DUP-10 pumps & Parker wheel motors | Dual Hydro-Gear™ PK-12 pumps & Parker wheel motors | Dual Hydro-Gear™ PK-12 pumps & Parker wheel motors |
| Ground speed | Fwd: 10 mph/Rev: 5 mph | Fwd: 10 mph/Rev: 5 mph | Fwd: 12 mph/Rev: 5 mph | Fwd: 12 mph/Rev: 5 mph |
| Hydraulic fluid | Rimula® – 15W40 | | | |
| Hydro fluid capacity | 2.5 qt. | 2.5 qt. | 3 qt. | 3 qt. |
| Hydraulic oil filter | Standard | | | |
| Controls | 3-way adjustable lap bars | | | |
| Lap bar dampers | Standard | | | |
| Return to neutral | Standard | | | |
| Braking/parking brake | Dynamic/Knott drum | | | |
| STEERING | | | | |
| Caster wheel pivot bearings | Sintered self-lubricating | Sintered self-lubricating | Timken® roller, greasable | Timken® roller, greasable |
| Front axle | Pivoting/fixed with lockout pins | | | |
| CHASSIS | | | | |
| Frame | Fully welded steel 2" square tubing | | | |
| TIRES | | | | |
| Front tire size | 13" x 5" – 6" (smooth) | 13" x 5" – 6" (smooth) | 13" x 6.5" – 6" (smooth) | 13" x 6.5" – 6" (smooth) |
| Rear tire size | 23" x 9.5" – 12" (turf) | 23" x 9.5" – 12" (turf) | 23" x 9.5" – 12" (turf) | 24" x 12" – 12" (turf) |
| DIMENSIONS | | | | |
| Length x width x height | 74" x 59" x 40.5" | 78" x 71" x 40.5" | 74.5" x 59" x 72" | 78" x 65" x 72" |
| Wheelbase | 44.5" | 48.5" | 44.5" | 50.5" |
| Front track width | 40" | 44" | 40.25" | 45.5" |
| Rear track width | 45.5" | 46.5" | 45.5" | 52" |
| Weight (approx.) | 995 lbs. | 1,035 lbs. | 1,080 lbs. | 1,100 lbs. |
| MOWING DECK | | | | |
| Deck size/type | 48" sloped-nose design | 60" sloped-nose design | 48" Select Cut System™ | 54" Select Cut System™ |
| Deck style/system | Floating | | | |
| Deck blades | 3-blade | | | |
| Deck construction | 10-gauge fabricated with 7-gauge reinforcements | 10-gauge fabricated with 7-gauge reinforcements | 10-gauge fabricated with 7- and 10-gauge reinforcements | 10-gauge fabricated with 7- and 10-gauge reinforcements |
| Deck wash | Patented SmartJet™ high-pressure deck washing system | | | |
| Deck lift | Foot lever, spring assisted | Foot lever, spring assisted | Dual pedal, spring assisted | Dual pedal, spring assisted |
| Deck height adjustment | 1" – 5" (in .25" increments) | | | |
| Blade spindle construction | Cast-aluminum | | | |
| Deck PTO | Electronic fingertip engagement | | | |
| Front anti-scalping wheels/nose roller | 2, greasable/1 nose roller | 2, greasable/1 nose roller | 4 standard, greasable | 4 standard, greasable |
| Rear anti-scalping rollers/striper | Full width, adjustable | | | |
| ADDITIONAL SPECIFICATIONS | | | | |
| ROPS | Standard, foldable | | | |
| Monitor/hour meter | Standard, electronic | | | |
| Seat type | High-back, lever adjustable suspension | | High-back suspension seat, foldable, fully adjustable with armrests | |
| Cup holder | Standard | | | |
| Storage pouch | Standard | | | |
| Rear bumper and hitch | Heavy-duty rear bumper w/bolt-on hitch standard | | | |
| WARRANTY* | | | | |
| | 2-year limited commercial | 2-year limited commercial | 3-year limited commercial | 3-year limited commercial |

| ENGINE | TANK™ M60-KH | TANK™ M60-KW | TANK™ M72-KW |
|--|---|---|--|
| Engine type | 27 HP* Kohler® Command® V-Twin OHV | 31 HP* Kawasaki® V-Twin OHV | 37 HP* Kawasaki® V-Twin OHV |
| Engine displacement/orientation | 725cc/vertical | 852cc/vertical | 999cc/vertical |
| Engine fuel | Gas | | |
| Ignition | Transistor controlled | | |
| Lubrication/filter | Full pressure w/spin-on oil filter | | |
| Cooling system | Air | | |
| Air cleaner | Heavy-duty remote-mounted replacement dual element | | |
| Alternator | 12V - 15 amp. regulated | | |
| Fuel capacity | Twin 7-gallon tanks | | |
| DRIVE SYSTEM | | | |
| Drive system | Dual Hydro-Gear™ PK-12 pumps & Parker wheel motors | | |
| Ground speed | Fwd: 12 mph/Rev: 5 mph | | |
| Hydraulic fluid with remote cooling system | Rimula® - 15W40 | | |
| Hydro fluid capacity | 3 qt. | | |
| Hydraulic oil filter | Standard | | |
| Controls | 3-way adjustable lap bars | | |
| Lap bar dampers | Standard | | |
| Return to neutral | Standard | | |
| Braking/parking brake | Dynamic/Knott drum | | |
| STEERING | | | |
| Caster wheel pivot bearings | Timken® roller, greasable | | |
| Front axle | Pivoting/fixed with lockout pins | | |
| CHASSIS | | | |
| Frame | Fully welded steel 2" square tubing | | |
| TIRES | | | |
| Front tire size | 13" x 6.5" - 6" (smooth) | | |
| Rear tire size | 24" x 12" - 12" (turf) | | |
| DIMENSIONS | | | |
| Length x width x height | 78" x 71" x 72" | 78" x 71" x 72" | 81" x 83" x 72" |
| Wheelbase | 50.5" | 50.5" | 53.5" |
| Front track width | 45.5" | 45.5" | 51" |
| Rear track width | 58" | | |
| Weight (approx.) | 1,150 lbs. | 1,150 lbs. | 1,380 lbs. |
| MOWING DECK | | | |
| Deck size/type | 60" Select Cut System™ | 60" Select Cut System™ | 72" Select Cut System™ |
| Deck style/system | Floating | | |
| Deck blades | 3-blade | | |
| Deck construction | 10-gauge fabricated with 7- and 10-gauge reinforcements | 10-gauge fabricated with 7- and 10-gauge reinforcements | 9-gauge fabricated with 7- and 10-gauge reinforcements |
| Deck wash | Patented SmartJet™ high-pressure deck washing system | | |
| Deck lift | Dual pedal, spring assisted | | |
| Deck height adjustment | 1" - 5" (in .25" increments) | | |
| Blade spindle construction | Cast-aluminum | | |
| Deck PTO | Electronic fingertip engagement | | |
| Front anti-scalping wheels | 4 standard, greasable | | |
| Rear anti-scalping rollers/striper | Full width, adjustable | Full width, adjustable | Full width, adjustable/2 rear corner rollers |
| ADDITIONAL SPECIFICATIONS | | | |
| ROPS | Standard, foldable | | |
| Monitor/hour meter | Standard, electronic | | |
| Seat type | High-back suspension seat, foldable, fully adjustable with armrests | | |
| Cup holder | Standard | | |
| Storage pouch | Standard | | |
| Rear bumper and hitch | Heavy-duty rear bumper w/bolt-on hitch standard | | |
| WARRANTY* | | | |
| 3-year limited commercial | | | |



ATTACHMENTS

Depending on the time of year or your geographic location, being productive can be a matter of having the right accessories. So whether it's challenging terrain, needing to work past dusk, collecting leaves or even plowing snow, Cub Cadet Commercial accessories make your job easier — and a lot more enjoyable.



LIGHT KIT
Easy-to-install kit provides increased visibility and safety for early or late days.



MULCHING KIT
Mulching baffles install easily to control airflow and reliably re-cut clippings for superior mulching.



12-VOLT OUTLET
Adding electrical power to your TANK™ is simple and easy.



ULTRA-TRACTION TIRES
Deliver improved traction on hills, or in sandy or snowy conditions.



72" BLADE
The steel blade attaches for light dozer work and snow plowing, with skid shoes for height adjustment.



TRIPLE BAGGER
Large, 10-bushel, triple-bag grass collection system for a professional, well-groomed look.



SPREADER
Attaches to either front or rear of the TANK™ to spread salt, seed or fertilizer.



POWER ASSIST DUMP HOPPER
Easily transports and unloads grass clippings or leaves.



ELECTRIC LIFT CYLINDER
Useful all year long. It raises the deck or snow blade easily.

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

Commercial products are intended for professional use.

773-03951 Printed in U.S.A. 12/09 © 2010 Cub Cadet

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>