

Model #: PR1000LCDRTXL2Ua

UPC: 649532010066 **MSRP**: \$579.95





The Smart App Sinewave LCD UPS Series provides an advanced level of power protection to support mission-critical servers, telecom equipment, VOIP and internetworking hardware.

The PR1000LCDRTXL2Ua has both a Pure Sinewave waveform and Full Automatic Voltage Regulation (AVR) technology, which delivers a consistent and clean AC signal that protects connected equipment and prevents costly business interruptions. The multifunction LCD readout provides ready access to power/battery condition vitals, such as: Runtime, Load, Temperature, and much more. The unit also features a battery expansion interface for an additional battery pack in order to increase back-up time.

It includes eight (8) battery and surge protected NEMA 5-15R output receptacles, including four (4) that are designed to serve as fail-safe options for protecting critical loads. It also comes with four maintenance-free, user-replaceable 12V/9Ah batteries. Bundled PowerPanel® Business Edition Management Software monitors UPS status and can provide unattended shutdown of two serially connected servers. The patented GreenPower UPS™ advanced circuitry reduces UPS energy costs by up to 75% compared to competitive models.

An optional SNMP / HTTP Remote Management adapter (RMCARD201) supports remote management and control of the PR1000LCDRTXL2Ua through a standard web browser. The unit's unique convertible design allows for use in either a Tower (T) or Rackmount (RM) form factor.

Backed by US-based Technical Support, an industry-leading 3-Year Warranty and a Connected Equipment Guarantee of \$400,000.

- Pure Sinewave This UPS generates pure sinewave energy that is identical to, or cleaner than the utility company's power grid. Benefits include: low total harmonic distortion, minimal electrical noise, and optimal line clarity.
- RM/T Configuration The PR series can be configured in either a Tower or a Rackmount (2U) form.
- Full AVR Boost/Buck Boost/Buck topology will both increase low voltages and decrease high voltages, without switching to battery-mode. This conserves battery life, and delivers a more stable signal to your connected equipment.
- Energy-Saving Technology The patented GreenPower UPS™ advanced circuitry reduces UPS energy costs by up to 75% compared to competitive models.
- Critical Load Outlets Prioritize the uptime of mission-critical loads during a power failure with critical load outlets that
 ensure power to selected systems during an extended blackout, preserving battery uptime for more critical equipment.
- EMI/RFI Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or "humming" that occurs over telephone lines or stereo electronics.
- PowerPanel Business Edition Software In the event of a power outage, PowerPanel will safely save and close your
 open files and shut your computer down in an orderly, intelligent manner. The software allows users to view detailed
 information about their electrical power and the vitals of the UPS. It includes configurable system notifications,
 automatic self tests, adjustable high/low voltage warnings, event/data logging, and scheduled shutdowns.
- Multifunction LCD readout The multifunction LCD readout provides ready access to power/battery condition vitals, such as: Runtime, Load, Temperature, and much more.
- Audible Alarms Audible tones identify when the unit is running off battery power, unit overloads, and low battery.
- Resettable Circuit Breaker Convenient unit reset switch in case of an overload.
- 3-year Warranty CyberPower will replace damaged units if within 3 years of purchase date. We stand behind our
 products and guarantee quality. CyberPower also offers a #1 rated technical support team that will assist you with
 product, installation, or warranty concerns --- Free of Charge!
- ISO & Safety Certifications All CyberPower manufacturing facilities are ISO-9001 Quality Tested. Our products are also certified by the FCC, cUL, and UL.
- Windows compatibility Our power management software has been fully tested and is compatible with Windows 2000, 2003, XP, and Vista x32 & x64.



Technical Specifications

General	
Model #	PR1000LCDRTXL2Ua
UPS Topology	Line-Interactive
Energy Saving	Yes - Green-UPS Energy Saving Technology
Input	
Voltage	80 - 150V
Frequency	50/60Hz +- 3Hz
Plug Type	NEMA 5-15P
Cord Length	10 ft
Output	
Output VA	1000
Watts	700
	Yes
Automatic Voltage Regulation	Sine Wave
On Battery Waveform Outlets - Total	
	8 8 V NEMA 5 45D
Outlets - Battery & Surge	8 x NEMA 5-15R None
Outlets - Surge-Only Transfer Time	4 ms
Transier Time	41115
Battery	
Runtime at Full-Load	18 Minutes
Runtime at Half-Load	39 Minutes
Battery Specification	4 x 12V/9Ah
Surge Protection and Filtering	
Surge Suppression	2060 Joules
Phone / Ethernet RJ11 / RJ45	1 x RJ11/45 Combo (One-in/One-out)
Coax Protection RG6	1 x RG-6
Management & Communications	
Indicators	Multifunction LCD Readout
USB Port	1 x HID Compliant
Serial Port	2 x DB9
Software	PowerPanel Business Edition
SNMP / HTTP Remote Monitoring	Yes [With optional RMCARD201]
Dhysical	
Physical	47.05" × 2.5" × 4.0"
Dimensions (WxHxD)	17.25" x 3.5" x 19"
Weight	62 lbs.
Warranty	
Product Warranty	3-year warranty. Free Tech Support.
Connected Equipment Guarantee	Lifetime
CEG Amount	\$400,000
OLO / MITOGRA	ψ 100,000



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com