

Model #: OP650

UPC: 649532706556 MSRP: \$119.99



The Smart App AVR Series are designed to protect office computers, corporate and departmental servers, computer workstations, as well as any connected peripherals.

Full Automatic Voltage Regulation (AVR) protection with both Boost and Buck ensures that your sensitive electronic equipment receives only clean, consistent, regulated power, without switching to battery-mode*. The Smart App AVR Series are fully manageable with the addition of an SNMP/HTTP adapter, and have microprocessor-based, fully digital controlled circuitry.

PowerPanel Plus [™] Smart Power Management software automatically saves and closes open files and shutdowns the PC in an intelligent and orderly manner. It also includes EMI/RFI noise filters, and comes with maintenance-free batteries which are user-replaceable.

The CyberPower OP650 carries a 3-year warranty, coupled with our professional Technical Support and a lifetime Connected Equipment Guarantee of \$125,000.

- Microprocessor-based Digital Control Digital routing is maintained through a network of integrated circuitry and discrete values used for internal system processing, which significantly increases efficiency and responsiveness.
- Full AVR Boost/Buck Boost/Buck topology will both increase low voltages and decrease high voltages, without switching to battery-mode. This conserves battery life, and delivers a more stable signal to your connected equipment.
- EMI/RFI Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is
 used to prevent line noise or "humming" that occurs over telephone lines or stereo electronics.
- PowerPanel Plus [™] Smart Power Management Software In the event of a power outage, PowerPanel Plus will safely save and close your open files and shut your computer down in an orderly, intelligent manner. The software allows users to view detailed information about their electrical power and the vitals of the UPS. It includes configurable system notifications, automatic self tests, adjustable high/low voltage warnings, event/data logging, and scheduled shutdowns.
- Metal Housing Rigid metal construction allows for placement in areas with a demanding environment.
- LED Indicators LED status lights indicate Power-On, Wiring faults, AVR Boost/Buck, and Battery-On.
- Audible Alarms Audible tones identify when the unit is running off battery power, unit overloads, and low battery.
- Resettable Circuit Breaker Convenient unit reset switch in case of an overload.
- 3-year Warranty CyberPower will replace damaged units if within 3 years of purchase date. We stand behind our
 products and guarantee quality. CyberPower also offers a #1 rated technical support team that will assist you with
 product, installation, or warranty concerns --- Free of Charge!
- ISO & Safety Certifications All CyberPower manufacturing facilities are ISO-9001 Quality Tested. Our products are also certified by the FCC, cUL, and UL.



Technical Specifications

| General | |
|--------------------------------|-------------------------------------|
| Model # | OP650 |
| UPS Topology | Line-Interactive |
| | |
| Input | |
| Voltage | 85 - 150V |
| Frequency | 57 - 63Hz |
| Plug Type | NEMA 5-15P |
| Cord Length | 6 ft |
| | |
| Output | |
| VA | 650 |
| Watts | 350 |
| Automatic Voltage Regulation | Yes |
| On Battery Waveform | Simulated Sine Wave |
| Outlets - Total | 6 |
| Outlets - Battery & Surge | 3 x NEMA 5-15R |
| Outlets - Surge-Only | 3 x NEMA 5-15R |
| Transfer Time | 4 ms |
| | |
| Battery | |
| Runtime at Full-Load | 2 Minutes |
| Runtime at Half-Load | 10 Minutes |
| Battery Specification | 1 x 12V/7Ah |
| | |
| Surge Protection and Filtering | |
| Surge Suppression | 1796 Joules |
| Phone / Ethernet RJ11 / RJ45 | 1 x RJ11/45 Combo (One-in/One-out) |
| Coax Protection RG6 | None |
| | |
| Management & Communications | |
| Indicators | LED Indicators |
| USB Port | None |
| Serial Port | 1 x DB9 |
| Software | PowerPanel Plus |
| SNMP / HTTP Remote Monitoring | Yes [With optional RMCARD100] |
| Dhysiasl | |
| | 2 5" x 6 5" x 11 5" |
| Dimensions (WxHxD) | 3.5" x 6.5" x 11.5" 15.4 lbs. |
| Weight | 10.4 IDS. |
| Warranty | |
| Product Warranty | 3-year warranty. Free Tech Support. |
| Connected Equipment Guarantee | Lifetime |
| CEG Amount | \$125,000 |
| | ψ120,000 |



Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com