



Model #: PR1500SWRM2U

UPC: 649532815029

MSRP: \$529.99



The Smart App Sinewave UPS Series provides an advanced level of power protection to support mission-critical servers, telecom equipment, VOIP and internetworking hardware.

The PR1500SWRM2U has both a Sinewave waveform and Full Automatic Voltage Regulation (AVR) technology, which delivers a consistent and clean AC signal that protects connected equipment and prevents costly business interruptions. It includes 6 battery and surge protected NEMA 5-15R output receptacles, and comes with four maintenance-free, user-replaceable 12V/7Ah batteries. Bundled PowerPanel Plus™ Management Software monitors UPS status and can provide unattended shutdown of two serially connected servers.

An optional SNMP / HTTP Remote Management adapter (RMCARD100) supports remote management and control of the PR1500SWRM2U through a standard web browser. Built-in LED indicators and audible alarms provide instant status notification for line power, load level, battery level, AVR status, on battery, low battery and overload conditions. The unit's unique convertible design allows for use in either a tower or Rackmount form factor.

Backed by US-based Technical Support, an industry-leading 3-Year Warranty and a Connected Equipment Guarantee of \$400,000.

- Pure Sinewave – The UPS generates energy that is identical to, or cleaner than the utility company's power grid. Benefits include: low total harmonic distortion, minimal electrical noise, and optimal line clarity.
- Microprocessor-based Digital Control – Digital routing is maintained through a network of integrated circuitry and discrete values are used for internal system processing, which significantly increases efficiency and response of CyberPower UPS's.
- RM/T Configuration – The PR series can be mounted either in Tower or Rackmount (2U) form.
- Full AVR – Boost/Buck – Boost/Buck topology will both increase low voltages and decrease high voltages, without switching to battery-mode. This conserves battery life, and delivers a more stable signal to your connected equipment.
- Dual PC Support – The unit has 2 (two) communication ports that allow the user full control of dual PCs or servers.
- EMI/RFI - Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or "humming" that occurs over telephone lines or stereo electronics.
- PowerPanel Plus™ Smart Power Management Software – In the event of a power outage, PowerPanel Plus will safely save and close your open files and shut your computer down in an orderly, intelligent manner. The software allows users to view detailed information about their electrical power and the vitals of the UPS. It includes configurable system notifications, automatic self tests, adjustable high/low voltage warnings, event/data logging, and scheduled shutdowns.
- Metal Housing – Rigid metal construction allows for placement in areas with a demanding environment.
- LED Indicators - LED status lights indicate Power-On, Wiring faults, AVR, and Battery level.
- Audible Alarms - Audible tones identify when the unit is running off battery power, unit overloads, and low battery.
- Resettable Circuit Breaker - Convenient unit reset switch in case of an overload.
- 3-year Warranty - CyberPower will replace damaged units if within 3 years of purchase date. We stand behind our products and guarantee quality. CyberPower also offers a #1 rated technical support team that will assist you with product, installation, or warranty concerns --- Free of Charge!
- ISO & Safety Certifications - All CyberPower's manufacturing facilities are ISO-9001 Quality Tested. Our products are also certified by the FCC, cUL, and UL.
- Windows compatibility - Our power management software has been fully tested and is compatible with Windows 2k, 2003, and XP.



Technical Specifications

General	
Model #	PR1500SWRM2U
UPS Topology	Line-Interactive
Input	
Voltage	85 - 150V
Frequency	47 - 63Hz
Plug Type	NEMA 5-15P
Cord Length	10 ft
Output	
VA	1500
Watts	1000
Automatic Voltage Regulation	Yes
On Battery Waveform	Sine Wave
Outlets - Total	6
Outlets - Battery & Surge	6 x NEMA 5-15R
Outlets - Surge-Only	None
Transfer Time	4 ms
Battery	
Runtime at Full-Load	5 Minutes
Runtime at Half-Load	15 Minutes
Battery Specification	4 x 12V/7Ah
Surge Protection and Filtering	
Surge Suppression	1780 Joules
Phone / Ethernet RJ11 / RJ45	1 x RJ11/45 Combo (One-in/One-out)
Coax Protection RG6	None
Management & Communications	
Indicators	LED Indicators
USB Port	None
Serial Port	2 x DB9
Software	PowerPanel Plus
SNMP / HTTP Remote Monitoring	Yes [With optional RMCARD100]
Physical	
Dimensions (WxHxD)	17.25" x 3.5" x 15.75"
Weight	56 lbs.
Warranty	
Product Warranty	3-year warranty. Free Tech Support.
Connected Equipment Guarantee	Lifetime
CEG Amount	\$400,000

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>