

CyberPower®

Model #: 1080

UPC: 649532010806

MSRP: \$31.99



The CyberPower 1080 surge suppressor is a Computer/Audio/Video Grade Surge Protector. This unit provides powerful surge suppression with a rating of 3600 Joules and has 10 outlets of MOV protection (4 transformer-friendly, 6 standard). It is equipped with a RJ-11 port that protects phone/fax/modem/DSL equipment, and also a RG-6 gold-plated coax port that is perfect for your cable modem, cable TV lines, and DSS equipment. EMI/RFI shielding will rid your equipment from any harmful interfaces, and MOV technology ensures the protection of all connected electronics, and the surge suppressor itself. CyberPower fully stands behind its products with a lifetime product warranty and Connected Equipment Guarantee of \$150,000.

- MOV (Metal Oxide Varistor) - MOV technology allows normal current to pass through the device, while diverting any surge/spikes through the ground circuit. This safely protects all connected electronics along with the surge suppressor itself.
- Transformer-spaced Outlets - Widely spaced outlets allow you to conveniently add large transformer-based plugs without compromising the utility of other outlets.
- EMI/RFI Shielding - Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or "humming" that occurs over telephone lines or stereo electronics.
- ISO & Safety Certifications - All CyberPower's manufacturing facilities are ISO-9001 Quality Tested. Our products are also UL Listed and CSA Certified.
- Child-safe Outlets: Outlets on the surge suppressor that are not used can be "closed off" so unwanted objects cannot be electrically charged.
- Keyhole Mounting Slots – Convenient mounting slots are located on the back on the surge suppressor.
- Sturdy ABS Case – Constructed of impact-resistant composite material for maximum durability.

Technical Specifications

General	
Model #	1080
Input	
Voltage	110/120V Nominal
Plug Type	NEMA 5-15P
Plug Style	Right-angle
Cord Length	8 ft
Output	
Outlets - Total	10
Outlets - Widely Spaced	4 x NEMA 5-15R
Outlets - Normal Spaced	6 x NEMA 5-15R
Surge Protection and Filtering	
Surge Suppression	3600 Joules
Phone Protection (RJ11)	One-in/Two-out
Ethernet Protection (RJ45)	None
Coax Protection (RG6)	One-in/One-out
Maximum Surge Current	180,000 Amps
Maximum Surge Current H-N	120,000 Amps
Maximum Surge Current H-G	30,000 Amps
Maximum Surge Current N-G	30,000 Amps
Maximum Surge Voltage	6,000V
Clamping Voltage	330 V
Response Time	<1 ns
EMI/RFI Filtration	EMI/RFI 150KHz to 100MHz
Attenuation	Up to 58dB
Indicators	
Indicator Lights	Power (Red); Surge (Red); Ground (Green)
Physical	
Dimensions (WxHxD)	11.75" x 4" x 1.75"
Weight	2.2875 lbs.
Color	Bronze
Warranty	
Product Warranty	Lifetime
Connected Equipment Guarantee	Lifetime
CEG Amount	\$150,000

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>