

Model #: 6050-Silver

UPC: 649532760503

MSRP: \$14.99



The CyberPower 6050-SILVER surge suppressor is an all-purpose electronic surge protector with one built-in RJ-11 port and 900 joule MOV technology. RJ-11 ports allow for protection of telecommunication devices such as phones, faxes, modems, and DSL lines, while MOV technology safely guards the surge protector and connected electronics against line abnormalities and lightning surges. This surge protector is ideal for personal computers, stereo electronics, phones/answering machines, and all other consumer electronics. The 6050 is also equipped with EMI/RFI filters that block unwanted line noise from all connected electronics. CyberPower fully stands behind its products with a lifetime product warranty and Connected Equipment Guarantee of \$45,000.

- MOV (Metal Oxide Varistor) MOV technology allows normal current to pass through the device, while diverting any surge/spikes through the ground circuit. This safely protects all connected electronics along with the surge suppressor itself.
- Transformer-spaced Surge Protector Outlets Widely spaced outlets allow you to conveniently add large transformer-based plugs without compromising the utility of other outlets.
- EMI/RFI Shielding Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or "humming" that occurs over telephone lines or stereo electronics.
- ISO & Safety Certifications All CyberPower's manufacturing facilities are ISO-9001 Quality Tested. Our products are also UL Listed and CSA Certified.
- Keyhole Mounting Slots Convenient mounting slots are located on the back on the surge protector.
- Sturdy ABS Case Constructed of impact-resistant composite material for maximum durability.

Technical Specifications

Model # 6050-SILVER	General	
Input Voltage 110/120V Nominal Plug Type NEMA 5-15P Plug Style Right-angle Cord Length 4ft Output Outlets - Total 6 Outlets - Widely Spaced 1x NEMA 5-15R Outlets - Normal Spaced 5x NEMA 5-15R Surge Protection and Filtering Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethemet Protection (RJ45) None Coax Protection (RG6) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current H-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicators Indicator Lights Power (Red); Surge (Red) Warranty Product Warranty Lifetime Connected Equipment Guarantee Lifetime		COEO CILVED
Voltage 110/120V Nominal Plug Type NEMA 5-15P Plug Style Right-angle Cord Length 4 ft Output Outlets - Total 6 Outlets - Widely Spaced 1 x NEMA 5-15R Outlets - Normal Spaced 5 x NEMA 5-15R Outlets - Normal Spaced 5 x NEMA 5-15R Surge Protection and Filtering Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current H-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee Lifetime	Model #	6050-SILVER
Voltage 110/120V Nominal Plug Type NEMA 5-15P Plug Style Right-angle Cord Length 4 ft Output Outlets - Total 6 Outlets - Widely Spaced 1 x NEMA 5-15R Outlets - Normal Spaced 5 x NEMA 5-15R Outlets - Normal Spaced 5 x NEMA 5-15R Surge Protection and Filtering Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current H-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee Lifetime	Input	
Plug Type NEMA 5-15P Plug Style Right-angle Cord Length 4ft Output Outlets - Total 6 Outlets - Widely Spaced 1 x NEMA 5-15R Outlets - Normal Spaced 5 x NEMA 5-15R Surge Protection and Filtering Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None Coax Protection (RG6) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee		110/120V Nominal
Plug Style Right-angle Cord Length 4 ft Output Outlets - Total 6 Outlets - Widely Spaced 1 x NEMA 5-15R Outlets - Normal Spaced 5 x NEMA 5-15R Surge Protection and Filtering Surge Suppression 900 Joules Phone Protection (RJ41) One-in/One-out Ethernet Protection (RJ45) None Coax Protection (RG6) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current H-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee Lifetime	_	
Cord Length 4 ft Output 6 Outlets - Widely Spaced 1 x NEMA 5-15R Outlets - Normal Spaced 5 x NEMA 5-15R Surge Protection and Filtering 8 Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None Coax Protection (RG6) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns		
Output Outlets - Total 6 Outlets - Widely Spaced 1 x NEMA 5-15R Outlets - Normal Spaced 5 x NEMA 5-15R Surge Protection and Filtering 900 Joules Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RG6) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current H-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns		
Outlets - Total 6 Outlets - Widely Spaced 1 x NEMA 5-15R Outlets - Normal Spaced 5 x NEMA 5-15R Surge Protection and Filtering Surge Suppression Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None Coax Protection (RG6) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns		
Outlets - Widely Spaced 1 x NEMA 5-15R Outlets - Normal Spaced 5 x NEMA 5-15R Surge Protection and Filtering Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None Coax Protection (RG6) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current H-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee	Output	
Outlets - Normal Spaced 5 x NEMA 5-15R Surge Protection and Filtering Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None Coax Protection (RG6) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current H-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee	Outlets - Total	6
Outlets - Normal Spaced 5 x NEMA 5-15R Surge Protection and Filtering Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None Coax Protection (RG6) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current H-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee	Outlets - Widely Spaced	1 x NEMA 5-15R
Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None Coax Protection (RG6) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current H-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee	Outlets - Normal Spaced	5 x NEMA 5-15R
Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None Coax Protection (RG6) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current H-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee		
Phone Protection (RJ11) Ethernet Protection (RJ45) Coax Protection (RG6) Maximum Surge Current Maximum Surge Current H-N Maximum Surge Current H-G Maximum Surge Current H-G Maximum Surge Current H-G Maximum Surge Current N-G Maximum Surge Voltage Maximum Surge Voltage Clamping Voltage Clamping Voltage Response Time EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Warranty Product Warranty Lifetime Lifetime Lifetime	Surge Protection and Filtering	
Ethernet Protection (RJ45) Coax Protection (RG6) Maximum Surge Current Maximum Surge Current H-N Maximum Surge Current H-G Maximum Surge Current H-G Maximum Surge Current N-G Maximum Surge Current N-G Maximum Surge Voltage Maximum Surge Voltage Clamping Voltage Clamping Voltage Salo V Response Time EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Warranty Product Warranty Lifetime Connected Equipment Guarantee	Surge Suppression	900 Joules
Coax Protection (RG6) Maximum Surge Current Maximum Surge Current H-N Maximum Surge Current H-G Maximum Surge Current H-G Maximum Surge Current H-G Maximum Surge Current N-G Maximum Surge Current N-G Maximum Surge Voltage G,000V Clamping Voltage Response Time EMI/RFI Filtration EMI/RFI Filtration Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee	Phone Protection (RJ11)	One-in/One-out
Maximum Surge Current Maximum Surge Current H-N Maximum Surge Current H-G Maximum Surge Current H-G Maximum Surge Current N-G Maximum Surge Current N-G Maximum Surge Current N-G Maximum Surge Voltage G,000V Clamping Voltage 330 V Response Time EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee	Ethernet Protection (RJ45)	None
Maximum Surge Current H-N Maximum Surge Current H-G Maximum Surge Current N-G Maximum Surge Current N-G Maximum Surge Voltage 6,000V Clamping Voltage Response Time EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee Lifetime	Coax Protection (RG6)	None
Maximum Surge Current H-G Maximum Surge Current N-G Maximum Surge Voltage 6,000V Clamping Voltage Response Time EMI/RFI Filtration Attenuation Indicators Indicator Lights Physical Dimensions (WxHxD) Weight Color Warranty Product Warranty Connected Equipment Guarantee 15,000 Amps 16,000 Amps 10,000	Maximum Surge Current	45,000 Amps
Maximum Surge Current N-G Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee 135,000 Amps 6,000V 105,000 Amps 105,00	Maximum Surge Current H-N	15,000 Amps
Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Connected Equipment Guarantee Lifetime	Maximum Surge Current H-G	15,000 Amps
Clamping Voltage Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Connected Equipment Guarantee Lifetime	Maximum Surge Current N-G	15,000 Amps
Response Time EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee Lifetime	Maximum Surge Voltage	6,000V
EMI/RFI Filtration Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Connected Equipment Guarantee Lifetime	Clamping Voltage	330 V
Attenuation Up to 58dB Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee Lifetime	Response Time	<1 ns
Indicators Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee Lifetime	EMI/RFI Filtration	EMI/RFI 150KHz to 100MHz
Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Connected Equipment Guarantee Lifetime	Attenuation	Up to 58dB
Indicator Lights Power (Red); Surge (Red) Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Connected Equipment Guarantee Lifetime		
Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Connected Equipment Guarantee Lifetime Lifetime		
Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Connected Equipment Guarantee Lifetime Lifetime	Indicator Lights	Power (Red); Surge (Red)
Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Connected Equipment Guarantee Lifetime Lifetime		
Weight 0.9375 lbs. Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee Lifetime	,	44 5" 0" 4 5"
Color Black/Silver Warranty Product Warranty Lifetime Connected Equipment Guarantee Lifetime		
Warranty Product Warranty Connected Equipment Guarantee Lifetime		
Product Warranty Lifetime Connected Equipment Guarantee Lifetime	Color	Black/Silver
Product Warranty Lifetime Connected Equipment Guarantee Lifetime	Warranty	
Connected Equipment Guarantee Lifetime	_	Lifetime
• • • • • • • • • • • • • • • • • • • •	·	
	· ·	



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com