

Model #: 1030HT

UPC: 649532010301 **MSRP:** \$119.99



The CyberPower 1030HT Home Theater Surge Suppressor is the ultimate high-end audio/video surge protector, offering 6000 Joules of MOV power protection. This shelf-mount unit has a rock-solid composite interior with a silver metal overlay shell. 16 LED's illuminate the front-panel display, giving the user full, visual diagnostic information. Exclusive Signal Scrubber ™ is a line conditioning technology that independently filters audio/video signals and delivers a true experience for high-end audio/video enthusiasts. RJ-11 ports protect phone/fax/modem/DSL equipment; RJ-45 ports protect network connected equipment such as computers, hubs, and routers; 3 (three) RG-6 gold-platted coax ports guard cable modems, cable TV lines, and DSS equipment. EMI/RFI filtering blocks electro-magnetic and radio interferences from entering your equipment, and MOV technology ensures the protection off all connected electronics, and the surge suppressor itself. CyberPower fully stands behind its products with a lifetime product warranty and Connected Equipment Guarantee of \$400.000.

- Signal Scrubber [™] Audio and video signals are isolated, and then independently filtered to guard against component cross-contamination and improve signal quality. The result is pure sound with expansive dynamic range, precise picture quality, and enhanced color depth.
- MOV (Metal Oxide Varistor) MOV technology allows normal current to pass through the device, while diverting any surge/spikes through the ground circuit. This safely protects all connected electronics along with the surge suppressor itself.
- Transformer-spaced Outlets Widely spaced outlets allow you to conveniently add large transformer-based plugs without compromising the utility of other outlets.
- EMI/RFI Shielding Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or "humming" that occurs over telephone lines or stereo electronics.
- ISO & Safety Certifications All CyberPower's manufacturing facilities are ISO-9001 Quality Tested. Our products are also UL Listed and CSA Certified.
- Keyhole Mounting Slots Convenient mounting slots are located on the back on the surge suppressor.
- Sturdy ABS Case Constructed of impact-resistant composite material for maximum durability.

Technical Specifications

Input	
Voltage	110/120V Nominal
Plug Type	NEMA 5-15P
Plug Style	Right-angle
Cord Length	8 ft
Output	
Outlets - Total	10
Outlets - Widely Spaced	4 x NEMA 5-15R
Outlets - Normal Spaced	6 x NEMA 5-15R
·	
Surge Protection and Filtering	
Surge Suppression	6000 Joules
Phone Protection (RJ11)	One-in/Two-out
Ethernet Protection (RJ45)	One-in/One-out
Coax Protection (RG6)	Three-in/Three-Out
Maximum Surge Current	260,000 Amps
Maximum Surge Current H-N	90,000 Amps
Maximum Surge Current H-G	90,000 Amps
Maximum Surge Current N-G	75,000 Amps
Maximum Surge Voltage	6,000V
Clamping Voltage	330 V
Response Time	<1 ns
EMI/RFI Filtration	EMI/RFI 100KHz to 100MHz
Attenuation	Up to 58dB
Indicators	
Indicator Lights	Power (Green); Surge (Green); Ground (Green); Switched (Yellow); 6 Usage Indicators; 6 Input Voltage Indicators
Physical	
Dimensions (WxHxD)	18" x 2.5" x 4.75"
Weight	6.2875 lbs.
Color	Silver
	5
Warranty	
Product Warranty	Lifetime
Connected Equipment Guarantee	Lifetime
CEG Amount	\$400,000



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com