

AN46860

Author: Praveen Kumar
Associated Project: No
Software Version: Astoria SDK 1.0
Associated Application Notes: None

Application Note Abstract

West Bridge® Astoria™ is a USB and mass storage peripheral control device that contains three main ports: processor interface (P-port), mass storage support (S-port), and USB interface (U-port). This application note discusses the hardware recommendations and guidelines to design a system using Astoria.

Introduction

The West Bridge® Astoria™ device is a peripheral controller that supports high speed USB and mass storage access. This controller provides access from a processor interface and a high speed USB (HS-USB) interface to peripherals including SD, MMC/MMC+, CE-ATA, SDIO, SLC, and MLC NAND. It supports interleaving accesses between the processor interface, HS-USB, and peripherals. This enables an external processor and an external USB host to transfer data simultaneously to each other and to the mass storage peripherals.

The hardware considerations to design Astoria into a system are:

P-Port

1. If operating in the asynchronous mode, CLK is tied LOW through a 10k resistor. In the synchronous mode, CLK is connected to the incoming signal from the processor interface.
2. In PCRAM and ADM mode, ADV# is tied to a signal on the processor interface that conforms to the timing specified in the West Bridge: Antioch USB/Mass Storage Peripheral Controller data sheet. If the signal is not available, tie ADV# to the CE# signal of the processor interface.
3. The DRQ Status Register and DRQ Mask Register indicate the available endpoints for transfer. They must be accessed even if a DMA or burst operation is not being implemented on the P-port interface. Use the DRQ# or the INT# signal to indicate to the processor that at least one of the bits in the DRQ Status Register is set. If INT# is used, an extra read of the P-port Interrupt Register must be done before the DRQ Status Register is read. In PNAND mode, R/B is used as an indication of End Point availability and is treated differently in LNA and nonLNA modes.

4. Ensure that TEST[2:0], A7, A3, and A2 settings are correct for the various P-port interface configurations.

Table 1 lists the TEST[2:0] and register settings for P-port interface configurations.

Table 1. P-Port Interface Configuration Options

TEST [2:0]	VMTYPE Field in CY_AN_MEM_P0_VM_SET Register	Interface
000	101	Non ADM PCRAM
000	111	SRAM
010	X	Extended Interface Mode

Table 2 lists the TEST[2:0] and address pin settings for the various extended interface modes.

Table 2. Extended Interface Modes

TEST [2:0]	A7	A3	A2	Interface
010	1	0	0	PNAND Mode-Small Block Device
010	0	0	0	PNAND Mode-Large Block Device
010	1	0	1	Address/Data Bus Multiplexing (ADM)
010	1	1	0	SPI Mode

5. When using extended P-port modes, SCL and SDA (A5 and A6) require external pull up. The pull up resistors are determined by the supply voltage, clock speed, and bus capacitance. A typical value for the I2C pull ups is 2 kΩ. This value must be adjusted based on the trace length and board layout conditions. The pull up on SDA is required even if I²C™ EEPROM is not being used. A low value resistor can cause overshoot and a high value resistor can cause timing violation depending on the capacitance on the bus.

6. DACK# is used in conjunction with DRQ#. If INT# is used to indicate that at least one bit is set in the DRQ# register, then DACK# remains unused. DACK# is not required for Astoria to function.
 7. INT#, DRQ#, and DACK# are in GVVDQ power domain. Therefore, pull up the input pin DACK# to GVDDQ using a 10k resistor, if it is not used.
 8. All unused inputs and input or output pins on the P-port are tied to a valid logic level (HIGH for lowest leakage) through a 10k resistor. Use a single resistor for all unused pins. When pulling HIGH, the unused pins are tied to the appropriate power domain, in this case, PVDDQ or GVDDQ.
- Refer to the Pin Assignments table in the data sheet for more details on pin configuration for each P-port interface mode and their corresponding power domains.
9. The INT# and DRQ# signals float when Astoria is in Standby state. These signals are active low. As a result, a pull up resistor must be connected to these signals to prevent the P-port processor from receiving any false interrupts.
 10. In the PNAND Interface Mode, external pull up is not required for the R/B# signal. R/B# signal is not an open drain or collector output.

S-Port

1. Use SD_D[3]/SD2_D[3] or GPIO[0]/GPIO[1] to detect cards on Astoria. If SD_D[3]/SD2_D[3] is used, then it must be pulled down using a 470 k Ω resistor.
2. Treat the SD_CLK signal as a high speed signal switching at a maximum of 48 MHz to determine the appropriate signal integrity precautions.
3. If you are designing an application supporting SD/MMC and CE-ATA, follow the trace length restrictions.

Table 3 lists acceptable frequencies for Astoria, and the maximum trace lengths corresponding to the frequencies for SD cards that cannot operate in high speed mode.

Table 3. Frequency vs. Trace Length (SD Default Mode)

SDFREQ (MHz)	Maximum Trace Length (in)
24.00	1.94
21.82	7.55
20.00	13.17
18.46	18.78
17.14	24.4

Table 4 lists the acceptable frequencies for Astoria and the corresponding maximum trace lengths for SD cards that are capable of operating in high speed mode.

Table 4. Frequency vs. Trace Length (SD High Speed Mode)

SDFREQ (MHz)	Maximum Trace Length (in)
48.00	8.18
40.00	20.66
34.29	33.13
30.00	45.61
26.67	58.08

Refer to the Pin Assignments table in the data sheet for more details on pin configuration for each pin in each S-port configuration and their corresponding power domains.

4. All unused inputs and input or output pins on the S-port are tied to a valid logic level (HIGH for lowest leakage) through a 10k resistor. Use a single resistor for all unused pins. When pulling HIGH, the unused pins are tied to the appropriate power domain, in this case, SSVDDQ, SNVDDQ, or GVDDQ.
5. The pull up resistor (Rp) used for NAND_R/B# varies from 1k to 10k based on the timing requirements and the manufacturer of the NAND device.
6. The SD_POW signal floats when Astoria is in standby. If this signal is used to control power to the SD card through an external switch, a pull up or pull down resistor must be connected on SD_POW, such that the switch remains ON and power to the card is retained during Astoria's standby condition.

U-Port

1. To avoid an impedance mismatch, lay out the USB differential signals (D+ and D-) with constant spacing and on one plane. Avoid vias and stubs. It is prudent to lay out the signals before laying out the rest of the board.
2. Minimize the trace lengths between the D+ and D- pins on Astoria and the USB connector.
3. If unused, SWD+/SWD- lines must be left floating or pulled low. A high on these lines may cause the USB to overlook detection in the system.

For further information, refer to the Cypress Application Note [AN1168](#), *High Speed USB PCB Layout Recommendations*.

Clocks

1. Ensure that the XTALSCLC[1:0] pin levels correspond to the frequency of the signal at XTALIN and XTALOUT.
2. Leave the XTALOUT floating if an external clock source is used.
3. Clock or crystal characteristics must conform to the requirements specified in the data sheet.
4. The design must adhere to the power supply noise specifications for the PLL specified in the data sheet.
5. XVDDQ is the select pin for crystal and clock. XVDDQ must be 3.3V when using a crystal. XVDDQ must be 1.8V when using a clock source as an input.

Table 5 lists the various clock selection input settings.

Table 5. Clock Selection Input Settings

XTALSCLC[1]	XTALSCLC[0]	Clock Frequency	Crystal Support
0	0	19.2 MHz	Yes
0	1	24 MHz	Yes
1	0	48 MHz	No
1	1	26 MHz	Yes

Decoupling for Power Supplies

1. VDD requires 2.2 μ F and 0.1 μ F decoupling.
2. Although AVDDQ is tied to the same supply as VDD, route it separately with 0.01 μ F and 0.1 μ F capacitors.
3. UVDDQ requires 2.2 μ F and 0.1 μ F decoupling.
4. GVDDQ, PVDDQ, SSVDDQ, SNVDDQ, and XVDDQ do not have any specific decoupling requirements. Combine them with the decoupling for other supplies at the same level. If in doubt, use 2.2 μ F and 0.1 μ F.

Miscellaneous

All unused output-only pins may be left floating, but do not leave unused input-only and input/output pins floating. Tie the unused input-only and input/output to a valid logic level using a single 10k pull up resistor. There is a negligible difference if the unused input-only pins are tied HIGH or LOW. For lowest leakage, tie unused input/output pins HIGH.

Ensure that all unused pins handled in this manner are tied to their corresponding power domain. For example, an unused GPIO[1] is tied HIGH to GVDDQ through a 10k pull up, which is shared with other unused signals in the GVDDQ power domain.

Astoria is not hardware backward compatible to Antioch. So, if the system is designed in Antioch, it requires PCB change when replaced by Astoria.

About the Author

Name: Praveen Kumar
Title: Applications Engineer
Contact: prku@cypress.com.

Document History

Document Title: Schematic Review Checklist for West Bridge® Astoria™

Document Number: 001-46860

Revision	ECN	Submission Date	Orig. of Change	Description of Change
**	2516790	06/16/2008	PRKU	New application note.
*A	2620808	12/12/2008	OSG/AESA	Numbered the paragraphs for better readability and added another point in both P-port and S-port sections. Changed title to "Schematic Review Checklist for West Bridge® Astoria™".

West Bridge, Astoria, and Antioch are trademarks of Cypress Semiconductor. All product and company names mentioned in this document are the trademarks of their respective holders.

Cypress Semiconductor
 198 Champion Court
 San Jose, CA 95134-1709
 Phone: 408-943-2600
 Fax: 408-943-4730
<http://www.cypress.com/>

© Cypress Semiconductor Corporation, 2008. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, life saving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

This Source Code (software and/or firmware) is owned by Cypress Semiconductor Corporation (Cypress) and is protected by and subject to worldwide patent protection (United States and foreign), United States copyright laws and international treaty provisions. Cypress hereby grants to licensee a personal, non-exclusive, non-transferable license to copy, use, modify, create derivative works of, and compile the Cypress Source Code and derivative works for the sole purpose of creating custom software and or firmware in support of licensee product to be used only in conjunction with a Cypress integrated circuit as specified in the applicable agreement. Any reproduction, modification, translation, compilation, or representation of this Source Code except as specified above is prohibited without the express written permission of Cypress.

Disclaimer: CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Use may be limited by and subject to the applicable Cypress software license agreement.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>