

DWL-G550



FEATURES

High-Powered Wireless Connectivity

- Increased Power Output Improves Signal Wireless Reception
- Up to 108Mbps¹ Using 802.11g
 Powered by D-Link 108G Technology
- Backward Compatible to 802.11b

Business-Class WLAN Utility

- Stores Multiple SSID Profiles
- Automatically Connects to Active Wireless Networks When Current Connection is Lost
- One-Click Driver Installation with Silent Installation Feature

Industry Standard Wireless Network Encryption

- WPA-Personal
- WPA-Enterprise
- WPA2
- 64/128-bit WFP

Business-class User Authentication

- 802.1x RADIUS
- EAP-TLS, EAP-TTLS, PEAP

Robust Wireless Data Encryption

- TKIP (Temporal Key Integrity Protocol)
- AES (Advanced Encryption Standard)

Certifications

- Wi-Fi 802.11b
- Wi-Fi 802.11g
- Microsoft WHQL (Windows Hardware Quality Labs)

Air Premier

High-Powered Wireless 108G Desktop Adapter

D-Link's *Air*Premier[®] line of networking products combine powerful business class features with a high-performance hardware platform specifically designed for corporate environments. The *Air*Premier line of networking products now adds wireless client adapters to its lineup including the DWL-G550 High-Powered Wireless 108G Desktop Adapter.

Powered by D-Link 108G Technology, this High-Powered Desktop Adapter is capable of delivering a maximum wireless signal rate of up to 108Mbps¹ when used with other D-Link Wireless 108G devices. The DWL-G550 is also backward compatible with virtually all 802.11b/g networks and devices.

The high-powered output featured on the DWL-G550 offers extended wireless signal reception while adhering to industry standards. Higher output power allows this client device to receive and maintain strong signals from wireless routers and access points at further distances.

The new business-class wireless LAN utility included with this device displays a management tool consistent with the Windows[®] User Interface guidelines. Key wireless information is displayed in an efficient manner while navigation through the utility is a straightforward and intuitive process. IT managers will also appreciate the Silent Installation feature of the DWL-G550. With this feature, the drivers can be configured to automatically install on the backend reducing the time needed to process and configure wireless network settings.

For accessing secure networks, this Wireless Desktop Adapter supports both Personal and Enterprise versions of WPA and WPA2. Now you can utilize EAP-TLS, EAP-TTLS and PEAP for secure user authentication through an 802.1x RADIUS server. Data traversing the wireless network is encrypted using either TKIP or AES.

The DWL-G550 can be used in peer-to-peer mode (ad-hoc) to directly connect to other 802.11b/g wirelessly enabled computers for direct file sharing, or in client mode (infrastructure) to connect with wireless access points or routers.

In addition to Wi-Fi certification for 802.11b and 11g, the DWL-G550 is also certified by Microsoft's WHQL, to ensure compatibly with Microsoft Windows® XP and 2000. These certifications ensure both wireless compatibility, robust data encryption, and reliable performance.

A perfect complement for your *Air*Premier wireless network, this High-Powered Wireless 108G Desktop Adapter is a convenient solution for providing superior wireless connectivity for your desktop PC.

Product Data Sheet



High-Powered Wireless 108G Desktop Adapter

Specifications

Standards

• 802.11b

• 802.11g

• 802.1x

Device Management

D-Link Business Class Utility

Wireless Signal Rate¹

- 802.11g: 6, 9,12,18, 24, 36, 48, 54, 108Mbps
- 802.11b:1, 2, 5.5 and 11Mbps

Security

- WEP 64/128bit
- WPA-Personal
- WPA-Enterprise
- WPA2-Personal
- WPA2-Enterprise

Wireless Frequency Range

• 2.4 – 2.5GHz

Wireless Signal Range¹

- 802.11b
- 2400 2497MHz ISM Band
- 802.11g
- 2400 2483.5MHz ISM Band

Modulation Technology

- 802.11b
- DQPSK DBPSK
- DSSS
- CCK

- 802.11g
- BPSK QPSK
- 160AM
- OFDM

Receiver Sensitivity

- 802.11b
- Typical -84dBm for 11Mbps @ 8% PER
- Typical -90dBm for 2Mbps @ 8% PER
- 802.11a
- Typical -87dBm for 6Mbps @ 10% PER
- Typical -86dBm for 9Mbps @ 10% PER
- Typical -85dBm for 12Mbps @ 10% PER
- Typical -83dBm for 18Mbps @ 10% PER
- Typical -80dBm for 24Mbps @ 10% PER
- Typical -76dBm for 36Mbps @ 10% PER
- Typical -71dBm for 48Mbps @ 10% PER
- Typical -66dBm for 54Mbps @ 10% PER

Wireless Transmit Power

- 802.11b
- Typical 21dBm at 11, 5.5, 2 an 1Mbps
- 802.11a
- Typical +15 18dBm for 54Mbps
- Typical +16 19dBm for 48Mbps
- Typical +17 20dBm for 36Mbps
- Typical +18 21dBm for 24, 18, 12, 9, 6Mbps

Maximum wireless signal rate derived from IEEE Standard 802.11g specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors will adversely affect wireless signal range

All references to speed are for comparison purposes only. Product specifications, size and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

D-Link Systems, Inc. 17595 Mt Herrmann, Fountain Valley CA, 92708-4160 www.dlink.com ©2005 D-Link Corporation/D-Link Systems, Inc. All rights reserved. D-Link, the D-Link logo and AirPremier are registered trademarks of D-Link Corporation or its subsidiaries in the United States and other countries. Other trademarks are the property of their respective owners. Visit www.dlink.com for more details.

External Antenna Type

· Omni-directional dipole antenna with 5dBi

LEDs

- Link
- Activity

Power Consumption

- 500mA at continuous transmit mode
- 300mA at continuous receive mode
- 30mA at sleep mode

Operating Voltage

• 3.3VDC +/- 10%

Operating Temperature

• 0° to +55°C

Non Operating Temperature

• -20° to +75°C

Operating Humidity

• 10% - 90%, RH, non-condensing

Non-Operating Humidity

• 5% - 95%, RH, non-condensing

Certifications (US Only)

- FCC part 15.247, 15.205, 15.209
- UL1950-3 for CSA Mark

Dimensions

- L 6.6in (168mm)
- W 4.2in (107mm)
- H 0.16in (4mm

Weight

• 0.17 lb (77g)

Mean Time Before Failure

• 30.000 Hours

Warranty

• 1-Year



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com