

INTRODUCTION

Congratulations on your purchase of a DB Drive state-of-the-art subwoofer component. Your selection of a DB Drive car audio product indicates a true appreciation of fine musical reproduction. Whether adding to an existing system or including a DB Drive subwoofer in a new system, you are certain to notice immediate performance benefits.

KEEP YOUR SALES RECEIPT

Take this time to attach your sales receipt to the manual and put in a safe place. In case of any unforeseen reason this product may need warranty service, your receipt will be necessary to establish purchase date. For detailed warranty information please refer to enclosed warranty card.

RECOMMENDATION

A speaker's performance is only as good as it's enclosure. Proper installation, enclosure size and crossover frequency will maximize the overall performance of the subwoofer. To properly design and build an enclosure, knowledge of wood-working as well as the proper tools are required. We highly recommend that you have your enclosure built by an authorized DB Drive retailer. However, if you decide to install it yourself, we have included the parameters of each driver and recommended enclosure sizes. If after reviewing the enclosed information you have any addition questions, please feel free to contact our technical dept.

WARNING!

Exposure to high pressure levels can cause hearing loss or damage. Listening to your system at loud levels while driving, will impair your ability to hear traffic sounds and emergency vehicles. Use common sense when listening to your system.

While installing your subwoofer enclosure in the vehicle. Securely fasten it to the frame or floorpan. If the enclosure is not secured properly, there is danger of it becoming a projectile in a collision.

Due to continuing product improvement, specifications and design are subject to change without notice.



PRODUCT SPECIFICATIONS

	K5 10D2	K5 10D4	K5 12D2	K5 12D4	K5 15D2	K5 15D4
(FS)	28.06Hz	28.88Hz	24.78Hz	24.39Hz	25.99Hz	27.26Hz
(Qts.)	0.30	0.32	0.35	0.37	0.46	0.54
(Qms)	4.00	3.63	4.40	3.82	4.19	4.30
(VAS)	21.86L	23.30L	51.55L	53.22L	105.01L	99.40L
(Xmax)	0.63in	0.63in	0.63in	0.63in	0.63in	0.63in
(Re)	3.64Ω	6.43Ω	3.63Ω	6.43Ω	3.63Ω	6.43Ω
(Pe)	750/1500	750/1500	750/1500	750/1500	750/1500	750/1500
(QES)	0.32	0.36	0.38	0.41	0.51	0.62
(Sens)	83.68dB	83.85dB	85.00dB	84.63dB	87.45dB	86.98dB

CALCULATING ENCLOSURES

It is difficult to give exact box dimensions that are universal for all cars and trucks. It is for this reason that you must be able to calculate the space in which you have available in order to achieve the proper air volume required.

It is recommended to build your enclosure from 3/4" thick MDF (medium density fiberboard). Make sure the enclosure is sealed airtight.

Calculating External Volume


- 1.) To calculate box volume, measure the outside Width x Height x Depth of the enclosure. *Example 12" x 14" x 9"=1512 ÷ 1728" Cubic feet*
- 2.) Next you must convert cubic inches into cubic feet. To do this, you must divide the cubic inches total by 1728". *Example 1512 ÷ 1728=.875 Cubic feet*

Calculating Internal Volume


- 1.) To calculate the internal (net) volume of the above box you must first multiply the thickness of the wood you are using by Two(2). *Example 3/4" x 2= 1.5"*
- 2.) Next subtract 1.5 from each of the outside measurements of the box.

Width	Height	Depth
12 - 1.5 = 10.5	14 - 1.5 = 12.5	9 - 1.5 = 7.5
- 3.) Multiple the new totals (H x W x D) *Example: 10.5 x 12.5 x 7.5 = .5696*
- 4.) Next you must convert cubic inches into cubic feet. To do this, you must divide the cubic inch total by 1728". *Example 984.375 ÷ 1728=.5696 cubic feet.*

Recommended Enclosures



sealed



ported

K5 10D2 / K5 10D4

Sealed Enclosure

Box Volume .89cu ft.


Ported Enclosure

Box Volume 1.42cu ft.

Box Tuning 39Hz

Port Diameter 4in

Port Length 16in



K5 12D2 / K5 12D4

Sealed Enclosure

Box Volume 1.25cu ft.


Ported Enclosure

Box Volume 1.57cu ft.

Box Tuning 39Hz

Port Diameter 2 x 3in

Port Length 18in



K5 15D2 / K5 15D4

Sealed Enclosure

Box Volume 1.54cu ft.


Ported Enclosure

Box Volume 2.75cu ft.

Box Tuning 39Hz

Port Diameter 2 x 4in

Port Length 14in



okur

Installation Instructions / Owner's Manual

MODEL

K5 10D2 / K5 10D4

K5 12D2 / K5 12D4

K5 15D2 / K5 15D4



DB Research L.L.P.

302 Hanmore Industrial Parkway // Harlingen, TX 78550

ph: 877.787.0101 // fx: 956.421.4513 // www.dbdrive.net

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>